

**TRANSZORB® Transient Voltage Suppressors****Case Style 1.5KE****PRIMARY CHARACTERISTICS**

|                                  |                |
|----------------------------------|----------------|
| $V_{BR}$ uni-directional         | 6.8 V to 540 V |
| $V_{BR}$ bi-directional          | 6.8 V to 440 V |
| $P_{PPM}$                        | 1500 W         |
| $P_D$                            | 6.5 W          |
| $I_{FSM}$ (uni-directional only) | 200 A          |
| $T_J$ max.                       | 175 °C         |

**DEVICES FOR BI-DIRECTION APPLICATIONS**

For bi-directional types, use C or CA suffix (e.g. 1.5KE440CA).

Electrical characteristics apply in both directions.

**FEATURES**

- Glass passivated chip junction
- Available in uni-directional and bi-directional
- 1500 W peak pulse power capability with a 10/1000  $\mu$ s waveform, repetitive rate (duty cycle): 0.01 %
- Excellent clamping capability
- Very fast response time
- Low incremental surge resistance
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

**RoHS**  
COMPLIANT**TYPICAL APPLICATIONS**

Use in sensitive electronics protection against voltage transients induced by inductive load switching and lighting on ICs, MOSFET, signal lines of sensor units for consumer, computer, industrial, automotive and telecommunication.

**MECHANICAL DATA**

**Case:** Molded epoxy body over passivated junction  
Molding compound meets UL 94 V-0 flammability rating

Base P/N-E3 - RoHS compliant, commercial grade  
Base P/NHE3 - RoHS compliant, high reliability/  
automotive grade (AEC Q101 qualified)

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix meets JESD 201 class 1A whisker test, HE3 suffix meets JESD 201 class 2 whisker test

**Note:**

- 1.5KE250 ~ 1.5KE540A and 1.5KE250C ~ 1.5KE440CA for commercial grade only

**Polarity:** For uni-directional types the color band denotes cathode end, no marking on bi-directional types

**MAXIMUM RATINGS** ( $T_A = 25$  °C unless otherwise noted)

| PARAMETER                                                                                   | SYMBOL         | LIMIT          | UNIT |
|---------------------------------------------------------------------------------------------|----------------|----------------|------|
| Peak pulse power dissipation with a 10/1000 $\mu$ s waveform <sup>(1)</sup> (Fig. 1)        | $P_{PPM}$      | 1500           | W    |
| Peak pulse current with a 10/1000 $\mu$ s waveform <sup>(1)</sup>                           | $I_{PPM}$      | See next table | A    |
| Power dissipation on infinite heatsink at $T_L = 75$ °C (Fig. 5)                            | $P_D$          | 6.5            | W    |
| Peak forward surge current 8.3 ms single half sine-wave uni-directional only <sup>(2)</sup> | $I_{FSM}$      | 200            | A    |
| Maximum instantaneous forward voltage at 100 A for uni-directional only <sup>(3)</sup>      | $V_F$          | 3.5/5.0        | V    |
| Operating junction and storage temperature range                                            | $T_J, T_{STG}$ | - 55 to + 175  | °C   |

**Notes:**

(1) Non-repetitive current pulse, per Fig. 3 and derated above  $T_A = 25$  °C per Fig. 2

(2) Measured on 8.3 ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum

(3)  $V_F = 3.5$  V for 1.5KE220 (A) and below;  $V_F = 5.0$  V for 1.5KE250(A) and above

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

| JEDEC<br>TYPE<br>NUMBER | GENERAL<br>SEMICONDUCTOR<br>PART NUMBER | BREAKDOWN<br>VOLTAGE<br>$V_{BR}$ AT $I_T$ <sup>(1)</sup><br>(V) |      | TEST<br>CURRENT<br>$I_T$<br>(mA) | STAND-OFF<br>VOLTAGE<br>$V_{WM}$ (V) | MAXIMUM<br>REVERSE<br>LEAKAGE<br>AT $V_{WM}$<br>$I_D$ <sup>(4)</sup> ( $\mu$ A) | MAXIMUM<br>PEAK<br>PULSE<br>CURRENT<br>AT $I_{PPM}$ <sup>(2)</sup> (A) | MAXIMUM<br>CLAMPING<br>VOLTAGE<br>AT $I_{PPM}$<br>$V_C$ (V) | MAXIMUM<br>TEMP.<br>COEFFICIENT<br>OF $V_{BR}$<br>(%/°C) |
|-------------------------|-----------------------------------------|-----------------------------------------------------------------|------|----------------------------------|--------------------------------------|---------------------------------------------------------------------------------|------------------------------------------------------------------------|-------------------------------------------------------------|----------------------------------------------------------|
|                         |                                         | MIN.                                                            | MAX. |                                  |                                      |                                                                                 |                                                                        |                                                             |                                                          |
| 1N6267                  | (+) $1.5KE6.8$                          | 6.12                                                            | 7.48 | 10                               | 5.50                                 | 1000                                                                            | 139                                                                    | 10.8                                                        | 0.057                                                    |
| 1N6267A                 | (+) $1.5KE6.8A$                         | 6.45                                                            | 7.14 | 10                               | 5.80                                 | 1000                                                                            | 143                                                                    | 10.5                                                        | 0.057                                                    |
| 1N6268                  | (+) $1.5KE7.5$                          | 6.75                                                            | 8.25 | 10                               | 6.05                                 | 500                                                                             | 128                                                                    | 11.7                                                        | 0.061                                                    |
| 1N6268A                 | (+) $1.5KE7.5A$                         | 7.13                                                            | 7.88 | 10                               | 6.40                                 | 500                                                                             | 133                                                                    | 11.3                                                        | 0.061                                                    |
| 1N6269                  | (+) $1.5KE8.2$                          | 7.38                                                            | 9.02 | 10                               | 6.63                                 | 200                                                                             | 120                                                                    | 12.5                                                        | 0.065                                                    |
| 1N6269A                 | (+) $1.5KE8.2A$                         | 7.79                                                            | 8.61 | 10                               | 7.02                                 | 200                                                                             | 124                                                                    | 12.1                                                        | 0.065                                                    |
| 1N6270                  | (+) $1.5KE9.1$                          | 8.19                                                            | 10.0 | 1.0                              | 7.37                                 | 50                                                                              | 109                                                                    | 13.8                                                        | 0.068                                                    |
| 1N6270A                 | (+) $1.5KE9.1A$                         | 8.65                                                            | 9.55 | 1.0                              | 7.78                                 | 50                                                                              | 112                                                                    | 13.4                                                        | 0.068                                                    |
| 1N6271                  | (+) $1.5KE10$                           | 9.00                                                            | 11.0 | 1.0                              | 8.10                                 | 10                                                                              | 100                                                                    | 15.0                                                        | 0.073                                                    |
| 1N6271A                 | (+) $1.5KE10A$                          | 9.50                                                            | 10.5 | 1.0                              | 8.55                                 | 10                                                                              | 103                                                                    | 14.5                                                        | 0.073                                                    |
| 1N6272                  | (+) $1.5KE11$                           | 9.90                                                            | 12.1 | 1.0                              | 8.92                                 | 5.0                                                                             | 92.6                                                                   | 16.2                                                        | 0.075                                                    |
| 1N6272A                 | (+) $1.5KE11A$                          | 10.5                                                            | 11.6 | 1.0                              | 9.40                                 | 5.0                                                                             | 96.2                                                                   | 15.6                                                        | 0.075                                                    |
| 1N6273                  | (+) $1.5KE12$                           | 10.8                                                            | 13.2 | 1.0                              | 9.72                                 | 5.0                                                                             | 86.7                                                                   | 17.3                                                        | 0.076                                                    |
| 1N6273A                 | (+) $1.5KE12A$                          | 11.4                                                            | 12.6 | 1.0                              | 10.2                                 | 5.0                                                                             | 89.8                                                                   | 16.7                                                        | 0.078                                                    |
| 1N6274                  | (+) $1.5KE13$                           | 11.7                                                            | 14.3 | 1.0                              | 10.5                                 | 5.0                                                                             | 78.9                                                                   | 19.0                                                        | 0.081                                                    |
| 1N6274A                 | (+) $1.5KE13A$                          | 12.4                                                            | 13.7 | 1.0                              | 11.1                                 | 5.0                                                                             | 82.4                                                                   | 18.2                                                        | 0.081                                                    |
| 1N6275                  | (+) $1.5KE15$                           | 13.5                                                            | 16.5 | 1.0                              | 12.1                                 | 1.0                                                                             | 68.2                                                                   | 22.0                                                        | 0.084                                                    |
| 1N6275A                 | (+) $1.5KE15A$                          | 14.3                                                            | 15.8 | 1.0                              | 12.8                                 | 1.0                                                                             | 70.8                                                                   | 21.2                                                        | 0.084                                                    |
| 1N6276                  | (+) $1.5KE16$                           | 14.4                                                            | 17.6 | 1.0                              | 12.9                                 | 1.0                                                                             | 63.8                                                                   | 23.5                                                        | 0.086                                                    |
| 1N6276A                 | (+) $1.5KE16A$                          | 15.2                                                            | 16.8 | 1.0                              | 13.6                                 | 1.0                                                                             | 66.7                                                                   | 22.5                                                        | 0.086                                                    |
| 1N6277                  | (+) $1.5KE18$                           | 16.2                                                            | 19.8 | 1.0                              | 14.5                                 | 1.0                                                                             | 56.6                                                                   | 26.5                                                        | 0.088                                                    |
| 1N6277A                 | (+) $1.5KE18A$                          | 17.1                                                            | 18.9 | 1.0                              | 15.3                                 | 1.0                                                                             | 59.5                                                                   | 25.2                                                        | 0.089                                                    |
| 1N6278                  | (+) $1.5KE20$                           | 18.0                                                            | 22.0 | 1.0                              | 16.2                                 | 1.0                                                                             | 51.5                                                                   | 29.1                                                        | 0.090                                                    |
| 1N6278A                 | (+) $1.5KE20A$                          | 19.0                                                            | 21.0 | 1.0                              | 17.1                                 | 1.0                                                                             | 54.2                                                                   | 27.7                                                        | 0.090                                                    |
| 1N6279                  | (+) $1.5KE22$                           | 19.8                                                            | 24.2 | 1.0                              | 17.8                                 | 1.0                                                                             | 47.0                                                                   | 31.9                                                        | 0.092                                                    |
| 1N6279A                 | (+) $1.5KE22A$                          | 20.9                                                            | 23.1 | 1.0                              | 18.8                                 | 1.0                                                                             | 49.0                                                                   | 30.6                                                        | 0.092                                                    |
| 1N6280                  | (+) $1.5KE24$                           | 21.6                                                            | 26.4 | 1.0                              | 19.4                                 | 1.0                                                                             | 43.2                                                                   | 34.7                                                        | 0.094                                                    |
| 1N6280A                 | (+) $1.5KE24A$                          | 22.8                                                            | 25.2 | 1.0                              | 20.5                                 | 1.0                                                                             | 45.2                                                                   | 33.2                                                        | 0.094                                                    |
| 1N6281                  | (+) $1.5KE27$                           | 24.3                                                            | 29.7 | 1.0                              | 21.8                                 | 1.0                                                                             | 38.4                                                                   | 39.1                                                        | 0.096                                                    |
| 1N6281A                 | (+) $1.5KE27A$                          | 25.7                                                            | 28.4 | 1.0                              | 23.1                                 | 1.0                                                                             | 40.0                                                                   | 37.5                                                        | 0.096                                                    |
| 1N6282                  | (+) $1.5KE30$                           | 27.0                                                            | 33.0 | 1.0                              | 24.3                                 | 1.0                                                                             | 34.5                                                                   | 43.5                                                        | 0.097                                                    |
| 1N6282A                 | (+) $1.5KE30A$                          | 28.5                                                            | 31.5 | 1.0                              | 25.6                                 | 1.0                                                                             | 36.2                                                                   | 41.4                                                        | 0.097                                                    |
| 1N6283                  | (+) $1.5KE33$                           | 29.7                                                            | 36.3 | 1.0                              | 26.8                                 | 1.0                                                                             | 31.4                                                                   | 47.7                                                        | 0.098                                                    |
| 1N6283A                 | (+) $1.5KE33A$                          | 31.4                                                            | 34.7 | 1.0                              | 28.2                                 | 1.0                                                                             | 32.8                                                                   | 45.7                                                        | 0.098                                                    |
| 1N6284                  | (+) $1.5KE36$                           | 32.4                                                            | 39.6 | 1.0                              | 29.1                                 | 1.0                                                                             | 28.8                                                                   | 52.0                                                        | 0.099                                                    |
| 1N6284A                 | (+) $1.5KE36A$                          | 34.2                                                            | 37.8 | 1.0                              | 30.8                                 | 1.0                                                                             | 30.1                                                                   | 49.9                                                        | 0.099                                                    |
| 1N6285                  | (+) $1.5KE39$                           | 35.1                                                            | 42.9 | 1.0                              | 31.6                                 | 1.0                                                                             | 26.6                                                                   | 56.4                                                        | 0.100                                                    |
| 1N6285A                 | (+) $1.5KE39A$                          | 37.1                                                            | 41.0 | 1.0                              | 33.3                                 | 1.0                                                                             | 27.8                                                                   | 53.9                                                        | 0.100                                                    |
| 1N6286                  | (+) $1.5KE43$                           | 38.7                                                            | 47.3 | 1.0                              | 34.8                                 | 1.0                                                                             | 24.2                                                                   | 61.9                                                        | 0.101                                                    |
| 1N6286A                 | (+) $1.5KE43A$                          | 40.9                                                            | 45.2 | 1.0                              | 36.8                                 | 1.0                                                                             | 25.3                                                                   | 59.3                                                        | 0.101                                                    |
| 1N6287                  | (+) $1.5KE47$                           | 42.3                                                            | 51.7 | 1.0                              | 38.1                                 | 1.0                                                                             | 22.1                                                                   | 67.8                                                        | 0.101                                                    |
| 1N6287A                 | (+) $1.5KE47A$                          | 44.7                                                            | 49.4 | 1.0                              | 40.2                                 | 1.0                                                                             | 23.1                                                                   | 64.8                                                        | 0.101                                                    |
| 1N6288                  | (+) $1.5KE51$                           | 45.9                                                            | 56.1 | 1.0                              | 41.3                                 | 1.0                                                                             | 20.4                                                                   | 73.5                                                        | 0.102                                                    |
| 1N6288A                 | (+) $1.5KE51A$                          | 48.5                                                            | 53.6 | 1.0                              | 43.6                                 | 1.0                                                                             | 21.4                                                                   | 70.1                                                        | 0.102                                                    |
| 1N6289                  | (+) $1.5KE56$                           | 50.4                                                            | 61.8 | 1.0                              | 45.4                                 | 1.0                                                                             | 18.6                                                                   | 80.5                                                        | 0.103                                                    |
| 1N6289A                 | (+) $1.5KE56A$                          | 53.2                                                            | 58.8 | 1.0                              | 47.8                                 | 1.0                                                                             | 19.5                                                                   | 77.0                                                        | 0.103                                                    |
| 1N6290                  | (+) $1.5KE62$                           | 55.8                                                            | 68.2 | 1.0                              | 50.2                                 | 1.0                                                                             | 16.9                                                                   | 89.0                                                        | 0.104                                                    |
| 1N6290A                 | (+) $1.5KE62A$                          | 58.9                                                            | 65.1 | 1.0                              | 53.0                                 | 1.0                                                                             | 17.6                                                                   | 85.0                                                        | 0.104                                                    |
| 1N6291                  | (+) $1.5KE68$                           | 61.2                                                            | 74.8 | 1.0                              | 55.1                                 | 1.0                                                                             | 15.3                                                                   | 98.0                                                        | 0.104                                                    |
| 1N6291A                 | (+) $1.5KE68A$                          | 64.6                                                            | 71.4 | 1.0                              | 58.1                                 | 1.0                                                                             | 16.3                                                                   | 92.0                                                        | 0.104                                                    |
| 1N6292                  | (+) $1.5KE75$                           | 67.5                                                            | 82.5 | 1.0                              | 60.7                                 | 1.0                                                                             | 13.9                                                                   | 109                                                         | 0.105                                                    |
| 1N6292A                 | (+) $1.5KE75A$                          | 71.3                                                            | 78.8 | 1.0                              | 64.1                                 | 1.0                                                                             | 14.6                                                                   | 104                                                         | 0.105                                                    |



# 1.5KE6.8 thru 1.5KE540A, 1N6267 thru 1N6303

Vishay General Semiconductor

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25 °C unless otherwise noted)

| JEDEC<br>TYPE<br>NUMBER | GENERAL<br>SEMICONDUCTOR<br>PART NUMBER | BREAKDOWN<br>VOLTAGE<br>V <sub>BR</sub> AT I <sub>T</sub> <sup>(1)</sup><br>(V) |       | TEST<br>CURRENT<br>I <sub>T</sub><br>(mA) | STAND-OFF<br>VOLTAGE<br>V <sub>WM</sub> (V) | MAXIMUM<br>REVERSE<br>LEAKAGE<br>AT V <sub>WM</sub><br>I <sub>D</sub> <sup>(4)</sup> (μA) | MAXIMUM<br>PEAK<br>PULSE<br>CURRENT<br>I <sub>PPM</sub> <sup>(2)</sup> (A) | MAXIMUM<br>CLAMPING<br>VOLTAGE<br>AT I <sub>PPM</sub><br>V <sub>C</sub> (V) | MAXIMUM<br>TEMP.<br>COEFFICIENT<br>OF V <sub>BR</sub><br>(%/°C) |
|-------------------------|-----------------------------------------|---------------------------------------------------------------------------------|-------|-------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------|
|                         |                                         | MIN.                                                                            | MAX.  |                                           |                                             |                                                                                           |                                                                            |                                                                             |                                                                 |
| 1N6293                  | (+).1.5KE82                             | 73.8                                                                            | 90.2  | 1.0                                       | 66.4                                        | 1.0                                                                                       | 12.7                                                                       | 118                                                                         | 0.105                                                           |
| 1N6293A                 | (+).1.5KE82A                            | 77.9                                                                            | 86.1  | 1.0                                       | 70.1                                        | 1.0                                                                                       | 13.3                                                                       | 113                                                                         | 0.105                                                           |
| 1N6294                  | (+).1.5KE91                             | 81.9                                                                            | 100.0 | 1.0                                       | 73.7                                        | 1.0                                                                                       | 11.5                                                                       | 131                                                                         | 0.106                                                           |
| 1N6294A                 | (+).1.5KE91A                            | 86.5                                                                            | 95.5  | 1.0                                       | 77.8                                        | 1.0                                                                                       | 12.0                                                                       | 125                                                                         | 0.106                                                           |
| 1N6295                  | (+).1.5KE100                            | 90.0                                                                            | 110   | 1.0                                       | 81.0                                        | 1.0                                                                                       | 10.4                                                                       | 144                                                                         | 0.106                                                           |
| 1N6295A                 | (+).1.5KE100A                           | 95.0                                                                            | 105   | 1.0                                       | 85.5                                        | 1.0                                                                                       | 10.9                                                                       | 137                                                                         | 0.106                                                           |
| 1N6296                  | (+).1.5KE110                            | 99.0                                                                            | 121   | 1.0                                       | 89.2                                        | 1.0                                                                                       | 9.5                                                                        | 158                                                                         | 0.107                                                           |
| 1N6296A                 | (+).1.5KE 110A                          | 105                                                                             | 116   | 1.0                                       | 94.0                                        | 1.0                                                                                       | 9.9                                                                        | 152                                                                         | 0.107                                                           |
| 1N6297                  | (+).1.5KE120                            | 108                                                                             | 132   | 1.0                                       | 97.2                                        | 1.0                                                                                       | 8.7                                                                        | 173                                                                         | 0.107                                                           |
| 1N6297A                 | (+).1.5KE120A                           | 114                                                                             | 126   | 1.0                                       | 102                                         | 1.0                                                                                       | 9.1                                                                        | 165                                                                         | 0.107                                                           |
| 1N6298                  | (+).1.5KE130                            | 117                                                                             | 143   | 1.0                                       | 105                                         | 1.0                                                                                       | 8.0                                                                        | 187                                                                         | 0.107                                                           |
| 1N6298A                 | (+).1.5KE130A                           | 124                                                                             | 137   | 1.0                                       | 111                                         | 1.0                                                                                       | 8.4                                                                        | 179                                                                         | 0.107                                                           |
| 1N6299                  | (+).1.5KE150                            | 136                                                                             | 165   | 1.0                                       | 121                                         | 1.0                                                                                       | 7.0                                                                        | 215                                                                         | 0.108                                                           |
| 1N6299A                 | (+).1.5KE150A                           | 143                                                                             | 158   | 1.0                                       | 128                                         | 1.0                                                                                       | 7.2                                                                        | 207                                                                         | 0.106                                                           |
| 1N6300                  | (+).1.5KE160                            | 144                                                                             | 176   | 1.0                                       | 130                                         | 1.0                                                                                       | 6.5                                                                        | 230                                                                         | 0.106                                                           |
| 1N6300A                 | (+).1.5KE160A                           | 152                                                                             | 168   | 1.0                                       | 136                                         | 1.0                                                                                       | 6.8                                                                        | 219                                                                         | 0.108                                                           |
| 1N6301                  | (+).1.5KE170                            | 153                                                                             | 187   | 1.0                                       | 138                                         | 1.0                                                                                       | 6.1                                                                        | 244                                                                         | 0.108                                                           |
| 1N6301A                 | (+).1.5KE170A                           | 162                                                                             | 179   | 1.0                                       | 145                                         | 1.0                                                                                       | 6.4                                                                        | 234                                                                         | 0.108                                                           |
| 1N6302                  | 1.5KE180                                | 162                                                                             | 198   | 1.0                                       | 146                                         | 1.0                                                                                       | 5.8                                                                        | 258                                                                         | 0.108                                                           |
| 1N6302A                 | 1.5KE180A                               | 171                                                                             | 189   | 1.0                                       | 154                                         | 1.0                                                                                       | 6.1                                                                        | 246                                                                         | 0.108                                                           |
| 1N6303                  | 1.5KE200                                | 180                                                                             | 220   | 1.0                                       | 162                                         | 1.0                                                                                       | 5.2                                                                        | 287                                                                         | 0.108                                                           |
| 1N6303A                 | 1.5KE200A*                              | 190                                                                             | 210   | 1.0                                       | 171                                         | 1.0                                                                                       | 5.5                                                                        | 274                                                                         | 0.108                                                           |
|                         | 1.5KE220                                | 198                                                                             | 242   | 1.0                                       | 175                                         | 1.0                                                                                       | 4.4                                                                        | 344                                                                         | 0.108                                                           |
|                         | 1.5KE220A*                              | 209                                                                             | 231   | 1.0                                       | 185                                         | 1.0                                                                                       | 4.6                                                                        | 328                                                                         | 0.108                                                           |
|                         | 1.5KE250                                | 225                                                                             | 275   | 1.0                                       | 202                                         | 1.0                                                                                       | 4.2                                                                        | 360                                                                         | 0.110                                                           |
|                         | 1.5KE250A                               | 237                                                                             | 263   | 1.0                                       | 214                                         | 1.0                                                                                       | 4.4                                                                        | 344                                                                         | 0.110                                                           |
|                         | 1.5KE300                                | 270                                                                             | 330   | 1.0                                       | 243                                         | 1.0                                                                                       | 3.5                                                                        | 430                                                                         | 0.110                                                           |
|                         | 1.5KE300A                               | 285                                                                             | 315   | 1.0                                       | 256                                         | 1.0                                                                                       | 3.6                                                                        | 414                                                                         | 0.110                                                           |
|                         | 1.5KE350                                | 315                                                                             | 385   | 1.0                                       | 284                                         | 1.0                                                                                       | 3.0                                                                        | 504                                                                         | 0.110                                                           |
|                         | 1.5KE350A                               | 333                                                                             | 368   | 1.0                                       | 300                                         | 1.0                                                                                       | 3.1                                                                        | 482                                                                         | 0.110                                                           |
|                         | 1.5KE400                                | 360                                                                             | 440   | 1.0                                       | 324                                         | 1.0                                                                                       | 2.6                                                                        | 574                                                                         | 0.110                                                           |
|                         | 1.5KE400A                               | 380                                                                             | 420   | 1.0                                       | 342                                         | 1.0                                                                                       | 2.7                                                                        | 548                                                                         | 0.110                                                           |
|                         | 1.5KE440                                | 396                                                                             | 484   | 1.0                                       | 356                                         | 1.0                                                                                       | 2.4                                                                        | 631                                                                         | 0.110                                                           |
|                         | 1.5KE440A                               | 418                                                                             | 462   | 1.0                                       | 376                                         | 1.0                                                                                       | 2.5                                                                        | 602                                                                         | 0.110                                                           |
|                         | 1.5KE480                                | 432                                                                             | 528   | 1.0                                       | 389                                         | 1.0                                                                                       | 2.19                                                                       | 686                                                                         | 0.110                                                           |
|                         | 1.5KE480A                               | 456                                                                             | 504   | 1.0                                       | 408                                         | 1.0                                                                                       | 2.28                                                                       | 658                                                                         | 0.110                                                           |
|                         | 1.5KE510                                | 459                                                                             | 561   | 1.0                                       | 413                                         | 1.0                                                                                       | 2.06                                                                       | 729                                                                         | 0.110                                                           |
|                         | 1.5KE510A                               | 485                                                                             | 535   | 1.0                                       | 434                                         | 1.0                                                                                       | 2.15                                                                       | 698                                                                         | 0.110                                                           |
|                         | 1.5KE540                                | 486                                                                             | 594   | 1.0                                       | 437                                         | 1.0                                                                                       | 1.94                                                                       | 772                                                                         | 0.110                                                           |
|                         | 1.5KE540A                               | 513                                                                             | 567   | 1.0                                       | 459                                         | 1.0                                                                                       | 2.03                                                                       | 740                                                                         | 0.110                                                           |

### Notes:

(1) Pulse test: t<sub>p</sub> ≤ 50 ms

(2) Surge current waveform per Fig. 3 and derate per Fig. 2

(3) All terms and symbols are consistent with ANSI/IEEE CA62.35

(4) For bi-directional types with V<sub>R</sub> 10 V and less the I<sub>D</sub> limit is doubled

\* Bi-directional versions are UL approved under component across the line protection, ULV1414 file number E108274 (1.5KE200CA, 1.5KE220CA)

(+) Underwriters laboratory recognition for the classification of protectors (QVQG2) under the UL standard for safety 497B and file number E136766 for both uni-directional and bi-directional devices

**THERMAL CHARACTERISTICS** ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

| PARAMETER                                       | SYMBOL          | VALUE | UNIT                 |
|-------------------------------------------------|-----------------|-------|----------------------|
| Typical thermal resistance, junction to ambient | $R_{\theta JA}$ | 75    | $^{\circ}\text{C/W}$ |
| Typical thermal resistance, junction to lead    | $R_{\theta JL}$ | 15.4  |                      |

**ORDERING INFORMATION** (Example)

| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE                    |
|--------------------------------|-----------------|------------------------|---------------|----------------------------------|
| 1.5KE6.8A-E3/54                | 0.968           | 54                     | 1400          | 13" diameter paper tape and reel |
| 1.5KE6.8AHE3/54 <sup>(1)</sup> | 0.968           | 54                     | 1400          | 13" diameter paper tape and reel |

**Note:**

(1) Automotive grade AEC-Q101 qualified

**RATINGS AND CHARACTERISTICS CURVES**( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

Figure 1. Peak Pulse Power Rating Curve



Figure 3. Pulse Waveform



Figure 2. Pulse Power or Current vs. Initial Junction Temperature



Figure 4. Typical Junction Capacitance



Figure 5. Power Derating Curve



Figure 8. Incremental Clamping Voltage Curve (Uni-Directional)



Figure 6. Maximum Non-Repetitive Forward Surge Current  
Uni-Directional only



Figure 9. Incremental Clamping Voltage Curve (Bi-directional)



Figure 7. Incremental Clamping Voltage Curve (Uni-Directional)



Figure 10. Incremental Clamping Voltage Curve (Bi-Directional)



Figure 11. Instantaneous Forward Voltage Characteristics Curve



Figure 12. Typical Transient Thermal Impedance

### PACKAGE OUTLINE DIMENSIONS in inches (millimeters)



### APPLICATION NOTES

- This series of Silicon Transient Suppressors is used in applications where large voltage transients can permanently damage voltage-sensitive components.
- The TVS diode can be used in applications where induced lightning on rural or remote transmission lines presents a hazard to electronic circuitry (ref: R.E.A. specification P.E. 60).
- This Transient Voltage Suppressor diode has a pulse power rating of 1500 W for 1 ms. The response time of TVS diode clamping action is effectively instantaneous ( $1 \times 10^{-9}$  s bi-directional); therefore, they can protect integrated circuits, MOS devices, hybrids, and other voltage sensitive semiconductors and components. TVS diodes can also be used in series or parallel to increase the peak power ratings.



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)