Dual Input Digital Thermometers

710 715

Temperature Meters

Two fully functional, highly accurate meters offer dual K-type thermocouple inputs, RS-232 output port, and large LCD displays. Model 715 datalogging meter provides a triple LCD display that shows T1, T2 and T1-T2 simultaneously. The unit can log up to 16,000 datapoints with an adjustable interval. Model 710 offer a dual display where T1 and T2 can be switched between the large and small digits. While T1 - T2 is displayed on the large digits, T1 and T2 alternate on the small digits. With the optional ThermoLink software and RS-232 cable (AK-710), even Model 710 becomes a real-time datalogging meter when attached to a PC.

Model 710 Dual-Display

Both units offer:

- **Max/Min**
- **Data Hold**
- **°C/°F readings**
- **Auto Power Off**
- **RS-232 output ports**

Model 715

Datalogging Temperature Meter

- **Triple display**
- **Datalogging RS-232 port w/ cable and software**
- **Time reading**
- **AC adapter port**

Model 710

Temperature Meter

- **Dual display**
- **RS-232 port**
- **ΔRel Function**
- **Avg/Max/Min readings**
- **T1,T2 & T1-T2 select**
- **AC adapter port**

Specifications

models

	715	710
Measurement Range	-328°~2,498°F (-200°~1,370°C)	
Resolution	0.1°F (0.1°C)	
Accuracy	±0.2%rdg+2°F (±0.2%rdg+1°C)	
Sensor Type	K-type thermocouple	
Input Protection	60V DC or 24V rms AC Maximum	
Sample Rate	1 time per second	
Record (Datalogging)	16,000 Points	Does not apply
Datalogging Interval	00m:01s to 59m:59s	Does not apply
Operating Temp. & Humidity	32°~122°F (0°~50°C) & 10~80% RH	
Storage Temp	-4°~140°F (-20°~60°C)	
Power Supply	9V NEDA 1604 Battery (Optional Adapter BE-9)	
Battery Life	Approximately 100 hrs (Alkaline)	
Dimensions (LxWxH)	7.24 x 2.52 x 1.18" (184 x 64 x 30mm)	
Weight	11.3 oz. (320g)	1.66 lbs. (760g)

Accessories

One Year Warranty

SUPPLIED: Instruction manual, Battery, 2 Bead Probes and Large carry case, Battery, 2 Bead Probes and Small carry pouch.

OPTIONAL: BE-9 AC Adapter, AK-710 Thermolink Software w/RS-232 Cable (Model 710) See page 87 for K-type Thermocouple Probes

ООО «ЛайфЭлектроникс» “LifeElectronics” LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru