

EtherNet/IP Double-Ended Cord Sets

Cat5e, High-Flex, 2 Twisted Bonded Pair, Stranded/Unshielded, 24 AWG, TPE Jacket

| Type | 0985 806 112 | 0985 806 124 | 0985 806 126 | 0985 806 103 | 0985 806 104 | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------------------|--|---|--|--|---|--------------|---|-------------|---|--------|---|-------|--|--|--|-----|-------|------|---|--------------|---|---|-------------|---|---|--------|---|---|-------|---|
| Product Description | EtherNet/IP, high-flex, double-ended cord set, M12 female, straight to M12 female straight, 4-pin, D-coding, 24 AWG TPE cable, stranded/unshielded, 2 twisted bonded pair with teal jacket. | EtherNet/IP, high-flex, double-ended cord set, M12 male, right angle to M12 male right angle, 4-pin, D-coding, 24 AWG TPE cable, stranded/unshielded, 2 twisted bonded pair with teal jacket. | EtherNet/IP, high-flex, double-ended cord set, M12 male, right angle to RJ45 male, 4-pin, D-coding, 24 AWG TPE cable, stranded/unshielded, 2 twisted bonded pair with teal jacket. | EtherNet I/P, high-flex, double-ended cord set, M12 male to RJ45 male, 4 pin, D-coded, 24 AWG, teal TPE jacket, stranded/unshielded cable with 2 twisted bonded pairs. | EtherNet/IP, high-flex, double-ended cord set, M12 female 4 pin, D-coded receptacle to male RJ45, 24 AWG, teal TPE jacket, stranded/unshielded with 2 bonded twisted pairs. | | | | | | | | | | | | | | | | | | | | | | | | | |
| Technical Illustration |  |  |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | |
| Wiring diagram | <table border="1"> <thead> <tr> <th>M12</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>White Orange</td> </tr> <tr> <td>2</td> <td>White Green</td> </tr> <tr> <td>3</td> <td>Orange</td> </tr> <tr> <td>4</td> <td>Green</td> </tr> </tbody> </table> | | M12 | Color | 1 | White Orange | 2 | White Green | 3 | Orange | 4 | Green | <table border="1"> <thead> <tr> <th>M12</th> <th>Color</th> <th>RJ45</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>White Orange</td> <td>1</td> </tr> <tr> <td>2</td> <td>White Green</td> <td>3</td> </tr> <tr> <td>3</td> <td>Orange</td> <td>2</td> </tr> <tr> <td>4</td> <td>Green</td> <td>6</td> </tr> </tbody> </table> | | | M12 | Color | RJ45 | 1 | White Orange | 1 | 2 | White Green | 3 | 3 | Orange | 2 | 4 | Green | 6 |
| M12 | Color | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | White Orange | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | White Green | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | Orange | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | Green | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M12 | Color | RJ45 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | White Orange | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | White Green | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | Orange | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | Green | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Face views |  |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Part number | 0985 806 112/...M | 0985 806 124/...M | 0985 806 126/...M | 0985 806 103/...M | 0985 806 104/...M | | | | | | | | | | | | | | | | | | | | | | | | | |
| Standard cable lengths | 0.5 M / 1 M / 2 M / 5 M / 10 M | 0.5 M / 1 M / 2 M / 5 M / 10 M / 15 M / 20 M / 30 M / 35 M / 40 M / 45 M / 50 M / 60 M / 70 M / 80 M | 0.5 M / 1 M / 2 M / 5 M / 10 M / 15 M / 20 M / 25 M / 30 M / 35 M | 0.5 M / 1 M / 2 M / 5 M / 10 M / 15 M / 20 M / 25 M / 30 M / 35 M | 0.5 M / 1 M / 2 M / 5 M / 10 M / 15 M / 20 M / 25 M / 30 M / 35 M | | | | | | | | | | | | | | | | | | | | | | | | | |

Be Certain with Belden

EtherNet/IP Double-Ended Cord Sets

Cat5e, High-Flex, 2 Twisted Bonded Pair, Stranded/Unshielded, 24 AWG, TPE Jacket

| Type | 0985 806 112 | 0985 806 124 | 0985 806 126 | 0985 806 103 | 0985 806 104 |
|----------------------------------|---|--------------|--------------|--|--------------|
| Degree of protection | IP68 | | | IP68 / IP20 | |
| Temperature | -40°C to 75°C | | | -20°C to 60°C | |
| Mechanical | | | | | |
| M12 and M12 Receptacle | | | | | |
| Molded body | PUR, black | | | | |
| Coupling nut | Brass, nickel plated | | | | |
| Contacts | Brass, gold plated | | | | |
| Insert | PUR, black | | | | |
| RJ45 | | | | | |
| Plug | Polycarbonate | | | | |
| Contacts | Phosphor Bronze, gold plated | | | | |
| Boot | Elastomer Polyolefin | | | | |
| Electrical | | | | | |
| Current rating | 4A | | | 1.5 A | |
| Voltage rating | 250V | | | 30V AC / 42V DC | |
| Performance | Cat5e, Belden bonded twisted pair cable | | | | |
| Cable specifications | | | | | |
| Cable jacket | TPE | | | | |
| Color | Teal | | | | |
| Overall diameter | .275" | | | | |
| Conductor | 24 AWG stranded tinned copper | | | | |
| Temperature | Operating: -40°C to 75°C / Installation: -25°C to 75°C | | | | |
| Flame test | UL: CMR / CSA: CMG | | | | |
| Continuous Flex | 2 million cycles @ 10X, 10 million cycles @ 20X bend radius | | | | |
| Characteristics | | | | | |
| | | | | <p>NOTE: Vibration & Oil Resistant applies to M12 side only.</p> | |
| Recommended panel cut out | | | | | |
| | | | | | |

The application of these products in harsh environments should always be checked before use.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru