


EH CONNECTOR

Radial Tape

2.5mm pitch/Disconnectable Crimp style connectors



This, the thinnest, 2.5mm pitch connector, is 8.1mm in height after mounting and 3.8mm in width. It is designed to meet the demand for the high-density connection of internal wires to printed circuit boards. It is compact, highly reliable and low in cost.

- ***Compact and slim***
- ***Highly reliable contact***
- ***Polarizing guides***
- ***Easy and effective crimping***

Specifications

- Current rating: 3A AC, DC (AWG #22)
- Voltage rating: 250V AC, DC
- Temperature range: -25˚C to +85˚C
  (including temperature rise in applying electrical current)
- Contact resistance: Initial value/ 10m Ω max.
  After environmental testing/ 20m Ω max.
- Insulation resistance: 1,000M Ω min.
- Withstanding voltage: 800V AC/minute
- Applicable wire: AWG #32 to #22
- Applicable PC board thickness: 0.8 to 1.6mm

* Compliant with RoHS.
* Refer to "General Instruction and Notice when using Terminals and Connectors" at the end of this catalog.
* Contact JST for details.


Standards

Recognized E60389


Certified LR20812

R50082349


Top entry type



Side entry type




Radial-tape



Note: 1. The above figure is the figure viewed from soldering side.
2. Tolerances are non-cumulative: ±0.05mm for all centers.
3. Hole dimension differ according to the kind of PC board and piercing method. If PC boards made of hard material are used, the hole dimensions should be larger. The dimensions above should serve as a guideline. Contact JST for details.

Contact



Model No.	Applicable wire		Insulation O.D. (mm)	Q'ty / reel
	mm²	AWG#		
SEH-001T-P0.6	0.05 ~0.33	30~22	1.0~1.9	9,000
***SEH-001T-P0.6L**	0.13 ~0.33	26~22	0.9~1.9	
***SEH-002T-P0.6L**	0.05 ~0.13	30~26	0.9~1.3	
***SEH-003T-P0.6L**	0.032~0.08	32~28	0.5~1.1	10,000

Material and Finish
Phosphor bronze, tin-plated (reflow treatment)

RoHS compliance


Note: 1. Contact JST for gold-plated products.
2. SEH-00( )T-P0.6L is low-insertion force type contact, for easier insertion/withdrawal, which would be less resistant to the vibration. The crimp height is different from the standard contact.
*3. *Marked products are not TÜV approved.*
4. Contact JST for details.

Contact	Crimping machine	Applicator		
		Crimp applicator	Dies	Crimp applicator with dies
SEH-001T-P0.6	AP-K2N	MKS-L	MK/SEH-001-06	APLMK SEH001-06
		*MKS-SC	SC/SEH-001-06	APLSC SEH001-06
SEH-001T-P0.6L		MKS-L	MK/SEH-001-06L	APLMK SEH001-06L
		*MKS-SC	SC/SEH-001-06L	APLSC SEH001-06L

*Note: *Strip-crimp applicator*

Contact	Crimping machine	Applicator		
		Crimp applicator	Dies	Crimp applicator with dies
SEH-002T-P0.6L	AP-K2N	MKS-L	MK/SEH-002-06L	APLMK SEH002-06L
		—	—	—
SEH-003T-P0.6L		MKS-L-10	MK/SEH-003-06L	APLMK SEH003-06L
		*MKS-SC-10	SC/SEH-003-06L	APLSC SEH003-06L

Housing



Circuits	Model No.	Dimensions (mm)		Q'ty / bag
		A	B	
2	**EHR-2**	2.5	7.0	1,000
3	**EHR-3**	5.0	9.5	1,000
4	**EHR-4**	7.5	12.0	1,000
5	**EHR-5**	10.0	14.5	1,000
6	**EHR-6**	12.5	17.0	1,000
7	**EHR-7**	15.0	19.5	1,000
8	**EHR-8**	17.5	22.0	1,000
9	**EHR-9**	20.0	24.5	1,000
10	**EHR-10**	22.5	27.0	1,000
11	**EHR-11**	25.0	29.5	1,000
12	**EHR-12**	27.5	32.0	1,000
13	**EHR-13**	30.0	34.5	1,000
14	**EHR-14**	32.5	37.0	1,000
15	**EHR-15**	35.0	39.5	1,000

Material
PA 66, UL94V-0, natural (white)

RoHS compliance

<For reference> As the color identification, the following alphabet shall be put in the underlined part. For availability, delivery and minimum order quantity, contact JST.

ex. **EHR-2-oo**


(blank)…natural (white)
K…black R…red TR…tomato red E…blue Y…yellow
L…lemon yellow M…green O…orange N…brown PL…purple
PK…pink H…gray LE…light blue FY…vivid yellow

Shrouded header


The shrouded headers are interchangeable with those of the HR crimp style and insulation displacement connectors.

Top entry type


(2 circuits)



(3 to 15 circuits)



Side entry type



Circuits	Model No.		Dimensions (mm)		Q'ty / box	
	Top entry type	Side entry type	A	B	Top entry type	Side entry type
2	**B2B-EH-A**	**S2B-EH**	2.5	7.5	1,000	1,000
3	**B3B-EH-A**	**S3B-EH**	5.0	10.0	1,000	1,000
4	**B4B-EH-A**	**S4B-EH**	7.5	12.5	1,000	1,000
5	**B5B-EH-A**	**S5B-EH**	10.0	15.0	1,000	1,000
6	**B6B-EH-A**	**S6B-EH**	12.5	17.5	1,000	500
7	**B7B-EH-A**	**S7B-EH**	15.0	20.0	1,000	500
8	**B8B-EH-A**	**S8B-EH**	17.5	22.5	500	500
9	**B9B-EH-A**	**S9B-EH**	20.0	25.0	500	500
10	**B10B-EH-A**	**S10B-EH**	22.5	27.5	500	500
11	**B11B-EH-A**	**S11B-EH**	25.0	30.0	500	250
12	**B12B-EH-A**	**S12B-EH**	27.5	32.5	500	250
13	**B13B-EH-A**	**S13B-EH**	30.0	35.0	250	250
14	**B14B-EH-A**	**S14B-EH**	32.5	37.5	250	250
15	**B15B-EH-A**	**S15B-EH**	35.0	40.0	250	250

Material and Finish
Post: Brass, copper-undercoated, tin-plated (reflow treatment) Wafer: PA 66, UL94V-0, natural (white)

RoHS compliance *This product displays (LF)(SN) on a label.*

Note: Also available and identified as model BxxB-EH is a top entry type having a post extension length of 4.0mm

<For reference> As the color identification, the following alphabet shall be put in the underlined part. For availability, delivery and minimum order quantity, contact JST.

<Top entry type>

ex. **B2B-EH-A-oo**

(blank)…natural (white)
K…black R…red E…blue Y…yellow M…green

<Side entry type>


ex. **S2B-EH-oo**

(blank)…natural (white)
K…black R…red TR…tomato red E…blue Y…yellow
L…lemon yellow M…green O…orange N…brown P…purple
PK…pink H…gray LE…light blue FY…vivid yellow


Shrouded header on radial-tape

●**TS type**


(2 circuits)



(3 to 8 circuits)



●**TV4 type**



Circuits	Model No.		Dimensions (mm)		Q'ty / box
	TS type	TV4 type	A	B	
2	**B2B-EH-TS**	—	—	—	1,400
3	**B3B-EH-TS**	**B3B-EH-TV4**	5.0	10.0	1,400
4	**B4B-EH-TS**	**B4B-EH-TV4**	7.5	12.5	700
5	**B5B-EH-TS**	**B5B-EH-TV4**	10.0	15.0	700
6	**B6B-EH-TS**	**B6B-EH-TV4**	12.5	17.5	700
7	**B7B-EH-TS**	**B7B-EH-TV4**	15.0	20.0	700
8	**B8B-EH-TS**	**B8B-EH-TV4**	17.5	22.5	700


Material and Finish
Pin/Post: Brass, copper-undercoated, tin-plated (reflow treatment) Wafer: PA 66, UL94V-0, natural (white)

RoHS compliance *This product displays (LF)(SN) on a label.*

<For reference> As the color identification,
the following alphabet shall be put in the underlined part.
For availability, delivery and minimum order quantity, contact JST.


ex. **B2B-EH-TS-oo**
(blank)…natural (white)
K…black R…red E…blue Y…yellow M…green N…brown

Taping specifications




Note: Conforms to JIC C 0806 of "Tape packaging of components with unidirectional leads on continuous tapes".

Packaging specifications



Distance between the end of the tape and
the first connector's center line (either end)



Package type		Flat pack (zigzag folded)
Distance between folds		24 indexing holes per fold (304.8mm)
Box size		316(W)×45(D)×330(H)mm
Distance between the end of the tape and the first connector's center line (either end)		19.05mm
Quantity	2, 3 circuits	1,400 pcs. / box
	4～8 circuits	700 pcs. / box

Note: Products of different packaging specifications are also available. Contact JST for details.

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru