OD1238 XJ Series

DC Fan 12V

120x38mm (4.7″x 1.5″)



Frame & Impeller	PBT, UL94V-O plastic
Connecion	3x Lead wires *
Motor	Brushless DC, auto restart, polarity protected.
Bearing System	Dual ball bearing
Insulation Resistance	Min. 10M at 500VDC
Dielectric Strength	1 minute at 500 VAC, max leakage < 500 MicroAmp
Temperature Range	-10C ~ +70C
Storage Temperature	-40C ~ +80C
Life (L10)	70,000 hours (40C)

Tachometer - Open Collector

Weight: ~ 375 g

* Connection
UL1007, 24AWG, ~320mm
Red (+)
Black (-)
White Tachometer

m1



Part Number	OD1238-12HBXJ01A
Nominal Voltage	12V DC
Voltage Range	7 ~ 13.2V DC
Rated Current	3.70 A
Rated Power	44.4 W
Rated Speed (RPM)	6000
Airflow (CFM)	250
Noise Level (dB)	69
Max. Static Pressure	1.48" H_2O

*Output type.....Open collector type
*Electrical design suggestion:



*Transistor Q1 at "ON" position
Collector current.....I_C=10mA Max
Saturation Voltage.....V_{OL}=1.0V Max
(Between Collector and Emitter at I_C=10mA)
*Transistor Q1 at "OFF" position
Release Voltage.....V_{OH}=15V Max

Knight Electronics, Inc.
10557 Metric Drive
Dallas, Texas 75243
214-340-0265

RoHS Compliant

Orion Fans

Information and data is subject to change without prior notification.

OD1238 XJ Series

DC Fan 12V

120x38mm (4.7"x 1.5")



Frame & Impeller	PBT, UL94V-O plastic
Connecion	4x Lead wires *
Motor	Brushless DC, auto restart, polarity protected.
Bearing System	Dual ball bearing
Insulation Resistance	Min. 10M at 500VDC
Dielectric Strength	1 minute at 500 VAC, max leakage < 500 MicroAmp
Temperature Range	-10C ~ +70C
Storage Temperature	-40C ~ +80C
Life (L10)	70,000 hours (40C)

———

Tachometer - Open Collector PWM

Weight: ~ 375 g

* Connection
UL1007, 24AWG, ~320mm
Red (+)
Black (-)
White Tachometer
Blue PWM

m1



Part Number	OD1238-12HBXJ10A
Nominal Voltage	12V DC
Voltage Range	7 ~ 13.2V DC
Rated Current	3.70 A
Rated Power	44.4 W
Rated Speed (RPM)	6000
Airflow (CFM)	250
Noise Level (dB)	69
Max. Static Pressure	1.48" H_2O

(External signal function design is decided by customer)



*TRANSISTOR Q1 AT "ON" POSITION
COLLECTOR CURRENT---------- I_C =10mA MAX
SATURATION VOLTAGE---------- V_{OL}=1 V MAX
*TRANSISTOR Q1 AT "OFF" POSITION
RELEASE VOLTAGE---------- V_{OH}=15 V MAX
*DIGITAL PWM SPEED CONTROL POSITION
PWM INPUT VOLTAGE HIGH---------- V_{IH}=3V~5.5 V
PWM INPUT VOLTAGE LOW---------- V_{IL}= 0V~0.5V

*PWM INPUT FREQUENCY---------- FPWM:18KHZ~30KHZ

Knight Electronics, Inc.
10557 Metric Drive
Dallas, Texas 75243
214-340-0265

RoHS Compliant

Orion Fans
Information and data is subject to change without prior notification.

OD1238 XJ Series

DC Fan 12V

120x38mm (4.7"x 1.5")



Frame & Impeller	PBT, UL94V-O plastic
Connecion	3x Lead wires *
Motor	Brushless DC, auto restart, polarity protected.
Bearing System	Dual ball bearing
Insulation Resistance	Min. 10M at 500VDC
Dielectric Strength	1 minute at 500 VAC, max leakage < 500 MicroAmp
Temperature Range	-10C ~ +70C
Storage Temperature	-40C ~ +80C
Life (L10)	70,000 hours (40C)

Tachometer - Open Collector

Weight: ~ 375 g

* Connection
UL1007, 24AWG, ~320mm
Red (+)
Black (-)
White Tachometer

m1



Part Number	OD1238-12MBXJ01A
Nominal Voltage	12V DC
Voltage Range	7 ~ 13.2V DC
Rated Current	2.30 A
Rated Power	27.6 W
Rated Speed (RPM)	5000
Airflow (CFM)	207
Noise Level (dB)	63
Max. Static Pressure	1.04" H_2O

*Output type.....Open collector type
*Electrical design suggestion:



*Transistor Q1 at "ON" position
Collector current.....I_C=10mA Max
Saturation Voltage.....V_{OL}=1.0V Max
(Between Collector and Emitter at I_C=10mA)
*Transistor Q1 at "OFF" position
Release Voltage.....V_{OH}=15V Max

Knight Electronics, Inc.
10557 Metric Drive
Dallas, Texas 75243
214-340-0265

RoHS Compliant

Orion Fans

Information and data is subject to change without prior notification.

OD1238 XJ Series

DC Fan 12V

120x38mm (4.7"x 1.5")



Frame & Impeller	PBT, UL94V-O plastic
Connecion	4x Lead wires *
Motor	Brushless DC, auto restart, polarity protected.
Bearing System	Dual ball bearing
Insulation Resistance	Min. 10M at 500VDC
Dielectric Strength	1 minute at 500 VAC, max leakage < 500 MicroAmp
Temperature Range	-10C ~ +70C
Storage Temperature	-40C ~ +80C
Life (L10)	70,000 hours (40C)

Tachometer - Open Collector PWM

Weight: ~ 375 g

* Connection
UL1007, 24AWG, ~320mm
Red (+)
Black (-)
White Tachometer
Blue PWM

m1



Part Number	OD1238-12MBXJ10A
Nominal Voltage	12V DC
Voltage Range	7 ~ 13.2V DC
Rated Current	2.30 A
Rated Power	27.6 W
Rated Speed (RPM)	5000
Airflow (CFM)	207
Noise Level (dB)	63
Max. Static Pressure	1.04" H_2O

(External signal function design is decided by customer)



*TRANSISTOR Q1 AT "ON" POSITION
COLLECTOR CURRENT---------- I_C =10mA MAX
SATURATION VOLTAGE---------- V_{OL}=1 V MAX
*TRANSISTOR Q1 AT "OFF" POSITION
RELEASE VOLTAGE---------- V_{OH}=15 V MAX
*DIGITAL PWM SPEED CONTROL POSITION
PWM INPUT VOLTAGE HIGH---------- V_{IH}=3V~5.5 V
PWM INPUT VOLTAGE LOW---------- V_{IL}= 0V~0.5V

*PWM INPUT FREQUENCY----------FPWM:18KHZ~30KHZ

Knight Electronics, Inc.
10557 Metric Drive
Dallas, Texas 75243
214-340-0265

RoHS Compliant

Orion Fans

Information and data is subject to change without prior notification.

OD1238-24HBXJ01A

DC Fan 24V

120x38mm (4.7″x 1.5″)



Frame & Impeller	PBT, UL94V-O plastic
Connecion	3x Lead wires *
Motor	Brushless DC, auto restart, polarity protected.
Bearing System	Dual ball bearing
Insulation Resistance	Min. 10M at 500VDC
Dielectric Strength	1 minute at 500 VAC, max leakage < 500 MicroAmp
Temperature Range	-10C ~ +70C
Storage Temperature	-40C ~ +80C
Life (L10)	70,000 hours (40C)

Tachometer - Open Collector

Weight: ~ 375 g

* Connection
UL1007, 24AWG, ~320mm
Red (+)
Black (-)
White Tachometer

m1



Part Number	OD1238-24HBXJ01A
Nominal Voltage	24V DC
Voltage Range	17 ~ 26.4V DC
Nominal Current	1.75 A
Nominal Power	42 W
Rated Speed (RPM)	6000
Airflow (CFM)	250
Noise Level (dB)	69
Max. Static Pressure	1.48” H2O

*Output type.....Open collector type
*Electrical design suggestion:
(External signal function design is decided by customer)



*Transistor Q1 at "ON" position
Collector current.....I_C=10mA Max
Saturation Voltage.....V_{OL}=1.0V Max
(Between Collector and Emitter at I_C=10mA)
*Transistor Q1 at "OFF" position
Release Voltage.....V_{OH}=30V Max

*Output waveform



Knight Electronics, Inc.
10557 Metric Drive
Dallas, Texas 75243
214-340-0265

RoHS Compliant

Orion Fans

Information and data is subject to change without prior notification.

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru