



Features

- Advanced Planar Technology
- Low On-Resistance
- Logic Level Gate Drive
- Dual N and P Channel MOSFET
- Surface Mount
- Fully Avalanche Rated
- Lead-Free, RoHS Compliant
- Automotive Qualified *



| | N-CH | P-CH |
|--------------------------|--------|--------|
| V_{DSS} | 30V | -30V |
| $R_{DS(on)}$ typ. | 0.023Ω | 0.042Ω |
| max. | 0.029Ω | 0.058Ω |
| I_D | 6.5A | -4.9A |



| G | D | S |
|------|-------|--------|
| Gate | Drain | Source |

Description

Specifically designed for Automotive applications, these HEXFET® Power MOSFET's in a Dual SO-8 package utilize the latest processing techniques to achieve extremely low on-resistance per silicon area. Additional features of these Automotive qualified HEXFET Power MOSFET's are a 150°C junction operating temperature, fast switching speed and improved repetitive avalanche rating. These benefits combine to make this design an extremely efficient and reliable device for use in Automotive applications and a wide variety of other applications. The efficient SO-8 package provides enhanced thermal characteristics and dual MOSFET die capability making it ideal in a variety of power applications. This dual, surface mount SO-8 can dramatically reduce board space and is also available in Tape & Reel.

| Base part number | Package Type | Standard Pack | | Orderable Part Number |
|------------------|--------------|---------------|----------|-----------------------|
| | | Form | Quantity | |
| AUIRF7319Q | SO-8 | Tape and Reel | 4000 | AUIRF7319QTR |

Absolute Maximum Ratings

Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only; and functional operation of the device at these or any other condition beyond those indicated in the specifications is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability. The thermal resistance and power dissipation ratings are measured under board mounted and still air conditions. Ambient temperature (TA) is 25°C, unless otherwise specified.

| Symbol | Parameter | Max. | | Units |
|--------------------------|---|--------------|-----------|-------|
| | | N-Channel | P-Channel | |
| V_{DS} | Drain-Source Voltage | 30 | -30 | V |
| $I_D @ T_A = 25^\circ C$ | Continuous Drain Current, $V_{GS} @ 10V$ | 6.5 | -4.9 | A |
| $I_D @ T_A = 70^\circ C$ | Continuous Drain Current, $V_{GS} @ 10V$ | 5.2 | -3.9 | |
| I_{DM} | Pulsed Drain Current ① | 30 | -30 | |
| I_S | Continuous Source Current (Diode Conduction) | 2.5 | -2.5 | |
| $P_D @ T_A = 25^\circ C$ | Maximum Power Dissipation ⑤ | 2.0 | | W |
| $P_D @ T_A = 70^\circ C$ | Maximum Power Dissipation ⑤ | 1.3 | | |
| E_{AS} | Single Pulse Avalanche Energy (Thermally Limited) ③ | 82 | 140 | mJ |
| I_{AR} | Avalanche Current | 4.0 | -2.8 | A |
| E_{AR} | Repetitive Avalanche Energy | 0.20 | | mJ |
| V_{GS} | Gate-to-Source Voltage | ± 20 | | V |
| dv/dt | Peak Diode Recovery dv/dt ② | 5.0 | -5.0 | V/ns |
| T_J T_{STG} | Operating Junction and Storage Temperature Range | -55 to + 150 | | °C |

Thermal Resistance

| Symbol | Parameter | Typ. | Max. | Units |
|-----------------|--|------|------|-------|
| $R_{\theta JA}$ | Junction-to-Ambient (PCB Mount, steady state) ⑤ | — | 62.5 | °C/W |

HEXFET® is a registered trademark of Infineon.

*Qualification standards can be found at www.infineon.com

Static @ T_J = 25°C (unless otherwise specified)

| | Parameter | | Min. | Typ. | Max. | Units | Conditions |
|--|--------------------------------------|------|------|--------|-------|-------|---|
| V _{(BR)DSS} | Drain-to-Source Breakdown Voltage | N-Ch | 30 | — | — | V | V _{GS} = 0V, I _D = 250μA |
| | | P-Ch | -30 | — | — | | V _{GS} = 0V, I _D = -250μA |
| ΔV _{(BR)DSS} /ΔT _J | Breakdown Voltage Temp. Coefficient | N-Ch | — | 0.022 | — | V/°C | Reference to 25°C, I _D = 1mA |
| | | P-Ch | — | -0.022 | — | | Reference to 25°C, I _D = -1mA |
| R _{DS(on)} | Static Drain-to-Source On-Resistance | N-Ch | — | 0.023 | 0.029 | Ω | V _{GS} = 10V, I _D = 5.8A ④ |
| | | | — | 0.032 | 0.046 | | V _{GS} = 4.5V, I _D = 4.7A ④ |
| | | P-Ch | — | 0.042 | 0.058 | | V _{GS} = -10V, I _D = -4.9A ⑤ |
| | | | — | 0.076 | 0.098 | | V _{GS} = -4.5V, I _D = -3.6A ④ |
| V _{GS(th)} | Gate Threshold Voltage | N-Ch | 1.0 | — | 3.0 | V | V _{DS} = V _{GS} , I _D = 250μA |
| | | P-Ch | -1.0 | — | -3.0 | | V _{DS} = V _{GS} , I _D = -250μA |
| g _{fs} | Forward Trans conductance | N-Ch | — | 14 | — | S | V _{DS} = 15V, I _D = 5.8A ④ |
| | | P-Ch | — | 7.7 | — | | V _{DS} = -15V, I _D = -4.9A ④ |
| I _{DSS} | Drain-to-Source Leakage Current | N-Ch | — | — | 1.0 | μA | V _{DS} = 24V, V _{GS} = 0V |
| | | P-Ch | — | — | -1.0 | | V _{DS} = -24V, V _{GS} = 0V |
| | | N-Ch | — | — | 25 | | V _{DS} = 24V, V _{GS} = 0V, T _J = 55°C |
| | | P-Ch | — | — | -25 | | V _{DS} = -24V, V _{GS} = 0V, T _J = 55°C |
| I _{GSS} | Gate-to-Source Forward Leakage | N-P | — | — | ± 100 | nA | V _{GS} = ± 20V |
| | Gate-to-Source Reverse Leakage | N-P | — | — | ± 100 | | V _{GS} = ± 20V |

Dynamic Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

| | | | | | | | |
|---------------------|------------------------------|------|---|-----|-----|----|---|
| Q _g | Total Gate Charge | N-Ch | — | 22 | 33 | nC | N-Channel I _D = 5.8A, V _{DS} = 15V, V _{GS} = 10V ④ |
| | | P-Ch | — | 23 | 34 | | |
| Q _{gs} | Gate-to-Source Charge | N-Ch | — | 2.6 | 3.9 | nC | P-Channel I _D = -4.9A, V _{DS} = -15V, V _{GS} = -10V |
| | | P-Ch | — | 3.8 | 5.7 | | |
| Q _{gd} | Gate-to-Drain Charge | N-Ch | — | 6.4 | 9.6 | nC | P-Channel I _D = -4.9A, V _{DS} = -15V, V _{GS} = -10V |
| | | P-Ch | — | 5.9 | 8.9 | | |
| t _{d(on)} | Turn-On Delay Time | N-Ch | — | 8.1 | 12 | ns | N-Channel V _{DD} = 15V, I _D = 1.0A, R _G = 6.0Ω, R _D = 15Ω ④ |
| | | P-Ch | — | 13 | 19 | | |
| t _r | Rise Time | N-Ch | — | 8.9 | 13 | ns | P-Channel V _{DD} = -15V, I _D = -1.0A, R _G = 6.0Ω, R _D = 15Ω ④ |
| | | P-Ch | — | 13 | 20 | | |
| t _{d(off)} | Turn-Off Delay Time | N-Ch | — | 26 | 39 | ns | P-Channel V _{DD} = -15V, I _D = -1.0A, R _G = 6.0Ω, R _D = 15Ω ④ |
| | | P-Ch | — | 34 | 51 | | |
| t _f | Fall Time | N-Ch | — | 17 | 26 | ns | P-Channel V _{DD} = -15V, I _D = -1.0A, R _G = 6.0Ω, R _D = 15Ω ④ |
| | | P-Ch | — | 32 | 48 | | |
| C _{iss} | Input Capacitance | N-Ch | — | 650 | — | pF | N-Channel V _{GS} = 0V, V _{DS} = 25V, f = 1.0MHz |
| | | P-Ch | — | 710 | — | | |
| C _{oss} | Output Capacitance | N-Ch | — | 320 | — | pF | P-Channel V _{GS} = 0V, V _{DS} = -25V, f = 1.0MHz |
| | | P-Ch | — | 380 | — | | |
| C _{rss} | Reverse Transfer Capacitance | N-Ch | — | 130 | — | pF | P-Channel V _{GS} = 0V, V _{DS} = -25V, f = 1.0MHz |
| | | P-Ch | — | 180 | — | | |

Diode Characteristics

| | Parameter | | Min. | Typ. | Max. | Units | Conditions |
|-----------------|--|------|------|-------|------|-------|---|
| I _S | Continuous Source Current (Body Diode) | N-Ch | — | — | 2.5 | A | |
| | | P-Ch | — | — | -2.5 | | |
| I _{SM} | Pulsed Source Current (Body Diode) ① | N-Ch | — | — | 30 | A | |
| | | P-Ch | — | — | -30 | | |
| V _{SD} | Diode Forward Voltage | N-Ch | — | 0.78 | 1.0 | V | T _J = 25°C, I _S = 1.7A, V _{GS} = 0V ④ |
| | | P-Ch | — | -0.78 | -1.0 | | T _J = 25°C, I _S = -1.7A, V _{GS} = 0V ④ |
| t _{rr} | Reverse Recovery Time | N-Ch | — | 45 | 68 | ns | N-Channel T _J = 25°C, I _F = 1.7A, di/dt = 100A/μs |
| | | P-Ch | — | 44 | 66 | | |
| Q _{rr} | Reverse Recovery Charge | N-Ch | — | 58 | 87 | nC | P-Channel T _J = 25°C, I _F = -1.7A, di/dt = 100A/μs ④ |
| | | P-Ch | — | 42 | 63 | | |

Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature. (See Fig. 22)
- ② N-Channel I_{SD} ≤ 4.0A, di/dt ≤ 74A/μs, V_{DD} ≤ V_{(BR)DSS}, T_J ≤ 150°C.
P-Channel I_{SD} ≤ -2.8A, di/dt ≤ 150A/μs, V_{DD} ≤ V_{(BR)DSS}, T_J ≤ 150°C
- ③ N-Channel Starting T_J = 25°C, L = 10mH, R_G = 25Ω, I_{AS} = 4.0A. (See Fig. 12)
P-Channel Starting T_J = 25°C, L = 35mH, R_G = 25Ω, I_{AS} = -2.8A.
- ④ Pulse width ≤ 300μs; duty cycle ≤ 2%.
- ⑤ Surface mounted on FR-4 board, t ≤ 10sec.




Fig. 1 Typical Output Characteristics




Fig. 2 Typical Output Characteristics




Fig. 3 Typical Transfer Characteristics




Fig. 4 Typical Source-Drain Diode Forward Voltage




Fig 5. Normalized On-Resistance Vs. Temperature




Fig 6. Typical On-Resistance Vs. Drain Current




Fig 7 Typical On-Resistance Vs. Gate Voltage




Fig 8. Maximum Avalanche Energy Vs. Drain Current




Fig 9. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 10. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient




Fig. 12 Typical Output Characteristics




Fig. 13 Typical Output Characteristics




Fig. 14 Typical Transfer Characteristics




Fig. 15 Typical Source-Drain Diode Forward Voltage




Fig 16. Normalized On-Resistance Vs. Temperature




Fig 17. Typical On-Resistance Vs. Drain Current




Fig 18 Typical On-Resistance Vs. Gate Voltage




Fig 19. Maximum Avalanche Energy Vs. Drain Current




Fig 20. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 21. Typical Gate Charge Vs. Gate-to-Source Voltage







Fig 22. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient


SO-8 Package Outline (Dimensions are shown in millimeters (inches))




| DIM | INCHES | | MILLIMETERS | |
|-----|------------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | .0532 | .0688 | 1.35 | 1.75 |
| A1 | .0040 | .0098 | 0.10 | 0.25 |
| b | .013 | .020 | 0.33 | 0.51 |
| c | .0075 | .0098 | 0.19 | 0.25 |
| D | .189 | .1968 | 4.80 | 5.00 |
| E | .1497 | .1574 | 3.80 | 4.00 |
| e | .050 BASIC | | 1.27 BASIC | |
| e 1 | .025 BASIC | | 0.635 BASIC | |
| H | .2284 | .2440 | 5.80 | 6.20 |
| K | .0099 | .0196 | 0.25 | 0.50 |
| L | .016 | .050 | 0.40 | 1.27 |
| y | 0° | 8° | 0° | 8° |




- NOTES:
1. DIMENSIONING & TOLERANCING PER ASME Y14.5M -1994.
 2. CONTROLLING DIMENSION: MILLIMETER
 3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
 4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA.
 5. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.15 [0.006].
 6. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.25 [0.010].
 7. DIMENSION IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE.



SO-8 Part Marking Information



SO-8 Tape and Reel (Dimensions are shown in millimeters (inches))

NOTES:

1. CONTROLLING DIMENSION : MILLIMETER.
2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
3. OUTLINE CONFORMS TO EIA-481 & EIA-541.


NOTES :

1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Qualification Information

| | | | |
|-----------------------------------|----------------------|---|------|
| Qualification Level | | Automotive (per AEC-Q101) | |
| | | Comments: This part number(s) passed Automotive qualification. Infineon's Industrial and Consumer qualification level is granted by extension of the higher Automotive level. | |
| Moisture Sensitivity Level | | SO-8 | MSL1 |
| ESD | Machine Model | Class M2 (+/- 200V) [†] AEC-Q101-002 | |
| | Human Body Model | Class H1A (+/- 500V) [†] AEC-Q101-001 | |
| | Charged Device Model | Class C5 (+/- 2000V) [†] AEC-Q101-005 | |
| RoHS Compliant | | Yes | |

† Highest passing voltage.

Revision History

| Date | Comments |
|-----------|--|
| 3/4/2014 | <ul style="list-style-type: none"> Added "Logic Level Gate Drive" bullet in the features section on page 1 Updated data sheet with new IR corporate template |
| 9/30/2015 | <ul style="list-style-type: none"> Updated datasheet with corporate template Corrected ordering table on page 1. |

Published by
Infineon Technologies AG
81726 München, Germany
 © Infineon Technologies AG 2015
All Rights Reserved.

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffungsgarantie"). With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (www.infineon.com).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru