





Thermal Transfer Labels

PANDUIT®

Thermal Transfer Labels

Panduit is a global leader in reliable and innovative solutions for identification and safety. Products are engineered for a wide variety of industries and applications – including electrical, electronics, industrial, and network. Panduit offers a complete, leading-edge line of labeling software, high-performance label materials (all RoHS compliant), and printers that provide enhanced productivity, dependability, and value to all infrastructure labeling requirements.





Cable/Wire Labels

Turn-Tell® Labels	4
Self-Laminating Labels	5 – 7
LabelCore™ Fiber Optic Cable Identification System	7 – 8
Flag Labels	8
Non-Laminated Vinyl Cloth Labels	9
Non-Laminated Nylon Cloth Labels	10

Marker Plates

High-Temperature Flame-Retardant Marker Plates	11
Halogen-Free Flame-Retardant Marker Plates	11
Standard Marker Plates	12

Heat Shrink Labels

Military Grade – Single-Sided Labels	13
Military Grade – Two-Sided Labels	14
Halogen-Free – Two-Sided Labels	15
Fluid-Resistant – Two-Sided Labels	16

Component Labels/Continuous Tapes

Raised Panel Labels	17 – 20
Polyester Component Labels	21
Super-Tack Polyester Component Labels	22
Tedlar® Component Labels	23
Tamper-Evident Polyester Component Labels	23
Non-Adhesive Polyester Component Labels	24
Vinyl Cloth Component Labels	24
Polyimide Component Labels	25
Paper Component Labels	26
Continuous Tapes	26 – 28

Safety and Solar Labels

Super-Tack Polyester Arc Flash Labels	29
Raised Panel Arc Flash Labels	29
Super-Tack Arc Flash Continuous Tapes	30
Super-Tack Polyester Facility Identification Labels	30
Polyester Photoluminescent Tapes	31
Raised Panel Solar Labels	31
Over-Laminate Labels	32
Super-Tack Polyester Solar Labels	32
Reflective Continuous Tapes for Solar Applications	32

Software/Printers/Accessories

Software	33
TDP43ME Printers, Accessories and Ribbons	34
TDP43HE & TDP46HE Printers, Accessories & Ribbons	35


Tedlar is a registered trademark of E.I. du Pont de Nemours and Company.

Turn-Tell® Labels



- Allows labels to rotate for visibility from any angle, and allows repositioning on the wire/cable to align legends for improved aesthetics

- Ideal for use in high-density or space-constrained cable applications
- Use thermal transfer hybrid ribbon
- Temperature range: -40°F to 150°F (-40°C to 66°C)



Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.		
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm					
R050X075V1T	White	0.50	12.7	0.75	19.1	0.25	6.4	0.12	3.1	0.16	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	8	5000		
R050X125V1T				1.25	31.8	0.38	9.7	0.16	4.1	0.22	5.6	Cat. 3 UTP/12 – 10 AWG				
R050X150V1T				1.50	38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/ Cat. 6A UTP/Cat. 5e FTP/ 10 – 6 AWG				
R100X075V1T		TIA Blue TIA Green TIA Gray TIA Red TIA Yellow White TIA Blue TIA Green TIA Gray TIA Red TIA Yellow	1.00	25.4	0.75	19.1	0.25	6.4	0.12	3.1	0.16	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	4	2500	
R100X125V1T	1.25				31.8	0.38	9.7	0.16	4.1	0.22	5.6	Cat. 3 UTP/12 – 10 AWG				
R100X150V1T	1.50				38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/ Cat. 6A UTP/				
R100X150V2T																
R100X150V3T																
R100X150V4T	2.25				57.2	0.75	19.1	0.28	7.1	0.39	9.9	Cat. 6 FTP/Cat. 6 UTP/ Cat. 6A FTP/8-4 AWG				
R100X150V7T																
R100X150V8T																
R100X225V1T	4.00				101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG				
R100X225V2T																
R100X225V3T																
R100X225V4T	1.50				38.1	0.50	12.7	0.22	5.6	0.28	7.1	0.39	9.9			Cat. 6 FTP/Cat. 6A UTP/ Cat. 6A FTP/8-4 AWG
R100X225V7T																
R100X225V8T																
R100X400V1T	White				1.50	38.1	4.00	101.6	1.00	25.4	0.39	9.9	0.95		24.1	2 – 1 AWG
R150X150V1T		1.50	38.1	0.50			12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/ Cat. 6A UTP/Cat. 5e FTP/ 10 – 6 AWG				
R200X150V1T		2.00	50.8	2.25	57.2	0.75	19.1	0.28	7.1	0.39	9.9	Cat. 6 FTP/Cat. 6A UTP/ Cat. 6A FTP/8 – 4 AWG	4			
R200X225V1T				4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG	2			
R200X400V1T				4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG	2			

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Vinyl Self-Laminating Labels

- Includes a colored print-on area and clear overlamine to protect the legend for clear and durable identification
- Sized specifically for wire and cable applications
- Thin and conformable; preferred material for most general wire/cable labeling

- Use thermal transfer hybrid ribbon
- Temperature range: -40°F to 150°F (-40°C to 66°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15-01, File # MH14979



	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.			Labels Per Row	Std. Pkg. Qty.	
Part Number		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	Wire Range			
S050X075VA1Y	White	0.50	12.7	0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.1	Cat. 6 28 AWG/ 18 – 14 AWG	8	5000	
S050X075VATY*														2500	
S050X125VA1Y				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/ 12 - 10 AWG		5000	
S050X125VATY*															
S050X150VA1Y				1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG			
S050X150VATY*				2.50	63.5	1.00	25.4	0.32	8.1	0.48	12.1	6 – 2 AWG			
S075X075VATY*				0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.0	Cat. 6 28 AWG/ 18 – 14 AWG			5
S075X100VATY*		1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/ 12 - 10 AWG					
S075X125VATY*															
S075X150VATY*		1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG					
S100X075VA1Y			1.00	25.4	0.75	19.1	0.25	6.4	0.08	0.50	2.0	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	4	2500
S100X075VATY*															5000
S100X125VA1Y		1.25			31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/ 12 - 10 AWG	2500		
S100X125VATY*													5000		
S100X150VA1Y														5000	
S100X150VATY															
S100X150VBTY		TIA Blue			1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/10 - 6 AWG		
S100X150CVTY	TIA Brown														
S100X150VDTY	TIA Green														
S100X150VETY	TIA Gray														
S100X150VFTY	TIA Orange														
S100X150VGTY	TIA Purple														

Order number of labels required in multiples of Standard Package Quantity.

*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Vinyl Self-Laminating Labels (continued)

	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.																		
Part Number		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm																					
S100X150VHTY*	TIA Red	1.00	25.4	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/ Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG	4	5000																		
S100X150VITY*	TIA Yellow																															
S100X150V0TY*	Black																															
S100X150V9TY*	Gold																															
S100X225VA1Y	White			2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/8 – 4 AWG																				
S100X225VATY*	White																															
S100X225VBTY*	TIA Blue																															
S100X225VCTY*	TIA Brown																															
S100X225VDTY*	TIA Green																															
S100X225VETY*	TIA Gray																															
S100X225VFTY*	TIA Orange																															
S100X225VGTY*	TIA Purple																															
S100X225VHTY*	TIA Red																															
S100X225VITY*	TIA Yellow																															
S100X225V0TY*	Black																															
S100X225V9TY*	Gold																															
S100X250VA1Y	White	2.50	63.5	1.00	25.4	0.32	8.1	0.48	12.1	6 - 2 AWG	1500																					
S100X250VATY*											5000																					
S100X400VA1Y											4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 - 1 AWG	1000												
S100X400VATY*																				2500												
S100X650VA1Y		6.50	165.1	1.50	38.1	0.48	12.1	1.59	40.4	1/0 - 250 MCM	250																					
S100X650VATY*											1000																					
S150X150VATY*		1.50	38.1	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG	5000																			
S150X225VATY*														2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	8 – 4 AWG										
S150X400VATY*														4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.1	2 – 1 AWG	2500									
S200X150VATY*		2.00	50.8	1.50	38.1	0.50	21.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG	2	5000																		
S200X225VA1Y	2.25														57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/8 - 4 AWG	500									
S200X225VATY*																							2.50	63.5	1.00	25.4	0.32	8.1	0.48	12.1	6 – 2 AWG	1000
S200X250VATY*																																500
S200X400VA1Y				4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 - 1 AWG		500																		
S200X400VATY*	1000																															
S200X650VA1Y	6.50			165.1	1.50	38.1	0.48	12.1	1.59	40.4	1/0 - 250 MCM	250																				
S200X650VATY*												1000																				

Order number of labels required in multiples of Standard Package Quantity.

*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

PVDF Self-Laminating Labels

- Self-extinguishing material and recommended alternative to Tedlar®
- Sized specifically for wire and cable applications
- Use thermal transfer hybrid ribbon

- Temperature range: -65°F to 275°F (-54°C to 135°C)
- UL969 recognized File # MH14979; cUL recognized C22.2 No. 0.15.01, File # MH149799



Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm			
S050X150T1T	White	0.50	12.7	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 - 6 AWG	8	5000
S075X125T1T		0.75	19.1	1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/12 - 10 AWG	5	
S100X075T1T		1.00	25.4	0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.0	Cat. 6 28 AWG/18 - 14 AWG	4	2500
S100X125T1T				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	12 - 10 AWG		
S100X150T1T				1.50	38.1	0.50	12.7	0.16	4.0	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 - 6 AWG		
S100X225T1T				2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/8 - 4 AWG		1500
S100X400T1T		2.00	50.8	4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 - 1 AWG	2	2500
S200X400T1T														500

Tedlar® is a registered trademark of E.I. du Pont de Nemours and Company.


Order number of labels required in multiples of Standard Package Quantity.

*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

LabelCore™ Fiber Optic Cable Identification System

PATENTED

- Provides a larger labeling surface on small fiber cables and allows legends to be clearly seen
- Sleeves are made of flexible PVC material
- Locate sleeve on straight section of cable at least 2 inches from fiber boot



Part Number	Color	Part Description	Std. Pkg. Qty.
NWSLC-2Y	Yellow	Yellow cable identification sleeve for 2mm simplex fiber cable, 1" long, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	100
NWSLC-2Y-AQ	Aqua	Aqua cable identification sleeve for 2mm simplex cable, 1" long, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	
NWSLC-3Y	Orange	Orange cable identification sleeve for 3mm simplex cable, 1" long, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	
NWSLC-7Y	White	White cable identification sleeve for 3mm duplex fiber cable, 1" long, use with labels: S100X225YAJ (Laser/Inkjet); S100X225VAC (LS8E Hand-held Printer); S100X225VATY or S200X225VATY (Thermal Transfer Printer).	

Order number of labels required in multiples of Standard Package Quantity.


LabelCore™ Fiber Optic Cable Identification System (continued)

Part Number	Color	Part Description	Std. Pkg. Qty.
NWSLC2-2Y	Yellow	Yellow cable identification sleeve for 2mm simplex cable, 2 inches long, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	100
NWSLC2-2Y-AQ	Aqua	Aqua cable identification sleeve for 2mm simplex cable, 2 inches long, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	
NWSLC2-3Y	Orange	Orange cable identification sleeve for 3mm simplex cable, 2 inches long, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	
NWSLC2-7Y	White	White cable identification sleeve for 3mm duplex fiber cable, 2 inches long, use with labels: S200X225YAJ (Laser/Inkjet) S200X225VATY (Thermal Transfer Printer).	

Order number of labels required in multiples of Standard Package Quantity.

Flag Labels

- Halogen-free, white polyester flag-style marker for wire/cable labeling
- Improved legibility and more information on small wires and cables provide clearer, more complete identification
- Innovative design allows the product to be applied as a permanent adhesive label or as a repositionable non-adhesive label
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14576 and File # MH14979; cUL recognized C22.2 No. 0.15-01, File # MH14979



Part Number	Width		Height		Print-On Area				Min. Cable O.D.		Max. Cable O.D.		Wire Range	Std. Pkg. Qty. Roll
	In.	mm	In.	mm	Width		Height		In.	mm	In.	mm		
F100X150AJT	1.00	25.4	1.50	38.1	0.88	22.4	0.75	19.1	0.12	3.1	0.20	5.1	12 – 10 AWG	2500
F100X213AJT			2.13	54.1					0.32	8.1	0.38	9.7	Cat. 5e – Cat. 6	
F100X300AJT			3.00	76.2			2.00	50.8	0.09	2.3	0.28	7.1	8 – 4 AWG	
F100X363AJT			3.63	92.2					0.20	5.1	0.46	11.7	2 – 1 AWG	

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME Printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Non-Laminated Vinyl Cloth Labels

- Thin and conformable material with repositionable adhesive allows label to be removed and reused in temporary applications
- Works well on Teflon[®] coated wires*
- Use thermal transfer hybrid ribbon
- Temperature range: -40° F to 170° F (-40° C to 77° C)
- UL969 recognized, File # MH14576 and MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14576



Part Number	Print-On Area Color	Width		Length		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm			
N025X075CBT	White	0.25	6.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	7	10000
N025X125CBT				1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		2500
N025X150CBT				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		
N025X175CBT				1.75	44.5	0.28	7.1	0.48	12.2	6 – 1 AWG		10000
N050X075CBT		0.50	12.7	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG		
N050X100CBT				1.00	25.4	0.16	4.1	0.24	6.1	10 – 8 AWG		
N050X125CBT				1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		
N050X150CBT				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		2500
N050X175CBT				1.75	44.5	0.28	7.1	0.48	12.2	6 – 1 AWG		
N100X075CBT		1.00	25.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	3	10000
N100X125CBT				1.25	31.8	0.20	4.1	0.32	8.1	10 – 6 AWG		5000
N100X150CBT				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		
N100X175CBT				1.75	44.5	0.28	7.1	0.48	12.2	6 – 1 AWG		2500
N150X075CBT		1.50	38.1	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	1	5000

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME Printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

* Teflon[®] is a registered trademark of E. I du Pont de Nemours and Company

Non-Laminated Nylon Cloth Labels

- Offer crisp, clear legends with superior legibility
- Used in flat applications and in a wrap format for wire/cable marking
- Use thermal transfer resin ribbon
- Temperature range: -65°F to 275°F (-54°C to 135°C)



Part Number	Color	Width		Length		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm			
N050X075C1T	White	0.50	12.7	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	5	10000
N050X075C2T	Yellow											
N050X125C1T	White			1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		
N050X125C2T	Yellow											
N050X150C1T	White			1.50	38.1	0.24	6.1	0.40	10.5	8 – 2 AWG		5000
N050X150C2T	Yellow											
N100X075C1T	White	1.00	25.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	3	10000
N100X075C2T	Yellow											
N100X125C1T	White			1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		5000
N100X125C2T	Yellow											
N100X150C1T	White			1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		
N100X150C2T	Yellow											

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME Printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

High-Temperature Flame-Retardant Marker Plates

- Used for identification markers in (Class 1E) harsh environments
- Compatible with Intermediate Cross Section cable ties
- Use thermal transfer RMER4BL-A resin ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)



Part Number	Color	Width		Height		Print-On Area Width		Labels Per Roll	Std. Pkg. Qty. (Roll)		
		In.	mm	In.	mm	In.	mm				
M200X042FQT	White	2.00	50.8	0.42	10.7	1.22	31.0	500	1		
M200X042FQT-B								2000			
M200X080FQT				0.80	20.3			250			
M200X080FQT-B								1000			

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Halogen-Free Flame-Retardant Marker Plates

- Used to identify wires, cables, equipment, and many other applications
- Offer crisp, clear legend with superior legibility and engineered to withstand high temperatures, harsh solvents, oils, and chemicals without over-lamination
- Compatible with Intermediate Cross Section cable ties
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 193°F (-40°C to 90°C)



Part Number	Color	Width		Height		Print-On Area Width		Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm		
M200X042UPT	White	2.00	50.8	0.42	10.7	1.30	33.0	500	1
M200X042UPT-B								2000	
M200X080UPT				0.80	20.3			500	
M200X080UPT-B								2000	


Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Standard Marker Plates

- Non-adhesive and halogen free; used to identify wires, cables, equipment, and many other applications
- Attachable in horizontal or vertical orientation. The 0.5" Plenum rated and 0.33" non-Plenum rated Hook & Loop Cable Ties can be used in hanging position

- Meets the outgassing requirements of ASTM E-595 suitable for use in air handling spaces
- Available in a variety of colors and sizes
- Use thermal transfer resin ribbon
- Temperature range: -58°F to 221°F (-50°C to 105°C)



		Width		Height		Print-On Area Width			Labels Per Roll	Std. Pkg. Qty. (Roll)
Part Number	Color	In.	mm	In.	mm	In.	mm	Cable Type		
M200X050Y6T	TIA Yellow	2.00	50.8	0.50	12.7	1.07	27.3	Intermediate Cross Section Cable Ties	500	1
M200X050Y7T	White									
M200X050ACT	TIA Blue									
M200X050AET	TIA Green									
M200X050AFT	TIA Gray									
M200X050AGT	TIA Orange									
M200X050AIT	TIA Red									
M200X100Y6T	TIA Yellow			1.00	25.4	0.80	20.3	Standard Cross Section Cable Ties	2000	
M200X100Y6T-B									500	
M200X100Y7T	White								2000	
M200X100Y7T-B										
M200X100ACT	TIA Blue									
M200X100AET	TIA Green									
M200X100AFT	TIA Gray									
M200X100AGT	TIA Orange									
M200X100AIT	TIA Red									
M300X050Y6T	TIA Yellow	3.00	76.2	0.50	12.7	2.07	52.6	Intermediate Cross Section Cable Ties	500	
M300X050Y7T	White									
M300X050ACT	TIA Blue									
M300X050AET	TIA Green									
M300X050AFT	TIA Gray									
M300X050AGT	TIA Orange									
M300X050AIT	TIA Red									
M300X100Y6T	TIA Yellow			1.00	25.4	1.80	45.7	Standard Cross Section Cable Ties		
M300X100Y7T	White									
M300X100ACT	TIA Blue									
M300X100AET	TIA Green									
M300X100AFT	TIA Gray									
M300X100AGT	TIA Orange									
M300X100AIT	TIA Red									

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Military Grade Single-Sided Heat Shrink Labels

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Meet UL Standard 224 with a VW-1 rating for flammability and AMS-DTL-23053/5C (Class 1 and Class 3)
- Meet SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin and hybrid thermal transfer ribbons
- Shrink ratio 3:1
- Tested for use as an identification marker in (Class 1E) harsh environments
- Use thermal transfer hybrid ribbon or white resin ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)
- UL224 recognized, File # E205133; CSA certified, C22.2 No. 198.1.06, File # 256205



				Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.						
Part Number	Part Number	Part Number	Part Number	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)	
H050X025H1T*	H050X025H2T	H050X025H3T	H050X025H4T	0.13	3.1	0.50	12.7	0.25	6.4	0.04	1.0	0.13	3.3	22 – 18 AWG	4	2000	1	
H075X025H1T*	H075X025H2T	H075X025H3T	H075X025H4T			0.75	19.1								2	1000		
H100X025H1T*	H100X025H2T	H100X025H3T	H100X025H4T			1.00	25.4								1	500		
H150X025H1T*	H150X025H2T	H150X025H3T	H150X025H4T			1.50	38.1								18 – 12 AWG	4		
H200X025H1T*	H200X025H2T	H200X025H3T	H200X025H4T			2.00	50.8											
H050X034H1T*	H050X034H2T	H050X034H3T	H050X034H4T	0.19	4.7	0.50	12.7	0.34	8.6	0.06	1.5	0.19	4.8	18 – 12 AWG	4	2000		
H075X034H1T*	H075X034H2T	H075X034H3T	H075X034H4T			0.75	19.1								2	1000		
H100X034H1T*	H100X034H2T	H100X034H3T	H100X034H4T			1.00	25.4								1	500		
H150X034H1T*	H150X034H2T	H150X034H3T	H150X034H4T			1.50	38.1								16 – 10 AWG	4		
H200X034H1T*	H200X034H2T	H200X034H3T	H200X034H4T			2.00	50.8											
H050X044H1T*	H050X044H2T	H050X044H3T	H050X044H4T	0.25	6.3	0.50	12.7	0.44	11.2	0.08	2.0	0.25	6.4	16 – 10 AWG	4	2000		
H075X044H1T*	H075X044H2T	H075X044H3T	H075X044H4T			0.75	19.1								2	1000		
H100X044H1T*	H100X044H2T	H100X044H3T	H100X044H4T			1.00	25.4								1	500		
H150X044H1T*	H150X044H2T	H150X044H3T	H150X044H4T			1.50	38.1								12 – 6 AWG	4		
H200X044H1T*	H200X044H2T	H200X044H3T	H200X044H4T			2.00	50.8											
H050X064H1T*	H050X064H2T	H050X064H3T	H050X064H4T	0.38	9.7	0.50	12.7	0.64	16.3	0.13	3.3	0.38	9.7	12 – 6 AWG	4	2000		
H100X064H1T*	H100X064H2T	H100X064H3T	H100X064H4T			1.00	25.4								2	1000		
H200X064H1T*	H200X064H2T	H200X064H3T	H200X064H4T			2.00	50.8								1	500		
H050X084H1T	—	—	—	0.50	12.7	0.50	12.7	0.84	21.3	0.17	4.3	0.50	12.7	8 – 1 AWG	4	2000		
H100X084H1T	H100X084H2T	H100X084H3T	H100X084H4T			1.00	25.4								2	1000		
H200X084H1T	H200X084H2T	H200X084H3T	H200X084H4T			2.00	50.8								1	500		
H050X165H1T	—	—	—	1.00	25.4	0.50	12.7	1.65	41.9	0.33	8.4	1.00	25.4	4 AWG–500 MCM	4	2000		
H100X165H1T	H100X165H2T	H100X165H3T	H100X165H4T			1.00	25.4								2	500		
H200X165H1T	H200X165H2T	H200X165H3T	H200X165H4T			2.00	50.8								1	250		
H200X240H1T	H200X240H2T	—	—	1.50	38.1	2.00	50.8	2.40	61.0	0.50	12.7	1.50	38.1	1 AWG - 1000 MCM	1	100		

Order number of labels required in multiples of Standard Package Quantity.

*Available in Bulk packages (5 times Labels Per Roll), add -B to end of part number

Military Grade Two-Sided Heat Shrink Labels

PATENTED

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Can be printed on both sides for improved visibility
- Meet the material requirements and physical properties of AMS-DTL-23053/5C (Class 1 and Class 3) and UL standard 224 with a VW-1 rating
- Meet SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B and D, and MIL-STD-202G Method 215K, Solutions A,C and D when printed using resin or hybrid thermal transfer ribbons
- Shrink ratio 3:1
- Tested as an identification marker for use in (Class 1E) harsh environments
- Use thermal transfer hybrid ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)
- UL224 recognized, File # E205133; CSA certified, C22.2 No. 198.1-06, File # 256205




Part Number	Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H100X025H1T-2	H100X025H2T-2	0.13	3.1	1.00	25.4	0.25	6.4	0.04	1.0	0.13	3.3	22 – 18 AWG	2	1000	1
H100X025H1T-2-B	H100X025H2T-2-B			1.00	25.4								1	5000	
H200X025H1T-2	H200X025H2T-2			2.00	50.8								1	500	
H200X025H1T-2-B	H200X025H2T-2-B			2.00	50.8								1	2500	
H100X034H1T-2	H100X034H2T-2	0.19	4.7	1.00	25.4	0.34	8.6	0.06	1.5	0.19	4.8	18 – 12 AWG	2	1000	
H100X034H1T-2-B	H100X034H2T-2-B			1.00	25.4								1	5000	
H200X034H1T-2	H200X034H2T-2			2.00	50.8								1	500	
H200X034H1T-2-B	H200X034H2T-2-B			2.00	50.8								1	2500	
H100X044H1T-2	H100X044H2T-2	0.25	6.3	1.00	25.4	0.44	11.2	0.08	2.0	0.25	6.4	16 – 10 AWG	2	1000	
H100X044H1T-2-B	H100X044H2T-2-B			1.00	25.4								1	5000	
H200X044H1T-2	H200X044H2T-2			2.00	50.8								1	500	
H200X044H1T-2-B	H200X044H2T-2-B			2.00	50.8								1	2500	
H100X064H1T-2	H100X064H2T-2	0.38	9.7	1.00	25.4	0.64	16.3	0.13	3.3	0.38	9.7	12 – 6 AWG	2	1000	
H100X064H1T-2-B	H100X064H2T-2-B			1.00	25.4								1	5000	
H200X064H1T-2	H200X064H2T-2			2.00	50.8								1	500	
H200X064H1T-2-B	H200X064H2T-2-B			2.00	50.8								1	2500	
H100X084H1T-2	H100X084H2T-2	0.50	12.7	1.00	25.4	0.84	21.3	0.17	4.3	0.50	12.7	8 – 1 AWG	2	1000	
H100X084H1T-2-B	H100X084H2T-2-B			1.00	25.4								1	5000	
H200X084H1T-2	H200X084H2T-2			2.00	50.8								1	500	
H200X084H1T-2-B	H200X084H2T-2-B			2.00	50.8								1	2500	
H100X122H1T-2	H100X122H2T-2	0.75	19.0	1.00	25.4	1.22	31.0	0.25	6.3	0.75	19.0	8 – 4/0 AWG	2	500	
H200X122H1T-2	H200X122H2T-2			2.00	50.8								1	250	
H100X165H1T-2	H100X165H2T-2	1.00	25.4	1.00	25.4	1.65	41.9	0.33	8.4	1.00	25.4	4 AWG – 500 MCM	2	500	
H200X165H1T-2	H200X165H2T-2			2.00	25.4								1	250	

Order number of labels required in multiples of Standard Package Quantity.

Halogen-Free Two-Sided Heat Shrink Labels



- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Can be printed on both sides for improved visibility
- Meet SAE-AS5942, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin and hybrid thermal transfer ribbons
- Meet BS6853; 1999 Vehicle Category 1A for burning behavior and toxic gas emissions; Smoke Density Class II
- Shrink ratio 2:1
- Use thermal transfer hybrid ribbon
- Temperature range: -22°F to 221°F (-30°C to 105°C)



Part Number	Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H100X025HFT-2	H100X025HGT-2	0.13	3.1	1.00	25.4	0.25	6.4	0.06	1.5	0.13	3.3	22 – 18 AWG	2	1000	1
H200X025HFT-2	H200X025HGT-2			2.00	50.8								1	500	
H100X034HFT-2	H100X034HGT-2	0.19	4.7	1.00	25.4	0.34	8.6	0.09	2.3	0.19	4.8	18 – 12 AWG	2	1000	
H200X034HFT-2	H200X034HGT-2			2.00	50.8								1	500	
H100X044HFT-2	H100X044HGT-2	0.25	6.4	1.00	25.4	0.44	11.1	0.13	3.3	0.25	6.4	16 – 10 AWG	2	1000	
H200X044HFT-2	H200X044HGT-2			2.00	50.8								1	500	
H100X064HFT-2	H100X064HGT-2	0.38	9.7	1.00	25.4	0.64	16.2	0.19	4.8	0.38	9.7	12 – 6 AWG	2	1000	
H200X064HFT-2	H200X064HGT-2			2.00	50.8								1	500	
H100X084HFT-2	H100X084HGT-2	0.50	12.7	1.00	25.4	0.84	21.3	0.25	6.4	0.50	12.7	8 – 1 AWG	2	1000	
H200X084HFT-2	H200X084HGT-2			2.00	50.8								1	500	
H100X165HFT-2	H100X165HGT-2	1.00	25.4	1.00	25.4	1.65	41.9	0.50	12.7	1.00	25.4	8 AWG – 500 MCM	2		
H200X165HFT-2	H200X165HGT-2			2.00	50.8								1	250	

Order number of labels required in multiples of Standard Package Quantity.

Fluid-Resistant Two-Sided Heat Shrink Labels

PATENTED

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Cross-linked, semi-rigid, fluid-resistant, shrinkable polyolefin material
- Available in yellow only
- Can be printed on both sides for improved visibility
- Meet the material requirements and physical properties AMS-DTL-23053/6 Class 1 and NF F00-608 Class A and H when printed with resin thermal transfer ribbons
- Meet SAE-AS5942, MIL-STD-883F Method 2015.13 Solutions A and D, and MIL-STD-202G Method 215K, Solutions A and D when printed with resin thermal transfer ribbons
- Shrink ratio 3:1
- Use thermal transfer RMER4BL-C resin ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)



Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H100X034HST-2	0.19	4.7	1.00	25.4	0.34	8.6	0.06	1.5	0.19	4.8	18 – 12 AWG	2	1000	1
H200X034HST-2			2.00	50.8								1	500	
H100X044HST-2	0.25	6.4	1.00	25.4	0.44	11.1	0.08	2.0	0.25	6.4	16 – 10 AWG	2	1000	
H200X044HST-2			2.00	50.8								1	500	
H100X064HST-2	0.38	9.7	1.00	25.4	0.64	16.2	0.13	3.3	0.38	9.7	12 – 6 AWG	2	1000	
H200X064HST-2			2.00	50.8								1	500	
H100X084HST-2	0.50	12.7	1.00	25.4	0.84	21.3	0.17	4.3	0.50	12.7	8 – 1 AWG	2	1000	
H200X084HST-2			2.00	50.8								1	500	
H100X165HST-2	1.00	25.4	1.00	25.4	1.65	41.9	0.33	8.4	1.00	25.4	4 AWG – 500 MCM	2		
H200X165HST-2			2.00	50.8								1	250	

Order number of labels required in multiples of Standard Package Quantity.

Raised Panel Push Button Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder coated surfaces
- Provide crisp, clear, and durable legends for your reliable, high-performance identification needs
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposure)
- Meet ASTM D3389 standard for abrasion resistance and also meet solar application standards
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



		Width		Height		Print-On Area Height		Hole Diameter		Labels Per Row	Std. Pkg. Qty.
Part Number	Color	In.	mm	In.	mm	In.	mm	In.	mm		
C120X150APT-22	White	1.20	30.5	1.50	38.1	0.45	11.4	0.87	22.0	3	500
C120X150A8T-22	Yellow										
C120X150AST-22	Green										
C120X150AWT-22	Red										
C120X150A0T-22	Black										
C120X190APT-22	White	1.20	30.5	1.90	48.3	0.85	21.6				
C120X190A8T-22	Yellow										
C120X190AST-22	Green										
C120X190AWT-22	Red										
C120X190A0T-22	Black										
C180X180APT-30	White	1.80	45.7	1.80	45.7	0.36	9.1	1.18	30.0	2	
C180X180A8T-30	Yellow										
C180X180AST-30	Green										
C180X180AWT-30	Red										
C180X180A0T-30	Black										
C240X240APT-30	White	2.40	61.0	2.40	61.0	0.90	22.9			1	
C240X240A8T-30	Yellow										
C240X240AST-30	Green										
C240X240AWT-30	Red										
C240X240A0T-30	Black										

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Raised Panel Push Button Over-Laminate Labels

- Provide additional print protection in harsh environments
- Over-laminates are not printable
- Temperature range: -51°F to 275°F (-46°C to 135°C)

Part Number	Color	Width		Height		Hole Diameter		Labels Per Roll	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm		
C120X150YK-22	Clear	1.20	30.5	1.50	38.1	0.87	22.0	3	500
C120X190YK-22				1.90	48.3				
C180X180YK-30		1.80	45.7	1.80	45.7	1.18	30.0	2	
C240X240YK-30		2.40	60.9	2.40	60.9	1.18	30.0	1	

Order number of labels required in multiples of Standard Package Quantity.

Raised Panel Half Push Button Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder-coated surfaces
- Provide crisp, clear, and durable legends for your reliable, high-performance identification needs
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Height		Print-On Area Height		Hole Diameter		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm		
C180X130APT-30H	White	1.80	45.7	1.30	33.0	0.73	18.5	1.18	30.0	1	500
C240X200APT-30H		2.40	61.0	2.00	50.8	1.43	36.3				

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Raised Panel Component Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder-coated surfaces
- Provide crisp, clear, and durable legends for your reliable, high-performance identification needs
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposure)
- Meet ASTM D3389 standard for abrasion resistance, and also meet solar application standards
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C100X050APT	White	1.00	25.4	0.50	12.7	3	500
C100X050A8T	Yellow						
C100X050AST	Green						
C100X050AUT	Orange						
C100X050AWT	Red						
C100X050A0T	Black						
C100X050AMT	Silver						
C125X030APT	White	1.25	31.8	0.30	7.6	1	
C125X030A0T	Black	1.70	43.2	0.90	22.9		
C170X090APT	White						
C170X090A8T	Yellow						
C170X090AST	Green						
C170X090AWT	Red						
C170X090AMT	Silver						
C200X100APT	White	2.00	50.8	1.00	25.4		
C200X100A8T	Yellow						
C200X100AST	Green						
C200X100AUT	Orange						
C200X100AWT	Red						
C200X100A0T	Black	2.52	64.0	0.30	7.6		
C200X100AMT	Silver						
C252X030APT	White						
C252X030A0T	Black						
C300X100APT	White	3.00	76.2	1.00	25.4		
C300X100A8T	Yellow						
C300X100AUT	Orange						
C300X100AWT	Red						
C300X100A0T	Black						
C300X250APT	White			2.50	63.5		
C300X250A8T	Yellow						
C300X250AST	Green						
C300X250AUT	Orange						
C300X250AWT	Red						
C300X250A0T	Black	3.50	88.9	3.00	76.2		
C300X250AMT	Silver						
C350X300APT	White						
C350X300A8T	Yellow						
C350X300AUT	Orange						
C350X300A0T	Black	3.79	96.3	0.30	7.6		
C379X030APT	White						
C379X030AQT	Blue						
C379X030AWT	Red						
C379X030A0T	Black	4.00	101.6	1.00	25.4		
C400X100APT	White						
C400X100A8T	Yellow						
C400X100AST	Green						
C400X100AUT	Orange						
C400X100AWT	Red						
C400X100A0T	Black						
C400X100AMT	Silver						

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Raised Panel Component Over-Laminate Labels


- Provide additional print protection in harsh environments
- Over-laminates are not printable
- Temperature range: -51°F to 275°F (-46°C to 135°C)

Part Number	Color	Width		Height		Labels Per Roll	Std. Pkg. Qty.
		In.	mm	In.	mm		
C100X050YK	Clear	1.00	25.4	0.50	12.7	1	500
C170X090YK		1.70	43.2	0.90	22.9		
C200X100YK		2.00	50.8	1.00	25.4		
C300X100YK		3.00	76.2	1.00	25.4		
C300X250YK				2.50	63.5		
C350X300YK		3.50	88.9	3.00	76.2		
C400X100YK		4.00	101.6	1.00	25.4		

Order number of labels required in multiples of Standard Package Quantity.

Raised Panel Pre-Printed Emergency Stop Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder-coated surfaces
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14576; cUL recognized C22.2 No. 0.15.01, File # MH14576



Part Number	Color	Diameter		Hole Diameter		Std. Pkg. Qty.
		In.	mm	In.	mm	
C235A8-30-ES	Black on Yellow	2.35	60.0	1.18	30.0	25
C235AW-30-ES	White on Red					
C350A8-30-ES	Black on Yellow	3.50	89.0	1.18	30.0	25
C350AW-30-ES	White on Red					

Order number of labels required in multiples of Standard Package Quantity.

Polyester Component Labels

- Provide durability; high-temperature resistance and dimensional stability; does not easily stretch or tear
- Use thermal transfer resin ribbon

- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14576 and File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979




		Width		Height		Labels Per Row	Std. Pkg. Qty.
Part Number	Color	In.	mm	In.	mm		
C025X025YJT	White	0.25	6.4	0.25	6.4	12	10000
C038X038YJT		0.38	9.7	0.38	9.7	7	
C050X044YJT		0.50	12.7	0.44	11.2	5	
C060X020YJT		0.60	15.2	0.20	5.1		
C075X025YJT		0.75	19.1	0.25	6.4		
C075X025YMT							
C080X020YJT	White	0.80	20.3	0.20	5.1	3	
C090X025YJT		0.90	22.9	0.25	6.4		
C100X025YJT		1.00	25.4	0.25	6.4		
C100X038YJT				0.38	9.7		
C100X050YJT				0.50	12.7		
C100X050YKT							
C100X050YMT	Silver						
C125X038YJT	White	1.25	31.8	0.38	9.7		
C150X050YJT		1.50	38.1	0.50	12.7		
C150X075YJT				0.75	19.1		
C150X075YMT		Silver					
C160X020YJT	White	1.60	40.6	0.20	5.1	5000	
C200X025YJT		2.00	50.8	0.25	6.4	10000	
C200X038YJT				0.38	9.7	5000	
C200X050YJT				0.50	12.7	2500	
C200X100YJT				1.00	25.4		
C200X100YKT							
C200X100YMT	Silver						
C275X125YJT	White	2.75	69.9	1.25	31.8	1	
C275X125YMT	Silver						
C300X025YJT	White	3.00	76.2	0.25	6.4		5000
C300X038YJT				0.38	9.7		
C300X100YJT				1.00	25.4		2500
C300X100YMT				White	2.00		50.8
C300X200YJT	Silver						
C350X100YJT	White			3.50	88.9		1.00
C400X100YJT		4.00	101.6	2.00	50.8		1000
C400X200YJT				3.00	76.2		2500
C400X200YMT				Silver	4.00		101.6
C400X300YJT	White			6.00	152.4		
C400X400YJT							
C400X600YJT							

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Super-Tack Polyester Component Labels

- Provide durability; high-temperature resistance and dimensional stability; does not stretch or easily tear; and has high-tack permanent adhesive
- Used to identify patch panels, faceplates, punchdown blocks, and other network systems hardware
- Meets DIN 40050-9, IP69K for washdown applications



- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979

		Width		Height			Labels Per Row	Std. Pkg. Qty.	
Part Number	Color	In.	mm	In.	mm	Type of Application			
C061X030YPT	White	0.61	15.5	0.30	7.6	1-port	4	2500	
C100X050YPT		1.00	25.4	0.50	12.7	general identifier	3	10000	
C125X030YPT		1.25	31.8	0.30	7.6	2-port			
C138X019YPT		Black	1.38	35.1	0.19	4.8	module	1	2500
C138X019YOT	White		1.88	47.8	0.30	7.6	3-port		
C188X030YPT		Black	2.00	50.8	1.00	25.4	general identifier		
C200X100YPT	White		2.52	64.0	0.30	7.6	1, 2, 3, or 4-port		
C200X100YOT									
C252X030YPT		4-port							
C252X030YPT-P*									
C252X030YQT-P*		TIA Blue							
C252X030YRT-P*		TIA Brown							
C252X030YST-P*		TIA Green							
C252X030YTT-P*		TIA Gray							
C252X030YUT-P*		TIA Orange							
C252X030YVT-P*		TIA Purple							
C252X030YWT-P*		TIA Red							
C252X030YOT-P*		Black							
C252X030Y8T-P*	TIA Yellow								
C252X030Y9T-P*	Gold								
C261X030YPT	White	2.61	66.3	0.30	7.6	4-port	1	2500	
C275X125YPT		Black	2.75	69.9	1.25	31.8			general identifier
C275X125YOT	White		2.88	73.2	0.30	7.6			5-port
C288X030YPT		3.00	76.2	2.00	50.8	general identifier			
C300X200YPT		3.15	80.0	0.30	7.6	5-port			
C315X030YPT		3.79	96.3	0.30	7.6	6-port			
C379X030YPT						1, 2, 3, 4, 5 or 6-port			
C379X030YPT-P*									
C379X030YQT-P*									TIA Blue
C379X030YRT-P*									TIA Brown
C379X030YST-P*									TIA Green
C379X030YTT-P*									TIA Gray
C379X030YUT-P*									TIA Orange
C379X030YVT-P*									TIA Purple
C379X030YWT-P*	TIA Red								
C379X030YOT-P*	Black								
C379X030Y8T-P*	TIA Yellow								
C379X030Y9T-P*	Gold								
C400X200Y8T	Yellow	4.00	101.6	2.00	50.8	general identifier	1000		
C400X300YPT	White			3.00	76.2		2500		

*Label is perforated to be used in 1, 2, 3, 4, or 6-Port position applications.
 Order number of labels required in multiples of Standard Package Quantity.
 Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Tedlar® Component Labels

- Self-extinguishing and ideal for labeling high-temperature areas
- Meet Federal Motor Vehicle Safety Standard (FMVSS-302) for flammability
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 225°F (-40°C to 106°C); tests at 275°F have shown acceptable results




Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C060X020TJT	White	0.60	15.2	0.20	5.1	3	10000
C090X025TJT		0.90	22.9	0.25	6.4		
C100X038TJT		1.00	25.4	0.38	9.7		
C100X050TJT				0.50	12.7		
C125X038TJT		1.25	31.8	0.38	9.7	1	2500
C200X038TJT		2.00	50.8				2500
C200X100TJT				1.00	25.4		2500
C300X038TJT		3.00	76.2	0.38	9.7		5000

Tedlar® is a registered trademark of E.I. du Pont de Nemours and Company.
 Order number of labels required in multiples of Standard Package Quantity.
 Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Tamper-Evident Polyester Component Labels

- Leaves a checkerboard of silver material allowing you to see if label has been tampered with
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14576 and File # MH14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C075X025AAT	Silver	0.75	19.1	0.25	6.4	3	10000
C100X050AAT		1.00	25.4	0.50	12.7		
C200X100AAT		2.00	50.8	1.00	25.4	1	2500
C275X125AAT		2.75	69.9	1.25	31.8		

Order number of labels required in multiples of Standard Package Quantity.
 Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Non-Adhesive Polyester Component Labels

- Used to identify patch panels, faceplates, punchdown blocks, and other network systems hardware

- Use thermal transfer resin ribbon
- Temperature range: -10°F to 302°F (-23°C to 150°C)



Part Number	Color	Width		Height		Application	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm			
C150X030Y1T	White	1.50	38.1	0.30	7.6	3-port identifier	2	1000
C195X040Y1T		1.95	49.5	0.40	10.2	Single-gang faceplate		
C261X035Y1T		2.61	66.3	0.35	8.9	4-port identifier		
C288X040Y1T		2.88	73.2	0.40	10.2	Double-gang faceplate		
C390X030Y1T		3.90	99.1	0.30	7.6	6-port identifier		
C750X050Y1T		7.50	190.5	0.50	12.7	110 block		
C788X050Y1T		7.88	200.2	0.50	12.7	GP6™ Punchdown System		

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Vinyl Cloth Component Labels

- Ideal for temporary marking of chips, boards, and ICs
- Removable without leaving any residue
- Pliable material is suitable for rough texture surfaces
- Use thermal transfer hybrid ribbon

- Temperature range: 50°F to 170°F (10°C to 77°C)
- UL969 recognized, File # MH14576 and File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14576



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.		
		In.	mm	In.	mm				
C050X044CBT	White	0.50	12.7	0.44	11.2	5	10000		
C060X020CBT		0.60	15.2	0.20	5.1	3			
C075X025CBT		0.75	19.1	0.25	6.4				
C100X025CBT		1.00	25.4					0.38	9.7
C100X038CBT								0.50	12.7
C100X050CBT				1.50	38.1			0.75	19.1
C150X075CBT		1.60	40.6	0.20	5.1	10000			
C160X020CBT		2.00	50.8	0.50	12.7	5000			
C200X050CBT		4.00	101.6	1.00	25.4	2500			

Order number of labels required in multiples of Standard Package Quantity.

Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Polyimide Component Labels

- Ideal for electronic components and internal circuitry applications
- Intended for applications requiring solvent and high-temperature resistance performance, such as the wave solder process

- Use thermal transfer resin ribbon on white polyimide
- Use thermal transfer hybrid ribbon on tan polyimide
- Temperature range: -40°F to 350°F (-40°C to 177°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C025X025KBT	White	0.25	6.4	0.25	6.4	12	10000
C025X025KCT	Tan			0.25	6.4	12	
C038X038KBT	White	0.38	9.7	0.38	9.7	7	
C038X038KCT	Tan			0.38	9.7	7	
C050X013KBT	White	0.50	12.7	0.13	3.3	5	
C050X013KCT	Tan			0.13	3.3		
C050X020KBT	White			0.20	5.1		
C050X044KBT				0.20	5.1		
C050X044KCT	Tan	0.44	11.2	11.2			
C060X020KBT	White	0.60	15.3	0.20	5.1	3	
C060X020KCT	Tan			0.20	5.1		
C065X019KBT	White	0.65	16.5	0.19	4.8		
C065X019KCT	Tan			0.19	4.8		
C075X025KBT	White	0.75	19.1	0.25	6.4		
C075X025KCT	Tan			0.25	6.4		
C080X020KBT	White	0.80	20.3	0.20	5.1		
C080X020KCT	Tan			0.20	5.1		
C090X025KBT	White	0.90	22.9	0.25	6.4		
C090X025KCT	Tan			0.25	6.4		
C100X019KBT	White	1.00	25.4	0.19	4.8		
C100X019KCT	Tan			0.19	4.8		
C100X025KBT	White			0.25	6.4		
C100X025KCT	Tan			0.25	6.4		
C100X038KBT	White			0.38	9.7		
C100X038KCT	Tan						
C125X025KBT	White	1.25	31.8	0.25	6.4	2	
C125X025KCT	Tan						
C150X025KBT	White	1.50	38.1	0.25	6.4		5000
C150X025KCT	Tan						
C160X020KBT	White	1.60	40.6	0.20	5.1	1	
C160X020KCT	Tan			0.20	5.1		
C200X025KBT	White	2.00	50.8	0.25	6.4		5000
C200X025KCT	Tan			0.25	6.4		
C200X038KBT	White	3.00	76.2	0.38	9.7		
C300X025KBT				0.38	9.7		
C300X025KCT	Tan	0.25	6.4				

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Paper Component Labels

- General purpose material
- Use thermal transfer hybrid ribbon

- Temperature range: -65°F to 160°F (-54°C to 71°C)
- UL969 recognized, File # MH14576 and File # MH14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C075X025PBT	White	0.75	19.1	0.25	6.4	3	10000
C100X050PBT		1.00	25.4	0.50	12.7		
C150X075PBT		1.50	38.1	0.75	19.1		5000
C200X100PBT		2.00	50.8	1.00	25.4		2500
C300X200PBT		3.00	76.2	2.00	50.8		1000
C400X100PBT		4.00	101.6	1.00	25.4	1	2500
C400X200PBT				2.00	50.8		1000
C400X300PBT				3.00	76.2		2500
C400X500PBT				5.00	127.0		1000
C400X600PBT				6.00	152.4		

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Reflective Continuous Tapes

- Used for illuminating or highlighting a range of objects
- Offer crisp, clear legends with superior legibility
- Conformable material for flat applications and safety and facility identification
- Can be over-laminated to increase durability (see page 28)

- Use thermal transfer resin ribbon
- Temperature range: -40°F to 180°F (-40°C to 82°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width		Length		Std. Pkg. Qty. (Roll)
		In.	mm	Ft.	m	
T100X000RP1	White	1.00	25.4	50.0	15.2	1
T100X000RU1	Orange					
T100X000RW1	Red					
T100X000RX1	Yellow					
T200X000RP1	White	2.00	50.8			
T200X000RU1	Orange					
T200X000RW1	Red					
T200X000RX1	Yellow					
T300X000RP1	White	3.00	76.2			
T400X000RP1		4.00	101.6			
T400X000RQ1	Blue					
T400X000RU1	Orange					
T400X000RW1	Red					
T400X000RX1	Yellow					

Order number of labels required in multiples of Standard Package Quantity.

Continuous Tapes

- Offer crisp, clear legends with superior legibility
- Conformable material for flat applications and safety and facility identification
- Can be over-laminated to increase durability (see page 28)
- Use thermal transfer resin ribbon
- For white, black, clear, blue, and yellow vinyl continuous tapes only: UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Material	Temperature Range	Width		Length		Std. Pkg. Qty. (Roll)
				In.	mm	Ft.	m	
T024X000FJT*	White	Polyolefin	-40°F to 180°F (-40°C to 82°C)	0.24	6.1	100.0	30.5	1
T031X000FJT*				0.31	7.9			
T038X000FJT*				0.38	9.7			
T050X000FJT*				0.50	12.7			
T100X000VP1Y								
T100X000VQ1Y	Blue	Vinyl	-58°F to 176°F (-50°C to 80°C)	1.00	25.4	100.0	30.5	1
T100X000VS1Y	Green							
T100X000VU1Y	Orange							
T100X000VW1Y	Red							
T100X000VX1Y	Yellow							
T100X000VY1Y	Black							
T100X000YK1	Clear							
T200X000VP1Y	White	Vinyl	-58°F to 176°F (-50°C to 80°C)	2.00	50.8	100.0	30.5	1
T200X000VQ1Y	Blue							
T200X000VR1Y	Brown							
T200X000VS1Y	Green							
T200X000VT1Y	Gray							
T200X000VU1Y	Orange							
T200X000VV1Y	Purple							
T200X000VW1Y	Red							
T200X000VX1Y	Yellow							
T200X000VY1Y	Black							
T200X000YK1	Clear							
T400X000VP1Y	White	Vinyl	-58°F to 176°F (-50°C to 80°C)	4.00	101.6	100.0	30.5	1
T400X000VQ1Y	Blue							
T400X000VR1Y	Brown							
T400X000VS1Y	Green							
T400X000VT1Y	Gray							
T400X000VU1Y	Orange							
T400X000VV1Y	Purple							
T400X000VW1Y	Red							
T400X000VX1Y	Yellow							
T400X000VY1Y	Black							
T400X000YK1	Clear							

Order number of rolls required in multiples of Standard Package Quantity.

*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Super-Tack Polyester Continuous Tapes

- Thermal transfer printable continuous tape format
- Super-tack polyester has ultra-aggressive adhesive
- Ideal for rough, textured, and coated surfaces
- Applications include rack unit labeling, cabinets, cable tray, pathways, control panels, enclosures, pipes, and much more
- Meets DIN 40050-9, IP69K for washdown applications.
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14979, cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Material	Width		Length		Std. Pkg. Qty. (Roll)
			In.	mm	Ft.	m	
T038X000Y01	Black	Polyester	0.38	9.7	100.0	30.5	1
T038X000YP1	White						
T050X000Y01	Black		0.50	12.7			
T050X000YP1	White						
T100X000Y01	Black		1.00	25.4			
T100X000Y81	Yellow						
T100X000YP1	White						
T100X000YQ1	Blue						
T100X000YS1	Green						
T100X000YU1	Orange						
T100X000YW1	Red						
T200X000Y01	Black		2.00	50.8			
T200X000Y81	Yellow						
T200X000YP1	White						
T200X000YQ1	Blue						
T200X000YS1	Green						
T200X000YU1	Orange						
T200X000YW1	Red						
T400X000Y01	Black		4.00	101.6			
T400X000Y81	Yellow						
T400X000YP1	White						
T400X000YQ1	Blue						
T400X000YS1	Green						
T400X000YU1	Orange						
T400X000YW1	Red						

Order number of labels required in multiples of Standard Package Quantity.

Non-Printable Clear Over-Laminate Continuous Tapes

- Over-laminates can be used for additional protection over the 2" and 4" continuous tapes
- When over-laminates are used with Super-Tack Polyester Labels, the labels meet DIN 40050-9, IP69K for washdown applications
- Temperature range: -40°F to 302°F (-40°C to 150°C)

Part Number	Color	Material	Width		Length		Std. Pkg. Qty. (Roll)
			In.	mm	Ft.	m	
T225X000YK1	Clear	Polyester	2.25	57.2	100.0	30.5	1
T425X000YK1			4.25	107.9			

Order number of labels required in multiples of Standard Package Quantity.

Super-Tack Polyester Arc Flash Labels

- Provide employees with the highest degree of safety through proper identification and communication
- Detailed formats compliant with NFPA 70E standard for Arc Flash labeling
- Clearly visible and recognizable hazard information to communicate arc flash hazards present
- Meets DIN 40050-9, IP69K for washdown applications
- Labels are constructed of durable polyester designed to withstand UV exposure, outdoor use, water and abrasion
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized; File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



C200X400A51



C200X400YZ1



C400X400A51



C400X400YZ1



C400X600A51



C400X600YX1



C400X600YZ1

Part Number	Width		Height		Part Description	Std. Pkg. Qty. (Roll)
	In.	mm	In.	mm		
C200X400A51	2.00	50.8	4.00	101.6	Polyester safety label, WARNING header orange and black, 250 labels per roll.	1
C200X400YZ1					Polyester safety label, DANGER header red and white, 250 labels per roll.	
C400X400A51	4.00	101.6	4.00	101.6	Polyester safety label, WARNING header orange and black, 250 labels per roll.	
C400X400YZ1					Polyester safety label, DANGER header red and white, 250 labels per roll.	
C400X600A51			6.00	152.4	Polyester safety label, WARNING header orange and black, 100 labels per roll.	
C400X600YX1					Polyester safety label, orange header, 100 labels per roll.	
C400X600YZ1					Polyester safety label, DANGER header red and white, 100 labels per roll.	

Order number of labels required in multiples of Standard Package Quantity

Raised Panel Arc Flash Labels

- Super-Tack adhesive provides strong holding power for rough, textured, and powered-coated surfaces
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposures)
- Meet ASTM D3389 standard for abrasion resistance, and also meets solar application standards
- Use thermal transfer resin ribbon
- Temperature Range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979, cUL recognized, C22.2 No. 0.15.01, File # MH 14979



C400X400AOT



C400X400ANT

Part Number	Color	Width		Height		Part Description	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm		
C400X400ANT	Orange	4.00	101.6	4.00	101.6	Raised Panel Safety Label, WARNING header, White and Orange/Black	1
C400X400AOT	Red					Raised Panel Safety Label, DANGER header, White and Red/Black	
	White						

Order number of labels required in multiples of Standard Package Quantity

Super-Tack Polyester Arc Flash Continuous Tapes



T400X000YX1



T400X000A91

Part Number	Width		Height		Part Description	Std. Pkg. Qty. (Roll)
	In.	mm	Ft	M		
T400X000YX1	4.00	101.6	50.0	15.2	Polyester arc flash continuous tape, orange header.	1
T400X000A91					Polyester arc flash continuous tape, red header.	

Order number of labels required in multiples of Standard Package Quantity

Super-Tack Polyester Facility Identification Labels

- Facility Identification created quickly to comply with workplace safety regulations contributing to the protection of employees and equipment from unexpected hazards
- Meets DIN 40050-9, IP69K for washdown applications
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized; File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



C400X600A41



C400X600A61



C400X600AX1



C400X600AY1



C400X600AZ1



C400X600Y81


Part Number	Width		Height		Part Description	Labels Per Row	Std. Pkg. Qty. (Roll)
	In.	mm	In	mm			
C400X600A41	4.00	101.6	6.00	152.4	Polyester safety label, DANGER header, red and black/white, 100 labels per roll.	1	1
C400X600A61					Polyester safety label, CAUTION header, yellow/black, 100 labels per roll.		
C400X600AX1					Polyester safety label, blue/white, NOTICE header, 100 labels per roll.		
C400X600AY1					Polyester safety label, green/ white, SAFETY FIRST header, 100 labels per roll.		
C400X600AZ1					Polyester safety label, yellow header, 100 labels per roll.		
C400X600Y81					Polyester safety label, yellow, 100 labels per roll.		

Order number of labels required in multiples of Standard Package Quantity


Polyester Photoluminescent Tapes

- Used to mark egress routes, fire alarms, and fire equipment
- Clearly visible for up to ten hours after power is lost
- Absorbs energy from ambient light and releases this energy in the form of a glow when power is lost

- Can be over-laminated to increase durability (see page 28)
- Use thermal transfer resin ribbon
- Temperature range: 40°F to 230°F (4.4°C to 110°C)
- UL969 recognized, File # MH14979



Normal Lighting



Blackout

Part Number	Color	Width		Length		Std. Pkg. Qty. (Roll)
		In.	mm	Ft	M	
T200X000Y2T	Photoluminescent	2.00	50.8	15.0	4.5	1
T400X000Y2T		4.00	101.6			

Order number of labels required in multiples of Standard Package Quantity

Raised Panel Solar Labels

- Print customized labels for solar applications
- Strong holding power for rough, textured, and coated surfaces
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposures)

- Use thermal transfer resin ribbon
- Temperature Range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979, cUL recognized, C22.2 No. 0.15.01, File # MH 14979




Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C200X100AWT	Red	2.00	50.8	1.00	25.4	1	500
C300X250AWT		3.00	76.2	2.50	63.5		
C400X100AWT		4.00	101.6	1.00	25.4		

Order number of labels required in multiples of Standard Package Quantity

Super-Tack Polyester Solar Labels

- Solar Labels are designed to meet required safety standards for PV installation labeling.
- Certain labels leave blank spaces where variable thermal transfer printing can be added when specific on-site power and series data is required.



- Meets DIN 40050-9, IP69K for washdown applications
- This product solution has an optional clear over-laminate to function in harsh environments.
- All labels are outdoor rated and are designed to have high resistance to direct UV exposure.
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 180°F (-40°C to 82°C)
- UL969 recognized; File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979

Part Number	Color	Width		Height		Application	Legend	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm			
C400X200SP1-AD	White on Red	4.00	101.6	2.00	50.8	AC Disconnect	VOLTAGE AND CURRENT RATINGS	50
C400X400SP1-ASM				4.00	101.6	AC Photovoltaic Module	VOLTAGE CURRENT AND POWER RATINGS	
C400X400SP1-DD						DC Disconnect	VOLTAGE AND CURRENT RATINGS	
C400X400SP1-DSM						DC Photovoltaic Module	VOLTAGE CURRENT AND POWER RATINGS	
C400X400SP1-PS						Photovoltaic Power Source	VOLTAGE AND CURRENT RANTINGS	
C600X175SP1-AD		6.00	152.4	1.75	44.5	AC Disconnect	PHOTOVOLTAIC - AC DISCONNECT	
C600X175SP1-DD						DC Disconnect	PHOTOVOLTAIC - DC DISCONNECT	

Order number of labels required in multiples of Standard Package Quantity

Over-Laminate Labels

Part Number	Color	Width		Height		Application	Std. Pkg. Qty.
		In.	mm	In.	mm		
C300X150SL1-OL	Clear	1.50	38.1	3.00	76.2	Additional Abrasion and UV Protection	250
C400X200SL1-OL		2.00	50.8	4.00	101.6	Additional Abrasion and UV Protection	
C400X400SL1-OL		4.00	101.6			Additional Abrasion and UV Protection	
C600X175SL1-OL		1.75	44.5	6.00	152.4	Additional Abrasion and UV Protection	

Order number of labels required in multiples of Standard Package Quantity

Reflective Continuous Tapes for Solar Applications



- Used for illuminating or highlighting a range of objects
- Conformable material for flat applications and safety and facility identification
- Use thermal transfer resin ribbon
- Temperature Range: -40°F to 180°F (-40°C to 82°C)
- UL969 recognized, File # MH14979, cUL recognized, C22.2 No. 0.15.01, File # MH 14979

Part Number	Color	Material	Width		Height		Std. Pkg. Qty. (Roll)
			In.	mm	Ft.	M	
T400X000RW1	Red	Polyester	4.00	101.6	50.0	15.2	1

Order number of labels required in multiples of Standard Package Quantity


Easy-Mark™ Labeling Software



- Quickly and easily generate labels
- Market specific labeling application tools assist in creation of identification solutions for data centers, network applications, panel shops, and construction and maintenance applications
- Saves time and money (up to 75%) with features such as WYSIWYG user interface, data import, symbol import, and pre-loaded formats
- Site license available for up to five additional installs per license
- Upgrades available at www.panduit.com

System Requirements:

- 64 MB hard drive space and 64 MB RAM (256 MB RAM recommended)
- Windows 2000, XP, Vista, 7, 8 or 10
- Mouse or compatible pointing device
- Microsoft.NET Framework 2.0 or higher
- CD-ROM Drive or USB Port



Part Number	Color	Std. Pkg. Qty	Std. Ctn. Qty.
PROG-EMCD3	Easy-Mark™ Labeling Software, CD-ROM	1	10
PROG-EM2GO	Easy-Mark™ Portable Application, USB Flash Drive		


^Windows is a registered trademark of Microsoft Corp. in the United States and/or other countries.

CAD-Connect™ Labeling Software

- Facilitates quick and easy organization of identifiers from CAD for printing within Easy-Mark™ Labeling Software
- Easily captures and organizes CAD data for future use and documentation
- Saves time and reduces errors by utilizing identifiers previously created in CAD files to eliminate manual entry of data into labeling software
- Compatible with full versions of AutoCAD* 2002 to 2016 and Visio version 2002 or newer
- Exports to alternative formats such as Excel^ (XLS) or Text (CSV) files for future use and documentation
- Upgrades available at www.panduit.com

System Requirements:

- 64 MB hard drive space and 64 MB RAM (256 MB RAM recommended)
- Windows 2000, XP, Vista, 7, 8 or 10
- Mouse or compatible pointing device
- Microsoft.NET Framework 2.0 or higher
- CD-ROM Drive



Part Number	Color	Std. Pkg. Qty	Std. Ctn. Qty.
PROG-CCCD	CAD-Connect™ Labeling Software, including Easy-Mark™ Labeling Software, CD-ROM.	1	10

^Visio, Windows and EXCEL are registered trademarks of Microsoft Corp. in the United States and/or other countries.

*AutoCAD is a registered trademark of Autodesk, Inc.

TDP43ME Desktop Printer and Accessories

- Creates durable, crisp, clear legends and graphics that offer superior legibility
- Prints durable legends for harsh industrial environments
- Fine resolution for small type characters and images
- Easy-Mark™ Labeling Software included with printer
- Up to 4 inches per second print speed
- Auto-sensing label gap and black mark sensors
- One-button operation, and automatic self test
- Connects quickly and easily to PC, and offers connectivity flexibility to print by USB, parallel serial, or Ethernet
- Easy ribbon loading reduces printer down time
- Able to connect to a network for sharing capability
- UL60950 listed, File # E165747



Part Number	Part Description	Std. Pkg. Qty.
TDP43ME	300 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RMEH4BL black hybrid ribbon, AC power adapter with US power cord, USB cable, user manual, quick start card, and driver disk; for use in North America	1
TDP43ME/E	300 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RMEH4BL black hybrid ribbon, EuroPlug cord, USB cable, user manual, quick start card, and driver disk; for use outside North America	
TDP43ME-KIT	TDP43ME printer kit. Includes: printer, Panduit® Easy-Mark™ Labeling Software, RMEH4BL black hybrid ribbon, AC power adapter with US power cord, USB cable, user manual, quick start card, TDP43ME-RS Roll Stand, TDP43ME-CASE, one roll of S100X150VATY labels, and driver disk; for use in North America	
TDP43ME/E-KIT	TDP43ME/E printer kit. Includes: printer, Panduit® Easy-Mark™ Labeling Software, RMEH4BL black hybrid ribbon, AC power adapter with EuroPlug cord, USB cable, user manual, quick start card, TDP43ME-RS Roll Stand, TDP43ME-CASE, one roll of S100X150VATY labels, and driver disk; for use outside North America	
TDP43ME-AC	Replacement AC power adapter with power cord (US cord only).	
TDP43ME-CASE	Hardside carrying case accommodates printer, AC power adapter, ribbons, printer cable, external roll stand, labels, and tools.	
TDP43ME-CUTTER	Optional power/automatic cutter for TDP43ME thermal transfer desktop printer; easy to install for automatic cutting of labels.	
TDP43ME-RS	External label roll stand for TDP43ME printer; used to rear feed labels that are supplied on 3" cores.	
TDP43ME-SPINDLE	Replacement ribbon spindle for TDP43ME Thermal Transfer Desktop Printer, Package of Two Spools.	
PTR-CLN	Printer cleaning kit – contains bottle of cleaning solution with MSDS, cleaning pen, swabs, alcohol wipes, and cleaning instructions.	

TDP43ME Desktop Printer Ribbons

Part Number	Part Description	Width		Length		Std. Pkg. Qty.
		In.	mm	Ft.	m	
RMEH4BL*	Black hybrid thermal transfer ribbon. Use with heat shrink, self-laminating, Turn-Tell®, tan polyimide labels, and vinyl cloth labels.	4.25	108.0	300.0	91.4	1
RMER4BL*	Black resin thermal transfer ribbon. Use with polyester and white polyimide labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4BU	Blue resin thermal transfer ribbon. Use with polyester and white polyimide labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4GR	Green resin thermal transfer ribbon. Use with polyester and white polyimide labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4RD	Red resin thermal transfer ribbon. Use with polyester and white polyimide labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4WH*	White resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.					
RMER4BL-A	Black resin thermal transfer ribbon. Use with high-temperature marker plates.					
RMER4BL-C	Black resin thermal transfer ribbon. Use with fluid-resistant heat shrink labels and white polyimide labels.					

Order number of ribbons required in multiples of Standard Package Quantity.

*For 2.5" wide ribbons, replace 4 in part number with 2. For example, the part number of a 2.5" wide black hybrid thermal transfer ribbon is RMEH2BL.

TDP43HE and TDP46HE Desktop Printers and Accessories

- Convenient, easy setup; quickly begin producing labels
- Durable, clear communication through superior legibility
- Print small, fine characters and high-quality images and bar codes
- Allow continuous use in construction, industrial, and harsh environments
- Reduce time required to switch between label styles
- Fast label production without sacrificing print quality
- Easy-Mark™ Labeling Software included with printer
- Up to 8 inches per second print speed
- Connect quickly and easily to PC, and offers connectivity flexibility to print by USB, parallel, Ethernet or serial
- Available with 300 or 600 dots per inch print resolution
- Able to connect to a network for sharing capability
- UL60950 listed, File # E165747



Part Number	Part Description	Std. Pkg. Qty.
TDP43HE	300 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, user manual, quick start card, driver disk and US power cord; for use in North America.	1
TDP43HE/E	300 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, user manual, quick start card, driver disk, and the following power cords: EuroPlug, Swiss, UK, and Japan JIS 8303 3-pin; for use outside North America.	
TDP46HE	600 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, user manual, quick start card, driver disk, and US power cord; for use in North America.	
TDP46HE/E	600 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, user manual, quick start card, driver disk, and the following power cords: Europlug, Swiss, UK, and Japan JIS 8303 3-pin; for use outside North America.	
PTR-CLN	Printer cleaning kit - contains bottle of cleaning solution with MSDS, cleaning pen, swabs, alcohol wipes, and cleaning instructions.	

TDP43HE and TDP46HE Desktop Printer Ribbons

Part Number	Part Description	Width		Length		Std. Pkg. Qty.
		In.	mm	Ft.	m	
RHEH4BL	Black hybrid thermal transfer ribbon. Use with heat shrink, self-laminating, Turn-Tell [®] , and vinyl cloth and tan polyimide labels.	4.33	110.0	1181.0	363.0	1
RHER4BL	Black resin thermal transfer ribbon. Use with polyester and white polyimide labels, continuous vinyl tape, marker plates, and raised panel labels.					
RHER4WH	White resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.	4.50	114.3			
RHER4BL-A	Black resin thermal transfer ribbon. Use with high-temperature marker plates.	4.33	110.0	1345.0	410.0	
RHER4BL-C	Black resin thermal transfer ribbon. Use with fluid resistant heat shrink markers.					
RHER4BL-E	Black resin thermal transfer ribbon. Used with standard marker plates and component labels for extra durability for harsh environments.					

Order number of ribbons required in multiples of Standard Package Quantity.

Real-World Solutions

With a proven reputation for excellence and innovation, Panduit and our partners work with you to overcome challenges and implement real-world solutions that create a competitive business advantage. Panduit offers the broadest range of solutions, from data centers and intelligent buildings to manufacturing operations, to help you build a smarter, unified business foundation.

Technology Leadership

Panduit develops innovative physical infrastructure solutions that meet the rapidly changing needs of our clients, from hardware and software to advisory services. This commitment is supported by investment in advanced research, solutions-focused product development, world-class manufacturing, and collaboration with customers at the forefront of technology.

Partner Ecosystem

Our best-in-class partner ecosystem offers a comprehensive portfolio of services that span the project lifecycle, from planning and design to delivery, deployment, maintenance, and operation. Panduit business partners – distributors, and certified architects, consultants, engineers, designers, system integrators, and contractors – are qualified to help you achieve your objectives and realize predictable and measurable results.

Strategic Alliances

Panduit cultivates long-term strategic alliances with industry leaders, including Cisco Systems, EMC, IBM, and Rockwell Automation, to develop, optimize, and validate solutions for our customers. This investment in people and resources helps solve our customers' greatest business challenges.

Global Business Commitment

Panduit is committed to delivering a consistently high level of quality and service the world over. With a presence in more than 100 countries, local Panduit sales representatives and technical specialists offer guidance and support that bring value to your business. Our global supply chain, which includes manufacturing, customer service, logistics, and distribution partners, provides prompt response to your inquiries and streamlines delivery to any worldwide destination.

Sustainability

With a commitment to environmental sustainability, Panduit develops and implements solutions that protect, replenish, and restore the world in which we live. This commitment is demonstrated by Panduit's LEED Gold certified World Headquarters, leveraging the Unified Physical InfrastructureSM approach to enable convergence of critical building systems to drive energy efficiency and ongoing operational improvement.

Transform Your
Physical Infrastructure

Call or visit us online,
we can show you how.

Panduit® Corp.
World Headquarters
Tinley Park, IL 60487

cs@panduit.com
US and Canada: 800.777.3300
Europe, Middle East, and Africa:
44.20.8601.7200
Latin America: 52.33.3777.6000
Asia Pacific: 65.6305.7575

www.panduit.com

PANDUIT®

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru