THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
HC	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED, REDRAWN IN TYCO FORMAT.	05AUG1997	KYLE	RDP





RECOMMENDED MOUNTING HOLE

1059902-1

PART NUMBER

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions PER	TEMPERATURE RATING -65° TO +125°C
Frequency Range (GHz) DC to 18.0	TYCO ELECTRONICS CATALOG	Vibration MIL-STD-202, Method
Volt Rating (VRMS MAX)	Recommended Mating	204, Condition D
@ Sea Level 335	Torque 12-15 IN-LBS	Shock MIL-STD-202, Method 213,
VSWR 1.05 + .01f(GHz)	Force to Engage and	Condition I
Insertion Loss (dB MAX) .05 $\sqrt{f(GHz)}$	Disengage (In-Lbs MAX) 3.0	Thermal Shock MIL-STD-202,
RF Leakage (dB MIN) -[100-f(GHz)]		Method 107, Condition B,
Corona, 70,000 Ft (VRMS MIN) N/A		EXCEPT HIGH TEMP +125°C
Dielectric Withstanding Voltage		Moisture Resistance MIL-STD-202,
(VRMS MIN) @ Sea Level 750		Method 106
Contact Resistance (Milliohms MAX)		Corrosion - MIL-STD-202, Method
Center Contact 10.0		101, Condition B, 5% salt spray
Outer Contact 2.0		
Cable to Housing N/A		
RF High Potential @ Sea Level		
(VRMS MIN @ 5 MHz) 667		
I.R.(Megohms MIN) 5,000		

COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM A 484 AND ASTM A582, TYPE 303	GOLD PLATE PER ASTM B 488
DIELECTRIC	PTFE FLUOROCARBON PER ASTM D 1710	N/A
CENTER CONTACT	IRON-NICKEL ALLOY PER AMS-I-23011	GOLD PLATE PER ASTM B 488
HERMETIC SEAL	GLASS BEAD	N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES/mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± -
1 PLC	± -
2 PLC	± -
3 PLC	± .005
4 PLC	± -
ANGLES	± 1°

MATERIAL: SEE TABLE

FINISH: SEE TABLE

DWN	JB	23FEB1987
CHK	MH/M	27FEB1987
APVD	BAR	03MAR1987
PRODUCT SPEC	—	
APPLICATION SPEC	—	
WEIGHT	—	

tyco Electronics

Tyco Electronics Corporation
Harrisburg, PA 17105-3608

NAME: OSSP FEETHRU PLUG, HERMETIC, PANEL, STRAIGHT TERMINAL (4757-3204-00)

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-1059902	—

CUSTOMER DRAWING

SCALE	SHEET	REV
10:1	1 OF 1	A

ООО «ЛайфЭлектроникс» “LifeElectronics” LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru