


## IR Receiver Modules for Remote Control Systems



16672

### MECHANICAL DATA

#### Pinning for TSOP44..., TSOP48...:

1 = OUT, 2 = GND, 3 =  $V_S$ 

#### Pinning for TSOP22..., TSOP24...:

1 = OUT, 2 =  $V_S$ , 3 = GND

### FEATURES

- Low supply current
- Photo detector and preamplifier in one package
- Internal filter for PCM frequency
- Improved shielding against EMI
- Supply voltage: 2.5 V to 5.5 V
- Improved immunity against ambient light
- Insensitive to supply voltage ripple and noise
- Material categorization:  
for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

### DESCRIPTION

The TSOP22..., TSOP48..., TSOP24... and TSOP44... series are miniaturized IR receiver modules for infrared remote control systems. A PIN diode and a preamplifier are assembled on lead frame, the epoxy package contains an IR filter.

The demodulated output signal can be directly connected to a microprocessor for decoding.



The TSOP24..., TSOP44... are optimized to suppress almost all spurious pulses from energy saving lamps like CFLs. The AGC4 used in the TSOP24... and TSOP44... may suppress some data signals. The TSOP22..., TSOP48... are legacy products for all common IR remote control data formats. Between these four receiver types, the TSOP24..., TSOP44... are preferred. Customers should initially try the TSOP24..., TSOP44 in their design.

These components have not been qualified according to automotive specifications.

| PARTS TABLE              |        |                                                                                                                                                           |                              |                                                           |                               |
|--------------------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|-----------------------------------------------------------|-------------------------------|
| AGC                      |        | LEGACY, FOR<br>LONG BURST REMOTE CONTROLS (AGC2)                                                                                                          |                              | RECOMMENDED FOR<br>LONG BURST CODES (AGC4) <sup>(1)</sup> |                               |
| Carrier<br>frequency     | 30 kHz | TSOP4830                                                                                                                                                  | TSOP2230                     | TSOP4430                                                  | TSOP2430                      |
|                          | 33 kHz | TSOP4833                                                                                                                                                  | TSOP2233                     | TSOP4433                                                  | TSOP2433                      |
|                          | 36 kHz | TSOP4836                                                                                                                                                  | TSOP2236                     | TSOP4436 <sup>(2)(3)(4)</sup>                             | TSOP2436 <sup>(2)(3)(4)</sup> |
|                          | 38 kHz | TSOP4838                                                                                                                                                  | TSOP2238                     | TSOP4438 <sup>(5)(6)(7)</sup>                             | TSOP2438 <sup>(5)(6)(7)</sup> |
|                          | 40 kHz | TSOP4840                                                                                                                                                  | TSOP2240                     | TSOP4440                                                  | TSOP2440                      |
|                          | 56 kHz | TSOP4856                                                                                                                                                  | TSOP2256                     | TSOP4456 <sup>(7)(8)</sup>                                | TSOP2456 <sup>(7)(8)</sup>    |
| Package                  |        | Mold                                                                                                                                                      |                              |                                                           |                               |
| Pinning                  |        | 1 = OUT, 2 = GND, 3 = $V_S$                                                                                                                               | 1 = OUT, 2 = $V_S$ , 3 = GND | 1 = OUT, 2 = GND, 3 = $V_S$                               | 1 = OUT, 2 = $V_S$ , 3 = GND  |
| Dimensions (mm)          |        | 6.0 W x 6.95 H x 5.6 D                                                                                                                                    |                              |                                                           |                               |
| Mounting                 |        | Leaded                                                                                                                                                    |                              |                                                           |                               |
| Application              |        | Remote control                                                                                                                                            |                              |                                                           |                               |
| Best remote control code |        | <sup>(2)</sup> RC-5 <sup>(3)</sup> RC-6 <sup>(4)</sup> Panasonic <sup>(5)</sup> NEC <sup>(6)</sup> Sharp <sup>(7)</sup> r-step <sup>(8)</sup> Thomson RCA |                              |                                                           |                               |

### Note

<sup>(1)</sup> We advise try AGC4 first if the burst length is unknown.

**BLOCK DIAGRAM****APPLICATION CIRCUIT**

The external components  $R_1$  and  $C_1$  are optional to improve the robustness against electrical overstress (typical values are  $R_1 = 100 \Omega$ ,  $C_1 = 0.1 \mu\text{F}$ ).

**ABSOLUTE MAXIMUM RATINGS**

| PARAMETER                   | TEST CONDITION                         | SYMBOL      | VALUE                 | UNIT |
|-----------------------------|----------------------------------------|-------------|-----------------------|------|
| Supply voltage              |                                        | $V_S$       | -0.3 to +6            | V    |
| Supply current              |                                        | $I_S$       | 5                     | mA   |
| Output voltage              |                                        | $V_O$       | -0.3 to 5.5           | V    |
| Voltage at output to supply |                                        | $V_S - V_O$ | -0.3 to $(V_S + 0.3)$ | V    |
| Output current              |                                        | $I_O$       | 5                     | mA   |
| Junction temperature        |                                        | $T_j$       | 100                   | °C   |
| Storage temperature range   |                                        | $T_{stg}$   | -25 to +85            | °C   |
| Operating temperature range |                                        | $T_{amb}$   | -25 to +85            | °C   |
| Power consumption           | $T_{amb} \leq 85 \text{ °C}$           | $P_{tot}$   | 10                    | mW   |
| Soldering temperature       | $t \leq 10 \text{ s}$ , 1 mm from case | $T_{sd}$    | 260                   | °C   |

**Note**

- Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect the device reliability.

**ELECTRICAL AND OPTICAL CHARACTERISTICS** ( $T_{amb} = 25 \text{ °C}$ , unless otherwise specified)

| PARAMETER             | TEST CONDITION                                                                             | SYMBOL             | MIN. | TYP.     | MAX. | UNIT              |
|-----------------------|--------------------------------------------------------------------------------------------|--------------------|------|----------|------|-------------------|
| Supply current        | $E_v = 0$ , $V_S = 5 \text{ V}$                                                            | $I_{SD}$           | 0.55 | 0.7      | 0.9  | mA                |
|                       | $E_v = 40 \text{ klx}$ , sunlight                                                          | $I_{SH}$           |      | 0.8      |      | mA                |
| Supply voltage        |                                                                                            | $V_S$              | 2.5  |          | 5.5  | V                 |
| Transmission distance | $E_v = 0$ , test signal see fig. 1, IR diode TSAL6200, $I_F = 200 \text{ mA}$              | $d$                |      | 45       |      | m                 |
| Output voltage low    | $I_{OSL} = 0.5 \text{ mA}$ , $E_e = 0.7 \text{ mW/m}^2$ , test signal see fig. 1           | $V_{OSL}$          |      |          | 100  | mV                |
| Minimum irradiance    | Pulse width tolerance: $t_{pi} - 5/f_o < t_{po} < t_{pi} + 6/f_o$ , test signal see fig. 1 | $E_e \text{ min.}$ |      | 0.12     | 0.25 | mW/m <sup>2</sup> |
| Maximum irradiance    | $t_{pi} - 5/f_o < t_{po} < t_{pi} + 6/f_o$ , test signal see fig. 1                        | $E_e \text{ max.}$ | 50   |          |      | W/m <sup>2</sup>  |
| Directivity           | Angle of half transmission distance                                                        | $\phi_{1/2}$       |      | $\pm 45$ |      | deg               |



## TYPICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - Output Active Low




Fig. 4 - Output Pulse Diagram




Fig. 2 - Pulse Length and Sensitivity in Dark Ambient




Fig. 5 - Frequency Dependence of Responsivity




Fig. 3 - Output Function




Fig. 6 - Sensitivity in Bright Ambient




Fig. 7 - Sensitivity vs. Supply Voltage Disturbances




Fig. 10 - Relative Spectral Sensitivity vs. Wavelength




Fig. 8 - Max. Envelope Duty Cycle vs. Burst Length




Fig. 11 - Horizontal Directivity




Fig. 9 - Sensitivity vs. Ambient Temperature




Fig. 12 - Sensitivity vs. Supply Voltage

## SUITABLE DATA FORMAT

This series is designed to suppress spurious output pulses due to noise or disturbance signals. The devices can distinguish data signals from noise due to differences in frequency, burst length, and envelope duty cycle. The data signal should be close to the device's band-pass center frequency (e.g. 38 kHz) and fulfill the conditions in the table below.

When a data signal is applied to the product in the presence of a disturbance, the sensitivity of the receiver is automatically reduced by the AGC to insure that no spurious pulses are present at the receiver's output. Some examples which are suppressed are:

- DC light (e.g. from tungsten bulbs sunlight)
- Continuous signals at any frequency
- Strongly or weakly modulated patterns from fluorescent lamps with electronic ballasts (see figure 13 or figure 14).




Fig. 13 - IR Disturbance from Fluorescent Lamp with Low Modulation




Fig. 14 - IR Disturbance from Fluorescent Lamp with High Modulation


|                                                                               | TSOP22..., TSOP48..                             | TSOP24..., TSOP44..                              |
|-------------------------------------------------------------------------------|-------------------------------------------------|--------------------------------------------------|
| Minimum burst length                                                          | 10 cycles/burst                                 | 10 cycles/burst                                  |
| After each burst of length<br>a minimum gap time is required of               | 10 to 70 cycles<br>≥ 12 cycles                  | 10 to 35 cycles<br>≥ 12 cycles                   |
| For bursts greater than<br>a minimum gap time in the data stream is needed of | 70 cycles<br>> 4 x burst length                 | 35 cycles<br>> 10 x burst length                 |
| Maximum number of continuous short bursts/second                              | 800                                             | 1300                                             |
| NEC code                                                                      | yes                                             | preferred                                        |
| RC5/RC6 code                                                                  | yes                                             | preferred                                        |
| Thomson 56 kHz code                                                           | yes                                             | preferred                                        |
| Sharp code                                                                    | yes                                             | preferred                                        |
| Suppression of interference from fluorescent lamps                            | Most common disturbance patterns are suppressed | Even extreme disturbance patterns are suppressed |

### Notes

- For data formats with short bursts please see the datasheet of TSOP23..., TSOP43..
- Best choice of AGC for some popular IR-codes:
  - TSOP4436, TSOP2436: RC-5, RC-6, Panasonic
  - TSOP4438, TSOP2438: NEC, Sharp, r-step
  - TSOP4456, TSOP2456: r-step, Thomson RCA
- For SIRCS 15 and 20 bit, Sony 12 bit IR-codes, please see the datasheet for TSOP4S40, TSOP2S40



## PACKAGE DIMENSIONS in millimeters



Drawing-No.: 6.550-5169.01-4

Issue: 9; 03.11.10


13655



## IR Receiver Modules for Remote Control Systems

Vishay offers stock molded IR receivers in four different packages:

- Loose packed in tubes, mounted on tape for reel or ammpack, or packed bulk in plastic bags.
- Vishay IR receiver with metal holders are packed in plastic trays. Vishay IR receiver with plastic holders are packed in plastic tubes.



### FEATURES

- Material categorization:  
For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)




**RoHS**  
COMPLIANT  
**GREEN**  
(5-2008)

### AVAILABLE FOR

- TSOP348..
- TSOP344..
- TSOP343..
- TSOP341..
- TSOP44...
- TSOP48...
- TSOP41...
- TSOP324..
- TSOP323..
- TSOP322..
- TSOP321..
- TSOP24...
- TSOP22...
- TSOP21...
- TSOP345..
- TSOP325..
- TSOP43...
- TSOP23...
- TSSP4..
- TSMP4..

### LOOSE PACKED IN TUBE

### ORDERING INFORMATION



O = for IR receiver applications  
M = for repeater/learning applications  
S = for sensor applications

#### Note



- d = "digit", please consult the list of available devices create a valid part number.

**Example: TSOP4838**

### PACKAGING QUANTITY

- 90 pieces per tube
- 24 tubes per carton

### PACKAGING DIMENSIONS in millimeters



Drawing-No.: 9.700-5185.0-4  
Rev. 13; Date: 20.11.03  
20273-1

Druck / Printing for tubes  
1.400-5548.0-3 Version 1




## TAPE AND REEL/AMMOPACK


Up to 3 consecutive components may be missing if the gap is followed by at least 6 components. A maximum of 0.5 % of the components per reel quantity may be missing. At least 5 empty positions are present at the start and the end of the tape to enable insertion.

Tensile strength of the tape: > 15 N


Pulling force in the plane of the tape, at right angles to the reel: > 5 N



80079 tape on reel-s



80079 ammpack-s



| VERSION | DIMENSION "H" |
|---------|---------------|
| BS      | 20 ± 0.5      |
| PS      | 23.3 ± 0.5    |
| OS      | 26 ± 0.5      |

## ORDERING INFORMATION

T S d P

O = for IR receiver applications  
M = for repeater/learning applications  
S = for sensor applications

d d d d d

2 or 3 digit product series  
2 digit frequency

S S 1

SS1 for T and R, bulk or ammpack

d d d d

dd = BS, PS or OS  
Tape and reel  
dd = 12 or 21

Z

Ammpack

### Note

- d = "digit", please consult the list of available devices create a valid part number.

Example: TSOP4838SS1BS12

TSOP2238SS1BS12Z


## PACKAGING QUANTITY

- 1000 pieces per reel
- 1000 pieces per ammpack



**BULK PACKAGING**

The option "BK" signifies bulk packaging in conductive plastic bags. A maximum of 0.3 % of the components per box may be missing.

**ORDERING INFORMATION****Note**

- d = "digit", please consult the list of available devices create a valid part number.

**EXAMPLE: TSOP4838SS1BK****TSOP2238SS1BK****PACKAGING QUANTITY**

- 250 pieces per bag (each bag is individually boxed)
- 6 bags per carton

**OUTER PACKAGING**

| <b>CARTON BOX DIMENSIONS</b> in millimeters                    |           |       |        |
|----------------------------------------------------------------|-----------|-------|--------|
|                                                                |           |       |        |
| KINDS OF CARTON BOX                                            | THICKNESS | WIDTH | LENGTH |
| <b>Packaging Plastic Tubes</b><br>(Normal/auxiliary devices)   | 80        | 150   | 600    |
| <b>Packaging Plastic Trays</b><br>(Devices with metal holders) | 120       | 290   | 490    |
| <b>Tape and Reel Box</b><br>(Taping in reels)                  | 400       | 310   | 410    |
| <b>Ammo-Box</b><br>(Zigzag taping)                             | 50        | 130   | 350    |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)