


EcoCable® Mini

Small Just Got Mini



AlphaWire

*Cables you trust. Service you deserve.*


# EcoCable® Mini Cable

The Smallest Solution to Your Biggest Cable Problems



**S**mall just got mini. Introducing EcoCable Mini. Our newest, completely recyclable high-performance cable is also our smallest and lightest to date. The latest addition to our EcoGen™ family of recyclable wire and cable, EcoCable Mini is small, but the performance advantages are big!

It has all the benefits of our regular EcoCable line, like low specific gravity, low outgassing, and zero halogens. But it's also up to 32% smaller and 44% lighter than standard 300 V PVC cable.



## Small Just got Mini

EcoCable Mini recyclable cable was developed in response to our customers' need for smaller, lighter 300 V cable.

By combining better performance and minimum environmental impact, EcoCable Mini uses its mPPE insulation and jacketing to provide application advantages in a smaller, lighter cable.

Its size makes routing and installation even easier, saving more time during production and maintenance. Even more convenient, it is available in over 250 standard configurations including four shielding options.

## Smaller Size, Lower Weight

Design smaller, lighter devices with EcoCable Mini. Up to 32% smaller and 44% lighter than standard PVC cable, EcoCable Mini uses finely stranded conductors for remarkable flexibility, giving you more options for fast, easy routing. And the thin-wall insulation and jackets give you the most efficient use of constrained spaces.

## Low Outgassing


In applications like medical devices and semiconductor manufacturing equipment, low outgassing is critical in preventing corrosion, contamination, and premature component failure.

EcoCable Mini cable gives you the advantage of up to 92% lower outgassing than PVC control cable. Low outgassing makes it well suited for cleanrooms, where an extremely low particle count is required to lessen the possibility of failure due to contamination.

## More Application Options

EcoCable Mini is a 300 V cable that's ideal for power and signal transmission applications in medical devices, semiconductor manufacturing equipment, and anywhere you are trying to take size and weight out of your design.

Size Comparison: 28 AWG, 2 conductor unshielded cable



It's also available in custom and composite configurations, so finding the right EcoCable Mini cable for your application is easier than ever.

### Take Advantage of all the Advantages

- Up to 32% smaller and 44% lighter than PVC
- 92% lower outgassing than PVC
- 28 to 20 AWG

- 100% recyclable mPPE insulation and jacketing
- Contains no halogens, phthalates, or heavy metals
- Meets RoHS and WEEE requirements

### Superior Availability

- Available from stock in most sizes and constructions
- Put-ups as small as 100'
- Same day shipment, next day delivery



Alpha Wire's next generation of eco-friendly, high-performance wire and cable, designed to provide better performance in a smaller package.

- EcoCable®
- EcoWire®
- EcoFlex® Cable
- EcoWire® Plus
- EcoCable® Mini

Learn more about the new EcoGen family of products at [www.alphawire.com/EcoGen](http://www.alphawire.com/EcoGen)



## Specifications

### Configurations

- Multiconductor or multipair
- Unshielded, foil shielded, individually shielded pairs + overall foil shield, and Supra-Shield Foil + Braid
- Custom and composite configurations available

### Materials

- Conductors: Tinned copper
- Insulation: mPPE
- Shielding: Foil
- Jacket: mPPE

### Temperature Range

- -40°C to +80°C

### Voltage Rating

- 300 V

### Properties

- Zero halogen
- Specific gravity: 1.03
- 100% recyclable
- Low outgassing

### Approvals

- UL AWM 21460
- CE
- CSA I A/B FT1
- RoHS
- REACH
- WEEE
- Suitable for use in NFPA 79 applications
- Meets UL VW-1 Flame Rating

### Availability

- 100 ft (30.5 m) and 1000 ft (305 m) lengths
- Bulk

# EcoCable Mini Cable



## Unshielded Multiconductor

### 28 AWG (0.0925 mm<sup>2</sup>)

Stranding: 19/40 (19 x 0.079 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78002	2	0.094	2.39
78003	3	0.099	2.51
78004	4	0.107	2.72
78006	6	0.124	3.15
78008	8	0.134	3.40

### 26 AWG (0.154 mm<sup>2</sup>)

Stranding: 19/38 (19 x 0.102 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78012	2	0.102	2.59
78013	3	0.107	2.72
78014	4	0.116	2.95
78016	6	0.136	3.45
78018	8	0.147	3.73
78020	10	0.170	4.32
78021	15	0.190	4.83

### 24 AWG (0.241 mm<sup>2</sup>)

Stranding: 19/36 (19 x 0.127 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78022	2	0.112	2.84
78023	3	0.118	3.00
78024	4	0.128	3.25
78026	6	0.152	3.86
78028	8	0.164	4.17
78030	10	0.190	4.83
78031	15	0.213	5.41
78403	20	0.238	6.05
78433	25	0.268	6.81

### 22 AWG (0.382 mm<sup>2</sup>)

Stranding: 19/34 (19 x 0.16 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78032	2	0.126	3.20
78033	3	0.133	3.38
78034	4	0.145	3.68
78036	6	0.173	4.39
78038	8	0.187	4.75
78040	10	0.218	5.54
78041	15	0.245	6.22
78404	20	0.275	6.98
78434	25	0.310	7.87

### 20 AWG (0.616 mm<sup>2</sup>)

Stranding: 19/32 (19 x 0.203 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78042	2	0.142	3.61
78043	3	0.150	3.81
78044	4	0.165	4.19
78046	6	0.197	5.00
78048	8	0.214	5.44
78050	10	0.250	6.35
78055	15	0.282	7.16
78405	20	0.317	8.05
78435	25	0.358	9.09

# EcoCable Mini Cable



## Unshielded Pairs

### 28 AWG (0.0925 mm<sup>2</sup>)

Stranding: 19/40 (19 x 0.079 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78052	2	0.132	3.35
78053	3	0.140	3.56
78054	4	0.153	3.89
78005	5	0.167	4.24
78056	6	0.182	4.62
78058	8	0.198	5.03
78009	9	0.213	5.41

### 26 AWG (0.154 mm<sup>2</sup>)

Stranding: 19/38 (19 x 0.102 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78062	2	0.146	3.71
78063	3	0.154	3.91
78064	4	0.169	4.29
78015	5	0.185	4.70
78066	6	0.202	5.13
78068	8	0.219	5.56
78019	9	0.237	6.02

### 24 AWG (0.241 mm<sup>2</sup>)

Stranding: 19/36 (19 x 0.127 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78072	2	0.162	4.11
78073	3	0.172	4.37
78074	4	0.189	4.80
78025	5	0.207	5.26
78076	6	0.227	5.77
78078	8	0.247	6.27
78029	9	0.267	6.78
78408	20	0.369	9.37
78438	25	0.418	10.62

### 22 AWG (0.382 mm<sup>2</sup>)

Stranding: 19/34 (19 x 0.16 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78082	2	0.185	4.70
78083	3	0.197	5.00
78084	4	0.217	5.51
78035	5	0.239	6.07
78086	6	0.261	6.63
78088	8	0.285	7.24
78039	9	0.309	7.85
78409	20	0.429	10.90
78439	25	0.487	12.37

### 20 AWG (0.616 mm<sup>2</sup>)

Stranding: 19/32 (19 x 0.203 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78092	2	0.211	5.36
78093	3	0.225	5.72
78094	4	0.248	6.30
78045	5	0.274	6.96
78096	6	0.301	7.65
78098	8	0.328	8.33
78049	9	0.356	9.04
78410	20	0.498	12.65
78440	25	0.565	14.35

## More Choice!

EcoCable Mini cable is available with up to 25 conductors and a variety of shielding options. Custom and composite configurations are also available. Consult Alpha Wire for the latest product specifications.

## Sample the Performance

Samples of EcoCable Mini cable are available today! Request yours at [www.alphawire.com/ecogen](http://www.alphawire.com/ecogen) or call 1-800-52 ALPHA

# EcoCable Mini Cable



## Foil Shielded Multiconductor

### 28 AWG (0.0925 mm<sup>2</sup>)

Stranding: 19/40 (19 x 0.079 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78102	2	0.098	2.49
78103	3	0.103	2.62
78104	4	0.111	2.82
78106	6	0.128	3.25
78108	8	0.138	3.51

### 26 AWG (0.154 mm<sup>2</sup>)

Stranding: 19/38 (19 x 0.102 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78112	2	0.106	2.69
78113	3	0.111	2.82
78114	4	0.12	3.05
78116	6	0.14	3.56
78118	8	0.151	3.84
78120	10	0.174	4.42
78121	15	0.194	4.93

### 24 AWG (0.241 mm<sup>2</sup>)

Stranding: 19/36 (19 x 0.127 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78122	2	0.116	2.95
78123	3	0.122	3.10
78124	4	0.132	3.35
78126	6	0.156	3.96
78128	8	0.168	4.27
78130	10	0.194	4.93
78131	15	0.217	5.51
78413	20	0.242	6.15
78443	25	0.272	6.91

### 22 AWG (0.382 mm<sup>2</sup>)

Stranding: 19/34 (19 x 0.16 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78132	2	0.13	3.30
78133	3	0.137	3.48
78134	4	0.149	3.78
78136	6	0.177	4.50
78138	8	0.191	4.85
78140	10	0.222	5.64
78141	15	0.249	6.32
78414	20	0.279	7.09
78444	25	0.314	7.98

### 20 AWG (0.616 mm<sup>2</sup>)

Stranding: 19/32 (19 x 0.203 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
78142	2	0.146	3.71
78143	3	0.154	3.91
78144	4	0.169	4.29
78146	6	0.201	5.11
78148	8	0.218	5.54
78150	10	0.254	6.45
78155	15	0.286	7.26
78415	20	0.321	8.15
78445	25	0.362	9.19

# EcoCable Mini Cable



## Foil Shielded Pairs

### 28 AWG (0.0925 mm<sup>2</sup>)

Stranding: 19/40 (19 x 0.079 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78152	2	0.136	3.45
78153	3	0.144	3.66
78154	4	0.157	3.99
78105	5	0.171	4.34
78156	6	0.186	4.72
78158	8	0.202	5.13
78109	9	0.217	5.51

### 26 AWG (0.154 mm<sup>2</sup>)

Stranding: 19/38 (19 x 0.102 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78162	2	0.150	3.81
78163	3	0.158	4.01
78164	4	0.173	4.39
78115	5	0.189	4.80
78166	6	0.206	5.23
78168	8	0.223	5.66
78119	9	0.241	6.12

### 24 AWG (0.241 mm<sup>2</sup>)

Stranding: 19/36 (19 x 0.127 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78172	2	0.166	4.22
78173	3	0.176	4.47
78174	4	0.193	4.90
78125	5	0.211	5.36
78176	6	0.231	5.87
78178	8	0.251	6.38
78129	9	0.271	6.88
78418	20	0.421	10.69
78448	25	0.478	12.14

### 22 AWG (0.382 mm<sup>2</sup>)

Stranding: 19/34 (19 x 0.16 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78182	2	0.189	4.80
78183	3	0.201	5.11
78184	4	0.221	5.61
78135	5	0.243	6.17
78186	6	0.265	6.73
78188	8	0.289	7.34
78139	9	0.313	7.95
78419	20	0.486	12.34
78449	25	0.551	14.00

### 20 AWG (0.616 mm<sup>2</sup>)

Stranding: 19/32 (19 x 0.203 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78192	2	0.215	5.46
78193	3	0.229	5.82
78194	4	0.252	6.40
78145	5	0.278	7.06
78196	6	0.305	7.75
78198	8	0.332	8.43
78149	9	0.360	9.14
78420	20	0.559	14.20
78450	25	0.635	16.13

## More Choice!

EcoCable Mini cable is available with up to 25 conductors and a variety of shielding options. Custom and composite configurations are also available. Consult Alpha Wire for the latest product specifications.

## Sample the Performance

Samples of EcoCable Mini cable are available today! Request yours at [www.alphawire.com/ecogen](http://www.alphawire.com/ecogen) or call 1-800-52 ALPHA

# EcoCable Mini Cable

## Individually Foil Shielded Pairs + Overall Foil Shield

### 28 AWG (0.0925 mm<sup>2</sup>)

Stranding: 19/40 (19 x 0.079 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78202	2	0.153	3.89
78213	3	0.162	4.11
78204	4	0.177	4.50
78205	5	0.194	4.93
78206	6	0.211	5.36
78208	8	0.229	5.82
78209	9	0.247	6.27

### 26 AWG (0.154 mm<sup>2</sup>)

Stranding: 19/38 (19 x 0.102 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78212	2	0.167	4.24
78223	3	0.177	4.50
78214	4	0.194	4.93
78215	5	0.213	5.41
78216	6	0.232	5.89
78218	8	0.252	6.40
78219	9	0.273	6.93

### 24 AWG (0.241 mm<sup>2</sup>)

Stranding: 19/36 (19 x 0.127 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78222	2	0.185	4.70
78233	3	0.196	4.98
78224	4	0.215	5.46
78225	5	0.237	6.02
78226	6	0.259	6.58
78228	8	0.282	7.16
78229	9	0.305	7.75

### 22 AWG (0.382 mm<sup>2</sup>)

Stranding: 19/34 (19 x 0.16 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78232	2	0.209	5.31
78243	3	0.222	5.64
78234	4	0.245	6.22
78235	5	0.270	6.86
78236	6	0.296	7.52
78238	8	0.322	8.18
78239	9	0.349	8.86

### 20 AWG (0.616 mm<sup>2</sup>)

Stranding: 19/32 (19 x 0.203 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78242	2	0.237	6.02
78253	3	0.253	6.43
78244	4	0.279	7.09
78245	5	0.308	7.82
78246	6	0.338	8.59
78248	8	0.369	9.37
78249	9	0.400	10.16

# EcoCable Mini Cable

## Supra-Shield Foil + Braid Multiconductor

### 28 AWG (0.0925 mm<sup>2</sup>)

Stranding: 19/40 (19 x 0.079 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
<b>78302</b>	2	0.125	3.18
<b>78303</b>	3	0.130	3.30
<b>78304</b>	4	0.138	3.51
<b>78306</b>	6	0.155	3.94
<b>78308</b>	8	0.165	4.19

### 26 AWG (0.154 mm<sup>2</sup>)

Stranding: 19/38 (19 x 0.102 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
<b>78312</b>	2	0.133	3.38
<b>78313</b>	3	0.138	3.51
<b>78314</b>	4	0.147	3.73
<b>78316</b>	6	0.167	4.24
<b>78318</b>	8	0.178	4.52
<b>78320</b>	10	0.201	5.11
<b>78321</b>	15	0.221	5.61

### 24 AWG (0.241 mm<sup>2</sup>)

Stranding: 19/36 (19 x 0.127 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
<b>78322</b>	2	0.143	3.63
<b>78323</b>	3	0.149	3.78
<b>78324</b>	4	0.159	4.04
<b>78326</b>	6	0.183	4.65
<b>78328</b>	8	0.195	4.95
<b>78330</b>	10	0.221	5.61
<b>78331</b>	15	0.244	6.20
<b>78423</b>	20	0.269	6.83
<b>78453</b>	25	0.299	7.59

### 22 AWG (0.382 mm<sup>2</sup>)

Stranding: 19/34 (19 x 0.16 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
<b>78332</b>	2	0.157	3.99
<b>78333</b>	3	0.164	4.17
<b>78334</b>	4	0.176	4.47
<b>78336</b>	6	0.204	5.18
<b>78338</b>	8	0.218	5.54
<b>78340</b>	10	0.249	6.32
<b>78341</b>	15	0.276	7.01
<b>78424</b>	20	0.306	7.77
<b>78454</b>	25	0.341	8.66

### 20 AWG (0.616 mm<sup>2</sup>)

Stranding: 19/32 (19 x 0.203 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Conductors	Nominal Diameter	
		Inch	mm
<b>78342</b>	2	0.173	4.39
<b>78343</b>	3	0.181	4.60
<b>78344</b>	4	0.196	4.98
<b>78346</b>	6	0.228	5.79
<b>78348</b>	8	0.245	6.22
<b>78350</b>	10	0.281	7.14
<b>78355</b>	15	0.313	7.95
<b>78425</b>	20	0.348	8.84
<b>78455</b>	25	0.389	9.88

## More Choice!

EcoCable Mini cable is available with up to 25 conductors and a variety of shielding options. Custom and composite configurations are also available. Consult Alpha Wire for the latest product specifications.

## Sample the Performance

Samples of EcoCable Mini cable are available today!  
Request yours at [www.alphawire.com/ecogen](http://www.alphawire.com/ecogen)  
or call 1-800-52 ALPHA

# EcoCable Mini Cable

## Supra-Shield Foil + Braid Pairs

### 28 AWG (0.0925 mm<sup>2</sup>)

Stranding: 19/40 (19 x 0.079 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78352	2	0.163	4.14
78353	3	0.171	4.34
78354	4	0.184	4.67
78305	5	0.198	5.03
78356	6	0.213	5.41
78358	8	0.229	5.82
78309	9	0.244	6.20

### 26 AWG (0.154 mm<sup>2</sup>)

Stranding: 19/38 (19 x 0.102 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78362	2	0.177	4.50
78363	3	0.185	4.70
78364	4	0.200	5.08
78315	5	0.216	5.49
78366	6	0.233	5.92
78368	8	0.250	6.35
78319	9	0.268	6.81

### 24 AWG (0.241 mm<sup>2</sup>)

Stranding: 19/36 (19 x 0.127 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78372	2	0.193	4.90
78373	3	0.203	5.16
78374	4	0.220	5.59
78325	5	0.238	6.05
78376	6	0.258	6.55
78378	8	0.278	7.06
78329	9	0.298	7.57
78428	20	0.400	10.16
78458	25	0.449	11.40

### 22 AWG (0.382 mm<sup>2</sup>)

Stranding: 19/34 (19 x 0.16 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78382	2	0.216	5.49
78383	3	0.228	5.79
78384	4	0.248	6.30
78335	5	0.270	6.86
78386	6	0.292	7.42
78388	8	0.316	8.03
78339	9	0.340	8.64

### 20 AWG (0.616 mm<sup>2</sup>)

Stranding: 19/32 (19 x 0.203 mm)  
Insulation thickness: 0.007 (0.18 mm)  
Jacket thickness: 0.015 (0.38 mm)

Part Number	Pairs	Nominal Diameter	
		Inch	mm
78392	2	0.242	6.15
78393	3	0.256	6.50
78394	4	0.279	7.09
78345	5	0.305	7.75
78396	6	0.332	8.43
78398	8	0.359	9.12
78349	9	0.387	9.83

## Cables you trust. Service you deserve.

Every application is critical and cable failure is not an option when the safety of your equipment and personnel is paramount. Specify Alpha products since the integrity of your system is only as robust as the products you use.

## Superior availability

Alpha offers wire and cable from stock in most sizes and constructions, in both small and large put-ups, so you can order it when you need it. Our products are available for same-day shipment, eliminating long lead times.

## Service and support, second-to-none

Selecting the correct cable for your critical application is essential to overall system reliability, performance, and safety. So we make it easy for you to select the right Alpha product for your specific application. Our online resources include a wire and cable selection guide, technical information, full product catalog, and a distributor locator to make it easy to select and get the wire or cable you need. Can't find what you're looking for? Design the cable to your specification. It's easy, just visit **[www.alphawire.com](http://www.alphawire.com)**!

GLOBAL HEADQUARTERS  
711 Lidgerwood Avenue  
Elizabeth, NJ 07207-0711 USA  
Toll Free: 1-800-52 ALPHA  
Tel: 1-908-925-8000  
Fax: 1-908-925-5411  
E-mail: [info@alphawire.com](mailto:info@alphawire.com)

EUROPE  
Alpha Wire International  
Saxon House  
1 Downside | Sunbury-on-Thames  
Middlesex | United Kingdom  
TW16 6RT  
Tel: +44-(0)-800-288-8809  
Fax: +44-(0)-800-288-8810  
E-mail: [europa@alphawire.com](mailto:europa@alphawire.com)

ASIA PACIFIC  
Alpha Wire  
Silver Center | Room 1708  
North Shanxi Road 1388  
Shanghai | China | 200060  
Tel: +86-21-61498201/61498205  
Fax: +86-21-61498001  
E-mail: [apac@alphawire.com](mailto:apac@alphawire.com)



Alpha Wire's next generation of eco-friendly, high-performance wire and cable, designed to provide better performance in a smaller package.



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)