





ORDERING CODE: **MRJ-59XX-X1**

SERIES, RUGGED RJ



RECEPTACLE, RIGHT ANGLE, ON PCB WITH TERMINAL BLOCKS

NUMBER OF CONTACTS
8= 8 CONTACTS
A=10 CONTACTS

LED OPTION
0=NONE
1=GREEN LEFT, YELLOW RIGHT
4=YELLOW LEFT, GREEN RIGHT
5=GREEN LEFT, GREEN RIGHT

MOUNTING HOLE THREAD OPTION
0= #4-40 UNC THREAD
M= M3 x 0.5 THREAD

SINGLE PORT



NOTES:


- MATERIAL:
ALL MATERIALS ARE RoHS COMPLIANT PER EU DIRECTIVE 2002/95/EC AND AMENDMENTS
 - SHELL - DIECAST ZINC, NICKEL PLATED
 - CONTACTS - PHOSPHOR BRONZE WITH 50 MICROINCHES (1.27 MICRONS) GOLD OVER 50 MICROINCHES (1.27 MICRONS) MINIMUM NICKEL ON THE MATING AREA AND MATTE TIN OVER NICKEL ON THE CONTACT TAILS.
 - INSERTS - ENGINEERING THERMOPLASTIC, UL FLAMMABILITY RATING 94V-0, REAR INSERTS: BLACK, FRONT INSERT: CLEAR
 - LED'S - EPOXY LENS, STEEL TAILS WITH TIN PLATING
 - GASKET - SILICONE RUBBER
 - PCB - FR-4 FIBERGLASS, LEAD FREE
 - TERMINAL BLOCKS - ENGINEERING THERMOPLASTIC HOUSING (UL94V-0, GREEN) WITH COPPER ALLOY, NICKEL PLATED CLAMPS & SCREWS AND COPPER ALLOY, TIN PLATED TERMINALS.
- ENVIRONMENTAL PERFORMANCE PER IEC 60529 CODE IP67 FOR SEAL BETWEEN MATING AREA AND PCB SIDE OF CONNECTOR. GASKET PROVIDES FOR SEAL TO INSIDE FACE OF PANEL.
- CURRENT RATING: 1.5 AMPERES.
- CONTACT RESISTANCE: 50 MILLIOHMS.
- OPERATING TEMPERATURE: -40C TO +105C.
- AVAILABLE MATING AREA COVERS PROVIDE ADDED PROTECTION. CONSULT WITH AMPHENOL CANADA FOR DETAILS.
- RECOMMENDED TORQUE FOR PANEL MOUNT SCREWS:
0.45 TO 0.65 Nm (4.00 - 5.75 IN-LBS) FOR STEEL SCREWS WITH 3.00 (.118) THREAD ENGAGEMENT.




PROPRIETARY AND CONFIDENTIAL
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

UNLESS OTHERWISE SPECIFIED:		DATE	Amphenol Canada Corp.	
DIMENSIONS ARE IN MILLIMETERS	DRAWN G.LI	FEB21/08	MRJ SERIES RUGGED MODULAR JACK, 8 & 10 POSITION RIGHT ANGLE, ON PCB WITH TERMINAL BLOCKS, RoHS COMPLIANT	
TOLERANCES:	DESIGNED			
FRACTIONAL: ±	CHECKED			
ANGULAR: MACH ± BEND ±	I.E. APPRD.			
TWO PLACE DECIMAL	Q. A. APPRD.		SIZE DWG. NO. REV C P-MRJ-59XX-X1 A	
THREE PLACE DECIMAL	DWG. APPRD. K.LAMBIE	FEB21/08		
INTERPRET GEOMETRIC TOLERANCING PER:	ENG. REL. NO. EAR 13226		SCALE: 3:1 WEIGHT: SHEET 1 OF 2	
MATERIAL	REF.			
FINISH	DIMENSIONS ARE IN MILLIMETERS	CODE ID. NO.		
NEXT ASSY	USED ON			
APPLICATION	DO NOT SCALE DRAWING			


VIEWS FOR 10 POSITION OR 8 POSITION WITH LED'S



VIEWS FOR 8 POSITION WITHOUT LED'S






REVISIONS			
REV	ECN, ERN NO.	DATE	APPRD.
A	PRODUCT DWG (EAR 13226)	FEB21/08	K.L.



RECOMMENDED PANEL CUTOUT

MRJ TO TERMINAL BLOCK CONNECTION CHART

MRJ CONNECTOR STYLE				CONNECTED TO TERMINAL BLOCK POSITION
8 POSITION NO LED'S	8 POSITION WITH LED'S	10 POSITION NO LED'S	10 POSITION WITH LED'S	
SHELL/GROUND	SHELL/GROUND	SHELL/GROUND	SHELL/GROUND	A1 & B1
CONTACT 4	CONTACT 4	CONTACT 5	CONTACT 5	A2
CONTACT 3	CONTACT 3	CONTACT 4	CONTACT 4	A3
CONTACT 2	CONTACT 2	CONTACT 3	CONTACT 3	A4
CONTACT 1	CONTACT 1	CONTACT 2	CONTACT 2	A5
---	---	CONTACT 1	CONTACT 1	A6
---	LED 1	---	LED 1	A7
---	LED 2	---	LED 2	A8
CONTACT 5	CONTACT 5	CONTACT 6	CONTACT 6	B2
CONTACT 6	CONTACT 6	CONTACT 7	CONTACT 7	B3
CONTACT 7	CONTACT 7	CONTACT 8	CONTACT 8	B4
CONTACT 8	CONTACT 8	CONTACT 9	CONTACT 9	B5
---	---	CONTACT 10	CONTACT 10	B6
---	LED 4	---	LED 4	B7
---	LED 3	---	LED 3	B8
5	8	8	8	POSITIONS / ROW
13.16 [.518]	20.78 [.818]	20.78 [.818]	20.78 [.818]	"A" DIMENSION



LED POLARITY



PROPRIETARY AND CONFIDENTIAL
THIS DOCUMENT CONTAINS
PROPRIETARY INFORMATION AND SUCH
INFORMATION MAY NOT BE DISCLOSED
TO OTHERS FOR ANY PURPOSE OR USED
FOR MANUFACTURING PURPOSES
WITHOUT WRITTEN PERMISSION FROM
AMPHENOL CANADA CORP.

UNLESS OTHERWISE SPECIFIED:		DATE	Amphenol Canada Corp.	
DIMENSIONS ARE IN MILLIMETERS	DRAWN	G.LI	FEB21/08	
TOLERANCES:	DESIGNED			
FRACTIONAL: ±	CHECKED			
ANGULAR: MACH ± BEND ±	I.E. APPRD.			
TWO PLACE DECIMAL ±	Q. A. APPRD.			
THREE PLACE DECIMAL ±	DWG. APPRD. K.LAMBIE	FEB21/08		
INTERPRET ISOMETRIC	ENG. REL. NO. EAR 13226			
TOLERANCING PER:	REF.			
MATERIAL	DIMENSIONS ARE IN	CODE ID. NO.		
FINISH	MILLIMETERS			
NEXT ASSY	USED ON			
APPLICATION	DO NOT SCALE DRAWING			
			SIZE DWG. NO.	REV
			C P-MRJ-59XX-X1	A
			SCALE: 4:1	WEIGHT:
			SHEET 2 OF 2	

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru