MOMENTARY ACTION, SEALED SUB-SUBMINIATURE PUSHBUTTON SNAP-ACTION SWITCHES

The P7 series incorporates OTTO's patented double break design in a significantly smaller package than the P1 series. These subminiature switches embrace today's technology requirements by allowing for a large number of switches to fit within a faceplate.

The long life snap-action design is protected from the environment by a silicon rubber boot, operating on a patented "rolling sleeve" principle that gives long sealed life and smooth operation.

The P7 series is designed to meet the requirements of MIL-PRF-8805 including low level switching (10mA @ 30mV) with power switching up to 5 amps at 28VDC as well.

A variety of mounting styles are offered to best match the application. The P7-1, P7-2, P7-7 and P7-8 case styles feature a swaged bushing shape to allow press fit installation in aircraft flight control and hand grips and similar applications. The other styles feature threaded bushing mounting. The P7-3 case style has a front panel bezel, while the P7-5 and P7-6 have conventional bushings for rear panel mounted installations. Silver or black bezels are standard. Other colors available on special order.

Pushbuttons are available in a choice of nine colors. Excellent tactile feedback assures the operator that contact transfer has been made.

A choice of MIL-SPEC and commercial versions of these switches are offered: Moistureproof and dusttight to IP64 and MIL-PRF-8805 Design 2 or watertight to IP68S and to MIL-PRF-8805 Design 3.

Features:

- **Low level switching capability**
- **Less than 25mΩ contact resistance**
- **High contact pressure**
- **6 circuit variations**
- **Positive tactile feedback**
- **Variety of mounting styles**
- **Qualified to MIL-PRF-8805/110**
- **Moistureproof & dusttight to IP64 & MIL-PRF-8805 Design 2 or watertight to IP68S & MIL-PRF-8805 Design 3**
- **RoHS/WEEE/Reach compliant**

Standard Characteristics/Ratings:

ELECTRICAL RATINGS:	Sea Level @ 28VDC			50,000 feet @ 28VDC		
Load **Circuits:**	**1 & 2**	**3–5**	**6**	**1 & 2**	**3–5**	**6**
Resistive	5A	2.5A	4A	5A	2.5A	4A
Inductive	3A	1.5A	2A	3A	1.5A	2A
Lamp	1A	0.5A	N/A	N/A	N/A	N/A
Motor	3A	1.5A	N/A	N/A	N/A	N/A
DWV	1050Vrms			400Vrms		
Center Contact	3A max					
Low Level	10mA @ 30mV					

Electrical Life:	25,000 cycles
Mechanical Life:	1,000,000 cycles
Seal:	IP64 and MIL-PRF-8805 Design 2 or IP68S and MIL-PRF-8805 Design 3
Operating Temp Range:	-55°C to +85°C
Operating Force:	1.7 +/- 0.5 lb.
Total Travel:	0.080 inches max
Overtravel:	0.010 inches min
MATERIALS:	
Case:	Anodized aluminum alloy
Button:	Thermoplastic
Terminals:	Brass with gold over silver
Terminal Hardware:	None provided
Mounting Hardware:	Hex nut, lockwasher and panel gasket when applicable

MINI-SIZED PER MIL-PRF-8805/110

SEALED AGAINST DUST & MOISTURE, LOW LEVEL SWITCHING OPTION

P7-1 Series

Case Style 1
Press Fit Mount

Also available with PC terminals.



P7-2 Series

Case Style 2
Press Fit Mount

Also available with PC pins.



P7-3 Series

Case Style 3
Bezel/Threaded Bushing

Also available with PC pins.



P7-5 Series

Case Style 5
1/4" Threaded Bushing

Also available with PC pins.



PC Pin Mounting Pattern

(As viewed from switch bottom. See above drawings for terminal identification.)



P7-6 Series

Case Style 6
15/32" Threaded Bushing

Also available with PC pins.



P7-7 Series

Case Style 7
Press Fit Mount

Also available with PC pins.



P7-8 Series

Case Style 8
Press Fit Mount
Guarded Button

Also available with PC pins.



P7-5 Series

Case Style 5
1/4" Threaded Bushing

Also available with PC pins.

Terminal Style "A" & "B"

Standard



P7 PART NUMBER CODE

P7 – X X X X X X

Case Style	Terminal Style/ Construction Grade	Circuit Form	Contact Rating	Bezel Color/ Button Dia.	Button Color
1. Style 1	**A.** Solder/Commercial	**1.** N.O.	**1.** Std.	**1.** Clear/Std.	**1.** Red
2. Style 2	**B.** Solder/Watertight Commercial	**2.** N.C.	**2.** Low Level	**2.** Black/Std.	**2.** Black
3. Style 3	**1.** Solder/Military/Short	**3.** N.C. 3 Terminal		**3.** Clear/0.312 ①	**3.** Orange
5. Style 5	**2.** Solder/Commercial/Short	**4.** N.O. 3 Terminal		**4.** Black/0.312 ①	**4.** Yellow
6. Style 6	**3.** Solder/Mil. Watertight/Short	**5.** 5 Terminal			**5.** Green
7. Style 7	**4.** PC Pin/Commercial	**6.** 2 Circuit			**6.** Blue
8. Style 8	**5.** PC Pin/Military				**7.** Purple
	6. PC Pin/Mil. Watertight				**8.** Gray
	7. Solder/Com. Watertight/Short				**9.** White
	8. PC Pin/Com. Watertight				

① Not available with Case Styles 1, 2 & 5.

Specifications Subject To Change Without Notice

EXAMPLES OF CUSTOMIZED P7 SEALED PUSHBUTTONS

Special Longer Length Button

Panel seal gasket and watertight enclosure. Button is black nylon. Bezel is black anodized aluminum alloy.

Actuation	OTTO Part Number
Momentary	P7-500001



Special Large Button, Press Fit

Available with a 0.375" dia. button with three color options.

Color	OTTO Part Number
Red	P7-900001
Black	P7-900002
White	P7-900009

Contact factory for additional button color options.



Special Snap-On Button, Wire Leads

Features changeable snap-on button caps available in two diameters and in a range of colors. Switch is splashproof sealed per MIL-PRF-8805 and is supplied with a silicone panel gasket.

Part Number: P7-500018

Button Color	0.440" Dia.	0.375" Dia.
Red	C400725-1	C400723-1
Black	C400725-2	C400723-2
Orange	C400725-3	C400723-3
White	C400725-9	C400723-9

Contact factory for additional button color options.



Mini Pushbutton, Shrouded

This shrouded pushbutton is designed to reduce the chance of inadvertant actuation. Button size is .19". Enclosure design is watertight per IP68S.

Actuation	OTTO Part Number
Momentary	P7-900196



PUSHBUTTONS

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru