

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Double-level terminal block, Cross section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, AWG: 26 - 14, Connection type: Push-in connection, Width: 3.5 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

### Product Features

- ✓ The push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- ✓ The compact design and front connection enable wiring in a confined space
- ✓ In addition to the testing facility in the double function shaft, all terminal blocks provide an additional test connection



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 PCE    |
| Minimum order quantity               | 50 PCE   |
| Weight per Piece (excluding packing) | 8.4 GRM  |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Poland   |

### Technical data

#### General

|                                         |               |
|-----------------------------------------|---------------|
| Number of levels                        | 2             |
| Number of connections                   | 4             |
| Color                                   | gray          |
| Insulating material                     | PA            |
| Inflammability class according to UL 94 | V0            |
| Rated surge voltage                     | 6 kV          |
| Surge voltage category                  | III           |
| Insulating material group               | I             |
| Connection in acc. with standard        | IEC 60947-7-1 |
| Nominal current I <sub>N</sub>          | 16 A          |

# Double-level terminal block - PTTBS 1,5/S-PV - 3214686

## Technical data

### General

|                                                                                 |                                                     |
|---------------------------------------------------------------------------------|-----------------------------------------------------|
| Nominal voltage $U_N$                                                           | 500 V                                               |
| Open side panel                                                                 | ja                                                  |
| Shock protection test specification                                             | DIN EN 50274 (VDE 0660-514):2002-11                 |
| Back of the hand protection                                                     | guaranteed                                          |
| Finger protection                                                               | guaranteed                                          |
| Surge voltage test setpoint                                                     | 7.3 kV                                              |
| Result of surge voltage test                                                    | Test passed                                         |
| Power frequency withstand voltage setpoint                                      | 1.89 kV                                             |
| Result of power-frequency withstand voltage test                                | Test passed                                         |
| Checking the mechanical stability of terminal points (5 x conductor connection) | Test passed                                         |
| Bending test rotation speed                                                     | 10 rpm                                              |
| Bending test turns                                                              | 135                                                 |
| Bending test conductor cross section/weight                                     | 0.14 mm <sup>2</sup> / 0.2 kg                       |
|                                                                                 | 1.5 mm <sup>2</sup> / 0.4 kg                        |
| Result of bending test                                                          | Test passed                                         |
| Conductor cross section tensile test                                            | 0.14 mm <sup>2</sup>                                |
| Tractive force setpoint                                                         | 10 N                                                |
| Conductor cross section tensile test                                            | 1.5 mm <sup>2</sup>                                 |
| Tractive force setpoint                                                         | 40 N                                                |
| Tensile test result                                                             | Test passed                                         |
| Tight fit on carrier                                                            | NS 35                                               |
| Setpoint                                                                        | 1 N                                                 |
| Result of tight fit test                                                        | Test passed                                         |
| Requirements, voltage drop                                                      | $\leq 3.2$ mV                                       |
| Result of voltage drop test                                                     | Test passed                                         |
| Temperature-rise test                                                           | Test passed                                         |
| Conductor cross section short circuit testing                                   | 1.5 mm <sup>2</sup>                                 |
| Short-time current                                                              | 0.18 kA                                             |
| Short circuit stability result                                                  | Test passed                                         |
| Ageing test for screwless modular terminal block temperature cycles             | 192                                                 |
| Result of aging test                                                            | Test passed                                         |
| Proof of thermal characteristics (needle flame) effective duration              | 30 s                                                |
| Result of thermal test                                                          | Test passed                                         |
| Test specification, oscillation, broadband noise                                | DIN EN 50155 (VDE 0115-200):2008-03                 |
| Test spectrum                                                                   | Service life test category 1, class B, body mounted |
| Test frequency                                                                  | $f_1 = 5$ Hz to $f_2 = 150$ Hz                      |

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Technical data

#### General

|                                                                       |                                            |
|-----------------------------------------------------------------------|--------------------------------------------|
| ASD level                                                             | 1.857 (m/s <sup>2</sup> ) <sup>2</sup> /Hz |
| Acceleration                                                          | 0.8 g                                      |
| Test duration per axis                                                | 5 h                                        |
| Test directions                                                       | X-, Y- and Z-axis                          |
| Oscillation, broadband noise test result                              | Test passed                                |
| Test specification, shock test                                        | DIN EN 50155 (VDE 0115-200):2008-03        |
| Shock form                                                            | Half-sine                                  |
| Acceleration                                                          | 5 g                                        |
| Shock duration                                                        | 30 ms                                      |
| Number of shocks per direction                                        | 3                                          |
| Test directions                                                       | X-, Y- and Z-axis (pos. and neg.)          |
| Shock test result                                                     | Test passed                                |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C                                     |
| Static insulating material application in cold                        | -60 °C                                     |

#### Dimensions

|                  |         |
|------------------|---------|
| Width            | 3.5 mm  |
| Length           | 78.8 mm |
| Height NS 35/7,5 | 48.2 mm |
| Height NS 35/15  | 55.7 mm |

#### Connection data

|                                                                            |                      |
|----------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                         | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                         | 1.5 mm <sup>2</sup>  |
| Conductor cross section stranded min.                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded max.                                      | 1.5 mm <sup>2</sup>  |
| Conductor cross section AWG/kcmil min.                                     | 26                   |
| Conductor cross section AWG/kcmil max                                      | 14                   |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>  |
| Conductor cross section stranded, with ferrule with plastic sleeve min.    | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve max.    | 1 mm <sup>2</sup>    |
| Connection method                                                          | Push-in connection   |
| Stripping length                                                           | 8 mm                 |
| Internal cylindrical gage                                                  | A1 / B1              |

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141121 |
| eCl@ss 4.1 | 27141121 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / GOST / GL / LR / CSA / GOST / cULus Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

#### Approval details

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Approvals

| UL Recognized  |       |       |       |
|-------------------------------------------------------------------------------------------------|-------|-------|-------|
|                                                                                                 | B     | C     | D     |
| mm <sup>2</sup> /AWG/kcmil                                                                      | 26-14 | 26-14 | 26-14 |
| Nominal current I <sub>N</sub>                                                                  | 15 A  | 15 A  | 5 A   |
| Nominal voltage U <sub>N</sub>                                                                  | 300 V | 300 V | 600 V |

| cUL Recognized  |       |       |       |
|--------------------------------------------------------------------------------------------------|-------|-------|-------|
|                                                                                                  | B     | C     | D     |
| mm <sup>2</sup> /AWG/kcmil                                                                       | 26-14 | 26-14 | 26-14 |
| Nominal current I <sub>N</sub>                                                                   | 15 A  | 15 A  | 5 A   |
| Nominal voltage U <sub>N</sub>                                                                   | 300 V | 300 V | 600 V |

|                                                                                          |  |  |  |
|------------------------------------------------------------------------------------------|--|--|--|
| GOST  |  |  |  |
|------------------------------------------------------------------------------------------|--|--|--|

|    |  |  |  |
|----|--|--|--|
| GL |  |  |  |
|----|--|--|--|

|    |  |  |  |
|----|--|--|--|
| LR |  |  |  |
|----|--|--|--|

| CSA  |       |       |       |
|-----------------------------------------------------------------------------------------|-------|-------|-------|
|                                                                                         | B     | C     | D     |
| mm <sup>2</sup> /AWG/kcmil                                                              | 26-14 | 26-14 | 26-14 |
| Nominal current I <sub>N</sub>                                                          | 15 A  | 15 A  | 5 A   |
| Nominal voltage U <sub>N</sub>                                                          | 300 V | 300 V | 600 V |

|                                                                                          |  |  |  |
|------------------------------------------------------------------------------------------|--|--|--|
| GOST  |  |  |  |
|------------------------------------------------------------------------------------------|--|--|--|

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Approvals

cULus Recognized  US

### Accessories

#### Accessories

##### Bridge

Jumper - FBS 1,5/S-PV - 3216263



Jumper, Length: 3 mm, Width: 3.5 mm, Color: black

Jumper - FBS 2-3,5 - 3213014



Jumper, Number of positions: 2, Color: red

Jumper - FBS 3-3,5 - 3213027



Jumper, Number of positions: 3, Color: red

Jumper - FBS 4-3,5 - 3213030



Jumper, Number of positions: 4, Color: red

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

Jumper - FBS 5-3,5 - 3213043



Jumper, Number of positions: 5, Color: red

---

Jumper - FBS 10-3,5 - 3213056



Jumper, Number of positions: 10, Color: red

---

Jumper - FBS 20-3,5 - 3213069



Jumper, Number of positions: 20, Color: red

---

### Documentation

Mounting material - PT-IL - 3208090

Operating decal for the Push-in Technology



### End block

End clamp - CLIPFIX 35 - 3022218



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

---

#### End clamp - CLIPFIX 35-5 - 3022276



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

#### End clamp - E/NS 35 N - 0800886



End clamp, width: 9.5 mm, color: gray

---

#### End cover

##### End cover - D-PTTBS 1,5/S - 3214699



End cover, Length: 78 mm, Width: 2.2 mm, Color: gray

---

#### Insulating sleeve

##### Insulating sleeve - MPS-IH WH - 0201663



Insulating sleeve, Color: white

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

Insulating sleeve - MPS-IH RD - 0201676



Insulating sleeve, Color: red

---

Insulating sleeve - MPS-IH BU - 0201689



Insulating sleeve, Color: blue

---

Insulating sleeve - MPS-IH YE - 0201692



Insulating sleeve, Color: yellow

---

Insulating sleeve - MPS-IH GN - 0201702



Insulating sleeve, Color: green

---

Insulating sleeve - MPS-IH GY - 0201728



Insulating sleeve, Color: gray

---

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

Insulating sleeve - MPS-IH BK - 0201731



Insulating sleeve, Color: black

---

### Labeled terminal marker

Zack marker strip - ZB 3,5 CUS - 0829415



Zack marker strip, Can be ordered: Strip, white, Labeled according to customer specifications, Mounting type: Snap into tall marker groove, For terminal block width: 3.5 mm, Lettering field: 3.5 x 10.5 mm

---

Marker for terminal blocks - UCT-TM 3,5 CUS - 0829581



Marker for terminal blocks, Can be ordered: By sheet, white, Labeled according to customer specifications, Mounting type: Snap into tall marker groove, For terminal block width: 3.5 mm, Lettering field: 2.95 x 10.5 mm

---

Zack Marker strip, flat - ZBF 3,5 CUS - 0829394



Zack Marker strip, flat, Can be ordered: Strip, white, Labeled according to customer specifications, Mounting type: Snap into flat marker groove, For terminal block width: 3.5 mm, Lettering field: 3.5 x 5.2 mm

---

Marker for terminal blocks - UCT-TMF 3,5 CUS - 0829644



Marker for terminal blocks, Can be ordered: By sheet, white, Labeled according to customer specifications, Mounting type: Snap into flat marker groove, For terminal block width: 3.5 mm, Lettering field: 2.7 x 4.7 mm

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

#### Marker carriers

Marker carriers - STP 3,5-2 - 0830131



Double marker carrier, can be snapped into the PTTB 1,5/S Push-in double-level terminal block, can be labeled with ZB 3,5 or ZBF 3,5

---

#### Mounting rail

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

---

DIN rail - NS 35/ 7,5 UNPERF 2000MM - 0801681



DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/ 7,5 WH PERF 2000MM - 1204119



DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/ 7,5 WH UNPERF 2000MM - 1204122



DIN rail 35 mm (NS 35)

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

---

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704



DIN rail, unperforated, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver

---

DIN rail - NS 35/ 7,5 ZN PERF 2000MM - 1206421



DIN rail, material: Galvanized, perforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



DIN rail, material: Galvanized, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/ 7,5 CU UNPERF 2000MM - 0801762



DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

End cap - NS 35/ 7,5 CAP - 1206560



DIN rail end piece, for DIN rail NS 35/7.5

---

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

DIN rail - NS 35/15 UNPERF 2000MM - 1201714



DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

DIN rail - NS 35/15 WH PERF 2000MM - 0806602



DIN rail 35 mm (NS 35)

DIN rail - NS 35/15 WH UNPERF 2000MM - 1204135



DIN rail 35 mm (NS 35)

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756



DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

DIN rail - NS 35/15 ZN PERF 2000MM - 1206599



DIN rail, material: Galvanized, perforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/15 ZN UNPERF 2000MM - 1206586



DIN rail, material: Galvanized, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/15 CU UNPERF 2000MM - 1201895



DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

---

End cap - NS 35/15 CAP - 1206573



DIN rail end piece, for DIN rail NS 35/15

---

DIN rail - NS 35/15-2,3 UNPERF 2000MM - 1201798



DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

---

### Partition plate

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

Partition plate - ATP-STTB 4 - 3030747



Partition plate, Length: 88.7 mm, Width: 2 mm, Height: 53 mm, Color: gray

---

### Planning and marking software

Software - CLIP-PROJECT ADVANCED - 5146040



Multilingual software for easy planning of Phoenix Contact on DIN rails together with the integrated TRABTECH-select software module for planning comprehensive surge protection concepts.

---

Software - CLIP-PROJECT PROFESSIONAL - 5146053



Multi-lingual software for terminal strip project planning. A marking module allows professional labeling of markers and labels for marking terminal blocks, conductors, cables and devices. The additionally integrated software module TRABTECH-select for planning comprehensive surge protection concepts.

---

### Screwdriver tools

Screwdriver - SZF 1-0,6X3,5 - 1204517



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

---

Screwdriver - SZF 0-0,4X2,5 - 1204504



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.4 x 2.5 x 75 mm, 2-component grip, with non-slip grip

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

---

#### Terminal marking

##### Zack marker strip - ZB 3,5:UNBEDRUCKT - 0829414



Zack marker strip, Strip, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Snap into tall marker groove, For terminal block width: 3.5 mm, Lettering field: 3.5 x 10.5 mm

---

##### Marker for terminal blocks - UCT-TM 3,5 - 0829484



Marker for terminal blocks, Sheet, white, Unlabeled, Can be labeled with: THERMOMARK CARD PLUS, THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, Mounting type: Snap into tall marker groove, For terminal block width: 3.5 mm, Lettering field: 2.95 x 10.5 mm

---

##### Zack Marker strip, flat - ZBF 3,5:UNBEDRUCKT - 0829392



Zack Marker strip, flat, Strip, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Snap into flat marker groove, For terminal block width: 3.5 mm, Lettering field: 3.5 x 5.2 mm

---

##### Marker for terminal blocks - UCT-TMF 3,5 - 0829486



Marker for terminal blocks, Sheet, white, Unlabeled, Can be labeled with: THERMOMARK CARD PLUS, THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, Mounting type: Snap into flat marker groove, For terminal block width: 3.5 mm, Lettering field: 2.7 x 4.7 mm

---

#### Test plug terminal block

## Double-level terminal block - PTTBS 1,5/S-PV - 3214686

### Accessories

Test plugs - MPS-MT - 0201744




Test plugs, Color: silver

---

### Drawings

Circuit diagram



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)