

www.vishay.com

Vishay Sfernice

Precision Linear Transducers, Conductive Plastic, up to 1000 mm



The 115 L is a simply mounted, robust, high precision industrial linear motion transducer.

QUICK REFERENCE DATA			
Sensor type	LINEAR, conductive plastic		
Output type Connector			
Market appliance	Industrial		
Dimensions	$L \times 31.7 \text{ mm} \times 34.8 \text{ mm} \text{ (with } L = \text{TET} + 75 \text{ mm)}$		

FEATURES

- Measurement range 25 mm to 1000 mm
- High accuracy ± 1 % down to ± 0.025 %
- ROHS

- · Excellent repeatability
- Essentially infinite resolution
- Non sensitive to temperature variations
- Material categorization: for definitions of compliance please see <u>www.vishay.com/doc?99912</u>

ELECTRICAL SPECIFICATIONS					
Theoretical electrical travel (TET) = E	From 25 mm to 1000 mm in increments of 25 mm				
Independent linearity (over TET) on request	\leq \pm 1 % \leq \pm 0.1 % \leq \pm 0.05 % for E \geq 100 mm \leq \pm 0.025 % for E \geq 200 mm				
Actual electrical travel (AET)	AET = TET + 1.5 mm min.				
Ohmic values (R _T)	400 Ω/cm to 2 kΩ/cm				
Resistance tolerance at 20 °C	± 20 %				
Repeatability ≤ ± 0.01 %					
Maximum power rating 0.05 W/cm at 70 °C, 0 W at 125 °C					
Wiper current	Recommended: a few μA - 1 mA max. (continuous)				
Load resistance	minimum 10 ³ x R _T				
Insulation resistance	≥ 1000 MΩ, 500 V _{DC}				
Dielectric strength	≥ 1000 V _{RMS} , 50 Hz				
Protection resistor	Integrated inside the transducer to protect against errors when setting up (short circuit)				


MECHANICAL SPECIFICATIONS				
Mechanical travel E + 8 ± 2 mm				
Housing	Anodized aluminum			
Operating force	7.5 N typical			
Shaft (free rotation)	Stainless steel			
Termination	Hydraulic type connector DIN 43650			
Wiper	Precious metal multifinger			
Mounting	ing Movable brackets			


PERFORMANCE					
Operating life	40 million cycles typical/1 Hz/T° = 20 °C ± 5 °C/80 % TET				
Temperature range	-55 °C to +125 °C				
Sine vibration on 3 axes	1.5 mm peak to peak 0 Hz to 10 Hz 15 <i>g</i> - 10 Hz - 2000 Hz				
Mechanical shocks on 3 axes 50 g - 11 ms - half sine					
Speed (max.)	8 m/s for f < 2 Hz; 3 m/s for f < 5 Hz				

Note

Nothing stated herein shall be construed as a guarantee of quality or durability.

Vishay Sfernice





ORDERING INFORMATION/DESCRIPTION								
REC	115	L	23	D	103	W	e.	
SERIES	MODEL	NUMBER OF TRACKS	THEORETICAL ELECTRICAL TRAVEL	LINEARITY	OHMIC VALUE	MODIFICATIONS	LEAD FINISH	
		L = 1	Times 25 mm	A: ± 1 % D: ± 0.1 % E: ± 0.05 % F: ± 0.025 %	First 2 digits are significant numbers 3 rd digit indicates number of zeros	Special feature code number		

SAP PART NUMBERING GUIDELINES							
RE	115 L	23	D	103	W		
SERIES	MODEL	TET	LINEARITY	OHMIC VALUE	SPECIAL FEATURES		



Legal Disclaimer Notice

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Revision: 02-Oct-12 Document Number: 91000



OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 P/C 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru