



### Main

|                                   |   |
|-----------------------------------|---|
| Range of product                  | 9012G   |
| Pressure sensor type              | Electromechanical pressure switch   |
| Pressure sensor name              | 9012G   |
| Pressure sensor size              | 2900 psi  |
| Maximum pressure                  | 15000 psi   |
| Contacts type and composition     | 2(NC-NO), DPDT-DB, Form ZZ, snap action, silver nickel contacts                   |
| Controlled fluid                  | Air<br>Non-corrosive liquids<br>Non-corrosive gas<br>Hydraulic oil (-15...250 °F) |
| Fluid connection type             | 0.25 inch 18 NPTF conforming to UL 508  |
| Pressure switch type of operation | Detection of 1 single threshold   |
| Scale type                        | Fixed   |
| Local display                     | Without   |

### Complementary

|                                      |  |
|--------------------------------------|--|
| Range on decreasing pressure         | 90...2900 psi  |
| Approx fix differential at mid range | 255 psi +/- 2.5 % full scale   |
| Cable entry                          | 0.5 inch NPT conduit entrance  |
| Terminal block type                  | 8 screw terminals  |
| Electrical connection                | Screw-clamp terminals, AWG 22...AWG 12   |
| Electrical circuit type              | Control circuit  |
| Local signalling                     | Without  |
| [In] rated current                   | 3 A (Ue = 240 V AC) contact code: A600 conforming to NEMA rating designation<br>6 A (Ue = 120 V AC) contact code: A600 conforming to NEMA rating designation<br>0.27 A (Ue = 250 V DC) contact code: R300 conforming to NEMA rating designation<br>0.22 A (Ue = 125 V DC) contact code: R300 conforming to NEMA rating designation |
| Setting                              | Internal   |
| Enclosure material                   | Cast aluminium   |
| Pressure actuator                    | Piston   |
| Height                               | 8.02 in  |
| Depth                                | 5.34 in  |
| Width                                | 7.13 in  |
| Operating position                   | Any position   |
| Materials in contact with fluid      | Teflon<br>Viton fluorocarbon<br>440 stainless steel<br>303 stainless steel   |
| Short-circuit protection             | 10 A by gL (cartridge) overload and short-circuit protection   |
| Operating rate                       | <= 120 cyc/mn  |
| Mechanical durability                | 3000000 cycles   |
| Repeat accuracy                      | 4 %  |
| Product weight                       | 18.5 lb(US)  |

### Environment

|                      |   |
|----------------------|---|
| vibration resistance | 2 gn conforming to IEC 68-2-6 (f = 40...150 Hz) |
| shock resistance     | 50 gn conforming to IEC 58-2-27                 |
| standards            | CE<br>UL 508<br>CSA C22.2 No 14                 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                                       |   |
|---------------------------------------|---|
| product certifications                | CE<br>UL listed file E12443 CCN NOWT<br>CSA LR26817 class 3218 02 |
| NEMA degree of protection             | NEMA 7/9 conforming to UL 698                                     |
| ambient air temperature for operation | -10...185 °F  |

### Offer Sustainability

|  |  |
|--|--|
| Not Green Premium product  | Not Green Premium product  |
| Will not be Compliant  | Will not be Compliant  |
| Reference not containing SVHC above the threshold  | Reference not containing SVHC above the threshold  |
| Available  | Available  |
| Available  | Available  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:   |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)