

# 3M™ MetPak™ 2-FB Header

2 mm 4/5 Row, Vertical, Solder or Press-Fit Tail, Shouldered Pin

MP2 Series



## Solder Tail

- End-to-end stackable
- Select load capability
- Monoblockable
- Shoulder Pin

## Press Fit

- End-to-end stackable
- Early mate late break for hot swapping (press-fit EMLB adjusted by application tooling)
- Select load capability
- Monoblockable
- Push-on shoulder pin
- Optional feed-through tail for rear plug-up midplane applications
- Accepts Universal Tooling
- RoHS Compliant. See the Regulatory Information Appendix (RIA) in the “RoHS compliance” section of [www.3Mconnector.com](http://www.3Mconnector.com) for compliance information (RIA E1 & C1 apply)

Date Modified: May 10, 2010

TS-1120-D  
Sheet 1 of 4

---

## Physical

### Insulation:

Material: High Temp LCP  
Flammability: UL 94V-0  
Color: Beige

### Contact:

Material: Phosphor Bronze

### Plating:

Underplating: 50  $\mu$ " [1.27  $\mu$ m] Nickel  
Wiping Area: See Ordering Information  
Solder Tails: See Ordering Information

---

## Electrical

**Current Rating:** Signal: 1.5 A – All contacts simultaneously

**Insulation Resistance:** 10<sup>3</sup> M $\Omega$

**Withstanding Voltage:** 1,000 V<sub>AC</sub>

---

## Environmental

**Temperature Rating:** -55°C to +125°C

**Process Temperature Rating:** 260°C (Profile per J-STD-020C)

**Moisture Sensitivity Level:** 1 (per J-STD-020C)

UL File No.: E68080

# 3M™ MetPak™ 2-FB Header

2 mm 4/5 Row, Vertical, Solder or Press-Fit Tail, Shouldered Pin

MP2 Series



FOR SPECIAL MONOBLOCKS  
AND PIN ARRANGEMENTS  
CONTACT 3M SALES  
REPRESENTATIVE



**4 ROW PRODUCT**

| Tolerance Unless Noted |    |      |       |
|------------------------|----|------|-------|
|                        | 0  | 0.0  | 0.00  |
| mm                     | ±3 | ±0.3 | ±0.13 |

[ ] Dimensions for Reference Only



**5 ROW PRODUCT**



**SOLDER TAIL PRODUCT**



**PRESS FIT PRODUCT**



**PRESS FIT PRODUCT REAR PLUG-UP**

Contact 3M For Rear Plug-Up Option



**Notes:**

1. Refer to IEC 61076-4-104 Futurebus+® global standard.
2. "Press Fit" describes a contact tail having a compliant section designed to make a reliable electrical connection with a plated through-hole (PTH) in a printed circuit board, typically a "back plane."

## Ordering Information



TS-1120-D  
Sheet 2 of 4

# 3M™ MetPak™ 2-FB Header

2 mm 4/5 Row, Vertical, Solder or Press-Fit Tail, Shouldered Pin

MP2 Series

| Pin Count | Dim. "A" mm [inch] | Dim "C" mm [inch] | Rows |
|-----------|--------------------|-------------------|------|
| 024       | 11.95 [0.471]      | 10.00 [0.394]     | 4    |
| 048       | 23.95 [0.943]      | 22.00 [0.866]     | 4    |
| 072       | 35.95 [1.415]      | 34.00 [1.339]     | 4    |
| 096       | 47.95 [1.889]      | 46.00 [1.811]     | 4    |
| 120       | 59.95 [2.36]       | 58.00 [2.283]     | 4    |
| 144       | 71.95 [2.833]      | 70.00 [2.756]     | 4    |
| 168       | 83.95 [3.305]      | 82.00 [3.228]     | 4    |
| 192       | 95.95 [3.778]      | 94.00 [3.701]     | 4    |
| 030       | 11.95 [0.471]      | 10.00 [0.394]     | 5    |
| 060       | 23.95 [0.943]      | 22.00 [0.866]     | 5    |
| 090       | 35.95 [1.415]      | 34.00 [1.339]     | 5    |
| 120       | 47.95 [1.888]      | 46.00 [1.811]     | 5    |
| 150       | 59.95 [2.361]      | 58.00 [2.283]     | 5    |
| 180       | 71.95 [2.833]      | 70.00 [2.756]     | 5    |
| 210       | 83.95 [3.305]      | 82.00 [3.228]     | 5    |
| 240       | 95.95 [3.778]      | 94.00 [3.701]     | 5    |

| Plating Suffix           | Press-Fit Tails*    | Solder Tails        | Plating Composition   |
|--------------------------|---------------------|---------------------|---|
| TG30                     | (RIA E2 & C2 apply) | (RIA E3 & C2 apply) | 0.76 µm [30 µ"] Min. Au Contact Area<br>2.54 µm [100 µ"] Min. SnPb Tail Area<br>1.27 µm [50 µ"] Min. Ni all over  |
| TR30                     | (RIA E2 & C2 apply) | (RIA E3 & C2 apply) | 0.08 µm [3 µ"] Min. Au Contact Area<br>0.67 µm [27 µ"] Min. PdNi Contact Area<br>2.54 µm [100 µ"] Min. SnPb Tail Area<br>1.27 µm [50 µ"] Min. Ni all over                       |
| KR                       | (RIA E1 & C1 apply) | (RIA E1 & C1 apply) | 0.76 µm [30 µ"] Min. Au Contact Area<br>2.54 µm [100 µ"] Min. Matt Whisker Mitigating Sn Tail Area<br>1.27 µm [50 µ"] Min. Ni all over  |
| LR                       | (RIA E1 & C1 apply) | (RIA E1 & C1 apply) | 0.08 µm [3 µ"] Min. Au Contact Area<br>0.67 µm [27 µ"] Min. PdNi Contact Area<br>2.54 µm [100 µ"] Min. Matt Whisker Mitigating Sn Tail Area<br>1.27 µm [50 µ"] Min. Ni all over |
| KV for rear plug-up only | (RIA E1 & C1 apply) |                     | 0.76 µm [30 µ"] Min. Au Dual Contact Areas<br>0.10 µm [4 µ"] Min. Au Needle Eye<br>1.27 µm [50 µ"] Min. Ni all over   |

| Plating Suffix |                 | Dim. "B"     |
|----------------|-----------------|--------------|
| Solder Tail    | Press-Fit* Tail |              |
| 1              | 1               | 4.60 [0.181] |
| 3              |                 | 2.72 [0.107] |

\*Compliant-Pin Tail

| Loading Pattern Code | Description          | Mate length Row A | Mate length Row B | Mate length Row C | Mate length Row D | Mate length Row E (5-Row Prod. Only) |
|----------------------|----------------------|-------------------|-------------------|-------------------|-------------------|--------------------------------------|
| 1                    | All Positions Filled | 5.00 [0.197]      | 5.00 [0.197]      | 5.00 [0.197]      | 5.00 [0.197]      | 5.00 [0.197]                         |
| 2                    | All Positions Filled | 6.50 [0.256]      | 5.00 [0.197]      | 5.00 [0.197]      | 5.00 [0.197]      | 5.00 [0.197]                         |
| 3                    | All Positions Filled | 6.50 [0.256]      | 5.75 [0.226]      | 5.75 [0.226]      | 6.50 [0.256]      | 6.50 [0.256]                         |
| 4                    | All Positions Filled | 6.50 [0.256]      | 6.50 [0.256]      | 6.50 [0.256]      | 6.50 [0.256]      | 6.50 [0.256]                         |
| 5                    | All Positions Filled | 5.75 [0.226]      | 7.25 [0.285]      | 5.75 [0.226]      | 5.75 [0.226]      | 5.75 [0.226]                         |
| 6                    | All Positions Filled | 7.25 [0.285]      | 5.75 [0.226]      | 5.75 [0.226]      | 5.75 [0.226]      | 5.75 [0.226]                         |
| 7                    | All Positions Filled | 6.50 [0.256]      | 5.75 [0.226]      | 5.00 [0.197]      | 5.00 [0.197]      | 5.00 [0.197]                         |
| 8                    | All Positions Filled | 6.50 [0.256]      | 5.00 [0.197]      | 6.50 [0.256]      | 6.50 [0.256]      | 6.50 [0.256]                         |
| 9                    | All Positions Filled | 5.00 [0.197]      | 6.50 [0.256]      | 5.00 [0.197]      | 5.00 [0.197]      | 5.00 [0.197]                         |
| A                    | All Positions Filled | 5.00 [0.197]      | 5.75 [0.226]      | 6.50 [0.256]      | 5.75 [0.226]      | 5.00 [0.197]                         |
| B                    | All Positions Filled | 5.75 [0.226]      | 5.75 [0.226]      | 5.75 [0.226]      | 5.75 [0.226]      | 5.75 [0.226]                         |
| C                    | All Positions Filled | 5.00 [0.197]      | 5.00 [0.197]      | 6.50 [0.256]      | 5.00 [0.197]      | 5.00 [0.197]                         |
| D                    | All Positions Filled | 5.75 [0.226]      | 5.75 [0.226]      | 7.25 [0.285]      | 5.75 [0.226]      | 5.75 [0.226]                         |
| E                    | All Positions Filled | 7.25 [0.285]      | 7.25 [0.285]      | 7.25 [0.285]      | 7.25 [0.285]      | 7.25 [0.285]                         |
| G                    | All Positions Filled | 7.25 [0.285]      | 5.75 [0.226]      | 5.75 [0.226]      | 5.00 [0.197]      | 5.00 [0.197]                         |
| H                    | All Positions Filled | 5.00 [0.197]      | 5.75 [0.226]      | 5.75 [0.226]      | 7.25 [0.285]      | 7.25 [0.285]                         |
| J                    | All Positions Filled | 8.00 [0.315]      | 8.00 [0.315]      | 8.00 [0.315]      | 8.00 [0.315]      | 8.00 [0.315]                         |
| K                    | All Positions Filled | 5.00 [0.197]      | 6.50 [0.256]      | 7.25 [0.285]      | 6.50 [0.256]      | 5.00 [0.197]                         |

TS-1120-D  
Sheet 3 of 4

# 3M™ MetPak™ 2-FB Header

2 mm 4/5 Row, Vertical, Solder or Press-Fit Tail, Shouldered Pin

MP2 Series



**RECOMMENDED 4 ROW SOLDER  
TAIL PCB HOLE MOUNTING PATTERN**




**RECOMMENDED 4 ROW PRESS-FIT  
PCB HOLE MOUNTING PATTERN**

**Table 5 – HOLE PLATING For TG30 and TR30 FINISHES ONLY**

| HOLE | Finished Dia. MM [in]    | Cu Thickness [mm [in]] | SnPb Thickness microns [μ"] | Drilled Hole Dia. mm [in] |
|------|--------------------------|------------------------|-----------------------------|---------------------------|
| "D"  | 0.65-0.80 [0.0256-.0315] | 0.025 [0.001] min.     | 15 [600] max.               | 0.81-0.86 [0.0319-.0339]  |

**Table 6 – HOLE PLATING For KR, LR, and KV FINISHES ONLY**

| HOLE | Finished Dia. MM [in]      | Immersion Matte Sn Thickness microns [μ"] | Electrolytic Au Thickness microns [μ"] | OSP ENTEK Thickness microns [μ"] | Drilled Hole Dia. mm [in]                               |
|------|----------------------------|---|--|----------------------------------|---|
| "D"  | 0.700-0.800 [0.0276-.0315] | 0.025-0.045 [0.001-0.002]                 | 0.1 - 0.5 [4 - 20]                     | 0.2 - 0.5 [8 - 20]               | 0.830-0.860 [0.0330-.0340] or 0.85 mm [#66] TWIST DRILL |



**RECOMMENDED 5 ROW SOLDER  
TAIL PCB HOLE MOUNTING PATTERN**



**RECOMMENDED 5 ROW PRESS-FIT  
PCB HOLE MOUNTING PATTERN**

TS-1120-D  
Sheet 4 of 4

**Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

**Warranty; Limited Remedy; Limited Liability.**

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

**3M Electronics Solutions Division**

6801 River Place Blvd.  
Austin, TX 78726-9000  
U.S.A.  
1-800-225-5373  
[www.3Mconnector.com](http://www.3Mconnector.com)

Please recycle. Printed in USA.  
© 3M 2010. All rights reserved.  
RIA-2217B-E

3M is a trademark of 3M Company.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)