

# MPXH6300A, 20 to 300 kPa, Absolute, Integrated, Pressure Sensor

Freescal's MPXH6300A series sensor integrates on-chip, bipolar op amp circuitry and thin film resistor networks to provide a high output signal and temperature compensation. The small form factor and high reliability of on-chip integration make the Freescal pressure sensor a logical and economical choice for the system designer.

The MPXH6300A series piezoresistive transducer is a state-of-the-art, monolithic, signal conditioned, silicon pressure sensor. This sensor combines advanced micromachining techniques, thin film metallization, and bipolar semiconductor processing to provide an accurate, high level analog output signal that is proportional to applied pressure.

## Features


- Improved accuracy at high temperature
- Available in super small outline package
- 1.5% maximum error over 0 °C to 85 °C
- Fully calibrated and compensated
- Ideally suited for microprocessor or microcontroller-based systems
- Temperature compensated from -40 °C to +125 °C
- Durable thermoplastic surface mount package
- Package porting and mounting options enable tube attachment for liquefied natural gas (LPG) or remote sensing applications

## Typical applications


- Fuel injected car engines
- Vehicles powered by green gases (for example LPG and CNG)
- Small engines
- Industrial controls

## MPXH6300A

### Super small outline package




MPXH6300A6U/6T1  
Case 98ARH99066A



MPXH6300AC6U/6T1  
Case 98ARH99089A

### Top view



Pin 1 identification, chamfered corner.

### Pinout

| Ordering information |               |             |            |        |      |               |              |          |                |
|----------------------|---------------|-------------|------------|--------|------|---------------|--------------|----------|----------------|
| Part number          | Shipping      | Package     | # of Ports |        |      | Pressure type |              |          | Device marking |
|                      |               |             | None       | Single | Dual | Gauge         | Differential | Absolute |                |
| MPXH6300A6U          | Rail          | 98ARH99066A | •          |        |      |               |              | •        | MPXH6300A      |
| MPXH6300A6T1         | Tape and Reel | 98ARH99066A | •          |        |      |               |              | •        | MPXH6300A      |
| MPXH6300AC6U         | Rail          | 98ARH99089A |            | •      |      |               |              | •        | MPXH6300A      |
| MPXH6300AC6T1        | Tape and Reel | 98ARH99089A |            | •      |      |               |              | •        | MPXH6300A      |

Freescal reserves the right to change the detail specifications as may be required to permit improvements in the design of its products.

© 2007, 2010, 2012, 2015 Freescal Semiconductor, Inc. All rights reserved.



# Contents

|          |                                                                |           |
|----------|----------------------------------------------------------------|-----------|
| <b>1</b> | <b>General Description</b>                                     | <b>3</b>  |
| 1.1      | Block diagram                                                  | 3         |
| 1.2      | Pinout                                                         | 3         |
| <b>2</b> | <b>Mechanical and Electrical Specifications</b>                | <b>4</b>  |
| 2.1      | Maximum ratings                                                | 4         |
| 2.2      | Operating characteristics                                      | 4         |
| <b>3</b> | <b>On-chip Temperature Compensation and Calibration</b>        | <b>5</b>  |
| <b>4</b> | <b>Package Information</b>                                     | <b>8</b>  |
| 4.1      | Pressure (P1)/Vacuum (P2) Side Identification                  | 8         |
| 4.2      | Minimum recommended footprint for surface mounted applications | 8         |
| 4.3      | Package Dimensions                                             | 9         |
| <b>5</b> | <b>Revision History</b>                                        | <b>11</b> |

## Related Documentation

The MPXH6300A device features and operations are described in a variety of reference manuals, user guides, and application notes. To find the most-current versions of these documents:

1. Go to the Freescale homepage at:  
<http://www.freescale.com/>
2. In the Keyword search box at the top of the page, enter the device number MPXH6300A.
3. In the Refine Your Result pane on the left, click on the Documentation link.

### MPXH6300A

# 1 General Description

## 1.1 Block diagram

Figure 1 shows a block diagram of the internal circuitry integrated on a pressure sensor chip.




Figure 1. Integrated pressure sensor block diagram

## 1.2 Pinout




Figure 2. Device pinout (top view)

Table 1. Pin functions

| Pin | Name      | Function                                                                              |
|-----|-----------|---------------------------------------------------------------------------------------|
| 1   | DNC       | Do not connect to external circuitry or ground. Pin 1 is notated by chamfered corner. |
| 2   | $V_S$     | Voltage supply                                                                        |
| 3   | GND       | Ground                                                                                |
| 4   | $V_{OUT}$ | Output voltage                                                                        |
| 5   | DNC       | Do not connect to external circuitry or ground.                                       |
| 6   | DNC       | Do not connect to external circuitry or ground.                                       |
| 7   | DNC       | Do not connect to external circuitry or ground.                                       |
| 8   | DNC       | Do not connect to external circuitry or ground.                                       |

## 2 Mechanical and Electrical Specifications

### 2.1 Maximum ratings

Table 2. Maximum ratings<sup>(1)</sup>

| Parametrics                                                  | Symbol           | Value       | Units |
|--------------------------------------------------------------|------------------|-------------|-------|
| Maximum pressure (P1 > P2)                                   | P <sub>max</sub> | 1200        | kPa   |
| Storage temperature                                          | T <sub>stg</sub> | -40 to +125 | °C    |
| Operating temperature                                        | T <sub>A</sub>   | -40 to +125 | °C    |
| Output source current @ full-scale output <sup>(2)</sup>     | I <sub>o+</sub>  | 0.5         | mAdc  |
| Output sink current @ minimum pressure offset <sup>(2)</sup> | I <sub>o-</sub>  | -0.5        | mAdc  |

1.Exposure beyond the specified limits may cause permanent damage or degradation to the device.

2.Maximum output current is controlled by effective impedance from V<sub>OUT</sub> to GND or V<sub>OUT</sub> to V<sub>S</sub> in the application circuit.

### 2.2 Operating characteristics

Table 3. Operating characteristics (V<sub>S</sub> = 5.1 V<sub>DC</sub>, T<sub>A</sub> = 25 °C unless otherwise noted, P1 > P2.)

| Characteristic                                                                   | Symbol           | Min   | Typ   | Max   | Unit              |
|----------------------------------------------------------------------------------|------------------|-------|-------|-------|-------------------|
| Pressure range                                                                   | P <sub>OP</sub>  | 20    | —     | 304   | kPa               |
| Supply voltage <sup>(1)</sup>                                                    | V <sub>S</sub>   | 4.74  | 5.1   | 5.46  | V <sub>DC</sub>   |
| Supply current                                                                   | I <sub>O</sub>   | —     | 6.0   | 10    | mAdc              |
| Minimum pressure offset <sup>(2)</sup> (0 to 85 °C) @ V <sub>S</sub> = 5.1 Volts | V <sub>OFF</sub> | 0.241 | 0.306 | 0.371 | V <sub>DC</sub>   |
| Full-scale output <sup>(3)</sup> (0 to 85 °C) @ V <sub>S</sub> = 5.1 Volts       | V <sub>FSO</sub> | 4.847 | 4.912 | 4.977 | V <sub>DC</sub>   |
| Full-scale span <sup>(4)</sup> (0 to 85 °C) @ V <sub>S</sub> = 5.1 Volts         | V <sub>FSS</sub> | 4.476 | 4.606 | 4.736 | V <sub>DC</sub>   |
| Accuracy <sup>(5)</sup> (0 to 85 °C)                                             | —                | —     | —     | ±1.5  | %V <sub>FSS</sub> |
| Sensitivity                                                                      | V/P              | —     | 16.2  | —     | mV/kPa            |
| Response time <sup>(6)</sup>                                                     | t <sub>R</sub>   | —     | 1.0   | —     | ms                |
| Warm-up time <sup>(7)</sup>                                                      | —                | —     | 20    | —     | ms                |
| Offset stability <sup>(8)</sup>                                                  | —                | —     | ±0.25 | —     | %V <sub>FSS</sub> |

1.Device is ratiometric within this specified excitation range.

2.Offset (V<sub>OFF</sub>) is defined as the output voltage at the minimum rated pressure.

3.Full-scale output (V<sub>FSO</sub>) is defined as the output voltage at the maximum or full-rated pressure.

4.Full-scale span (V<sub>FSS</sub>) is defined as the algebraic difference between the output voltage at full-rated pressure and the output voltage at the minimum rated pressures

5.Accuracy is the deviation in actual output from nominal output over the entire pressure range and temperature range as a percent of span at 25 °C due to all sources of error including the following:

Linearity: Output deviation from a straight line relationship with pressure over the specified pressure range.

Temperature hysteresis: Output deviation at any temperature within the operating temperature range, after the temperature is cycled to and from the minimum or maximum operating temperature points, with zero differential pressure applied.

Pressure hysteresis: Output deviation at any pressure within the specified range, when this pressure is cycled to and from minimum or maximum rated pressure at 25 °C

TcSpan: Output deviation over the temperature range of 0 to 85 °C, relative to 25 °C.

TcOffset: Output deviation with minimum rated pressure applied, over the temperature range of 0 to 85 °C, relative to 25 °C.

Variation from Nominal: The variation from nominal values, for offset or full-scale span, as a percent of V<sub>FSS</sub>, at 25 °C.

6.Response time is defined as the time for the incremental change in the output to go from 10% to 90% of its final value when subjected to a specified step change in pressure.

7.Warm-up time is defined as the time required for the product to meet the specified output voltage after the pressure has been stabilized.

8.Offset stability is the product's output deviation when subjected to 1000 cycles of pulsed pressure, temperature cycling with bias test.

### 3 On-chip Temperature Compensation and Calibration

Figure 3 illustrates the absolute sensing chip in the basic super small outline chip carrier (case 98ARH99066A).

Figure 4 shows a typical application circuit (output source current operation).

Figure 5 shows the sensor output signal relative to pressure input. Typical minimum and maximum output curves are shown for operation over 0 to 85 °C temperature range. The output will saturate outside of the rated pressure range.

A fluorosilicone gel isolates the die surface and wire bonds from the environment, while allowing the pressure signal to be transmitted to the silicon diaphragm. The MPXH6300A pressure sensor operating characteristics, internal reliability and qualification tests are based on use of dry air as the pressure media. Media other than dry air may have adverse effects on sensor performance and long-term reliability. Contact the factory for information regarding media compatibility in your application.




Figure 3. Cross-sectional diagram (not-to-scale)




Figure 4. Recommended power supply decoupling and output filtering





**Figure 5. Output vs. absolute pressure**

**Nominal Transfer Value:**  $V_{out} = V_S \times (0.00318 \times P - 0.00353)$   
 $\pm (\text{Pressure Error} \times \text{Temp Factor} \times 0.00318 \times V_S)$   
 $V_S = 5.1 \pm 0.36 \text{ Vdc}$

**Figure 6. Transfer function**



NOTE: The Temperature Multiplier is a linear response from 0 °C to -40 °C and from 85 °C to 125 °C.

**Figure 7. Temperature error band**




**Figure 8. Pressure error band**

## 4 Package Information

### 4.1 Minimum recommended footprint for surface mounted applications

Surface mount board layout is a critical portion of the total design. The footprint for the semiconductor package must be the correct size to ensure proper solder connection interface between the board and the package. With the correct pad geometry, the packages will self-align when subjected to a solder reflow process. It is always recommended to fabricate boards with a solder mask layer to avoid bridging and/or shorting between solder pads, especially on tight tolerances and/or tight layouts.





Figure 9. SSOP footprint


## 4.2 Package Dimensions

This drawing is located at [http://cache.freescale.com/files/shared/doc/package\\_info/98ARH99066A.pdf](http://cache.freescale.com/files/shared/doc/package_info/98ARH99066A.pdf).



|                                                         |                           |                          |                            |             |
|---------------------------------------------------------|---------------------------|--------------------------|----------------------------|-------------|
| © FREESCALE SEMICONDUCTOR, INC.<br>ALL RIGHTS RESERVED. | <b>MECHANICAL OUTLINE</b> |                          | PRINT VERSION NOT TO SCALE |             |
| TITLE: 8 LEAD<br>SSOP                                   |                           | DOCUMENT NO: 98ARH99066A |                            | REV: H      |
|                                                         |                           | CASE NUMBER: 1317-04     |                            | 13 APR 2012 |
|                                                         |                           | STANDARD: NON-JEDEC      |                            |             |

**Case 98ARH99066A, super small outline package, surface mount**



DETAIL "D"

|                                                         |                |                          |  |                            |  |
|---------------------------------------------------------|----------------|--------------------------|--|----------------------------|--|
| © FREESCALE SEMICONDUCTOR, INC.<br>ALL RIGHTS RESERVED. |                | MECHANICAL OUTLINE       |  | PRINT VERSION NOT TO SCALE |  |
| TITLE:                                                  | 8 LEAD<br>SSOP | DOCUMENT NO: 98ARH99066A |  | REV: H                     |  |
|                                                         |                | CASE NUMBER: 1317-04     |  | 13 APR 2012                |  |
|                                                         |                | STANDARD: NON-JEDEC      |  |                            |  |


Case 98ARH99066A, super small outline package, surface mount

NOTES:

1. ALL DIMENSIONS IN INCHES.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.  
MOLD FLASH OR PROTRUSION SHALL NOT EXCEED .006 INCHES PER SIDE.
4. ALL VERTICAL SURFACES TO BE 5° MAXIMUM.
5. DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.  
ALLOWABLE DAMBAR PROTRUSION SHALL BE .008 INCHES MAXIMUM.

|                                                         |                           |                            |             |
|---------------------------------------------------------|---------------------------|----------------------------|-------------|
| © FREESCALE SEMICONDUCTOR, INC.<br>ALL RIGHTS RESERVED. | <b>MECHANICAL OUTLINE</b> | PRINT VERSION NOT TO SCALE |             |
| TITLE:<br><br>8 LEAD<br>SSOP                            | DOCUMENT NO: 98ARH99066A  |                            | REV: H      |
|                                                         | CASE NUMBER: 1317-04      |                            | 13 APR 2012 |
|                                                         | STANDARD: NON-JEDEC       |                            |             |

**Case 98ARH99066A, super small outline package, surface mount**



|                                                         |                          |                            |
|---------------------------------------------------------|--------------------------|----------------------------|
| © FREESCALE SEMICONDUCTOR, INC.<br>ALL RIGHTS RESERVED. | MECHANICAL OUTLINE       | PRINT VERSION NOT TO SCALE |
| TITLE:                                                  | DOCUMENT NO: 98ARH99089A | REV: G                     |
| 8 LD, PORTED SSOP                                       | STANDARD: NON-JEDEC      |                            |
|                                                         |                          | 09 NOV 2012                |

Case 98ARH99089A, super small outline package, surface mount

NOTES:

- 1. ALL DIMENSIONS IN INCHES.
- 2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M–1994.
- 3. DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.  
MOLD FLASH OR PROTRUSION SHALL NOT EXCEED .006 INCHES PER SIDE.
- 4. ALL VERTICAL SURFACES TO BE 5° MAXIMUM.
- 5. DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.  
ALLOWABLE DAMBAR PROTRUSION SHALL BE .008 INCHES MAXIMUM.

|                                                         |                          |                            |
|---------------------------------------------------------|--------------------------|----------------------------|
| © FREESCALE SEMICONDUCTOR, INC.<br>ALL RIGHTS RESERVED. | MECHANICAL OUTLINE       | PRINT VERSION NOT TO SCALE |
| TITLE:<br><br>8 LD, PORTED SSOP                         | DOCUMENT NO: 98ARH99089A | REV: G                     |
|                                                         | STANDARD: NON-JEDEC      |                            |
|                                                         |                          | 09 NOV 2012                |

Case 98ARH99089A, super small outline package, surface mount



# 5      Revision History

Table 4. Revision history

| Revision number | Revision date | Description                                                          |
|-----------------|---------------|----------------------------------------------------------------------|
| 5.1             | 05/2012       | • Updated Package Drawing 98ARH99066A was Rev. F, updated to Rev. H. |
| 6.0             | 09/2015       | • Corrected figure 4.<br>• Updated format.                           |

**How to Reach Us:****Home Page:**

freescale.com

**Web Support:**

freescale.com/support

Information in this document is provided solely to enable system and software implementers to use Freescale products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document.

Freescale reserves the right to make changes without further notice to any products herein. Freescale makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in Freescale data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. Freescale does not convey any license under its patent rights nor the rights of others. Freescale sells products pursuant to standard terms and conditions of sale, which can be found at the following address: [freescale.com/salestermsandconditions](http://freescale.com/salestermsandconditions).

Freescale and the Freescale logo are trademarks of Freescale Semiconductor, Inc., Reg. U.S. Pat. & Tm. Off. All other product or service names are the property of their respective owners.

© 2007, 2010, 2012, 2015 Freescale Semiconductor, Inc.

Document Number: MPXH6300A

Rev. 6.0

09/2015



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)