


# Lead (Pb)-free Commodity Thick Film Chip Resistors



## FEATURES

- High volume product suitable for commercial applications
- Pure tin solder contacts on Ni barrier layer provides compatibility with lead (Pb)-free and lead containing soldering processes
- Metal glaze on high quality ceramic
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

## STANDARD ELECTRICAL SPECIFICATIONS

| MODEL                                                                                                         | CASE SIZE INCH | CASE SIZE METRIC | POWER RATING<br>$P_{70}$<br>W | LIMITING ELEMENT VOLTAGE<br>$U_{max.}$<br>$AC_{RMS}/DC$<br>V | TEMPERATURE COEFFICIENT<br>ppm/K | TOLERANCE<br>% | RESISTANCE RANGE<br>$\Omega$ | SERIES   |
|---------------------------------------------------------------------------------------------------------------|----------------|------------------|-------------------------------|--------------------------------------------------------------|----------------------------------|----------------|------------------------------|----------|
| CRCW0201                                                                                                      | 0201           | RR 0603M         | 0.05                          | 30                                                           | ± 200                            | ± 0.5          | 10.0 to 10M                  | E96      |
|                                                                                                               |                |                  |                               |                                                              | - 200/+ 400                      |                | 1.0 to 9.76                  |          |
|                                                                                                               |                |                  |                               |                                                              | ± 100                            | ± 1            | 47.0 to 10M                  | E24; E96 |
|                                                                                                               |                |                  |                               |                                                              | ± 200                            |                | 10.0 to 10M                  |          |
|                                                                                                               |                |                  |                               |                                                              | - 200/+ 400                      |                | 1.0 to 9.76                  |          |
|                                                                                                               |                |                  |                               |                                                              | ± 200                            | ± 5            | 10.0 to 10M                  | E24      |
|                                                                                                               |                |                  |                               |                                                              | - 200/+ 400                      |                | 1.0 to 9.76                  |          |
| Zero-Ohm-Resistor: $R_{max.} = 50\text{ m}\Omega$ , $I_{max.}$ at $70\text{ }^{\circ}\text{C} = 1.0\text{ A}$ |                |                  |                               |                                                              |                                  |                |                              |          |

## Notes

- These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime.
- Power rating depends on the max. temperature at the solder point, the component placement density and the substrate material.

## TECHNICAL SPECIFICATIONS

| PARAMETER                                              | UNIT             | CRCW0201      |
|--------------------------------------------------------|------------------|---------------|
| Rated Dissipation at $70^\circ\text{C}$ <sup>(1)</sup> | W                | 0.05          |
| Operating Voltage $U_{max. AC_{RMS}/DC}$               | V                | 30            |
| Insulation Voltage $U_{ins}$ (1 min)                   | V                | 50            |
| Insulation Resistance                                  | $\Omega$         | $> 10^9$      |
| Operating Temperature Range                            | $^\circ\text{C}$ | - 55 to + 155 |
| Weight/1000 Pieces                                     | mg               | 0.17          |

## Note

- <sup>(1)</sup> The power dissipation on the resistor generates a temperature rise against the local ambient, depending on the heat flow support of the printed-circuit board (thermal resistance). The rated dissipation applies only if the permitted film temperature of  $155^\circ\text{C}$  is not exceeded.

**PART NUMBER AND PRODUCT DESCRIPTION**
**PART NUMBER: CRCW02011K00FNED**

|   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| C | R | C | W | 0 | 2 | 0 | 1 | 1 | K | 0 | 0 | F | K | E | D |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|

|                 |
|-----------------|
| MODEL           |
| <b>CRCW0201</b> |

|                                                             |
|-------------------------------------------------------------|
| VALUE                                                       |
| R = Decimal<br>K = Thousand<br>M = Million<br>0000 = Jumper |

|                                                         |
|---------------------------------------------------------|
| TOLERANCE                                               |
| D = ± 0.5 %<br>F = ± 1.0 %<br>J = ± 5.0 %<br>Z = Jumper |

|                                                                                 |
|---------------------------------------------------------------------------------|
| TCR                                                                             |
| K = ± 100 ppm/K<br>N = ± 200 ppm/K<br>X = - 200 ppm/K/+ 400 ppm/K<br>0 = Jumper |

|                |
|----------------|
| PACKAGING      |
| ED<br>EE<br>EI |

**PRODUCT DESCRIPTION: CRCW0201 100 1K0 1 % ET7 e3**

|                 |
|-----------------|
| CRCW0201        |
| MODEL           |
| <b>CRCW0201</b> |

|                                                 |
|-------------------------------------------------|
| 100                                             |
| TCR                                             |
| ± 200 ppm/K<br>± 100 ppm/K<br>- 200/+ 400 ppm/K |

|                                                                                    |
|------------------------------------------------------------------------------------|
| 562R                                                                               |
| RESISTANCE<br>VALUE                                                                |
| 1R0 = 1 Ω<br>10R = 10 Ω<br>1K0 = 1 kΩ<br>10K = 10 kΩ<br>1M0 = 1 MΩ<br>0R0 = Jumper |



|                           |
|---------------------------|
| 1 %                       |
| TOLERANCE<br>VALUE        |
| ± 0.5 %<br>± 1 %<br>± 5 % |

|                   |
|-------------------|
| ET7               |
| PACKAGING         |
| ET7<br>EF4<br>ET2 |

|                                     |
|-------------------------------------|
| e3                                  |
| LEAD (Pb)-FREE                      |
| e3 = Pure tin<br>termination finish |

**PACKAGING**


| MODEL    | CODE     | QUANTITY | CARRIER TAPE                                | WIDTH | PITCH | REEL DIAMETER |
|----------|----------|----------|---------------------------------------------|-------|-------|---------------|
| CRCW0201 | ED = ET7 | 10 000   | Paper tape acc.<br>to IEC 60068-3<br>Type I | 8 mm  | 2 mm  | 180 mm/7"     |
|          | EI = ET2 | 20 000   |                                             |       |       | 254 mm/10"    |
|          | EE = EF4 | 50 000   |                                             |       |       | 330 mm/13"    |

**DIMENSIONS** in millimeters


| SIZE |        | DIMENSIONS |            |             |             |                                       | SOLDER PAD DIMENSIONS |      |      |
|------|--------|------------|------------|-------------|-------------|---------------------------------------|-----------------------|------|------|
| INCH | METRIC | L          | W          | H           | T1          | T2                                    | a                     | b    | l    |
| 0201 | 0603   | 0.6 ± 0.05 | 0.3 ± 0.05 | 0.23 ± 0.05 | 0.15 ± 0.05 | 0.2 <sup>+0.05</sup> <sub>-0.10</sub> | 0.28                  | 0.43 | 0.23 |

**Note**

- No marking for 0201 size.

**DERATING**


| TEST PROCEDURES AND REQUIREMENTS |                                  |                             |                                                                                                     |                                                                                          |
|----------------------------------|----------------------------------|-----------------------------|-----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| EN 60115-1<br>CLAUSE             | IEC<br>60068-2<br>TEST<br>METHOD | TEST                        | PROCEDURE                                                                                           | REQUIREMENTS<br>PERMISSIBLE CHANGE ( $\Delta R$ )                                        |
|                                  |                                  |                             | Stability for product types:                                                                        | 1 $\Omega$ to 10 M $\Omega$                                                              |
|                                  |                                  |                             | <b>CRCW0201 e3</b>                                                                                  |                                                                                          |
| 4.5                              | -                                | Resistance                  | -                                                                                                   | $\pm 0.5 \%$ ; $\pm 1 \%$ ; $\pm 5 \%$                                                   |
| 4.7                              | -                                | Voltage proof               | $U = 1.4 \times U_{ins}$ ; 60 s                                                                     | No flashover or breakdown                                                                |
| 4.13                             | 58 (Td)                          | Solderability               | Solder bath method;<br>Sn60Pb40<br>non activated flux;<br>(235 $\pm$ 5) °C<br>(2 $\pm$ 0.2) s       | Good tinning ( $\geq 95 \%$ covered)<br>no visible damage                                |
|                                  |                                  |                             | Solder bath method;<br>Sn96.5Ag3Cu0.5<br>non-activated flux;<br>(245 $\pm$ 5) °C<br>(3 $\pm$ 0.3) s | Good tinning ( $\geq 95 \%$ covered)<br>no visible damage                                |
| 4.8.4.2                          | -                                | Temperature coefficient     | (20/- 55/20) °C and<br>(20/125/20) °C                                                               | $\pm 100$ ppm/K,<br>$\pm 200$ ppm/K,<br>- 200 ppm/K/+ 400 ppm/K                          |
| 4.32                             | 21 (Uu <sub>3</sub> )            | Shear<br>(adhesion)         | 9 N                                                                                                 | No visible damage                                                                        |
| 4.33                             | 21 (Uu <sub>1</sub> )            | Substrate bending           | Depth 2 mm;<br>3 times                                                                              | No visible damage,<br>no open circuit in bent position<br>$\pm (0.5 \% R + 0.05 \Omega)$ |
| 4.19                             | 14 (Na)                          | Rapid change of temperature | 30 min. at - 55 °C;<br>30 min. at 125 °C                                                            | $\pm (0.5 \% R + 0.05 \Omega)$<br>$\pm (1 \% R + 0.05 \Omega)$                           |
|                                  |                                  |                             | 5 cycles<br>1000 cycles                                                                             |                                                                                          |

| TEST PROCEDURES AND REQUIREMENTS |                                  |                                            |                                                                                                               |                                                                |
|----------------------------------|----------------------------------|--------------------------------------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| EN 60115-1<br>CLAUSE             | IEC<br>60068-2<br>TEST<br>METHOD | TEST                                       | PROCEDURE                                                                                                     | REQUIREMENTS<br>PERMISSIBLE CHANGE ( $\Delta R$ )              |
|                                  |                                  |                                            | Stability for product types:                                                                                  | 1 $\Omega$ to 10 M $\Omega$                                    |
|                                  |                                  |                                            | <b>CRCW0201 e3</b>                                                                                            |                                                                |
| 4.23                             | -                                | Climatic sequence:                         | -                                                                                                             | $\pm (2 \% R + 0.1 \Omega)$                                    |
| 4.23.2                           | 2 (Ba)                           | Dry heat                                   | 125 °C; 16 h                                                                                                  |                                                                |
| 4.23.3                           | 30 (Db)                          | Damp heat, cyclic                          | 55 °C; $\geq 90 \% RH$ ;<br>24 h; 1 cycle                                                                     |                                                                |
| 4.23.4                           | 1 (Aa)                           | Cold                                       | - 55 °C; 2 h                                                                                                  |                                                                |
| 4.23.5                           | 13 (M)                           | Low air pressure                           | 1 kPa; (25 $\pm$ 10) °C; 1 h                                                                                  |                                                                |
| 4.23.6                           | 30 (Db)                          | Damp heat, cyclic                          | 55 °C; $\geq 90 \% RH$ ;<br>24 h; 5 cycles                                                                    |                                                                |
| 4.23.7                           | -                                | DC load                                    | $U = \sqrt{P_{70} \times R} \leq U_{max.}$                                                                    |                                                                |
| 4.25.1                           | -                                | Endurance at 70 °C                         | $U = \sqrt{P_{70} \times R} \leq U_{max.};$<br>1.5 h on; 0.5 h off;<br><br>70 °C; 1000 h<br><br>70 °C; 8000 h | $\pm (2 \% R + 0.1 \Omega)$<br><br>$\pm (4 \% R + 0.1 \Omega)$ |
| 4.18.2                           | 58 (Td)                          | Resistance to soldering heat               | Solder bath method<br>(260 $\pm$ 5) °C;<br>(10 $\pm$ 1) s                                                     | $\pm (1 \% R + 0.05 \Omega)$                                   |
| 4.35                             | -                                | Flamability, needle flame test             | IEC 60695-11-5;<br>10 s                                                                                       | No burning after 30 s                                          |
| 4.24                             | 78 (Cab)                         | Damp heat, steady state                    | (40 $\pm$ 2) °C;<br>(93 $\pm$ 3) % RH;<br>56 days                                                             | $\pm (2 \% R + 0.1 \Omega)$                                    |
| 4.25.3                           | -                                | Endurance at<br>upper category temperature | 155 °C, 1000 h                                                                                                | $\pm (2 \% R + 0.1 \Omega)$                                    |
| 4.29                             | 45 (XA)                          | Component solvent resistance               | Isopropyl alcohol;<br>50 °C; method 2                                                                         | No visible damage                                              |
| 4.22                             | 6 (Fc)                           | Vibration, endurance<br>by sweeping        | f = 10 Hz to 2000 Hz;<br>x, y, z $\leq$ 1.5 mm;<br>A $\leq$ 200 m/s <sup>2</sup> ;<br>10 sweeps per axis      | $\pm (0.5 \% R + 0.05 \Omega)$                                 |

All tests are carried out in accordance with the following specifications:

- EN 60115-1, generic specification
- EN 140400, sectional specification
- EN 140401-802, detail specification
- IEC 60068-2-x, environmental test procedures

Packaging of components is done in paper tapes according to IEC 60286-3.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)