




0970 PSL 112



Profibus I/O Modules with 8-Digital Outputs

8 OUT

Profibus-DP device with 8 digital outputs to connect standard actuators, combined M12 socket, rotary switches for addressing, M12 bus connection, M23 power supply.



Bit Assignment

Bit	7	6	5	4	3	2	1	0
M12 Output								
Byte 0	8	7	6	5	4	3	2	1
Diagnostic								
DIA-Byte	-	UVA	ASC	-	-	-	-	-

UVA: Undervoltage actuator
ASC: Actuator short-circuit

Diagnostic Indication

LED	Indication	Condition
1...8 A	yellow	channel status
1...8	red	actuator short-circuit
Us	green	actuator supply active
UL	green	module electronic supply active
BF	red	bus error
DIA	red	module diagnostics (sensor short-circuit / sensor overload)

Pin Assignment

Bus connection M12	Power supply M23	Input M12	
<p>1 = +5 V¹ 2 = Line A 3 = GND (0 V)¹ 4 = Line B 5 = earth</p>	<p>1 = Earth 2 = +24 V² 3 = GND (0 V)² 4 = +24 V³ 5 = GND (0 V)³ 6 = n.c.</p>	<p>1 = n.c. 2 = n.c. 3 = GND (0 V) 4 = OUT 5 = Earth</p>	<p>1 = internal signals 2 = actuators 3 = system</p>



Be Certain with Belden

Profibus I/O Modules with 8-Digital Outputs

0970 PSL 112

Technical Data

Environmental

Degree of protection IP 67
 Operating temperature range -0°C (+32°F) to +60°C (+140°F)

Mechanical

Weight 535 g
 Housing material PUR

Bus system

Profibus
 ID number 044D hex
 GSD file Lum_044D.gsd
 Transmission rate max. 12 MBaud
 Address range 1–126 dec
 Rotary address switches 1–99 dec
 Default address 99 dec

Output power supply

Us
 Rated voltage 24 V DC
 Voltage range 19–30 V DC
 Potential separation present
 Reverse polarity protection yes/antiparallel diode
 Indication LED green

Outputs

Type 2 A acc. to IEC 61131-2
 Rated output current 2 A per channel
 Short circuit-proof yes
 Max. output current 15 A per module
 Overload-proof yes
 Number of digital channels 8
 Channel type N.O. p-switching
 Channel status indicator LED yellow per channel
 Diagnostic indication LED red per channel

Included in delivery/accessories

Dust covers M12 2 pieces
 Attachable labels 10 pieces

Part Number

0970 PSL 112



The application of these products in harsh environments should always be checked before use.
 Specifications subject to alteration.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru