Inductors for Power Circuits

Wound/STD • magnetic shielded

VLS series

Type:

VLS201610E
VLS201612E
VLS2010E
VLS2012E
VLS252008E
VLS252010E
VLS252012E
VLS252015E
VLS3010E
VLS3012E
VLS3015E
VLS4012E

Issue date: October 2012

- All specifications are subject to change without notice.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

TDK

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS201610E

FEATURES

- Miniature size
  Mount area: 2×1.6mm
  Height: 0.95mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

Cellular phones, DVCs, DSCs, PDAs, LCD displays,HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm

RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (µH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS201610ET-R47N	0.47	±30	1.0	0.065	0.054	1.85	2.10	1.95
VLS201610ET-R68N	0.68	±30	1.0	0.086	0.072	1.65	1.85	1.65
VLS201610ET-1R0N	1.0	±30	1.0	0.119	0.099	1.35	1.50	1.40
VLS201610ET-1R5N	1.5	±30	1.0	0.181	0.151	1.10	1.20	1.15
VLS201610ET-2R2M	2.2	±20	1.0	0.276	0.230	0.94	1.05	0.95
VLS201610ET-3R3M	3.3	±20	1.0	0.458	0.382	0.75	0.84	0.73
VLS201610ET-4R7M	4.7	±20	1.0	0.554	0.462	0.64	0.72	0.67
VLS201610ET-6R8M	6.8	±20	1.0	0.840	0.700	0.53	0.59	0.54
VLS201610ET-100M	10	±20	1.0	1.380	1.150	0.40	0.45	0.42

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS201610ET-R47N



VLS201610ET-R68N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS201610ET-1R0N



VLS201610ET-1R5N



VLS201610ET-2R2M



VLS201610ET-3R3M



VLS201610ET-4R7M



VLS201610ET-6R8M



VLS201610ET-100M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS201612E

FEATURES

- Miniature size
  Mount area: 2×1.6mm
  Height: 1.2mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

Cellular phones, DVCs, DSCs, PDAs, LCD displays,HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm



RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (μH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS201612ET-R47N	0.47	±30	1.0	0.063	0.052	1.90	2.15	2.00
VLS201612ET-R68N	0.68	±30	1.0	0.072	0.060	1.70	1.90	1.85
VLS201612ET-1R0N	1.0	±30	1.0	0.093	0.077	1.50	1.65	1.65
VLS201612ET-1R5N	1.5	±30	1.0	0.159	0.132	1.20	1.30	1.25
VLS201612ET-2R2M	2.2	±20	1.0	0.195	0.162	1.05	1.15	1.15
VLS201612ET-3R3M	3.3	±20	1.0	0.357	0.297	0.79	0.88	0.85
VLS201612ET-4R7M	4.7	±20	1.0	0.438	0.365	0.70	0.78	0.75
VLS201612ET-6R8M	6.8	±20	1.0	0.708	0.590	0.58	0.65	0.60
VLS201612ET-100M	10	±20	1.0	1.026	0.855	0.47	0.53	0.50

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS201612ET-R47N



VLS201612ET-R68N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS201612ET-1R0N



VLS201612ET-1R5N



VLS201612ET-2R2M



VLS201612ET-3R3M



VLS201612ET-4R7M



VLS201612ET-6R8M



VLS201612ET-100M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS2010E

FEATURES

- Miniature size
  Mount area: 2×2mm
  Height: 1.0mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

Cellular phones, DVCs, DSCs, PDAs, LCD displays, HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm



RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (µH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS2010ET-R56N	0.56	±30	1.0	0.060	0.050	2.00	2.25	2.05
VLS2010ET-1R0N	1.0	±30	1.0	0.108	0.090	1.45	1.65	1.55
VLS2010ET-1R5N	1.5	±30	1.0	0.156	0.130	1.20	1.30	1.25
VLS2010ET-2R2M	2.2	±20	1.0	0.228	0.190	1.00	1.10	1.05
VLS2010ET-3R3M	3.3	±20	1.0	0.348	0.290	0.83	0.93	0.86
VLS2010ET-4R7M	4.7	±20	1.0	0.408	0.340	0.70	0.78	0.79
VLS2010ET-6R8M	6.8	±20	1.0	0.648	0.540	0.57	0.64	0.63
VLS2010ET-100M	10	±20	1.0	0.936	0.780	0.47	0.52	0.52
VLS2010ET-150M	15	±20	1.0	1.476	1.230	0.40	0.44	0.41
VLS2010ET-220M	22	±20	1.0	2.040	1.700	0.33	0.37	0.35

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS2010ET-R56N



VLS2010ET-1R0N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS2010ET-1R5N



VLS2010ET-2R2M



VLS2010ET-3R3M



VLS2010ET-4R7M



VLS2010ET-6R8M



VLS2010ET-100M



VLS2010ET-150M



VLS2010ET-220M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS2012E

FEATURES

- Miniature size
  Mount area: 2×2mm
  Height: 1.2mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

Cellular phones, DVCs, DSCs, PDAs, LCD displays, HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm

RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (µH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS2012ET-R47N	0.47	±30	1.0	0.059	0.049	2.05	2.25	2.00
VLS2012ET-R68N	0.68	±30	1.0	0.066	0.055	1.70	1.90	1.85
VLS2012ET-1R0N	1.0	±30	1.0	0.086	0.071	1.45	1.65	1.65
VLS2012ET-1R5N	1.5	±30	1.0	0.108	0.090	1.20	1.30	1.45
VLS2012ET-2R2M	2.2	±20	1.0	0.153	0.127	1.00	1.10	1.25
VLS2012ET-3R3M	3.3	±20	1.0	0.228	0.190	0.84	0.93	1.00
VLS2012ET-4R7M	4.7	±20	1.0	0.336	0.280	0.70	0.78	0.84
VLS2012ET-6R8M	6.8	±20	1.0	0.498	0.415	0.57	0.64	0.69
VLS2012ET-100M	10	±20	1.0	0.834	0.695	0.47	0.52	0.53
VLS2012ET-150M	15	±20	1.0	1.062	0.885	0.40	0.44	0.47
VLS2012ET-220M	22	±20	1.0	1.764	1.470	0.33	0.37	0.35

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS2012ET-R47N



VLS2012ET-R68N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS2012ET-1R0N



VLS2012ET-1R5N



VLS2012ET-2R2M



VLS2012ET-3R3M



VLS2012ET-4R7M



VLS2012ET-6R8M



VLS2012ET-100M



VLS2012ET-150M



VLS2012ET-220M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS252008E

FEATURES

- Miniature size
  Mount area: 2.5×2mm
  Height: 0.8mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

Cellular phones, DVCs, DSCs, PDAs, LCD displays,HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm

RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (µH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS252008ET-R47N	0.47	±30	1.0	0.140	0.116	1.65	1.80	1.20
VLS252008ET-1R0N	1.0	±30	1.0	0.219	0.182	1.20	1.35	0.97
VLS252008ET-1R5N	1.5	±30	1.0	0.248	0.206	1.00	1.10	0.91
VLS252008ET-2R2M	2.2	±20	1.0	0.290	0.241	0.77	0.86	0.84
VLS252008ET-3R3M	3.3	±20	1.0	0.416	0.346	0.73	0.82	0.70
VLS252008ET-4R7M	4.7	±20	1.0	0.580	0.483	0.61	0.68	0.59
VLS252008ET-6R8M	6.8	±20	1.0	0.818	0.681	0.49	0.55	0.50
VLS252008ET-100M	10.0	±20	1.0	1.232	1.026	0.43	0.48	0.41

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS252008ET-R47N



VLS252008ET-1R0N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS252008ET-1R5N



VLS252008ET-2R2M



VLS252008ET-3R3M



VLS252008ET-4R7M



VLS252008ET-6R8M



VLS252008ET-100M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS252010E

FEATURES

- Miniature size
  Mount area: 2.5×2mm
  Height: 1.0mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

Cellular phones, DVCs, DSCs, PDAs, LCD displays,HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm

RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (µH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS252010ET-R47N	0.47	±30	1.0	0.046	0.038	2.50	2.80	2.65
VLS252010ET-R68N	0.68	±30	1.0	0.062	0.052	2.05	2.30	2.20
VLS252010ET-1R0N	1.0	±30	1.0	0.084	0.070	1.75	1.90	1.90
VLS252010ET-1R5N	1.5	±30	1.0	0.128	0.107	1.45	1.60	1.50
VLS252010ET-2R2M	2.2	±20	1.0	0.190	0.158	1.20	1.30	1.20
VLS252010ET-3R3M	3.3	±20	1.0	0.275	0.229	0.94	1.05	1.00
VLS252010ET-4R7M	4.7	±20	1.0	0.398	0.332	0.80	0.89	0.82
VLS252010ET-6R8M	6.8	±20	1.0	0.532	0.443	0.68	0.76	0.71
VLS252010ET-100M	10	±20	1.0	0.854	0.712	0.56	0.63	0.55

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS252010ET-R47N



VLS252010ET-R68N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS252010ET-1R0N



VLS252010ET-1R5N



VLS252010ET-2R2M



VLS252010ET-3R3M



VLS252010ET-4R7M



VLS252010ET-6R8M



VLS252010ET-100M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS252012E

FEATURES

- Miniature size
  Mount area: 2.5×2mm
  Height: 1.2mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

DVCs, DSCs, PDAs, LCD displays, cellular phones, HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm



RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (µH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS252012ET-R47N	0.47	±30	1.0	0.056	0.047	2.75	3.10	2.15
VLS252012ET-1R0N	1.0	±30	1.0	0.087	0.073	2.20	2.45	1.70
VLS252012ET-1R5N	1.5	±30	1.0	0.126	0.105	1.80	2.00	1.45
VLS252012ET-2R2M	2.2	±20	1.0	0.154	0.129	1.55	1.75	1.30
VLS252012ET-3R3M	3.3	±20	1.0	0.272	0.227	1.25	1.40	0.98
VLS252012ET-4R7M	4.7	±20	1.0	0.405	0.338	1.05	1.20	0.81
VLS252012ET-6R8M	6.8	±20	1.0	0.612	0.510	0.85	0.95	0.65
VLS252012ET-100M	10	±20	1.0	0.756	0.630	0.73	0.82	0.59

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS252012ET-R47N



VLS252012ET-1R0N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS252012ET-1R5N



VLS252012ET-2R2M



VLS252012ET-3R3M



VLS252012ET-4R7M



VLS252012ET-6R8M



VLS252012ET-100M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS252015E

FEATURES

- Miniature size
  Mount area: 2.5×2mm
  Height: 1.5mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

DVCs, DSCs, PDAs, LCD displays, cellular phones, HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm



RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (µH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS252015ET-1R0N	1.0	±30	1.0	0.082	0.068	1.95	2.20	1.75
VLS252015ET-1R5N	1.5	±30	1.0	0.120	0.100	1.75	1.95	1.45
VLS252015ET-2R2M	2.2	±20	1.0	0.160	0.133	1.50	1.70	1.25
VLS252015ET-3R3M	3.3	±20	1.0	0.219	0.182	1.20	1.35	1.05
VLS252015ET-4R7M	4.7	±20	1.0	0.318	0.265	1.00	1.15	0.89
VLS252015ET-6R8M	6.8	±20	1.0	0.480	0.400	0.85	0.95	0.73
VLS252015ET-100M	10	±20	1.0	0.588	0.490	0.72	0.80	0.66

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS252015ET-1R0N



VLS252015ET-1R5N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS252015ET-2R2M



VLS252015ET-3R3M



VLS252015ET-4R7M



VLS252015ET-6R8M



VLS252015ET-100M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS3010E

FEATURES

- Miniature size
  Mount area: 3×3mm
  Height: 1.0mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

Cellular phones, DVCs, DSCs, PDAs, LCD displays, HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm

RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (μH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS3010ET-1R0N	1.0	±30	1.0	0.072	0.060	1.60	1.80	2.10
VLS3010ET-1R5N	1.5	±30	1.0	0.085	0.071	1.35	1.50	1.90
VLS3010ET-2R2M	2.2	±20	1.0	0.116	0.097	1.20	1.30	1.70
VLS3010ET-3R3M	3.3	±20	1.0	0.156	0.130	1.00	1.10	1.50
VLS3010ET-4R7M	4.7	±20	1.0	0.204	0.170	0.81	0.90	1.30
VLS3010ET-6R8M	6.8	±20	1.0	0.312	0.260	0.69	0.77	1.00
VLS3010ET-100M	10	±20	1.0	0.468	0.390	0.56	0.63	0.80
VLS3010ET-150M	15	±20	1.0	0.612	0.510	0.48	0.54	0.70
VLS3010ET-220M	22	±20	1.0	0.900	0.750	0.38	0.43	0.60

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS3010ET-1R0N



VLS3010ET-1R5N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS3010ET-2R2M



VLS3010ET-3R3M



VLS3010ET-4R7M



VLS3010ET-6R8M



VLS3010ET-100M



VLS3010ET-150M



VLS3010ET-220M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

TDK

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS3012E

FEATURES

- Miniature size
  Mount area: 3×3mm
  Height: 1.2mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

DSCs, DVCs, PDAs, portable game devices, cellular phones, LCD displays, HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm

RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (μH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS3012ET-1R0N	1.0	±30	1.0	0.068	0.056	1.90	2.15	2.00
VLS3012ET-1R5N	1.5	±30	1.0	0.076	0.063	1.50	1.70	1.85
VLS3012ET-2R2M	2.2	±20	1.0	0.096	0.080	1.35	1.50	1.70
VLS3012ET-3R3M	3.3	±20	1.0	0.120	0.100	1.05	1.20	1.55
VLS3012ET-4R7M	4.7	±20	1.0	0.156	0.130	0.95	1.05	1.30
VLS3012ET-6R8M	6.8	±20	1.0	0.228	0.190	0.81	0.90	1.05
VLS3012ET-100M	10	±20	1.0	0.336	0.280	0.64	0.76	0.89
VLS3012ET-150M	15	±20	1.0	0.516	0.430	0.55	0.62	0.74
VLS3012ET-220M	22	±20	1.0	0.756	0.630	0.44	0.49	0.61
VLS3012ET-330M	33	±20	1.0	1.248	1.040	0.37	0.41	0.48
VLS3012ET-470M	47	±20	1.0	1.500	1.250	0.31	0.35	0.44

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS3012ET-1R0N



VLS3012ET-1R5N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS3012ET-2R2M



VLS3012ET-3R3M



VLS3012ET-4R7M



VLS3012ET-6R8M



VLS3012ET-100M



VLS3012ET-150M



VLS3012ET-220M



VLS3012ET-330M



VLS3012ET-470M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS3015E

FEATURES

- Miniature size
  Mount area: 3×3mm
  Height: 1.5mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

APPLICATIONS

DSCs, DVCs, PDAs, portable game devices, cellular phones, LCD displays, HDDs, etc.

SHAPES AND DIMENSIONS



Dimensions in mm

RECOMMENDED PC BOARD PATTERN



Dimensions in mm

ELECTRICAL CHARACTERISTICS

Part No.	Inductance (µH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS3015ET-1R0N	1.0	±30	1.0	0.058	0.048	2.00	2.20	2.10
VLS3015ET-1R5N	1.5	±30	1.0	0.075	0.062	1.50	1.70	1.85
VLS3015ET-2R2M	2.2	±20	1.0	0.084	0.070	1.35	1.50	1.75
VLS3015ET-3R3M	3.3	±20	1.0	0.112	0.093	1.15	1.30	1.50
VLS3015ET-4R7M	4.7	±20	1.0	0.136	0.113	1.00	1.10	1.35
VLS3015ET-6R8M	6.8	±20	1.0	0.216	0.180	0.92	1.00	1.05
VLS3015ET-100M	10	±20	1.0	0.288	0.240	0.70	0.78	0.94
VLS3015ET-150M	15	±20	1.0	0.456	0.380	0.58	0.65	0.75
VLS3015ET-220M	22	±20	1.0	0.660	0.550	0.48	0.54	0.62
VLS3015ET-330M	33	±20	1.0	0.984	0.820	0.39	0.43	0.51
VLS3015ET-470M	47	±20	1.0	1.500	1.250	0.32	0.35	0.41

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS3015ET-1R0N



VLS3015ET-1R5N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS3015ET-2R2M



VLS3015ET-3R3M



VLS3015ET-4R7M



VLS3015ET-6R8M



VLS3015ET-100M



VLS3015ET-150M



VLS3015ET-220M



VLS3015ET-330M



VLS3015ET-470M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

Inductors for Power Circuits
Wound/STD • Magnetic Shielded

Conformity to RoHS Directive

VLS Series VLS4012E

FEATURES

- Miniature size
  Mount area: 4×4mm
  Height: 1.2mm max.
- Generic use for portable DC to DC converter line.
- High magnetic shield construction should actualize high resolution for EMC protection.
- Available for automatic mounting in tape and real package.
- The products do not contain lead and support lead-free soldering.

SHAPES AND DIMENSIONS



Dimensions in mm

APPLICATIONS

Cellular phones, DVCs, DSCs, PDAs, LCD displays, HDDs, etc.

RECOMMENDED PC BOARD PATTERN



Dimensions in mm



ELECTRICAL CHARACTERISTICS

Part No.	Inductance (µH)	Inductance tolerance (%)	Test frequency (MHz)	DC resistance (Ω)		Rated current(A)*		
						Based on inductance change		Based on temperature rise
				max.	typ.	max.	typ.	typ.
VLS4012ET-1R0N	1.0	±30	1.0	0.060	0.050	2.50	2.80	2.65
VLS4012ET-1R5N	1.5	±30	1.0	0.072	0.060	2.10	2.30	2.45
VLS4012ET-2R2M	2.2	±20	1.0	0.081	0.067	1.70	1.90	2.20
VLS4012ET-3R3M	3.3	±20	1.0	0.102	0.085	1.40	1.60	2.00
VLS4012ET-4R7M	4.7	±20	1.0	0.118	0.098	1.20	1.40	1.90
VLS4012ET-6R8M	6.8	±20	1.0	0.156	0.130	1.00	1.20	1.60
VLS4012ET-100M	10	±20	1.0	0.228	0.190	0.89	0.99	1.33
VLS4012ET-150M	15	±20	1.0	0.372	0.310	0.70	0.78	1.05
VLS4012ET-220M	22	±20	1.0	0.468	0.390	0.63	0.70	0.95
VLS4012ET-330M	33	±20	1.0	0.804	0.670	0.47	0.53	0.70
VLS4012ET-470M	47	±20	1.0	1.020	0.850	0.41	0.46	0.61

* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the nominal value of inductance has fallen by 30%, whichever is smaller.

- Operating temperature range: –40 to +105°C (Including self-temperature rise)

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS4012ET-1R0N



VLS4012ET-1R5N



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. DC SUPERPOSITION CHARACTERISTICS

VLS4012ET-2R2M



VLS4012ET-3R3M



VLS4012ET-4R7M



VLS4012ET-6R8M



VLS4012ET-100M



VLS4012ET-150M



VLS4012ET-220M



VLS4012ET-330M



VLS4012ET-470M



TEST CIRCUIT



1: LCR meter 4285A f=1MHz
2: DC constant current

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru