



## Main

|                           |                  |
|---------------------------|------------------|
| Range of product          | 9007             |
| Series name               | Miniature potted |
| Product or component type | Limit switch     |
| Device short name         | 9007MS/ML        |
| Sensor design             | Miniature        |
| Body type                 | Fixed            |
| Head type                 | Plunger head     |
| Material                  | Metal            |
| Body material             | Cast zinc        |
| Number of poles           | 1                |

## Complementary

|                                              |                                                                                                                                           |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Fixing mode                                  | By the head                                                                                                                               |
| Movement of operating head                   | Linear                                                                                                                                    |
| Type of operator                             | Spring return cross roller plunger steel (bushing mounted)                                                                                |
| Type of approach                             | Traverse approach 2 directions                                                                                                            |
| Switch actuation                             | By 30° cam                                                                                                                                |
| Contacts type and composition                | NC-NO                                                                                                                                     |
| Switch function                              | SPDT                                                                                                                                      |
| Contact form                                 | Form C                                                                                                                                    |
| Contacts material                            | Silver contacts                                                                                                                           |
| Contact operation                            | Snap action                                                                                                                               |
| Positive opening                             | Without                                                                                                                                   |
| Electrical connection                        | Pre-wired cable bottom                                                                                                                    |
| Type of cable                                | SJTO cable (AWG 18), 12 ft, yellow                                                                                                        |
| Terminals description ISO n°1                | (green-yellow)gnd<br>(black)com<br>(white)NO<br>(red)NC                                                                                   |
| Wire insulation material                     | PVC                                                                                                                                       |
| Maximum force for tripping                   | 80 ozf                                                                                                                                    |
| [Ie] rated operational current               | 6 Aat 120 V AC, A300 conforming to NEMA rating designation<br>3 Aat 240 V AC, A300 conforming to NEMA rating designation<br>5 Aat 28 V DC |
| [Ithe] conventional enclosed thermal current | 10 A                                                                                                                                      |
| [Ui] rated insulation voltage                | 300 V degree of pollution 3 conforming to UL 508<br>300 V degree of pollution 3 conforming to CSA C22.2 No 14                             |
| Electrical durability                        | 100000 cycles                                                                                                                             |
| Mechanical durability                        | 10000000 cycles                                                                                                                           |
| Marking                                      | CE<br>CSA<br>UL                                                                                                                           |
| Sale per indivisible quantity                | 1                                                                                                                                         |
| Height                                       | 1.75 in                                                                                                                                   |
| Width                                        | 1.56 in                                                                                                                                   |
| Depth                                        | 0.62 in                                                                                                                                   |
| Product weight                               | 1.2 lb(US)                                                                                                                                |

## Environment

|                  |                                                      |
|------------------|------------------------------------------------------|
| shock resistance | 35 gn (duration = 9 ms) conforming to IEC 60068-2-27 |
|------------------|------------------------------------------------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                                       |                                                                                                                                                                                             |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| vibration resistance                  | 10 gn (f = 75...1200 Hz) conforming to IEC 60529                                                                                                                                            |
| NEMA degree of protection             | NEMA 1 conforming to Nema type 250<br>NEMA 2 conforming to Nema type 250<br>NEMA 4 conforming to Nema type 250<br>NEMA 6 conforming to Nema type 250<br>NEMA 6P conforming to Nema type 250 |
| IP degree of protection               | IP67 conforming to IEC 60529                                                                                                                                                                |
| ambient air temperature for operation | -40...220 °F                                                                                                                                                                                |
| ambient air temperature for storage   | -40...220 °F                                                                                                                                                                                |
| protective treatment                  | Epoxy powder coat                                                                                                                                                                           |
| product certifications                | CE<br>CSA<br>UL                                                                                                                                                                             |
| standards                             | LR 25490 Class 32 11 03<br>E78403                                                                                                                                                           |

## Offer Sustainability

|                                                                                                                           |                                                                                                                           |
|---------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Not Green Premium product                                                                                                 | Not Green Premium product                                                                                                 |
| Will not be Compliant                                                                                                     | Will not be Compliant                                                                                                     |
| Reference not containing SVHC above the threshold                                                                         | Reference not containing SVHC above the threshold                                                                         |
| Available                                                                                                                 | Available                                                                                                                 |
| Need no specific recycling operations                                                                                     | Need no specific recycling operations                                                                                     |
| WARNING: This product can expose you to chemicals including:                                                              | WARNING: This product can expose you to chemicals including:                                                              |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                               | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                               |
| Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                             | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                             |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)