


features


- Small size allows for high mounting density
- Suitable for reflow soldering
- Large DC current capacity with low DC resistance
- Polarity identification available
- E-6 series of values (customs available)
- Marking: Black body color with no marking
- Products with lead-free terminations meet EU RoHS requirements

dimensions and construction




4045, 10065, 12065

Size	Dimensions inches (mm)					
	A	B	C	D	E	F
4045	$\phi .157 \pm .008$ ($\phi 4.0 \pm 0.2$)	$.169 \pm .009$ (4.3 ± 0.2)	$.177 \pm .008$ (4.5 ± 0.2)	$.118 \pm .008$ (3.0 ± 0.2)	.138 (3.5)	$.039 \pm .112$ (1.0 ± 0.3)
4235	—	.138 Max. (3.5 Max.)	$.177 \pm .008$ (4.5 ± 0.2)	$.079 \pm .008$ (2.0 ± 0.2)	$.165 \pm .008$ (4.2 ± 0.2)	$.039 \pm .008$ (1.0 ± 0.2)
9040N	$\phi .354 \pm .004$ ($\phi 9.0 \pm 0.1$)	.193 Max. (4.9 Max.)	.402 Max. (10.2 Max.)	$.079 \pm .008$ (2.0 ± 0.2)	—	$.071 \pm .008$ (1.8 ± 0.2)
10065	$\phi .394 \pm .008$ ($\phi 10.0 \pm 0.2$)	.295 Max. (7.5 Max.)	$.409 \pm .008$ (10.4 ± 0.2)	$.315 \pm .008$ (8.0 ± 0.2)	.354 (9.0)	$.098 \pm .008$ (2.5 ± 0.2)
12065	$\phi .472 \pm .008$ ($\phi 12.0 \pm 0.2$)	.295 Max. (7.5 Max.)	$.488 \pm .008$ (12.4 ± 0.2)	$.472 \pm .008$ (10.0 ± 0.2)	.433 (11.0)	$.146 \pm .112$ (3.7 ± 0.3)



4235



9040N

ordering information

New Part #	LPC	4045	A	TED	101	K
Type		Size	Termination Material	Packaging	Nominal Inductance	Tolerance
		4045	A: SnAg	TED: 10" embossed plastic	101: 100μH	K: ±10%
		4235	T: Sn (LPC4235 only)	(4045 - 1,000 pieces/reel)	221: 220μH	M: ±20%
		9040N		(4235 - 2,000 pieces/reel)	152: 1500μH	N: ±30%
		10065		(9040N - 500 pieces/reel)		
		12065		(10065 - 300 pieces/reel)		
				(12065 - 300 pieces/reel)		

For further information on packaging, please refer to Appendix A.

applications and ratings

Part Designation	Inductance (μH)	Inductance Tolerance	Quality Factor Minimum (MHz)	Self Resonant Frequency Minimum (MHz)	DC Resistance Maximum (Ω)	Allowable DC Current Maximum (Amps)	Measured Frequency (Hz)
LPC4045ATED1R0M	1.0	M: ±20%	20	90.0	0.015	3.10	1000
LPC4045ATED1R5M	1.5			70.0	0.020	2.80	
LPC4045ATED2R2M	2.2			55.0	0.023	2.50	
LPC4045ATED3R3M	3.3			45.0	0.044	1.80	
LPC4045ATED4R7M	4.7			35.0	0.062	1.45	
LPC4045ATED6R8M	6.8			25.0	0.075	1.30	
LPC4045ATED100K	10	K: ±10%	40	23.5	0.10	1.02	
LPC4045ATED150K	15			18.5	0.15	0.84	
LPC4045ATED220K	22			14.0	0.21	0.70	
LPC4045ATED330K	33			12.0	0.41	0.52	
LPC4045ATED470K	47			10.5	0.52	0.46	
LPC4045ATED680K	68			8.0	0.67	0.40	
LPC4045ATED101K	100			6.3	0.92	0.28	
LPC4045ATED151K	150			5.2	1.80	0.25	
LPC4045ATED221K	220			3.9	2.25	0.18	
LPC4045ATED331K	330			3.0	4.27	0.15	
LPC4045ATED471K	470			2.7	5.23	0.14	
LPC4045ATED681K	680			2.2	6.67	0.12	
LPC4235TTEDR82M	0.82	M: ±20%	—	146.6	0.017	3.34	—
LPC4235TTED1R0M	1.0			125.1	0.020	3.27	
LPC4235TTED1R2M	1.2			114.7	0.023	3.10	
LPC4235TTED1R5M	1.5			101.4	0.031	2.53	
LPC4235TTED2R2M	2.2			78.8	0.039	2.28	
LPC4235TTED3R3M	3.3			66.7	0.070	1.63	
LPC4235TTED4R7M	4.7	K: ±10%	—	52.0	0.090	1.44	
LPC4235TTED6R8M	6.8			43.5	0.109	1.29	
LPC4235TTED100K	10			33.5	0.190	0.91	
LPC4235TTED150K	15			29.1	0.230	0.87	
LPC4235TTED220K	22			21.7	0.366	0.69	
LPC4235TTED330K	33			13.9	0.542	0.52	
LPC4235TTED470K	47			12.0	0.688	0.47	
LPC4235TTED680K	68			12.7	1.30	0.34	
LPC4235TTED101K	100			10.4	1.66	0.31	
LPC4235TTED151K	150			7.5	2.96	0.22	
LPC4235TTED221K	220			6.7	3.77	0.20	
LPC9040NATED100M	10	M: ±20%	40	25.0	0.07	1.55	10 kHz
LPC9040NATED150K	15	K: ±10%	30	21.0	0.09	1.40	
LPC9040NATED220K	22		20	15.0	0.11	1.25	
LPC9040NATED330K	33			13.5	0.14	1.10	
LPC9040NATED470K	47		10	11.5	0.20	0.99	
LPC9040NATED680K	68			10.0	0.27	0.91	
LPC9040NATED101K	100			8.0	0.41	0.70	
LPC9040NATED151K	150			7.0	0.55	0.60	
LPC9040NATED221K	220			5.0	0.81	0.50	
LPC9040NATED331K	330			3.3	1.86	0.29	
LPC9040NATED471K	470			2.8	2.07	0.22	
LPC9040NATED681K	680			1.2	2.65	0.14	
LPC10065ATEDR68M	0.68	M: ±20%	40	75.0	6.0 mΩ	9.50	L Meas. Freq. 1 MHz Q Meas. Freq. 2.52 MHz
LPC10065ATED1R0M	1.0		30	65.0	7.0 mΩ	9.00	
LPC10065ATED1R5M	1.5			50.0	8.0 mΩ	8.50	
LPC10065ATED2R2M	2.2			40.0	9.0 mΩ	7.50	
LPC10065ATED3R3M	3.3		20	30.0	0.012	6.80	
LPC10065ATED4R7M	4.7			25.0	0.017	5.70	
LPC10065ATED6R8M	6.8	K: ±10%	15	20.0	0.024	4.70	
LPC10065ATED100K	10			15.0	0.036	3.90	
LPC10065ATED150K	15			12.0	0.054	3.15	
LPC10065ATED220K	22		15	9.0	0.080	2.60	
LPC10065ATED330K	33			8.0	0.120	2.30	
LPC10065ATED470K	47			6.0	0.175	1.79	

applications and ratings (continued)

Part Designation	Inductance (μH)	Inductance Tolerance	Quality Factor Minimum (MHz)	Self Resonant Frequency Minimum (MHz)	DC Resistance Maximum (Ω)	Allowable DC Current Maximum (Amps)	Measured Frequency (Hz)
LPC10065ATED680K	68	K: ±10%	30	5.0	0.255	1.48	100 MHz
LPC10065ATED101K	100			4.0	0.380	1.22	
LPC10065ATED151K	150			3.0	0.580	1.00	
LPC10065ATED221K	220			2.5	0.850	0.82	
LPC10065ATED331K	330			2.0	1.30	0.67	
LPC10065ATED471K	470			1.5	1.85	0.57	
LPC10065ATED681K	680			1.0	2.70	0.47	
LPC10065ATED102K	1.0 mH			0.95	4.00	0.38	
LPC10065ATED152K	1.5 mH			0.85	6.10	0.31	
LPC10065ATED222K	2.2 mH			0.70	9.00	0.26	
LPC10065ATED332K	3.3 mH			0.55	13.5	0.21	
LPC12065ATEDR68N	0.68	N: ±30%	40	77.0	5.0 mΩ	10.0	2.52 MHz
LPC12065ATED1R0N	1.0			60.0	7.0 mΩ	9.50	
LPC12065ATED1R5N	1.5			47.0	8.0 mΩ	9.00	
LPC12065ATED2R2N	2.2			38.0	10.0 mΩ	8.00	
LPC12065ATED3R3M	3.3	M: ±20%	30	30.0	0.012	7.00	
LPC12065ATED4R7M	4.7			24.0	0.016	6.50	
LPC12065ATED6R8M	6.8			19.0	0.022	5.40	
LPC12065ATED100K	10	K: ±10%	20	15.0	0.031	4.50	
LPC12065ATED150K	15			12.0	0.046	3.63	
LPC12065ATED220K	22			9.5	0.065	3.00	
LPC12065ATED330K	33			7.5	0.093	2.40	
LPC12065ATED470K	47			6.2	0.130	2.05	
LPC12065ATED680K	68			4.9	0.182	1.70	
LPC12065ATED101K	100		15	4.0	0.260	1.38	100 KHz
LPC12065ATED151K	150			3.2	0.380	1.14	
LPC12065ATED221K	220			2.5	0.540	0.94	
LPC12065ATED331K	330			2.0	0.790	0.77	
LPC12065ATED471K	470			1.6	1.08	0.65	
LPC12065ATED681K	680			1.3	1.55	0.53	
LPC12065ATED102K	1.0 mH		30	1.0	2.21	0.44	
LPC12065ATED152K	1.5 mH			0.83	3.20	0.35	
LPC12065ATED222K	2.2 mH			0.67	4.60	0.29	
LPC12065ATED332K	3.3 mH			0.53	6.60	0.23	
LPC12065ATED472K	4.7 mH			0.43	9.30	0.19	
LPC12065ATED682K	6.8 mH			0.34	13.2	0.16	

environmental applications

Performance Characteristics

Parameter	Maximum Δ L	Test Method
High Temperature Exposure	±5%	LPC4045, LPC9040, LPC10065, LPC12065: +85°C ± 2°C, 500 hours LPC4235, LPC9040E: +125°C ± 2°C, 500 hours
Low Temperature Exposure	±5%	-40°C, 500 hours
Moisture Exposure	±5%	+40°C, 90 - 95% RH, 500 hours
Temperature Cycling	±5%	-40°C (30 minutes)/+85°C (30 minutes), 100 cycles

Surface Temperature Rise graphs and additional environmental applications can also be found at www.koaspeer.com

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

11/23/08

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru