



# Military COTS 270V<sub>IN</sub> Filter

**M-FIAM3**

Example Model Number **M-FIAM3M21**

Actual size:  
2.28 x 2.2 x 0.5in  
[57,9 x 55,9 x 12,7mm]

## Input Attenuator Module

### Features & Benefits

- EMI filtering: MIL-STD-461E<sup>[b]</sup>
- Transient protection: MIL-STD-704E/F
- Environments: MIL-STD-810, MIL-STD-202
- Environmental stress screening
- Low-profile mounting options
- Output current up to 3A
- Mini-sized package
- Inrush current limiting

### Product Highlights

The M-FIAM3 is a DC front-end module that provides EMI filtering and transient protection. The M-FIAM3 enables designers using Vicor Maxi, Mini, Micro Series 300V DC-DC converters to meet conducted emission/ conducted susceptibility per MIL-STD-461E; and input transients per MIL-STD-704E/F. The M-FIAM3 accepts an input voltage of 180 – 375V<sub>DC</sub> and delivers output current up to 3A.

M-FIAM3 is housed in an industry-standard “half-brick” module measuring 2.28 x 2.2 x 0.5in and depending upon model selected, may be mounted onboard or inboard for height-critical applications.

### Compatible Products

- Maxi, Mini, Micro Series 300V Input DC-DC converters

### Absolute Maximum Rating

| Parameter                 | Rating    | Unit            | Notes               |
|---------------------------|-----------|-----------------|---------------------|
| +IN to -IN                | 375       | V <sub>DC</sub> | Continuous          |
|                           | 400       | V <sub>DC</sub> | 100ms               |
| Mounting torque           | 5 [0.57]  | in-lbs [N·m]    | 6 each, #4-40 or M3 |
| Pin Soldering temperature | 500 [260] | °F [°C]         | <5sec; wave solder  |
|                           | 750 [390] | °F [°C]         | <7sec; hand solder  |

### Thermal Resistance and Capacity

| Parameter                                                                  | Min | Typ  | Max | Unit    |
|----------------------------------------------------------------------------|-----|------|-----|---------|
| Baseplate to sink<br>flat, greased surface<br>with thermal pad (P/N 20264) |     | 0.16 |     | °C/Watt |
|                                                                            |     | 0.1  |     | °C/Watt |
| Baseplate to ambient<br>Free convection<br>1000LFM                         |     | 7.9  |     | °C/Watt |
|                                                                            |     | 2.2  |     | °C/Watt |

### MTBF per MIL-HDBK-217F (M-FIAM3M21)

| Temperature | Environment                      | MTBF   | Unit     |
|-------------|----------------------------------|--------|----------|
| 25°C        | Ground Benign: G.B.              | 13,291 | 1,000Hrs |
| 50°C        | Naval Sheltered: N.S.            | 2,392  | 1,000Hrs |
| 65°C        | Airborne Inhabited Cargo: A.I.C. | 1,874  | 1,000Hrs |

### Part Numbering

|                |                                                                                                                                                          |                                                                                                                                                                                                                                               |                                                                                |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| <b>M-FIAM3</b> | <b>M</b>                                                                                                                                                 | <b>2</b>                                                                                                                                                                                                                                      | <b>1</b>                                                                       |
| Product        | Product Grade Temperatures (°C)<br>Grade    Operating    Storage<br><b>H</b> =    -40 to +100    -55 to +125<br><b>M</b> =    -55 to +100    -65 to +125 | Pin Style<br><b>1</b> = Short Pin<br><b>2</b> = Long Pin<br><b>S</b> = Short ModuMate <sup>[a]</sup><br><b>N</b> = Long ModuMate <sup>[a]</sup><br><b>F</b> = Short RoHS<br><b>G</b> = Long RoHS<br><b>K</b> = Extra Long RoHS <sup>[c]</sup> | Baseplate<br><b>1</b> = Slotted<br><b>2</b> = Threaded<br><b>3</b> = Thru hole |

<sup>[a]</sup> Compatible with SurfMate and InMate socketing system

<sup>[b]</sup> EMI performance is subject to a wide variety of external influences such as PCB construction, circuit layout etc. External components in addition to those listed herein may be required in specific instances to gain full compliance to the standards specified at various line and load conditions.

<sup>[c]</sup> Not intended for socket or Surfmate mounting

Note: Product images may not highlight current product markings.

## Specifications

Typical at  $T_{BP} = 25^{\circ}\text{C}$ , nominal line and 75% load, unless otherwise specified.

### Input Specifications

| Parameter          | Min | Typ | Max   | Unit             | Notes                            |
|--------------------|-----|-----|-------|------------------|----------------------------------|
| Input voltage      | 180 | 270 | 375   | $V_{DC}$         | Continuous                       |
| Inrush limiting    |     |     | 0.018 | A/ $\mu\text{F}$ |                                  |
| Transient immunity |     |     |       |                  | Exceeds limits of MIL-STD-704E/F |

### Output Specifications

| Parameter             | Min | Typ | Max | Unit          | Notes                           |
|-----------------------|-----|-----|-----|---------------|---------------------------------|
| Output current        |     |     | 3   | A             |                                 |
| Efficiency            | 96  | 98  |     | %             |                                 |
| Internal voltage drop |     | 3.0 | 5.0 | V             | @ 3A, 100°C baseplate           |
| External capacitance  | 10  |     | 22  | $\mu\text{F}$ | See Figure 5 on page 4.<br>400V |

### Control Pin Specifications

| Parameter      | Min | Typ | Max | Unit     | Notes                                   |
|----------------|-----|-----|-----|----------|-----------------------------------------|
| ON/OFF control |     |     |     |          |                                         |
| Enable (ON)    | 0.0 |     | 1.0 | $V_{DC}$ | Referenced to $-V_{OUT}$                |
| Disable (OFF)  | 3.5 |     | 5.0 | $V_{DC}$ | 100k $\Omega$ internal pull-up resistor |

### Safety Specifications

| Parameter            | Min   | Typ | Max | Unit      | Notes                |
|----------------------|-------|-----|-----|-----------|----------------------|
| Dielectric withstand | 1,500 |     |     | $V_{RMS}$ | Input/Output to Base |
|                      | 2,121 |     |     | $V_{DC}$  | Input/Output to Base |

### EMI

| Standard                  | Test Procedure             | Notes |
|---------------------------|----------------------------|-------|
| MIL-STD-461E              |                            |       |
| Conducted emissions:      | CE101, CE102               |       |
| Conducted susceptibility: | CS101, CS114, CS115, CS116 |       |

EMI performance is subject to a wide variety of external influences such as PCB construction, circuit layout etc. As such, external components in addition to those listed herein may be required in specific instances to gain full compliance to the standards specified.

## Specifications (Cont.)

Typical at  $T_{BP} = 25^{\circ}\text{C}$ , nominal line and 75% load, unless otherwise specified.

### General Specifications

| Parameter | Min | Typ      | Max | Unit           | Notes |
|-----------|-----|----------|-----|----------------|-------|
| Weight    |     | 3.3 [94] |     | Ounces [grams] |       |
| Warranty  |     |          | 2   | Years          |       |

### Environmental Qualification

|                                                                                                                                                                                                                                                                                                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Altitude</b><br>MIL-STD-810F, Method 500.4, Procedure I & II, 40,000ft. and 70,000ft. Operational.                                                                                                                                                                                                                                         |
| <b>Explosive Atmosphere</b><br>MIL-STD-810F, Method 511.4, Procedure I, Operational.                                                                                                                                                                                                                                                          |
| <b>Vibration</b><br>MIL-STD-810F, Method 514.5, Procedure I, Category 14, Sine and Random vibration per Table 514.5C for Helicopter AH-6J Main Rotor with overall level of 5.6Grms for 4 hours per axis. MIL-STD-810F, Method 514.5C, General Minimum Integrity Curve per Figure 514.5C-17 with overall level of 7.7Grms for 1 hour per axis. |
| <b>Shock</b><br>MIL-STD-810F, Method 516.5, Procedure I, Functional Shock, 40g. MIL-S-901D, Lightweight Hammer Shock, 3 impacts/axis, 1,3,5 ft.<br>MIL-STD-202F, Method 213B, 60g, 9ms half sine. MIL-STD-202F, Method 213B, 75g, 11ms Saw Tooth Shock.                                                                                       |
| <b>Acceleration</b><br>MIL-STD-810F, Method 513.5, Procedure II, table 513.5-II, Operational, 2-7g, 6 directions.                                                                                                                                                                                                                             |
| <b>Humidity</b><br>MIL-STD-810F, Method 507.4.                                                                                                                                                                                                                                                                                                |
| <b>Solder Test</b><br>MIL-STD-202G, Method 208H, 8 hour aging.                                                                                                                                                                                                                                                                                |


### Environmental Stress Screening

| Parameter                           | H-Grade                                            | M-Grade                                            |
|-------------------------------------|----------------------------------------------------|----------------------------------------------------|
| Operating temperature               | -40 to +100°C                                      | -55 to +100°C                                      |
| Storage temperature                 | -55 to +125°C                                      | -65 to +125°C                                      |
| Temperature cycling*                | 12 cycles<br>-65 to +100°C                         | 12 cycles<br>-65 to +100°C                         |
| Ambient test @ 25°C                 | Yes                                                | Yes                                                |
| Power cycling burn-in               | 12 hours, 29 cycles                                | 24 hours, 58 cycles                                |
| Functional and parametric ATE tests | -40 and +100°C                                     | -55 and +100°C                                     |
| Hi-Pot test                         | Yes                                                | Yes                                                |
| Visual inspection                   | Yes                                                | Yes                                                |
| Test data                           | <a href="http://vicorpower.com">vicorpower.com</a> | <a href="http://vicorpower.com">vicorpower.com</a> |


\*Temperature cycled with power off, 17°C per minute rate of change.

## Storage


Vicor products, when not installed in customer units, should be stored in ESD safe packaging in accordance with ANSI/ESD S20.20, "Protection of Electrical and Electronic Parts, Assemblies and Equipment" and should be maintained in a temperature controlled factory/warehouse environment not exposed to outside elements controlled between the temperature ranges of 15°C and 38°C. Humidity shall not be condensing, no minimum humidity when stored in an ESD compliant package.




**Figure 1** — Conducted noise; M-FIAM3 and V300A48C500BG DC-DC converter operating at 270V<sub>DC</sub> input at 450W




**Figure 2** — Transient immunity; M-FIAM3 output response to an input transient



**Figure 3** — Inrush limiting; inrush current with 22μF external capacitance, (C1 in Figure 5)



**Figure 4** — Insertion loss curve



**Figure 5** — Basic connection diagram with transient, surge protection and recommended reverse-polarity protection

## Mechanical Drawings




Figure 6 — Mechanical diagram




Figure 7 — PCB mounting specifications

**Vicor's comprehensive line of power solutions includes high density AC-DC and DC-DC modules and accessory components, fully configurable AC-DC and DC-DC power supplies, and complete custom power systems.**

Information furnished by Vicor is believed to be accurate and reliable. However, no responsibility is assumed by Vicor for its use. Vicor makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication. Vicor reserves the right to make changes to any products, specifications, and product descriptions at any time without notice. Information published by Vicor has been checked and is believed to be accurate at the time it was printed; however, Vicor assumes no responsibility for inaccuracies. Testing and other quality controls are used to the extent Vicor deems necessary to support Vicor's product warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

**Specifications are subject to change without notice.**

Visit [http://www.vicorpower.com/mil-cots\\_dc-dc/mil-cots\\_m-fiam\\_filter\\_input\\_attenuator\\_module](http://www.vicorpower.com/mil-cots_dc-dc/mil-cots_m-fiam_filter_input_attenuator_module) for the latest product information.

**Vicor's Standard Terms and Conditions and Product Warranty**

All sales are subject to Vicor's Standard Terms and Conditions of Sale, and Product Warranty which are available on Vicor's webpage (<http://www.vicorpower.com/termsconditionswarranty>) or upon request.

**Life Support Policy**

VICOR'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE CHIEF EXECUTIVE OFFICER AND GENERAL COUNSEL OF VICOR CORPORATION. As used herein, life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness. Per Vicor Terms and Conditions of Sale, the user of Vicor products and components in life support applications assumes all risks of such use and indemnifies Vicor against all liability and damages.

**Intellectual Property Notice**

Vicor and its subsidiaries own Intellectual Property (including issued U.S. and Foreign Patents and pending patent applications) relating to the products described in this data sheet. No license, whether express, implied, or arising by estoppel or otherwise, to any intellectual property rights is granted by this document. Interested parties should contact Vicor's Intellectual Property Department.

Contact Us: <http://www.vicorpower.com/contact-us>

**Vicor Corporation**  
25 Frontage Road  
Andover, MA, USA 01810  
Tel: 800-735-6200  
Fax: 978-475-6715  
[www.vicorpower.com](http://www.vicorpower.com)

**email**

Customer Service: [custserv@vicorpower.com](mailto:custserv@vicorpower.com)  
Technical Support: [apps@vicorpower.com](mailto:apps@vicorpower.com)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vicor:](#)

[M-FIAM3H21](#) [M-FIAM3H22](#) [M-FIAM3H22-01](#) [M-FIAM3H23](#) [M-FIAM3HF1](#) [M-FIAM3HG1](#) [M-FIAM3HG2](#) [M-FIAM3HG3](#) [M-FIAM3HK3](#) [M-FIAM3HN1](#) [M-FIAM3HN2](#) [M-FIAM3HN3](#) [M-FIAM3HS1](#) [M-FIAM3HS2](#) [M-FIAM3HS3](#) [M-FIAM3M11](#) [M-FIAM3M12](#) [M-FIAM3M13](#) [M-FIAM3M21](#) [M-FIAM3M22](#) [M-FIAM3M23](#) [M-FIAM3MG1](#) [M-FIAM3MK1](#) [M-FIAM3MN1](#) [M-FIAM3MN2](#) [M-FIAM3MN3](#) [M-FIAM3MS1](#) [M-FIAM3H12](#) [M-FIAM3H11](#) [M-FIAM3H13](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)