



### Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Range of product          | Preventa XY2                         |
| Product or component type | Dual emergency stop rope pull switch |
| Device short name         | XY2CED                               |
| Housing colour            | Red RAL 3000                         |
| Overvoltage category      | Class I conforming to EN/IEC 61140   |

### Complementary

|                                              |                                                                                                                                                                                                                                                                                                                                   |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local signalling                             | With pilot light, yellow, 24...130 V                                                                                                                                                                                                                                                                                              |
| Number of cables                             | 2                                                                                                                                                                                                                                                                                                                                 |
| Trigger cable maximum length                 | 2 x 100 m                                                                                                                                                                                                                                                                                                                         |
| Bellow material                              | Nitril                                                                                                                                                                                                                                                                                                                            |
| Body material                                | Zamak                                                                                                                                                                                                                                                                                                                             |
| Cover material                               | Stainless steel                                                                                                                                                                                                                                                                                                                   |
| Reset                                        | By key-release push-button                                                                                                                                                                                                                                                                                                        |
| Key number                                   | 455                                                                                                                                                                                                                                                                                                                               |
| Contacts type and composition                | 2 x (1 NC + 1 NO)                                                                                                                                                                                                                                                                                                                 |
| Contact operation                            | Slow-break                                                                                                                                                                                                                                                                                                                        |
| Trigger cable anchor point                   | RH and LH sides                                                                                                                                                                                                                                                                                                                   |
| Connections - terminals                      | Screw clamp terminal 1 x 0.5...2 x 1.5 mm <sup>2</sup>                                                                                                                                                                                                                                                                            |
| Tightening torque                            | 7.08...10.62 lbf.in (0.8...1.2 N.m)                                                                                                                                                                                                                                                                                               |
| Cable entry number                           | 3 plain hole Pg 13.5 or ISO M20 cable gland                                                                                                                                                                                                                                                                                       |
| Safety level                                 | Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to EN/IEC 61508 |
| Safety reliability data                      | B10d = 300000 with value given for a life time of 20 years limited by mechanical or contact wear conforming to IEC 60947-5-5                                                                                                                                                                                                      |
| Marking                                      | CE                                                                                                                                                                                                                                                                                                                                |
| Mechanical durability                        | 60000 cycles                                                                                                                                                                                                                                                                                                                      |
| Distance between cable supports              | 3...5 m                                                                                                                                                                                                                                                                                                                           |
| [Ie] rated operational current               | 3 A at 240 V AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A<br>0.27 A at 250 V DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A                                                                                                                                                                                       |
| [Ithe] conventional enclosed thermal current | 10 A                                                                                                                                                                                                                                                                                                                              |
| [Ui] rated insulation voltage                | 500 V (degree of pollution: 3) conforming to EN/IEC 60947-1<br>300 V (degree of pollution: conforming to UL 508<br>300 V (degree of pollution: conforming to CSA C22.2 No 14                                                                                                                                                      |
| [Uimp] rated impulse withstand voltage       | 6 kV conforming to EN/IEC 60947-1                                                                                                                                                                                                                                                                                                 |
| Positive opening                             | With conforming to EN/IEC 60947-5-1                                                                                                                                                                                                                                                                                               |
| Resistance across terminals                  | <= 25 MOhm conforming to EN/IEC 60255-7 category 3                                                                                                                                                                                                                                                                                |
| Short-circuit protection                     | 10 A by gG cartridge fuse conforming to EN/IEC 60269                                                                                                                                                                                                                                                                              |
| Terminals description ISO n°1                | (13-14)NO<br>(21-22)NC                                                                                                                                                                                                                                                                                                            |
| Product weight                               | 4.19 lb(US) (1.9 kg)                                                                                                                                                                                                                                                                                                              |


The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| Environment                           |                                                                                                                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| standards                             | EN/IEC 60204-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-5<br>EN/ISO 13850<br>UL 508<br>Machinery directive 2006/42/EC<br>CSA C22.2 No 14<br>Work equipment directive 2009/104/EC |
| product certifications                | UL category NISD emergency stop devices<br>CSA<br>CCC<br>EAC                                                                                                                  |
| protective treatment                  | TC                                                                                                                                                                            |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                                                                                                    |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                                                                                    |
| vibration resistance                  | 10 gn (f = 10...300 Hz) conforming to EN/IEC 60068-2-6                                                                                                                        |
| shock resistance                      | 50 gn 11 ms conforming to EN/IEC 60068-2-27                                                                                                                                   |
| IP degree of protection               | IP65 conforming to IEC 60529                                                                                                                                                  |

|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Green Premium product                                                                                                      | Green Premium product                                                                                                      |
| Compliant - since 1532 - Schneider Electric declaration of conformity                                                      | Compliant - since 1532 - Schneider Electric declaration of conformity                                                      |
| Reference not containing SVHC above the threshold                                                                          | Reference not containing SVHC above the threshold                                                                          |
| Available                                                                                                                  | Available                                                                                                                  |
| Need no specific recycling operations                                                                                      | Need no specific recycling operations                                                                                      |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

[illegible]


## 2 / 4



## Electrical Curves

### AC Supply 50/60 Hz. $\mu$ m Inductive Circuit

2-pole Contact Block



(y) Millions of operating cycles


(x) Current in A

### DC Supply. Power Broken in W for 1 Million Operating Cycles. $\mu$ m Inductive Circuit

|           |    |    |     |
|-----------|----|----|-----|
| Voltage V | 24 | 48 | 120 |
| $\mu$ m W | 13 | 9  | 7   |

## Mounting and Clearance

### Adjustment Values (With End Spring)



In Prohibited zone  
grey :

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)