



TS824-2.5

HIGH THERMAL STABILITY MICROPOWER SHUNT VOLTAGE REFERENCE

- LOW Tc: 50 ppm/°C MAXIMUM
- 2.5V OUTPUT VOLTAGE
- LOW OPERATING CURRENT: 60µA max @ 25°C
- HIGH PRECISION AT 25°C: ±0.5% AND ±1%
- STABLE WHEN USED WITH CAPACITIVE LOADS
- INDUSTRIAL TEMPERATURE RANGE: -40 to +85°C

DESCRIPTION

The TS824-2.5 is a low power shunt voltage reference featuring a very low temperature coefficient of 50ppm/°C as a maximum value. Providing a 2.5V output voltage, the TS824-2.5 operates over the industrial temperature range (-40 to +85°C). Ideal for battery-powered equipments where power conservation is critical, the TS824 is housed in a tiny SOT23-3 package allowing space saving.

The TS824 is typically stable with any capacitive loads within the entire temperature range. The product is thus easy to use and the design simplified.

APPLICATION


- Instrumentation,
- Data acquisition systems,
- Portable, Battery powered equipments
- Power management

ORDER CODE


| Voltage | Precision | SOT23-3 | SOT23 Marking |
|---------|-----------|---------------|---------------|
| 2.5V | ±1% | TS824ILT-2.5 | L252 |
| | ±0.5% | TS824AILT-2.5 | L253 |

Single temperature range: -40 to +85°C

LT = Tiny Package (SOT23-3) - only available in Tape & Reel (LT)



PIN CONNECTIONS (top view)



ABSOLUTE MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|------------|--|-------------|------|
| I_K | Reverse Breakdown Current | 20 | mA |
| I_F | Forward Current | 10 | mA |
| P_D | Power Dissipation (note1) SOT23-3 | 360 | mW |
| T_{Std} | Storage Temperature | -65 to +150 | °C |
| ESD | Human Body Model (HBM) (note2) | 2 | kV |
| | Machine Model (MM) (note 2) | 200 | V |
| T_{Lead} | Lead Temperature (soldering, 10 seconds) | 260 | °C |

Note 1: The maximum power dissipation must be derated at high temperature. It can be calculated using T_{JMAX} (maximum junction temperature), R_{THJA} (Thermal resistance junction to ambient) and T_A (Ambient temperature). The maximum power dissipation formula at any temperature is $P_{DMAX} = (T_{JMAX} - T_A) / R_{THJA}$. R_{THJA} is 340°C/W for the SOT23-3 package.

Note 2: The Human Body Model (HBM) is defined as a 100pF capacitor discharge through a 1.5kΩ resistor into each pin.
The Machine Mode (MM) is defined as a 200pF capacitor discharge directly into each pins.

OPERATING CONDITIONS

| Symbol | Parameter | Value | Unit |
|------------|--------------------------------------|------------|------|
| I_{min} | Minimum Operating Current | 60 | μA |
| I_{max} | Maximum Operating Current | 15 | mA |
| T_{oper} | Operating Free Air Temperature Range | -40 to +85 | °C |

ELECTRICAL CHARACTERISTICS (note 3)

$T_{amb} = 25^\circ\text{C}$ (unless otherwise specified)


| Symbol | Parameter | Test Condition | Min. | Typ. | Max. | Unit |
|---------------------------|---|--|--------------|-------|--------------|--------|
| V_K | Reverse Breakdown Voltage | $I_K = 100\mu\text{A}, \pm 0.5\%$ | 2.4875 | 2.500 | 2.5125 | V |
| | | $I_K = 100\mu\text{A}, \pm 1\%$ | 2.475 | 2.500 | 2.525 | |
| V_K | Reverse Breakdown Voltage Tolerance | $I_K = 100\mu\text{A}, \pm 0.5\%$ $-40^\circ\text{C} < T_{amb} < +85^\circ\text{C}$ | -12.5 -20 | | +12.5 +20 | mV |
| | | $I_K = 100\mu\text{A}, \pm 1\%$ $-40^\circ\text{C} < T_{amb} < +85^\circ\text{C}$ | -25 -33 | | +25 +33 | |
| I_{KMIN} | Minimum Operating Current | $T_{amb} = 25^\circ\text{C}$ | | 50 | 60 | μA |
| | | $-40^\circ\text{C} < T_{amb} < +85^\circ\text{C}$ | | | 65 | |
| $\Delta V_K / \Delta T$ | Average Temperature Coefficient (note 5) | $I_K = 100\mu\text{A}$ | | | 50 | ppm/°C |
| $\Delta V_K / \Delta I_K$ | Reverse Breakdown Voltage Change with Operating Current Range | $I_{KMIN} < I_K < 1\text{mA}$ $-40^\circ\text{C} < T_{amb} < +85^\circ\text{C}$ | | 0.4 | 1 1.2 | mV |
| | | $1\text{mA} < I_K < 15\text{mA}$ $-40^\circ\text{C} < T_{amb} < +85^\circ\text{C}$ | | 4.5 | 8 10 | |
| R_{KA} | Static Impedance | $\Delta I_K = I_{KMIN}$ to 1mA $-40^\circ\text{C} < T_{amb} < +85^\circ\text{C}$ | | 0.4 | 1 1.2 | Ω |
| | | $\Delta I_K = 1\text{mA}$ to 15mA $-40^\circ\text{C} < T_{amb} < +85^\circ\text{C}$ | | 0.3 | 0.6 0.7 | |
| K_{VH} | Long Term Stability | $I_K = 100\mu\text{A}, t = 1000\text{hrs}$ | | 120 | | ppm |
| E_N | Wide Band Noise | $I_K = 100\mu\text{A}$ $100\text{Hz} < f < 10\text{kHz}$ | | 350 | | nV/√Hz |

Note 3: Limits are 100% production tested at 25°C. Limits over temperature are guaranteed through correlation and by design.


Note 4: The total tolerance within the industrial range, where the maximum ΔT versus 25°C is 65°C, is explained hereafter:
 $\pm 1\% + (\pm 50 \text{ ppm/}^\circ\text{C} \times 65^\circ\text{C}) = \pm 1.325\%$




Reference voltage versus cathode current




Reference voltage versus cathode current




Test circuit




Reference voltage versus Temperature




$\Delta V_K / \Delta I_K$ for $I_K < 1 \text{ mA}$ versus temperature




$\Delta V_K / \Delta I_K$ for $I_K > 1 \text{ mA}$ versus temperature




Start-up response with low cathode current




Start-up schematic with low cathode current




Overshoot versus cathode current



Noise versus frequency



PACKAGE MECHANICAL DATA
3 PINS - TINY PACKAGE (SOT23-3)



| Dimensions | Millimeters | | | Inches | | |
|------------|-------------|-------|-------|--------|-------|-------|
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 0.890 | | 1.120 | 0.035 | | 0.044 |
| A1 | 0.010 | | 0.100 | 0.0004 | | 0.004 |
| A2 | 0.880 | 0.950 | 1.020 | | 0.037 | 0.040 |
| b | 0.300 | | 0.500 | 0.012 | | 0.020 |
| c | 0.080 | | 0.200 | 0.003 | | 0.008 |
| D | 2.800 | 2.900 | 3.040 | 0.110 | 0.114 | 0.120 |
| E | 2.100 | | 2.640 | 0.083 | | 0.104 |
| E1 | 1.200 | 1.300 | 1.400 | 0.047 | 0.051 | 0.055 |
| e | | 0.950 | | | 0.037 | |
| e1 | | 1.900 | | | 0.075 | |
| L | 0.400 | 0.500 | 0.600 | 0.016 | 0.020 | 0.024 |
| L1 | | 0.540 | | | 0.021 | |
| k | 0° | | 8° | | | |

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2002 STMicroelectronics - Printed in Italy - All Rights Reserved
STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia
Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States

© <http://www.st.com> - United Kingdom



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru