



### Main

|                                   |   |
|-----------------------------------|---|
| Range of product                  | 9012G   |
| Pressure sensor type              | Electromechanical pressure switch                                     |
| Pressure sensor name              | 9012G   |
| Pressure sensor size              | 150 psi   |
| Maximum pressure                  | 475 psi   |
| Contacts type and composition     | NC-NO, SPDT, Form C, snap action, silver nickel contacts              |
| Controlled fluid                  | Selected corrosive liquids (-15...250 °F)<br>Selected corrosive gases |
| Fluid connection type             | 0.25 inch 18 NPTF conforming to UL 508                                |
| Pressure switch type of operation | Regulation between 2 thresholds                                       |
| Scale type                        | Adjustable differential   |
| Local display                     | Without   |

### Complementary

|   |   |
|---|---|
| Range on decreasing pressure                | 3...150 psi   |
| Approx adjustable differential at mid range | 4.2...22 psi +/- 2.5 % full scale   |
| Cable entry                                 | 0.5 inch NPT conduit entrance   |
| Terminal block type                         | 4 screw terminals   |
| Electrical connection                       | Screw-clamp terminals, AWG 22...AWG 12  |
| Electrical circuit type                     | Control circuit   |
| Local signalling                            | Without   |
| [In] rated current                          | 3 A (Ue = 240 V AC) contact code: A600 conforming to NEMA rating designation<br>6 A (Ue = 120 V AC) contact code: A600 conforming to NEMA rating designation<br>0.27 A (Ue = 250 V DC) contact code: R300 conforming to NEMA rating designation |
| Setting                                     | Internal  |
| Pressure actuator                           | Diaphragm (Viton fluorocarbon)  |
| Height                                      | 5.41 in   |
| Depth                                       | 2.46 in   |
| Width                                       | 2.06 in   |
| Operating position                          | Any position  |
| Materials in contact with fluid             | 316 stainless steel<br>Viton fluorocarbon   |
| Short-circuit protection                    | 10 A by gL (cartridge) overload and short-circuit protection  |
| Operating rate                              | <= 120 cyc/mn   |
| Mechanical durability                       | 5000000 cycles  |
| Repeat accuracy                             | 4 %   |
| Product weight                              | 2 lb(US)  |

### Environment

|                                       |   |
|---------------------------------------|---|
| vibration resistance                  | 2 gn conforming to IEC 68-2-6 (f = 40...150 Hz)                   |
| shock resistance                      | 50 gn conforming to IEC 58-2-27                                   |
| standards                             | CE<br>UL 508<br>CSA C22.2 No 14                                   |
| product certifications                | CE<br>CSA LR25490 class 3211 03<br>UL listed file E12158 CCN NKPZ |
| NEMA degree of protection             | No enclosure rating (open device) conforming to UL 508            |
| ambient air temperature for operation | -10...185 °F  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|  |  |
|--|--|
| Not Green Premium product  | Not Green Premium product  |
| Will not be Compliant  | Will not be Compliant  |
| Reference not containing SVHC above the threshold  | Reference not containing SVHC above the threshold  |
| Available  | Available  |
| Available  | Available  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:   |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)  
Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)