


# PCI-9114 Series

## 32-CH 16-Bit Up to 250 kS/s Multi-Function DAQ Cards



### Introduction

ADLINK's PCI-9114 series are 32-CH, 16-bit, high-resolution multi-function DAQ cards. The PCI-9114 device features flexible configurations on analog input. The devices are divided into 2 kinds: normal gain version and high gain version. Both versions provide 4 programmable input ranges for bipolar and unipolar inputs. The A/D on the PCI-9114DG device features a sampling rate of 100 kS/s with resolution at 16 bits, while PCI-9114A-DG/HG device features a sampling rate of up to 250 kS/s with resolution at 16 bits. The device supports automatic analog input scanning, and offers a differential mode for 8-CH analog inputs and maximum noise elimination, as well as single-ended modes for 16-CH analog inputs.

The PCI-9114 also features 1-CH 16-bit general-purpose timer/counter, 16-CH TTL isolated digital inputs and 16-CH TTL isolated digital outputs. ADLINK PCI-9114 delivers cost-effective and reliable data acquisition capabilities and is ideal for a broad variety of applications.

### Features

- Supports a 32-bit 5 V PCI bus
- 16-bit A/D resolution
- Up to 100 kS/s sampling rate (PCI-9114DG)
- Up to 250 kS/s sampling rate (PCI-9114A-DG and PCI-9114A-HG)
- 32-CH single-ended or 16-CH differential analog inputs
- Bipolar or unipolar analog input ranges
- Onboard 1 k-sample A/D FIFO
- Programmable gains:
  - x1, x2, x4, x8 (PCI-9114DG and PCI-9114A-DG)
  - x1, x10, x100 (PCI-9114A-HG)
- Automatic analog inputs scanning
- 16-CH isolated digital inputs and 16-CH isolated digital outputs
- 2500 VRMS optical isolation for digital inputs and outputs
- 1-CH 16-bit general-purpose timer/counter
- +12 V and -12 V power available on the 37-pin D-sub connector
- Onboard resettable fuses for power output protection
- Compact, half-size PCB
- Operating Systems
  - Windows 7/Vista/XP/2000/2003 Server
  - Linux
- Recommended Software
  - AD-Logger
  - VB.NET/VC.NET/VB/VC++/BCB/Delphi
  - DAQBench
- Drivers Support
  - DAQPilot for LabVIEW™
  - DAQ-MTLB for MATLABR
  - PCIS-DASK for Windows
  - PCIS-DASK/X for Linux

### Accuracy

Device	Gain	Input Range
PCI-9114DG	1	0.01% of FSR ± 1 LSB
	2,4	0.02% of FSR ± 1 LSB
	8	0.04% of FSR ± 1 LSB
PCI-9114A-HG	1, 10	0.01% of FSR ± 1 LSB
	100	0.02% of FSR ± 1 LSB

- Input coupling: DC
- Overvoltage protection: continuous ±35 V
- Input impedance: 1 GΩ
- Trigger modes: software, pacer, and external trigger (5 V/TTL compatible)
- FIFO buffer size: 1 k samples
- Data transfers: polling, interrupt

### Isolated Digital Input

- Number of channels: 16
- Maximum input range: 24 V, non-polarity
- Digital logic levels
  - 0 - 24 V, non-polarity
  - Input high voltage: 5 - 24 V
  - Input low voltage: 0 - 1.5 V
- Input resistance: 2.4 KΩ @ 0.5 W
- Isolation voltage: 2500 VRMS
- Data transfers: programmed I/O

### Isolated Digital Output

- Number of channels: 16
- Output type: open emitter Darlington transistors
- Sink current
  - 350 mA for one channel @ 100% duty
  - 260 mA for all channels @ 10% duty
- Power dissipation: Max. 1.47 W per chip (8 DO channels)
- Supply voltage: 5-35 V
- Isolation voltage: 2500 VRMS
- Data transfers: programmed I/O

### Power Output

- Output voltage: +12 V and -12 V
- Resettable fuse protection: 500 mA

### General-Purpose Timer/Counter

- Number of channels: 1
- Resolution: 16 bits
- Compatibility: 5 V/TTL
- Base clock available: 2 MHz, external clock to 2 MHz

### General Specifications

- I/O connector
  - 37-pin D-sub female
  - 20-pin ribbon male x 2
- Operating temperature: 0°C to 55°C
- Storage temperature: -20°C to 80°C
- Relative humidity: 5% to 95%, non-condensing
- Power requirements
 

+5 V	+12 V
600 mA typical	100 mA typical
- Dimensions (not including connectors)  
175 mm x 107 mm

### Terminal Boards & Cables

#### ■ DIN-37D-01\*

Terminal Board with One 37-pin D-sub Connector and DIN-Rail Mounting

#### ■ DIN-20P-01\*

Terminal Board with One 20-pin Ribbon Connector and DIN-Rail Mounting

#### ■ ACLD-9137-01

General-Purpose Terminal Board with One 37-pin D-sub Male Connector

#### ■ ACLD-9188-01\*

General-Purpose Terminal Board with Two 20-pin Ribbon Connectors and One 37-pin D-sub Connector

\* Cables are not included. For information on mating cables, refer to P2-61/62

### Ordering Information

#### ■ PCI-9114DG

32-CH 16-Bit 100 kS/s Normal-Gain Multi-Function DAQ Card

#### ■ PCI-9114A-DG

32-CH 16-Bit 250 kS/s Normal-Gain Multi-Function DAQ Card

#### ■ PCI-9114A-HG

32-CH 16-Bit 250 kS/s High-Gain Multi-Function DAQ Card

### Pin Assignment

CN1		CN2	
+12Vout	1	20	GND
-12Vout	2	21	(AIL15) AI31
AI15 (AIH15)	3	22	(AIL14) AI30
AI14 (AIH14)	4	23	(AIL13) AI29
AI13 (AIH13)	5	24	(AIL12) AI28
AI12 (AIH12)	6	25	(AIL11) AI27
AI11 (AIH11)	7	26	(AIL10) AI26
AI10 (AIH10)	8	27	(AIL9) AI25
AI9 (AIH9)	9	28	(AIL8) AI24
AI8 (AIH8)	10	29	AGND
AGND	11	30	(AIL7) AI23
AI7 (AIH7)	12	31	(AIL6) AI22
AI6 (AIH6)	13	32	(AIL5) AI21
AI5 (AIH5)	14	33	(AIL4) AI20
AI4 (AIH4)	15	34	(AIL3) AI19
AI3 (AIH3)	16	35	(AIL2) AI18
AI2 (AIH2)	17	36	(AIL1) AI17
AI1 (AIH1)	18	37	(AIL0) AI16
AI0 (AIH0)	19		

CN3	
DO_0	1
DO_1	2
DO_2	3
DO_3	4
DO_4	5
DO_5	6
DO_6	7
DO_7	8
DO_8	9
DO_9	10
DO_10	11
DO_11	12
DO_12	13
DO_13	14
DO_14	15
DO_15	16
EOGND	17
VDD	18
VDD	19
VDD	20

### Specifications

#### Analog Input

- Number of channels: 32 single-ended or 16 differential
- Resolution: 16 bits
- Conversion time:
  - 10 μs (PCI-9114DG)
  - 4 μs (PCI-9114A-DG & PCI-9114A-HG)
- Maximum sampling rate

Device	Sampling rate
PCI-9114DG	100 kS/s
PCI-9114A-DG PCI-9114A-HG	250 kS/s

- Input ranges (software programmable)

Device	Gain	Input Range
PCI-9114DG	1	±10 V
	2	±5 V
	4	±2.5 V
PCI-9114A-DG	8	±1.25 V
	1	±10 V
	10	±1 V
PCI-9114A-HG	100	±0.1 V

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)