General Specifications

Electrical Capacity (Resistive Load)

Power Level: 3A @ 250V AC

Other Ratings

Contact Resistance: 20 milliohms maximum
Insulation Resistance: 1,000 megohms minimum @ 500V DC
Dielectric Strength: 1,000V AC minimum between contacts for 1 minute minimum;
1,500V AC minimum between contacts & case for 1 minute minimum
Mechanical Life: 30,000 cycles minimum
Electrical Life: 10,000 cycles minimum
Static Capability: Withstands 15 kilovolts minimum ESD minimum (for CKM models only)
Nominal Operating Torque: 16mm Bushing (CKM models):
.04 mNm (5.67 oz•in) for Flat Key
.08 mNm (11.33 oz•in) for Tubular Key
19mm Bushing (CKL models):
.05 mNm (7.08 oz•in) for Flat Key
.07 mNm (9.91 oz•in) for Tubular Key
Contact Timing: Break-before-make
Angle of Throw: 90° for 2-position & 45° for 3-position

Materials & Finishes

Keys for CKM: Brass with nickel plating with ABS handle
Keys for CKL: Brass with nickel plating for tubular key;
brass with chrome plating for flat key
Housing/Bushing: Glass fiber reinforced PBT for CKM models;
zinc alloy with chrome plating for CKL
Base: LCP (Liquid Crystal Polymer)
Contact Terminals: Copper with silver plating
Common Terminals: Copper with silver plating
Movable Contactor: Copper
Movable Contacts: Silver

Environmental Data

Operating Temperature Range: –25°C through +70°C (–13°F through +158°F)
Humidity: 90 ~ 95% humidity for 240 hours @ 40°C (104°F) for CKM;
90 ~ 95% humidity for 96 hours @ 40°C (104°F) for CKL
Vibration: 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm for CKM or 0.7mm for CKL traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours
Shock: 50G (490m/s^2) acceleration for CKM; 30G (294m/s^2) acceleration for CKL; (CKM & CKL tested in 6 right angled directions, with 5 shocks in each direction)

Installation

Mounting Torque: 1.5 Nm (13.28 lb•in) maximum
Soldering Time & Temperature: Manual Soldering: See Profile A in Supplement section.

Distinctive Characteristics

High insulating material for 16mm CKM models withstands over 15 kilovolts of electrostatic discharge, thus providing antistatic feature.

Rugged, die cast housing 19mm CKL models designed for higher security requirements.

Vertically rotating switching mechanism combines with self-cleaning sliding contacts for high reliability and long operating life.

16mm and 19mm diameter bushings available.

CKL and CKM on-off-on models with tubular keys have push-and-lock mechanism which allows contactor to drop and slide over stationary contacts.

Available in both flat and tubular key styles; flat key is reversible for easier setting.

Epoxy sealed terminals prevent entry of flux and other contaminants.

Interior construction provides seal for contact area.

High dielectric strength of 1,500 volts between contacts and case.



Actual Size CKM with Tubular Key



TYPICAL SWITCH ORDERING EXAMPLE

CK | M | 1 | 2A | F | W | 01

Bushings

M	16mm Diameter
L	19mm Diameter

Poles

1	SPDT

Keys

F	Flat
T	Tubular

Terminals

01	Solder Lug *

* Wire harness & cable assemblies offered only in Americas

Circuits & Key-Removable Positions

Code	Pos. 1	Pos. 2	Pos. 3	Key Removes
2A	ON	NONE	ON	Positions 1 and 3
2B	ON	NONE	ON	Position 1
3E	ON	OFF	ON	Position 2

Contact Material

W	Silver Rated 3A @ 250V AC

DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

CKM12AFW01

One key supplied with each switch

SPDT ON-NONE-ON Circuit
Key Removable in Positions 1 and 3

16mm Diameter Bushing

Solder Lug Terminals

Silver Contacts
Rated 3A @ 250V AC

POLES, CIRCUITS & KEY-REMOVABLE POSITIONS

Pole & Throw	Model	Key Positions Pos 1	Pos 2	Pos 3	Connected Terminals (Terminal numbers are on switch) Pos 1	Pos 2	Pos 3	Schematic	◉ = Key Removable • = Not Removable ◡ = Maximum Arc
SPDT	**CKM12A CKL12A**	ON	NONE	ON	COM-1	——	COM-2	COM 1 2	POS 1 3
SPDT	**CKM12B CKL12B**	ON	NONE	ON	COM-1	——	COM-2		POS 1 3
SPDT	**CKM13E CKL13E**	ON	OFF	ON	COM-1	OPEN	COM-2	COM OPEN 1 2	2 POS 1 3

KEYS

F **Flat Key**

AT4147 for CKM 16mm
Brass with Nickel Plating key base & ABS key handle
AT4153 for CKL 19mm
Brass with Chrome Plating (crosshatch texture on handle)

One key provided with each switch (no master key available)
For ordering additional keys, indicate the same key number that is engraved on the face of your switch.

Randomly assigned key number (001 through 010 for CKM models & 001 through 025 for CKL models).

Typical Key Ordering Example: AT4153-001

T **Tubular Key**
(must be pressed inward to actuate)

AT4146 for CKM 16mm
Brass with Nickel Plating key base & ABS key handle
AT4152 for CKL 19mm
Brass with Nickel Plating (smooth)

One key provided with each switch (no master key available)
For ordering additional keys, indicate the same key number that is engraved on the face of your switch.

Randomly assigned key number (001 through 025 for CKM models & 001 through 050 for CKL models).

Typical Key Ordering Example: AT4146-001

AT4147



AT4153



AT4146



AT4152



CONTACT MATERIALS, RATINGS & TERMINALS

W **Silver over Silver**
Power Level 3A @ 250V AC

01 **Solder Lug Terminals**

Solder Lug Terminal for CKM



Solder Lug Terminal for CKL



TYPICAL SWITCH DIMENSIONS

16mm Bushing • Flat Key

90° Angular Throw



45° Angular Throw



CKM12AFW01

16mm Bushing • Tubular Key

90° Angular Throw



45° Angular Throw



CKM13ETW01

PANEL CUTOUT & STANDARD HARDWARE FOR 16MM BUSHING

Maximum Effective Panel Thickness: .469" (11.9mm)



AT016
16mm Hex Mounting Nut for CKM

1 included with each switch
Steel



TYPICAL SWITCH DIMENSIONS

19mm Bushing • Flat Key

90° Angular Throw





45° Angular Throw





CKL12AFW01

19mm Bushing • Tubular Key

90° Angular Throw





45° Angular Throw





CKL13ETW01

PANEL CUTOUT & STANDARD HARDWARE FOR 19MM BUSHING

Maximum Effective Panel Thickness: .496" (12.6mm)



AT019
19mm Hex Mounting Nut for CKL

1 included with each switch
Steel



LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru