










SECTION C-C

SECTION D-D


spec ref -				dr Wei-Long Zhang		2012/08/09		projection		MM		size A2		scale 4:1	
tolerance std -		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng Sunny2 Liu		2016/05/06						ecn no ELX-DG-24036-1			
ASME Y14.5				chr Terris Liu		2016/05/20		product family CARD EDGE		rel level Released					
				appr Pei-Ming Zheng		2016/05/24									
surface -		linear		Amphenol FCI		title STD STRADDLE MT		dwg no 10122237		rev B					
		0.X ±0.3													
		0.XX ±0.1													
		0.XXX ±0.05													
ASME Y14.5		angular 0° ±0°				cat. no. -		Product - Customer Drw		sheet 1 of 4					



RECOMMENDED HOST BOARD LAYOUT AS VIEWED




spec ref	-	dr	Wei-Long Zhang	2012/08/09	projection	MM	size	A2	scale	2:1
tolerance std	-	eng	Sunny2 Liu	2016/05/06	chr	Terris Liu	2016/05/20	ecn no	ELX-DG-24036-1	
ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED	appr	Pei-Ming Zheng	2016/05/24	product family	-	rel level	Released		
surface	linear	0.X	±0.3	0.XX	±0.1	0.XXX	±0.05	angular	0°	±°
ASME Y14.5	ASME Y14.5	Amphenol FCI	STD STRADDLE MT	HIGH POWER CARD EDGE - UNIVERSAL	cat. no.	-	Product - Customer Drw	sheet 2 of 4	rev	B



RECOMMENDED MATING BOARD
FOOTPRINT

spec ref -		dr Wei-Long Zhang		2012/08/09		projection		MM		size A2		scale 1:1			
tolerance std -		eng Sunny2 Liu		2016/05/06						ecn no ELX-DG-24036-1		rel level Released			
ASME Y14.5		chr Terris Liu		2016/05/20											
		appr Pei-Ming Zheng		2016/05/24											
				product family											
surface -		linear		0.X		±0.3		Amphenol FCI		title STD STRADDLE MT		dwg no 10122237		rev B	
				0.XX		±0.1									
				0.XXX		±0.05									
ASME Y14.5		angular		0°		±0°									
				cat. no.				Product - Customer Drw				sheet 3 of 4			



NOTES:

1. CONNECTOR MATERIALS:

HOUSING: HIGH TEMPERATURE THERMAL PLASTIC, BLACK
UL 94V-0 COMPLIANT
CONTACTS: HIGH PERFORMANCE COPPER ALLOY.

2. CONTACT FINISH REF. GS-12-604 SECTION 5.2.

3. PRODUCT SPECIFICATION: GS-12-604.

4. APPLICATION SPECIFICATION: GS-20-128.

5. PRODUCT MARKING ON HOUSING IN AREA SHOWN MEETS AFCI SPECIFICATION: GS-24-007.

6. PACKAGING MEETS FCI SPECIFICATION GS-14-937.


7. HOUSING COMPONENT WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 60 SECONDS IN A CONVECTION, INFRA-RED, OR VAPOR PHASE REFLOW OVEN.




8. MAXIMUM OVERALL LENGTH IS 100mm.

9. DIM IS NOT APPLICABLE IF NO 4 BEAM CONTACT OR 2 BEAM CONTACT.

10. A SYMBOL  WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.

DIM	TABLE 2. LENGTH FORMULAS
DIM A ⑧	(MM + NN) / 2 x 2.54 + (PP / 2) x 1.27 + 17.2
DIM B	DIM A - 13.08
DIM C	DIM A - 7.5
DIM D	DIM A - 10.42
DIM E ⑨	(MM / 8 - 1) x 10.16 + (NN / 4 - 1) x 5.08 + 16.84 (WITH 4 BEAM CONTACT) 6.68 (WITHOUT 4 BEAM CONTACT)
DIM F	DIM A - 13.38
DIM G ⑨	(MM / 8 - 1) x 10.16 + (NN / 4 - 1) x 5.08 + 13.34 (WITH 4 BEAM CONTACT) 3.18 (WITHOUT 4 BEAM CONTACT)



spec ref		-		dr		Wei-Long Zhang		2012/08/09		projection				MM		size		A2		scale		4:1	
tolerance std		-		eng		Sunny2 Liu		2016/05/06						ecn no		ELX-DG-24036-1		rel level		Released			
ASME Y14.5		TOLERANCES UNLESS OTHERWISE SPECIFIED		chr		Terris Liu		2016/05/20															
				appr		Pei-Ming Zheng		2016/05/24															
										product family		CARD EDGE											
surface		-		linear		0.X		±0.3		Amphenol FCI		title		STD STRADDLE MT		dwg no		10122237		rev		B	
				0.XX		±0.1																	
				0.XXX		±0.05																	
ASME Y14.5				angular		0°		±°						cat. no.		-		Product - Customer Drw		sheet 4 of 4			

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru