


## Sensor/actuator terminal block - PTIO 1,5/S/4-PE - 3244465

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sensor/actuator terminal block, Connection method: Push-in connection, Cross section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, AWG: 26 - 14, Width: 3.5 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

### Product Features

- ✓ The push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- ✓ The compact design and front connection enable wiring in a confined space
- ✓ In addition to the testing facility in the double function shaft, all terminal blocks provide an additional test connection



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 10.4 GRM |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Poland   |

### Technical data

#### General

|                                         |        |
|-----------------------------------------|--------|
| Number of levels                        | 4      |
| Number of connections                   | 5      |
| Color                                   | gray   |
| Insulating material                     | PA     |
| Inflammability class according to UL 94 | V0     |
| Maximum load current                    | 13.5 A |
| Rated surge voltage                     | 4 kV   |
| Pollution degree                        | 3      |
| Surge voltage category                  | III    |
| Insulating material group               | I      |

# Sensor/actuator terminal block - PTIO 1,5/S/4-PE - 3244465

## Technical data

### General

|                                                                                 |                                     |
|---------------------------------------------------------------------------------|-------------------------------------|
| Connection in acc. with standard                                                | IEC 60947-7-1 / IEC 60947-7-2       |
| Nominal current $I_N$                                                           | 13.5 A                              |
| Nominal voltage $U_N$                                                           | 250 V                               |
| Open side panel                                                                 | ja                                  |
| Shock protection test specification                                             | DIN EN 50274 (VDE 0660-514):2002-11 |
| Back of the hand protection                                                     | guaranteed                          |
| Finger protection                                                               | guaranteed                          |
| Surge voltage test setpoint                                                     | 4.8 kV                              |
| Result of surge voltage test                                                    | Test passed                         |
| Power frequency withstand voltage setpoint                                      | 1.5 kV                              |
| Result of power-frequency withstand voltage test                                | Test passed                         |
| Checking the mechanical stability of terminal points (5 x conductor connection) | Test passed                         |
| Bending test rotation speed                                                     | 10 rpm                              |
| Bending test turns                                                              | 135                                 |
| Bending test conductor cross section/weight                                     | 0.14 mm <sup>2</sup> / 0.2 kg       |
|                                                                                 | 1.5 mm <sup>2</sup> / 0.4 kg        |
| Result of bending test                                                          | Test passed                         |
| Conductor cross section tensile test                                            | 0.14 mm <sup>2</sup>                |
| Tractive force setpoint                                                         | 10 N                                |
| Conductor cross section tensile test                                            | 1.5 mm <sup>2</sup>                 |
| Tractive force setpoint                                                         | 40 N                                |
| Tensile test result                                                             | Test passed                         |
| Tight fit on carrier                                                            | NS 35                               |
| Setpoint                                                                        | 1 N                                 |
| Result of tight fit test                                                        | Test passed                         |
| Requirements, voltage drop                                                      | $\leq 3.2$ mV                       |
| Result of voltage drop test                                                     | Test passed                         |
| Temperature-rise test                                                           | Test passed                         |
| Conductor cross section short circuit testing                                   | 1.5 mm <sup>2</sup>                 |
| Short-time current                                                              | 0.8 kA                              |
| Short circuit stability result                                                  | Test passed                         |
| Ageing test for screwless modular terminal block temperature cycles             | 192                                 |
| Result of aging test                                                            | Test passed                         |
| Proof of thermal characteristics (needle flame) effective duration              | 30 s                                |
| Result of thermal test                                                          | Test passed                         |
| Test specification, oscillation, broadband noise                                | DIN EN 50155 (VDE 0115-200):2008-03 |

# Sensor/actuator terminal block - PTIO 1,5/S/4-PE - 3244465

## Technical data

### General

|                                                                       |                                                |
|-----------------------------------------------------------------------|------------------------------------------------|
| Test spectrum                                                         | Service life test category 2, bogie mounted    |
| Test frequency                                                        | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level                                                             | $6.12 \text{ (m/s}^2\text{)}^2/\text{Hz}$      |
| Acceleration                                                          | 3.12 g                                         |
| Test duration per axis                                                | 5 h                                            |
| Test directions                                                       | X-, Y- and Z-axis                              |
| Oscillation, broadband noise test result                              | Test passed                                    |
| Test specification, shock test                                        | DIN EN 50155 (VDE 0115-200):2008-03            |
| Shock form                                                            | Half-sine                                      |
| Acceleration                                                          | 30 g                                           |
| Shock duration                                                        | 18 ms                                          |
| Number of shocks per direction                                        | 3                                              |
| Test directions                                                       | X-, Y- and Z-axis (pos. and neg.)              |
| Shock test result                                                     | Test passed                                    |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C                                         |
| Static insulating material application in cold                        | -60 °C                                         |

### Dimensions

|                  |         |
|------------------|---------|
| Width            | 3.5 mm  |
| Length           | 90.8 mm |
| Height NS 35/7,5 | 41.5 mm |
| Height NS 35/15  | 49 mm   |

### Connection data

|                                                                            |                               |
|----------------------------------------------------------------------------|-------------------------------|
| Connection in acc. with standard                                           | IEC 60947-7-1 / IEC 60947-7-2 |
| Connection method                                                          | Push-in connection            |
| Conductor cross section solid min.                                         | 0.14 mm <sup>2</sup>          |
| Conductor cross section solid max.                                         | 1.5 mm <sup>2</sup>           |
| Conductor cross section AWG/kcmil min.                                     | 26                            |
| Conductor cross section AWG/kcmil max                                      | 14                            |
| Conductor cross section stranded min.                                      | 0.14 mm <sup>2</sup>          |
| Conductor cross section stranded max.                                      | 1.5 mm <sup>2</sup>           |
| Min. AWG conductor cross section, stranded                                 | 26                            |
| Max. AWG conductor cross section, stranded                                 | 14                            |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.14 mm <sup>2</sup>          |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>           |
| Conductor cross section stranded, with ferrule with plastic sleeve min.    | 0.14 mm <sup>2</sup>          |
| Conductor cross section stranded, with ferrule with plastic sleeve max.    | 1 mm <sup>2</sup>             |

## Sensor/actuator terminal block - PTIO 1,5/S/4-PE - 3244465

### Technical data

#### Connection data

|                           |         |
|---------------------------|---------|
| Stripping length          | 8 mm    |
| Internal cylindrical gage | A1 / B1 |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141118 |
| eCl@ss 4.1 | 27141118 |
| eCl@ss 5.0 | 27141118 |
| eCl@ss 5.1 | 27141118 |
| eCl@ss 6.0 | 27141128 |
| eCl@ss 7.0 | 27141128 |
| eCl@ss 8.0 | 27141128 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000900 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

---

Approvals

GOST

---

Ex Approvals

---

Approvals submitted

## Sensor/actuator terminal block - PTIO 1,5/S/4-PE - 3244465

### Approvals


---

#### Approval details

GOST 

### Drawings

#### Circuit diagram



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)