Band-pass filter for spectral analyzers
BA3830S

The BA3830S is a 6 + 1 band band-pass filter for spectral analyzer displays with internal recording indicator output. All of the capacitors comprising the filter are internal capacitors, making it possible to significantly reduce the number of attached components. This enables configuration of compact sets with a high level of reliability.

●Applications

CD radio cassette players, mini-components, car stereos

●Features

1) Six internal band-pass filters for spectral analyzers
2) Internal input/output for recording indicators
3) Internal capacitors reduce the number of attachments.

●Absolute maximum ratings (Ta = 25°C)


Parameter	Symbol	Limits	Unit
Power supply voltage	V_{CC}	9	V
Power dissipation	Pd	600*	mW
Operating temperature	Topr	−25～+75	℃
Storage temperature	Tstg	−55～+150	℃

* Reduced by 6.0mW for each increase in Ta of 1℃ over 25℃.

●Recommended operating conditions (Ta = 25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit
Operating power supply voltage	V_{CC}	4.5	—	8.0	V

●Block diagram



●Electrical characteristics (unless otherwise noted, Ta = 25°C, V_{CC} = 5V, R_L = 10MΩ, $R\phi_1$ = 270kΩ, $R\phi_2$ = 270kΩ)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Coniditions
Quiescent current	Io	—	3.8	5.2	mA	
Reference output level (LEVEL)	V_{ol}	−3	0	3	dB	V_{IN}=−30dBV, V_o=1.5V (0dB) When f=center frequencies is input
Max. output level (LEVEL)	V_{olmax}	3.2	4.2	—	V	V_{IN}=−14dBV, When f=center frequencies is input
Reference output level (REC LEVEL)	V_{or}	−3	0	3	dB	V_{IN}=−30dBV, V_o=1.5V (0dB) f=1kHz
Max. output level (REC LEVEL)	V_{olmax}	3.8	4.8	—	V	V_{IN}=−14dBV, f=1kHz
Output offset voltage	V_{off}	—	30	90	mV	With no signal
Center frequency 1	f_{01}	49	63	77	Hz	V_{IN}=−30dBV
Center frequency 2	f_{02}	117	150	183	Hz	V_{IN}=−30dBV
Center frequency 3	f_{03}	257	330	403	Hz	V_{IN}=−30dBV
Center frequency 4	f_{04}	0.78	1	1.22	kHz	V_{IN}=−30dBV
Center frequency 5	f_{05}	2.55	3.3	4.03	kHz	V_{IN}=−30dBV
Center frequency 6	f_{06}	7.8	10	12.2	kHz	V_{IN}=−30dBV
Input current when Reset pin is HIGH	I_{IN}	150	215	280	μA	V_{IN}=5V
Threshold level when Reset pin is ON	V_{th}	—	1.4	1.8	V	
Threshold level when Reset pin is OFF	V_{th}	1.0	1.4	—	V	

*Q is set to 4.5.
◎Not designed for radiation resistance.

●Measurement circuit





Fig.1

●Circuit operation

(1) LINE and REC input circuits

The LINE and REC input circuits are configured as differential amplifiers, and the gain can be set to any desired value using an external resistor. The input impedance is determined by the external resistor.



(Note: All resistance values in the internal circuit diagrams noted here are reference values.)

Fig.2





Fig.3

(2) Bias circuit

A bias voltage of $V_{CC}/2$ is applied to each of the circuits. Since the output stage uses a push-pull configuration, a stable bias source can be obtained.



(Note: All resistance values in the internal circuit diagrams noted here are reference values.)

Fig.4

(3) BPF circuit

This is a circuit that selects the required frequency component from the input signal and amplifies it. With this configuration, no external capacitor is needed. In addition, the center frequency is set based on the current, so f_{01} and f_{02} to f_{06} can be set individually, using separate external resistors (pins1 and 2).

Q is set to 4.5V (Typ.).




Fig.5

(4) DET circuit

This circuit carries out phase detection on the signal selected and amplified by the BPF, and holds it at the peak level. It is configured so that all of the capacitors are internal.

The charge that was charged by the internal capacitors in the DET circuit is set to be discharged at 75ms/V (Typ.), but in order to eliminate any effects of disparity, a reset circuit is also included.




Fig.6

(5) Output section circuit

The signal level held at peak level by the DET undergoes V/I conversion and is output. Since the next stage supports MOS (high-input impedance), there is a resistance of 33.9kΩ (44.3kΩ for REC output only) between the output pin and the GND in the IC, so the output value changes based on the input impedance.




Fig.7

●Application example




Fig.8

●Operation notes

(1) Precautions concerning the load resistance

The various characteristics were measured at the output resistance value of 10MΩ noted in the specifications manual. Moreover, because the output of this IC supports the MOS configuration, be aware that it is current output, and the output changes depending on the input impedance at the next stage.

(2) Precautions concerning the RESET capacitor

If the reset function is to be used, a capacitor of at least 3300pF is required for RESET C (pin 7). Failing to connect this capacitor can result in erroneous displays, so make sure a sufficient capacitance is provided.

(3) Precautions concerning the coupling capacitor

When determining the polarity of the input electrolytic coupling capacitor, the potential relation with the other end of the coupling must be taken into consideration.

●Electrical characteristic curves




Fig.9 Output vs. frequency




Fig.10 Input vs. output level
(f_{01} to f_{06} modes)





Fig.11 Input vs. output level
(REC mode)

●External dimensions (Units: mm)



SDIP18

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru