# 74HC597; 74HCT597

## 8-bit shift register with input flip-flops

Rev. 4 — 25 February 2016 Product data sheet

## 1. General description

The 74HC597; 74HCT597 is an 8-bit shift register with input flip-flops. It consists of an 8-bit storage register feeding a parallel-in, serial-out 8-bit shift register. Both the storage register and the shift register have positive edge-triggered clocks. The shift register also has direct load (from storage) and clear inputs. Inputs include clamp diodes that enable the use of current limiting resistors to interface inputs to voltages in excess of $V_{CC}$.

## 2. Features and benefits

- Complies with JEDEC standard JESD7A
- Input levels:
  - For 74HC597: CMOS level
  - For 74HCT597: TTL level
- 8-bit parallel storage register inputs
- Shift register has direct overriding load and clear
- ESD protection:
  - HBM EIA/JESD22-A114F exceeds 2000 V
  - MM EIA/JESD22-A115-A exceeds 200 V
- Specified from −40 °C to +85 °C and from −40 °C to +125 °C
- Multiple package options

## 3. Ordering information

**Table 1. Ordering information**

| Type number | Package | | | |
|---|---|---|---|---|
| | Temperature range | Name | Description | Version |
| 74HC597D | −40 °C to +125 °C | SO16 | plastic small outline package; 16 leads; body width 3.9 mm | SOT109-1 |
| 74HCT597D | | | | |
| 74HC597DB | −40 °C to +125 °C | SSOP16 | plastic shrink small outline package; 16 leads; body width 5.3 mm | SOT338-1 |
| 74HCT597DB | | | | |
| 74HC597PW | −40 °C to +125 °C | TSSOP16 | plastic thin shrink small outline package; 16 leads; body width 4.4 mm | SOT403-1 |

## 4. Functional diagram




Fig 1. Functional diagram




Fig 2. Logic symbol




Fig 3. IEC Logic symbol


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




**Fig 4. Logic diagram**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

# 5. Pinning information

## 5.1 Pinning




**Fig 5. Pin configuration SO16, SSOP16 and TSSOP16**

## 5.2 Pin description

**Table 2. Pin description**

| Symbol | Pin | Description |
|---|---|---|
| GND | 8 | ground (0 V) |
| Q | 9 | serial data output |
| $\overline{MR}$ | 10 | asynchronous master reset input (active LOW) |
| SHCP | 11 | shift register clock input (LOW-to-HIGH, edge-triggered) |
| STCP | 12 | storage register clock input (LOW-to-HIGH, edge-triggered) |
| $\overline{PL}$ | 13 | parallel load input (active LOW) |
| DS | 14 | serial data input |
| D0, D1, D2, D3, D4, D5, D6, D7 | 15, 1, 2, 3, 4, 5, 6, 7 | parallel data inputs |
| $V_{CC}$ | 16 | supply voltage |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

# 6. Functional description

**Table 3. Function table[1]**

| Inputs | | | | Function |
|---|---|---|---|---|
| STCP | SHCP | $\overline{PL}$ | $\overline{MR}$ | |
| ↑ | X | X | X | data loaded to input latches |
| ↑ | X | L | H | data loaded from inputs to shift register |
| no clock edge | X | L | H | data transferred from input flip-flops to shift register |
| X | X | L | L | invalid logic, state of shift register is indeterminate when signals removed |
| X | X | H | L | shift register cleared |
| X | ↑ | H | H | shift register clocked Qn = Qn–1, Q0 = DS |

[1] H = HIGH voltage level.
L = LOW voltage level.
X = don't care.
↑ = positive-going transition.




**Fig 6. Timing diagram**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

# 7. Limiting values

**Table 4. Limiting values**

*In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).*

| Symbol | Parameter | Conditions | Min | Max | Unit |
|---|---|---|---|---|---|
| $V_{CC}$ | supply voltage | | –0.5 | +7 | V |
| $I_{IK}$ | input clamping current | $V_I < –0.5$ V or $V_I > V_{CC} + 0.5$ V | - | ±20 | mA |
| $I_{OK}$ | output clamping current | $V_O < –0.5$ V or $V_O > V_{CC} + 0.5$ V | - | ±20 | mA |
| $I_O$ | output current | $V_O = –0.5$ V to $(V_{CC} + 0.5$ V) | - | ±25 | mA |
| $I_{CC}$ | supply current | | - | +50 | mA |
| $I_{GND}$ | ground current | | –50 | - | mA |
| $T_{stg}$ | storage temperature | | –65 | +150 | °C |
| $P_{tot}$ | total power dissipation | SO16, SSOP16 and TSSOP16 packages [1] | - | 500 | mW |

[1] For SO16 package: $P_{tot}$ derates linearly with 8 mW/K above 70 °C.
For SSOP16 and TSSOP16 packages: $P_{tot}$ derates linearly with 5.5 mW/K above 60 °C.

# 8. Recommended operating conditions

**Table 5. Recommended operating conditions**

*Voltages are referenced to GND (ground = 0 V)*

| Symbol | Parameter | Conditions | 74HC597 | | | 74HCT597 | | | Unit |
|---|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | Min | Typ | Max | |
| $V_{CC}$ | supply voltage | | 2.0 | 5.0 | 6.0 | 4.5 | 5.0 | 5.5 | V |
| $V_I$ | input voltage | | 0 | - | $V_{CC}$ | 0 | - | $V_{CC}$ | V |
| $V_O$ | output voltage | | 0 | - | $V_{CC}$ | 0 | - | $V_{CC}$ | V |
| $T_{amb}$ | ambient temperature | | –40 | +25 | +125 | –40 | +25 | +125 | °C |
| $\Delta t/\Delta V$ | input transition rise and fall rate | $V_{CC} = 2.0$ V | - | - | 625 | - | - | - | ns/V |
| | | $V_{CC} = 4.5$ V | - | 1.67 | 139 | - | 1.67 | 139 | ns/V |
| | | $V_{CC} = 6.0$ V | - | - | 83 | - | - | - | ns/V |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

## 9. Static characteristics

**Table 6. Static characteristics**

*At recommended operating conditions; voltages are referenced to GND (ground = 0 V).*

| Symbol | Parameter | Conditions | 25 °C | | | –40 °C to +85 °C | | –40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | Min | Max | Min | Max | |
| **74HC597** | | | | | | | | | | |
| $V_{IH}$ | HIGH-level input voltage | $V_{CC}$ = 2.0 V | 1.5 | 1.2 | - | 1.5 | - | 1.5 | - | V |
| | | $V_{CC}$ = 4.5 V | 3.15 | 2.4 | - | 3.15 | - | 3.15 | - | V |
| | | $V_{CC}$ = 6.0 V | 4.2 | 3.2 | - | 4.2 | - | 4.2 | - | V |
| $V_{IL}$ | LOW-level input voltage | $V_{CC}$ = 2.0 V | - | 0.8 | 0.5 | - | 0.5 | - | 0.5 | V |
| | | $V_{CC}$ = 4.5 V | - | 2.1 | 1.35 | - | 1.35 | - | 1.35 | V |
| | | $V_{CC}$ = 6.0 V | - | 2.8 | 1.8 | - | 1.8 | - | 1.8 | V |
| $V_{OH}$ | HIGH-level output voltage | $V_I$ = $V_{IH}$ or $V_{IL}$ | | | | | | | | |
| | | $I_O$ = –20 μA; $V_{CC}$ = 2.0 V | 1.9 | 2.0 | - | 1.9 | - | 1.9 | - | V |
| | | $I_O$ = –20 μA; $V_{CC}$ = 4.5 V | 4.4 | 4.5 | - | 4.4 | - | 4.4 | - | V |
| | | $I_O$ = –20 μA; $V_{CC}$ = 6.0 V | 5.9 | 6.0 | - | 5.9 | - | 5.9 | - | V |
| | | $I_O$ = –4.0 mA; $V_{CC}$ = 4.5 V | 3.98 | 4.32 | - | 3.84 | - | 3.7 | - | V |
| | | $I_O$ = –5.2 mA; $V_{CC}$ = 6.0 V | 5.48 | 5.81 | - | 5.34 | - | 5.2 | - | V |
| $V_{OL}$ | LOW-level output voltage | $V_I$ = $V_{IH}$ or $V_{IL}$ | | | | | | | | |
| | | $I_O$ = 20 μA; $V_{CC}$ = 2.0 V | - | 0 | 0.1 | - | 0.1 | - | 0.1 | V |
| | | $I_O$ = 20 μA; $V_{CC}$ = 4.5 V | - | 0 | 0.1 | - | 0.1 | - | 0.1 | V |
| | | $I_O$ = 20 μA; $V_{CC}$ = 6.0 V | - | 0 | 0.1 | - | 0.1 | - | 0.1 | V |
| | | $I_O$ = 4.0 mA; $V_{CC}$ = 4.5 V | - | 0.15 | 0.26 | - | 0.33 | - | 0.4 | V |
| | | $I_O$ = 5.2 mA; $V_{CC}$ = 6.0 V | - | 0.16 | 0.26 | - | 0.33 | - | 0.4 | V |
| $I_I$ | input leakage current | $V_I$ = $V_{CC}$ or GND; $V_{CC}$ = 6.0 V | - | - | ±0.1 | - | ±1.0 | - | ±1.0 | μA |
| $I_{CC}$ | supply current | $V_I$ = $V_{CC}$ or GND; $I_O$ = 0 A; $V_{CC}$ = 6.0 V | - | - | 8.0 | - | 80.0 | - | 160.0 | μA |
| $C_I$ | input capacitance | | - | 3.5 | - | - | - | - | - | pF |
| **74HCT597** | | | | | | | | | | |
| $V_{IH}$ | HIGH-level input voltage | $V_{CC}$ = 4.5 V to 5.5 V | 2.0 | 1.6 | - | 2.0 | - | 2.0 | - | V |
| $V_{IL}$ | LOW-level input voltage | $V_{CC}$ = 4.5 V to 5.5 V | - | 1.2 | 0.8 | - | 0.8 | - | 0.8 | V |
| $V_{OH}$ | HIGH-level output voltage | $V_I$ = $V_{IH}$ or $V_{IL}$; $V_{CC}$ = 4.5 V | | | | | | | | |
| | | $I_O$ = –20 μA | 4.4 | 4.5 | - | 4.4 | - | 4.4 | - | V |
| | | $I_O$ = –4.0 mA | 3.98 | 4.32 | - | 3.84 | - | 3.7 | - | V |
| $V_{OL}$ | LOW-level output voltage | $V_I$ = $V_{IH}$ or $V_{IL}$; $V_{CC}$ = 4.5 V | | | | | | | | |
| | | $I_O$ = 20 μA | - | 0 | 0.1 | - | 0.1 | - | 0.1 | V |
| | | $I_O$ = 4.0 mA | - | 0.15 | 0.26 | - | 0.33 | - | 0.4 | V |
| $I_I$ | input leakage current | $V_I$ = $V_{CC}$ or GND; $V_{CC}$ = 5.5 V | - | - | ±0.1 | - | ±1.0 | - | ±1.0 | μA |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

**Table 6. Static characteristics** *…continued*

*At recommended operating conditions; voltages are referenced to GND (ground = 0 V).*

| Symbol | Parameter | Conditions | 25 °C | | | –40 °C to +85 °C | | –40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | Min | Max | Min | Max | |
| $I_{CC}$ | supply current | $V_I = V_{CC}$ or GND; $I_O = 0$ A; $V_{CC} = 5.5$ V | - | - | 8.0 | - | 80.0 | - | 160.0 | µA |
| $\Delta I_{CC}$ | additional supply current | $V_I = V_{CC} - 2.1$ V; other inputs at $V_{CC}$ or GND; $V_{CC} = 4.5$ V to 5.5 V; $I_O = 0$ A | | | | | | | | |
| | | per input pin; DS input | - | 25 | 90 | - | 112.5 | - | 122.5 | µA |
| | | per input pin; Dn inputs | - | 30 | 108 | - | 135 | - | 147 | µA |
| | | per input pin; $\overline{PL}$, $\overline{MR}$ inputs | - | 150 | 540 | - | 675 | - | 735 | µA |
| | | per input pin; STCP, SHCP inputs | - | 150 | 540 | - | 675 | - | 735 | µA |
| $C_I$ | input capacitance | | - | 3.5 | - | - | - | - | - | pF |

## 10. Dynamic characteristics

**Table 7. Dynamic characteristics**

*Voltages are referenced to GND (ground = 0 V); $C_L = 50$ pF unless otherwise specified; for test circuit, see Figure 13.*

| Symbol | Parameter | Conditions | 25 °C | | | –40 °C to +85 °C | | –40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | Min | Max | Min | Max | |
| **74HC597** | | | | | | | | | | |
| $t_{pd}$ | propagation delay | SHCP to Q; see Figure 7 [1] | | | | | | | | |
| | | $V_{CC} = 2.0$ V | - | 55 | 175 | - | 220 | - | 265 | ns |
| | | $V_{CC} = 4.5$ V | - | 20 | 35 | - | 44 | - | 53 | ns |
| | | $V_{CC} = 5.0$ V; $C_L = 15$ pF | - | 17 | - | - | - | - | - | ns |
| | | $V_{CC} = 6.0$ V | - | 16 | 30 | - | 37 | - | 45 | ns |
| | | $\overline{MR}$ to Q; see Figure 8 [1] | | | | | | | | |
| | | $V_{CC} = 2.0$ V | - | 58 | 175 | - | 220 | - | 265 | ns |
| | | $V_{CC} = 4.5$ V | - | 21 | 35 | - | 44 | - | 53 | ns |
| | | $V_{CC} = 6.0$ V | - | 17 | 30 | - | 37 | - | 45 | ns |
| | | STCP to Q; see Figure 7 [1] | | | | | | | | |
| | | $V_{CC} = 2.0$ V | - | 80 | 250 | - | 315 | - | 375 | ns |
| | | $V_{CC} = 4.5$ V | - | 29 | 50 | - | 63 | - | 75 | ns |
| | | $V_{CC} = 5.0$ V; $C_L = 15$ pF | - | 25 | - | - | - | - | - | ns |
| | | $V_{CC} = 6.0$ V | - | 23 | 43 | - | 54 | - | 64 | ns |
| | | $\overline{PL}$ to Q; see Figure 9 [1] | | | | | | | | |
| | | $V_{CC} = 2.0$ V | - | 69 | 215 | - | 270 | - | 325 | ns |
| | | $V_{CC} = 4.5$ V | - | 25 | 43 | - | 54 | - | 65 | ns |
| | | $V_{CC} = 5.0$ V; $C_L = 15$ pF | - | 21 | - | - | - | - | - | ns |
| | | $V_{CC} = 6.0$ V | - | 20 | 37 | - | 46 | - | 55 | ns |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

**Table 7. Dynamic characteristics** *...continued*

*Voltages are referenced to GND (ground = 0 V); $C_L$ = 50 pF unless otherwise specified; for test circuit, see Figure 13.*

| Symbol | Parameter | Conditions | 25 °C | | | –40 °C to +85 °C | | –40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | Min | Max | Min | Max | |
| $t_t$ | transition time | see Figure 9 [2] | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | - | 19 | 75 | - | 95 | - | 110 | ns |
| | | $V_{CC}$ = 4.5 V | - | 7 | 15 | - | 19 | - | 22 | ns |
| | | $V_{CC}$ = 6.0 V | - | 6 | 13 | - | 16 | - | 19 | ns |
| $t_W$ | pulse width | STCP HIGH or LOW; see Figure 7 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 80 | 11 | - | 100 | - | 120 | - | ns |
| | | $V_{CC}$ = 4.5 V | 16 | 4 | - | 20 | - | 24 | - | ns |
| | | $V_{CC}$ = 6.0 V | 14 | 3 | - | 17 | - | 20 | - | ns |
| | | SHCP HIGH or LOW; see Figure 7 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 80 | 14 | - | 100 | - | 120 | - | ns |
| | | $V_{CC}$ = 4.5 V | 16 | 5 | - | 20 | - | 24 | - | ns |
| | | $V_{CC}$ = 6.0 V | 14 | 4 | - | 17 | - | 20 | - | ns |
| | | $\overline{MR}$ LOW; see Figure 8 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 80 | 22 | - | 100 | - | 120 | - | ns |
| | | $V_{CC}$ = 4.5 V | 16 | 8 | - | 20 | - | 24 | - | ns |
| | | $V_{CC}$ = 6.0 V | 14 | 6 | - | 17 | - | 20 | - | ns |
| | | $\overline{PL}$ LOW; see Figure 9 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 80 | 22 | - | 100 | - | 120 | - | ns |
| | | $V_{CC}$ = 4.5 V | 16 | 8 | - | 20 | - | 24 | - | ns |
| | | $V_{CC}$ = 6.0 V | 14 | 6 | - | 17 | - | 20 | - | ns |
| $t_{rec}$ | recovery time | $\overline{MR}$ to SHCP; see Figure 10 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 60 | –3 | - | 75 | - | 90 | - | ns |
| | | $V_{CC}$ = 4.5 V | 12 | –1 | - | 15 | - | 18 | - | ns |
| | | $V_{CC}$ = 6.0 V | 10 | –1 | - | 13 | - | 15 | - | ns |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

**Table 7. Dynamic characteristics** *...continued*

*Voltages are referenced to GND (ground = 0 V); $C_L$ = 50 pF unless otherwise specified; for test circuit, see Figure 13.*

| Symbol | Parameter | Conditions | 25 °C | | | –40 °C to +85 °C | | –40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | Min | Max | Min | Max | |
| $t_{su}$ | set-up time | Dn to STCP; see Figure 11 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 60 | 8 | - | 75 | - | 90 | - | ns |
| | | $V_{CC}$ = 4.5 V | 12 | 3 | - | 15 | - | 18 | - | ns |
| | | $V_{CC}$ = 6.0 V | 10 | 2 | - | 13 | - | 15 | - | ns |
| | | DS to SHCP; see Figure 11 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 60 | 11 | - | 75 | - | 90 | - | ns |
| | | $V_{CC}$ = 4.5 V | 12 | 4 | - | 15 | - | 18 | - | ns |
| | | $V_{CC}$ = 6.0 V | 10 | 3 | - | 13 | - | 15 | - | ns |
| | | $\overline{PL}$ to SHCP; see Figure 12 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 60 | 11 | - | 75 | - | 90 | - | ns |
| | | $V_{CC}$ = 4.5 V | 12 | 4 | - | 15 | - | 18 | - | ns |
| | | $V_{CC}$ = 6.0 V | 10 | 3 | - | 13 | - | 15 | - | ns |
| $t_h$ | hold time | Dn to STCP; see Figure 11 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 5 | –3 | - | 5 | - | 5 | - | ns |
| | | $V_{CC}$ = 4.5 V | 5 | –1 | - | 5 | - | 5 | - | ns |
| | | $V_{CC}$ = 6.0 V | 5 | –1 | - | 5 | - | 5 | - | ns |
| | | $\overline{PL}$, DS to SHCP; see Figure 11 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 5 | –6 | - | 5 | - | 5 | - | ns |
| | | $V_{CC}$ = 4.5 V | 5 | –2 | - | 5 | - | 5 | - | ns |
| | | $V_{CC}$ = 6.0 V | 5 | –2 | - | 5 | - | 5 | - | ns |
| $f_{max}$ | maximum frequency | SHCP; see Figure 7 | | | | | | | | |
| | | $V_{CC}$ = 2.0 V | 6.0 | 29 | - | 4.8 | - | 4.0 | - | MHz |
| | | $V_{CC}$ = 4.5 V | 30 | 87 | - | 24 | - | 20 | - | MHz |
| | | $V_{CC}$ = 5.0 V; $C_L$ = 15 pF | - | 96 | - | - | - | - | - | MHz |
| | | $V_{CC}$ = 6.0 V | 35 | 104 | - | 28 | - | 24 | - | MHz |
| $C_{PD}$ | power dissipation capacitance | $C_L$ = 50 pF; f = 1 MHz; $V_I$ = GND to $V_{CC}$ [3] | - | 29 | - | - | - | - | - | pF |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

**Table 7. Dynamic characteristics** *...continued*

*Voltages are referenced to GND (ground = 0 V); $C_L$ = 50 pF unless otherwise specified; for test circuit, see Figure 13.*

| Symbol | Parameter | Conditions | 25 °C | | | –40 °C to +85 °C | | –40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | Min | Max | Min | Max | |
| **74HCT597** | | | | | | | | | | |
| $t_{pd}$ | propagation delay | SHCP to Q; see Figure 7 [1] | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | - | 23 | 40 | - | 50 | - | 60 | ns |
| | | $V_{CC}$ = 5.0 V; $C_L$ = 15 pF | - | 20 | - | - | - | - | - | ns |
| | | $\overline{MR}$ to Q; see Figure 8 [1] | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | - | 28 | 49 | - | 61 | - | 74 | ns |
| | | STCP to Q; see Figure 7 [1] | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | - | 33 | 57 | - | 71 | - | 86 | ns |
| | | $V_{CC}$ = 5.0 V; $C_L$ = 15 pF | - | 29 | - | - | - | - | - | ns |
| | | $\overline{PL}$ to Q; see Figure 9 [1] | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | - | 30 | 52 | - | 65 | - | 78 | ns |
| | | $V_{CC}$ = 5.0 V; $C_L$ = 15 pF | - | 26 | - | - | - | - | - | ns |
| $t_t$ | transition time | see Figure 7 [2] | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | - | 7 | 15 | - | 19 | - | 22 | ns |
| $t_W$ | pulse width | STCP HIGH or LOW; see Figure 7 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 16 | 6 | - | 20 | - | 24 | - | ns |
| | | SHCP HIGH or LOW; see Figure 7 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 16 | 7 | - | 20 | - | 24 | - | ns |
| | | $\overline{MR}$ LOW; see Figure 8 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 25 | 14 | - | 31 | - | 38 | - | ns |
| | | $\overline{PL}$ LOW; see Figure 9 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 20 | 10 | - | 25 | - | 30 | - | ns |
| $t_{rec}$ | recovery time | $\overline{MR}$ to SHCP; see Figure 10 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 12 | –2 | - | 15 | - | 18 | - | ns |
| $t_{su}$ | set-up time | Dn to STCP; see Figure 11 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 12 | 5 | - | 15 | - | 18 | - | ns |
| | | DS to SHCP; see Figure 11 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 12 | 2 | - | 15 | - | 18 | - | ns |
| | | $\overline{PL}$ to SHCP; see Figure 12 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 12 | 4 | - | 15 | - | 18 | - | ns |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

**Table 7. Dynamic characteristics** *...continued*

*Voltages are referenced to GND (ground = 0 V); $C_L$ = 50 pF unless otherwise specified; for test circuit, see Figure 13.*

| Symbol | Parameter | Conditions | 25 °C | | | –40 °C to +85 °C | | –40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | Min | Max | Min | Max | |
| $t_h$ | hold time | Dn to STCP; see Figure 11 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 5 | –1 | - | 5 | - | 5 | - | ns |
| | | $\overline{PL}$, DS to SHCP; see Figure 11 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 5 | –2 | - | 5 | - | 5 | - | ns |
| $f_{max}$ | maximum frequency | SHCP; see Figure 7 | | | | | | | | |
| | | $V_{CC}$ = 4.5 V | 30 | 75 | - | 24 | - | 20 | - | MHz |
| | | $V_{CC}$ = 5.0 V; $C_L$ = 15 pF | - | 83 | - | - | - | - | - | MHz |
| $C_{PD}$ | power dissipation capacitance | $C_L$ = 50 pF; f = 1 MHz; $V_I$ = GND to $V_{CC}$ – 1.5 V [3] | - | 32 | - | - | - | - | - | pF |

[1] $t_{pd}$ is the same as $t_{PLH}$ and $t_{PHL}$.

[2] $t_t$ is the same as $t_{THL}$ and $t_{TLH}$.

[3] $C_{PD}$ is used to determine the dynamic power dissipation ($P_D$ in μW).
$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:
$f_i$ = input frequency in MHz;
$f_o$ = output frequency in MHz;
$C_L$ = output load capacitance in pF;
$V_{CC}$ = supply voltage in V;
N = number of inputs switching;
$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.

## 11. Waveforms




Measurement points are given in Table 8.

$V_{OL}$ and $V_{OH}$ are typical voltage output levels that occur with the output load.

**Fig 7. Shift clock and storage clock inputs to output, propagation delays, pulse widths and maximum clock frequency**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




Measurement points are given in Table 8.

$V_{OL}$ and $V_{OH}$ are typical voltage output levels that occur with the output load.

**Fig 8. input ($\overline{MR}$) to (Q), output propagation delays and ($\overline{MR}$) pulse width**




Measurement points are given in Table 8.

$V_{OL}$ and $V_{OH}$ are typical voltage output levels that occur with the output load.

**Fig 9. Input ($\overline{PL}$) to (Q), output propagation delays, $\overline{PL}$ pulse width and output transition times**




Measurement points are given in Table 8.

**Fig 10. Input ($\overline{MR}$) to shift clock (SHCP) and storage clock (STCP) recovery times**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




Measurement points are given in Table 8.

**Fig 11. Hold and set-up times for (DS), (Dn) inputs to (SHCP), (STCP) inputs**




Measurement points are given in Table 8.

**Fig 12. Set-up times for ($\overline{PL}$) input to (SHCP) input**

**Table 8. Measurement points**

| Type | Input | | Output |
|---|---|---|---|
| | $V_M$ | $V_I$ | $V_M$ |
| 74HC597 | $0.5 \times V_{CC}$ | GND to $V_{CC}$ | $0.5 \times V_{CC}$ |
| 74HCT597 | 1.3 V | GND to 3 V | 1.3 V |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




Test data is given in Table 9.

Definitions test circuit:

$R_T$ = Termination resistance should be equal to output impedance $Z_o$ of the pulse generator.

$C_L$ = Load capacitance including jig and probe capacitance.

$R_L$ = Load resistance.

S1 = Test selection switch.

**Fig 13. Test circuit for measuring switching times**

**Table 9. Test data**

| Type | Input | | Load | | S1 position | | |
|---|---|---|---|---|---|---|---|
| | $V_I$ | $t_r$, $t_f$ | $C_L$ | $R_L$ | $t_{PHL}$, $t_{PLH}$ | $t_{PZH}$, $t_{PHZ}$ | $t_{PZL}$, $t_{PLZ}$ |
| 74HC597 | $V_{CC}$ | 6 ns | 15 pF, 50 pF | 1 kΩ | open | GND | $V_{CC}$ |
| 74HCT597 | 3 V | 6 ns | 15 pF, 50 pF | 1 kΩ | open | GND | $V_{CC}$ |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

## 12. Package outline

**SO16: plastic small outline package; 16 leads; body width 3.9 mm** **SOT109-1**




**DIMENSIONS (inch dimensions are derived from the original mm dimensions)**

| UNIT | A max. | $A_1$ | $A_2$ | $A_3$ | $b_p$ | c | $D^{(1)}$ | $E^{(1)}$ | e | $H_E$ | L | $L_p$ | Q | v | w | y | $Z^{(1)}$ | θ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | 1.75 | 0.25<br>0.10 | 1.45<br>1.25 | 0.25 | 0.49<br>0.36 | 0.25<br>0.19 | 10.0<br>9.8 | 4.0<br>3.8 | 1.27 | 6.2<br>5.8 | 1.05 | 1.0<br>0.4 | 0.7<br>0.6 | 0.25 | 0.25 | 0.1 | 0.7<br>0.3 | $8^o$<br>$0^o$ |
| inches | 0.069 | 0.010<br>0.004 | 0.057<br>0.049 | 0.01 | 0.019<br>0.014 | 0.0100<br>0.0075 | 0.39<br>0.38 | 0.16<br>0.15 | 0.05 | 0.244<br>0.228 | 0.041 | 0.039<br>0.016 | 0.028<br>0.020 | 0.01 | 0.01 | 0.004 | 0.028<br>0.012 | |

**Note**

1. Plastic or metal protrusions of 0.15 mm (0.006 inch) maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|---|---|---|---|---|---|---|
| | IEC | JEDEC | JEITA | | | |
| SOT109-1 | 076E07 | MS-012 | | | | ~~99-12-27~~<br>03-02-19 |

**Fig 14. Package outline SOT109-1 (SO16)**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

**SSOP16: plastic shrink small outline package; 16 leads; body width 5.3 mm** **SOT338-1**




**DIMENSIONS (mm are the original dimensions)**

| UNIT | A max. | $A_1$ | $A_2$ | $A_3$ | $b_p$ | c | D (1) | E (1) | e | $H_E$ | L | $L_p$ | Q | v | w | y | Z (1) | θ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | 2 | 0.21<br>0.05 | 1.80<br>1.65 | 0.25 | 0.38<br>0.25 | 0.20<br>0.09 | 6.4<br>6.0 | 5.4<br>5.2 | 0.65 | 7.9<br>7.6 | 1.25 | 1.03<br>0.63 | 0.9<br>0.7 | 0.2 | 0.13 | 0.1 | 1.00<br>0.55 | 8°<br>0° |

**Note**

1. Plastic or metal protrusions of 0.25 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|---|---|---|---|---|---|---|
| | IEC | JEDEC | JEITA | | | |
| SOT338-1 | | MO-150 | | | | ~~99-12-27~~<br>03-02-19 |

**Fig 15. Package outline SOT338-1 (SSOP16)**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

**TSSOP16: plastic thin shrink small outline package; 16 leads; body width 4.4 mm** **SOT403-1**




**DIMENSIONS (mm are the original dimensions)**

| UNIT | A max. | $A_1$ | $A_2$ | $A_3$ | $b_p$ | c | D (1) | E (2) | e | $H_E$ | L | $L_p$ | Q | v | w | y | Z (1) | θ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | 1.1 | 0.15<br>0.05 | 0.95<br>0.80 | 0.25 | 0.30<br>0.19 | 0.2<br>0.1 | 5.1<br>4.9 | 4.5<br>4.3 | 0.65 | 6.6<br>6.2 | 1 | 0.75<br>0.50 | 0.4<br>0.3 | 0.2 | 0.13 | 0.1 | 0.40<br>0.06 | 8°<br>0° |

**Notes**

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.
2. Plastic interlead protrusions of 0.25 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|---|---|---|---|---|---|---|
| | IEC | JEDEC | JEITA | | | |
| SOT403-1 | | MO-153 | | | | ~~99-12-27~~<br>03-02-18 |

**Fig 16. Package outline SOT403-1 (TSSOP16)**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

## 13. Abbreviations

**Table 10. Abbreviations**

| Acronym | Description |
|---|---|
| CMOS | Complementary Metal Oxide Semiconductor |
| DUT | Device Under Test |
| ESD | ElectroStatic Discharge |
| HBM | Human Body Model |
| MM | Machine Model |
| TTL | Transistor-Transistor Logic |

## 14. Revision history

**Table 11. Revision history**

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|---|---|---|---|---|
| 74HC_HCT597 v.4 | 20160225 | Product data sheet | - | 74HC_HCT597 v.3 |
| Modifications: | • Type numbers 74HC597N and 74HCT597N (SOT38-4) removed. | | | |
| 74HC_HCT597 v.3 | 20140415 | Product data sheet | - | 74HC_HCT597_CNV v.2 |
| Modifications: | • The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors.<br>• Legal texts have been adapted to the new company name where appropriate. | | | |
| 74HC_HCT597_CNV v.2 | 19901201 | Product specification | - | - |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

# 15. Legal information

## 15.1 Data sheet status

| Document status[1][2] | Product status[3] | Definition |
|---|---|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nexperia.com.

## 15.2 Definitions

**Draft —** The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet —** A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification —** The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

## 15.3 Disclaimers

**Limited warranty and liability —** Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

**Right to make changes —** Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use —** Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications —** Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

**Limiting values —** Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale —** Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nexperia.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

**No offer to sell or license —** Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

**Export control —** This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Non-automotive qualified products —** Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

**Translations —** A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

### 15.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 16. Contact information

For more information, please visit: **http://www.nexperia.com**

For sales office addresses, please send an email to: **salesaddresses@nexperia.com**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

## 17. Contents


**1 General description . . . . . 1**
**2 Features and benefits . . . . . 1**
**3 Ordering information . . . . . 1**
**4 Functional diagram . . . . . 2**
**5 Pinning information . . . . . 4**
5.1 Pinning . . . . . 4
5.2 Pin description . . . . . 4
**6 Functional description . . . . . 5**
**7 Limiting values . . . . . 6**
**8 Recommended operating conditions . . . . . 6**
**9 Static characteristics . . . . . 7**
**10 Dynamic characteristics . . . . . 8**
**11 Waveforms . . . . . 12**
**12 Package outline . . . . . 16**
**13 Abbreviations . . . . . 19**
**14 Revision history . . . . . 19**
**15 Legal information . . . . . 20**
15.1 Data sheet status . . . . . 20
15.2 Definitions . . . . . 20
15.3 Disclaimers . . . . . 20
15.4 Trademarks . . . . . 21
**16 Contact information . . . . . 21**
**17 Contents . . . . . 22**


© **Nexperia B.V. 2017. All rights reserved**

For more information, please visit: http://www.nexperia.com
For sales office addresses, please send an email to: salesaddresses@nexperia.com
**Date of release: 25 February 2016**

LifeElectronics
Живое партнерство

**ООО «ЛайфЭлектроникс»** **“LifeElectronics” LLC**

*ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703*

*Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.*

*С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров*

*Мы предлагаем:*

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

*В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.*

*Конструкторский отдел помогает осуществить:*

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

*Тел: +7 (812) 336 43 04 (многоканальный)*
*Email: org@lifeelectronics.ru*

***www.lifeelectronics.ru***