DDTD (LO-R1) U

NPN PRE-BIASED 500 mA SURFACE MOUNT TRANSISTOR

Features

- Epitaxial Planar Die Construction
- Complementary PNP Types Available (DDTB)
- Built-In Biasing Resistors
- **Lead Free/RoHS Compliant (Note 2)**
- **"Green" Device, Note 3 and 4**

Mechanical Data

- Case: SOT-323
- Case Material: Molded Plastic, "Green" Molding Compound, Note 4. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Marking Information: See Table Below & Page 3
- Ordering Information: See Page 3
- Weight: 0.006 grams (approximate)



SOT-323		
Dim	**Min**	**Max**
A	0.25	0.40
B	1.15	1.35
C	2.00	2.20
D	0.65 Nominal	
E	0.30	0.40
G	1.20	1.40
H	1.80	2.20
J	0.0	0.10
K	0.90	1.00
L	0.25	0.40
M	0.10	0.18
α	0°	8°
All Dimensions in mm		

P/N	R1 (NOM)	R2 (NOM)	MARKING
DDTD122LU	0.22KΩ	10KΩ	N75
DDTD142JU	0.47KΩ	10KΩ	N76
DDTD122TU	0.22KΩ	OPEN	N77
DDTD142TU	0.47KΩ	OPEN	N78



Schematic and Pin Configuration

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Value	Unit
Supply Voltage, (3) to (2)		V_{CC}	50	V
Input Voltage, (1) to (2)	DDTD122LU DDTD142JU	V_{IN}	-5 to +6 -5 to +6	V
Input Voltage, (2) to (1)	DDTD122TU DDTD142TU	$V_{EBO\ (MAX)}$	5	V
Output Current	All	I_C	500	mA
Power Dissipation	(Note 1)	P_d	200	mW
Thermal Resistance, Junction to Ambient Air	(Note 1)	$R_{\theta JA}$	625	°C/W
Operating and Storage Temperature Range		T_j, T_{STG}	-55 to +150	°C

Notes:
1. Mounted on FR4 PC Board with recommended pad layout at http://www.diodes.com/datasheets/ap02001.pdf.
2. No purposefully added lead.
3. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
4. Product manufactured with Date Code 0627 (week 27, 2006) and newer are built with Green Molding Compound. Product manufactured prior to Date Code 0627 are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.

© Diodes Incorporated

Electrical Characteristics @T_A = 25°C unless otherwise specified — R1, R2 Types

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
Input Voltage	DDTD122LU DDTD142JU	$V_{I(off)}$	0.3 0.3	—	—	V	V_{CC} = 5V, I_O = 100μA
	DDTD122LU DDTD142JU	$V_{I(on)}$	—	—	2.0 2.0	V	V_O = 0.3V, I_O = 20mA V_O = 0.3V, I_O = 20mA
Output Voltage		$V_{O(on)}$	—	—	0.3V	V	I_O/I_I = 50mA/2.5mA
Input Current	DDTD122LU DDTD142JU	I_I	—	—	28 13	mA	V_I = 5V
Output Current		$I_{O(off)}$	—	—	0.5	μA	V_{CC} = 50V, V_I = 0V
DC Current Gain	DDTD122LU DDTD142JU	G_I	56 56	—	—	—	V_O = 5V, I_O = 50mA
Gain-Bandwidth Product*		f_T	—	200	—	MHz	V_{CE} = 10V, I_E = 5mA, f = 100MHz

* Transistor - For Reference Only

Electrical Characteristics @T_A = 25°C unless otherwise specified — R1-Only, R2-Only Types

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
Collector-Base Breakdown Voltage		BV_{CBO}	50	—	—	V	I_C = 50μA
Collector-Emitter Breakdown Voltage		BV_{CEO}	40	—	—	V	I_C = 1mA
Emitter-Base Breakdown Voltage	DDTD122TU DDTD142TU	BV_{EBO}	5	—	—	V	I_E = 50μA I_E = 50μA
Collector Cutoff Current		I_{CBO}	—	—	0.5	μA	V_{CB} = 50V
Emitter Cutoff Current	DDTD122TU DDTD142TU	I_{EBO}	— —	—	0.5 0.5	μA	V_{EB} = 4V
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	—	—	0.3	V	I_C = 50mA, I_B = 2.5mA
DC Current Transfer Ratio	DDTD122TU DDTD142TU	h_{FE}	100 100	250 250	600 600	—	I_C = 5mA, V_{CE} = 5V
Gain-Bandwidth Product*		f_T	—	200	—	MHz	V_{CE} = 10V, I_E = -5mA, f = 100MHz

* Transistor - For Reference Only

© Diodes Incorporated



Fig. 1 Power Derating Curve

Ordering Information (Note 4 & 5)

Device	Packaging	Shipping
DDTD122LU-7-F	SOT-323	3000/Tape & Reel
DDTD142JU-7-F	SOT-323	3000/Tape & Reel
DDTD122TU-7-F	SOT-323	3000/Tape & Reel
DDTD142TU-7-F	SOT-323	3000/Tape & Reel

Notes: 5. For packaging details, go to our website at http://www.diodes.com/datasheets/ap02007.pdf.

Marking Information



NXX = Product Type Marking Code
See Page 1 Table
YM = Date Code Marking
Y = Year ex: T = 2006
M = Month ex: 9 = September

Date Code Key

Year	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012
Code	N	P	R	S	T	U	V	W	X	Y	Z

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

© Diodes Incorporated

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru