

74LVT16240A

3.3 V 16-bit inverting buffer/driver; 3-state

Rev. 4 — 1 October 2018

Product data sheet

1. General description

The 74LVT16240A is a high-performance BiCMOS product designed for V_{CC} operation at 3.3 V.

This device is an inverting 16-bit buffer that is ideal for driving bus lines. The device features four output enable inputs (1OE, 2OE, 3OE, 4OE), each controlling four of the 3-state outputs.

2. Features and benefits

- 16-bit bus interface
- 3-state buffers
- Output capability: +64 mA/-32 mA
- TTL input and output switching levels
- Input and output interface capability to systems at 5 V supply
- Bus-hold data inputs eliminate the need for external pull-up resistors to hold unused inputs
- Live insertion/extraction permitted
- Power-up 3-state
- No bus current loading when output is tied to 5 V bus
- Latch-up protection:
 - JESD78B Class II exceeds 500 mA
- ESD protection:
 - HBM: JESD22-A114F exceeds 2000 V
 - MM: JESD22-A115-A exceeds 200 V

3. Ordering information

Table 1. Ordering information

| Type number | Package | | | |
|----------------|-------------------|---------|------------------------------------------------------------------------|----------|
| | Temperature range | Name | Description | Version |
| 74LVT16240ADGG | -40 °C to +85 °C | TSSOP48 | plastic thin shrink small outline package; 48 leads; body width 6.1 mm | SOT362-1 |

4. Functional diagram




Fig. 1. Logic symbol

Fig. 2. IEC logic symbol

5. Pinning information

5.1. Pinning




Fig. 3. Pin configuration SOT362-1 (TSSOP48)

5.2. Pin description

Table 2. Pin description

| Symbol | Pin | Description |
|--------------------|-------------------------------|-----------------------------------|
| 1OE, 2OE, 3OE, 4OE | 1, 48, 25, 24 | output enable inputs (active LOW) |
| 1A0, 1A1, 1A2, 1A3 | 47, 46, 44, 43 | data inputs |
| 2A0, 2A1, 2A2, 2A3 | 41, 40, 38, 37 | data inputs |
| 3A0, 3A1, 3A2, 3A3 | 36, 35, 33, 32 | data inputs |
| 4A0, 4A1, 4A2, 4A3 | 30, 29, 27, 26 | data inputs |
| 1Y0, 1Y1, 1Y2, 1Y3 | 2, 3, 5, 6 | data outputs |
| 2Y0, 2Y1, 2Y2, 2Y3 | 8, 9, 11, 12 | data outputs |
| 3Y0, 3Y1, 3Y2, 3Y3 | 13, 14, 16, 17 | data outputs |
| 4Y0, 4Y1, 4Y2, 4Y3 | 19, 20, 22, 23 | data outputs |
| GND | 4, 10, 15, 21, 28, 34, 39, 45 | ground (0 V) |
| V _{CC} | 7, 18, 31, 42 | supply voltage |

6. Functional description

Table 3. Function table

H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

| Input | | Output |
|-------|-----|--------|
| nOE | nAn | nYn |
| L | L | H |
| L | H | L |
| H | X | Z |

7. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | Min | Max | Unit |
|------------------|-------------------------|-----------------------------------|----------|------|------|
| V _{CC} | supply voltage | | -0.5 | +4.6 | V |
| V _I | input voltage | | [1] -0.5 | +7.0 | V |
| V _O | output voltage | output in OFF-state or HIGH-state | [1] -0.5 | +7.0 | V |
| I _{IK} | input clamping current | V _I < 0 V | -50 | - | mA |
| I _{OK} | output clamping current | V _O < 0 V | -50 | - | mA |
| I _O | output current | output in LOW-state | - | 128 | mA |
| | | output in HIGH-state | -64 | - | mA |
| T _{stg} | storage temperature | | -65 | +150 | °C |
| T _j | junction temperature | | [2] - | +150 | °C |

[1] The input and output negative voltage ratings may be exceeded if the input and output clamp current ratings are observed.

[2] The performance capability of a high-performance integrated circuit in conjunction with its thermal environment can create junction temperatures which are detrimental to reliability.

8. Recommended operating conditions

Table 5. Operating conditions

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---------------------|-------------------------------------|-----------------|-----|-----|-----|------|
| V_{CC} | supply voltage | | 2.7 | - | 3.6 | V |
| V_I | input voltage | | 0 | - | 5.5 | V |
| T_{amb} | ambient temperature | in free air | -40 | - | +85 | °C |
| $\Delta t/\Delta V$ | input transition rise and fall rate | outputs enabled | - | - | 10 | ns/V |

9. Static characteristics

Table 6. Static characteristics

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | Min | Typ[1] | Max | Unit |
|----------------|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------|----------------|-----------|---------------|---------------|
| V_{IK} | input clamping voltage | $V_{CC} = 2.7\text{ V}; I_{IK} = -18\text{ mA}$ | - | -0.85 | -1.2 | V |
| V_{IH} | HIGH-level input voltage | | 2.0 | - | - | V |
| V_{IL} | LOW-level input voltage | | - | - | 0.8 | V |
| V_{OH} | HIGH-level output voltage | $V_{CC} = 2.7\text{ V to }3.6\text{ V}; I_{OH} = -100\text{ }\mu\text{A}$ | $V_{CC} - 0.2$ | V_{CC} | - | V |
| | | $V_{CC} = 2.7\text{ V}; I_{OH} = -8\text{ mA}$ | 2.4 | 2.5 | - | V |
| | | $V_{CC} = 3.0\text{ V}; I_{OH} = -32\text{ mA}$ | 2.0 | 2.3 | - | V |
| V_{OL} | LOW-level output voltage | $V_{CC} = 2.7\text{ V}; I_{OL} = 100\text{ }\mu\text{A}$ | - | 0.07 | 0.2 | V |
| | | $V_{CC} = 2.7\text{ V}; I_{OL} = 24\text{ mA}$ | - | 0.3 | 0.5 | V |
| | | $V_{CC} = 3.0\text{ V}; I_{OL} = 16\text{ mA}$ | - | 0.25 | 0.4 | V |
| | | $V_{CC} = 3.0\text{ V}; I_{OL} = 32\text{ mA}$ | - | 0.3 | 0.5 | V |
| | | $V_{CC} = 3.0\text{ V}; I_{OL} = 64\text{ mA}$ | - | 0.4 | 0.55 | V |
| I_{OH} | HIGH-level output current | | - | - | -32 | mA |
| I_{OL} | LOW-level output current | | - | - | 32 | mA |
| | | current duty cycle $\leq 50\%$; $f \geq 1\text{ kHz}$ | - | - | 64 | mA |
| I_I | input leakage current | all input pins | | | | |
| | | $V_{CC} = 0\text{ V or }3.6\text{ V}; V_I = 5.5\text{ V}$ | - | 0.4 | 10 | μA |
| | | control pins | | | | |
| | | $V_{CC} = 3.6\text{ V}; V_I = V_{CC}\text{ or GND}$ | - | ± 0.1 | ± 1 | μA |
| | | data pins | | | | |
| | $V_{CC} = 3.6\text{ V}; V_I = V_{CC}$ [2] | - | 0.1 | 1 | μA | |
| | $V_{CC} = 3.6\text{ V}; V_I = 0\text{ V}$ [2] | - | -0.4 | -5 | μA | |
| I_{OFF} | power-off leakage current | $V_{CC} = 0\text{ V}; V_I\text{ or }V_O = 0\text{ V to }4.5\text{ V}$ | - | 0.1 | ± 100 | μA |
| I_{BHL} | bus hold LOW current | nAn input; $V_{CC} = 3\text{ V}; V_I = 0.8\text{ V}$ | 75 | 135 | - | μA |
| I_{BHH} | bus hold HIGH current | nAn input; $V_{CC} = 3\text{ V}; V_I = 2.0\text{ V}$ | -75 | -135 | - | μA |
| I_{BHLO} | bus hold LOW overdrive current | nAn input; $V_{CC} = 3.6\text{ V}; V_I = 0\text{ V to }3.6\text{ V}$ [3] | 500 | - | - | μA |
| I_{BHHO} | bus hold HIGH overdrive current | nAn input; $V_{CC} = 3.6\text{ V}; V_I = 0\text{ V to }3.6\text{ V}$ [3] | - | - | -500 | μA |
| I_{CEX} | output high leakage current | output in HIGH-state when $V_O > V_{CC}$; $V_O = 5.5\text{ V}; V_{CC} = 3.0\text{ V}$ | - | 50 | 125 | μA |
| $I_{O(pu/pd)}$ | power-up/power-down output current | $V_{CC} \leq 1.2\text{ V}; V_O = 0.5\text{ V to }V_{CC}$; $V_I = \text{GND or }V_{CC}$; nOE = don't care [4] | - | 1 | ± 100 | μA |

| Symbol | Parameter | Conditions | Min | Typ[1] | Max | Unit |
|------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------|-----|--------|------|------|
| I _{oZ} | OFF-state output current | V _{CC} = 3.6 V; V _I = V _{IL} or V _{IH} | | | | |
| | | output HIGH: V _O = 3.0 V | - | 0.5 | 5 | μA |
| | | output LOW: V _O = 0.5 V | - | 0.5 | -5 | μA |
| I _{CC} | supply current | V _{CC} = 3.6 V; V _I = GND or V _{CC} ; I _O = 0 A | | | | |
| | | outputs HIGH | - | 0.07 | 0.12 | mA |
| | | outputs LOW | - | 4.0 | 6 | mA |
| | | outputs disabled [5] | - | 0.07 | 0.12 | mA |
| ΔI _{CC} | additional supply current | per input pin; V _{CC} = 3 V to 3.6 V; one input at V _{CC} - 0.6 V and other inputs at V _{CC} or GND [6] | - | 0.1 | 0.2 | mA |
| C _I | input capacitance | n $\overline{O}E$; V _I = 0 V or 3 V | - | 3 | - | pF |
| C _O | output capacitance | Outputs disabled; V _O = 0 V or 3.0 V | - | 9 | - | pF |

[1] All typical values are at V_{CC} = 3.3 V and T_{amb} = 25 °C.

[2] Unused pins at V_{CC} or GND.

[3] This is the bus hold overdrive current required to force the input to the opposite logic state.

[4] This parameter is valid for any V_{CC} between 0 V and 1.2 V with a transition time of up to 10 ms. From V_{CC} = 1.2 V to V_{CC} = 3.3 V ± 0.3 V a transition time of 100 μs is permitted. This parameter is valid for T_{amb} = 25 °C only.

[5] Measured with outputs pulled up to V_{CC} or GND.

[6] This is the increase in supply current for each input at the specified voltage level other than V_{CC} or GND.

10. Dynamic characteristics

Table 7. Dynamic characteristics

At recommended operating conditions; voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 6.

| Symbol | Parameter | Conditions | Min | Typ[1] | Max | Unit |
|------------------|-------------------------------------|-----------------------------------------------------|-----|--------|-----|------|
| t _{PLH} | LOW to HIGH propagation delay | nAn to n \overline{Y} n; see Fig. 4 | | | | |
| | | V _{CC} = 2.7 V | - | - | 4.0 | ns |
| | | V _{CC} = 3.3 V ± 0.3 V | 0.5 | 1.8 | 3.2 | ns |
| t _{PHL} | HIGH to LOW propagation delay | nAn to n \overline{Y} n; see Fig. 4 | | | | |
| | | V _{CC} = 2.7 V | - | - | 4.0 | ns |
| | | V _{CC} = 3.3 V ± 0.3 V | 0.5 | 2.0 | 3.2 | ns |
| t _{PZH} | OFF-state to HIGH propagation delay | n $\overline{O}E$ to n \overline{Y} n; see Fig. 5 | | | | |
| | | V _{CC} = 2.7 V | - | - | 5.0 | ns |
| | | V _{CC} = 3.3 V ± 0.3 V | 1.0 | 2.3 | 4.0 | ns |
| t _{PZL} | OFF-state to LOW propagation delay | n $\overline{O}E$ to n \overline{Y} n; see Fig. 5 | | | | |
| | | V _{CC} = 2.7 V | - | - | 4.8 | ns |
| | | V _{CC} = 3.3 V ± 0.3 V | 1.0 | 2.1 | 4.4 | ns |
| t _{PHZ} | HIGH to OFF-state propagation delay | n $\overline{O}E$ to n \overline{Y} n; see Fig. 5 | | | | |
| | | V _{CC} = 2.7 V | - | - | 5.0 | ns |
| | | V _{CC} = 3.3 V ± 0.3 V | 1.0 | 3.2 | 4.5 | ns |
| t _{PLZ} | LOW to OFF-state propagation delay | n $\overline{O}E$ to n \overline{Y} n; see Fig. 5 | | | | |
| | | V _{CC} = 2.7 V | - | - | 4.8 | ns |
| | | V _{CC} = 3.3 V ± 0.3 V | 1.0 | 3.0 | 4.4 | ns |

[1] Typical values are at V_{CC} = 3.3 V and T_{amb} = 25 °C.

10.1. Waveforms and test circuit





Table 8. Measurement points

| Input | | Output | | |
|----------|-------|--------|------------------|------------------|
| V_{CC} | V_M | V_M | V_X | V_Y |
| 2.7 V | 1.5 V | 1.5 V | $V_{OL} + 0.3 V$ | $V_{OH} - 0.3 V$ |




Table 9. Test data

| Input | | | | Load | | V_{EXT} | | |
|-------|---------------|--------|---------------|-------|--------------|--------------------|--------------------|--------------------|
| V_I | f_i | t_w | t_r, t_f | C_L | R_L | t_{PHZ}, t_{PZH} | t_{PLZ}, t_{PZL} | t_{PLH}, t_{PHL} |
| 2.7 V | ≤ 10 MHz | 500 ns | ≤ 2.5 ns | 50 pF | 500 Ω | GND | 6 V | open |

11. Package outline

TSSOP48: plastic thin shrink small outline package; 48 leads; body width 6.1 mm

SOT362-1




Fig. 7. Package outline TSSOP48 (SOT362-1)

12. Abbreviations

Table 10. Abbreviations

| Acronym | Description |
|---------|-------------------------------------------------|
| BiCMOS | Bipolar Complementary Metal Oxide Semiconductor |
| DUT | Device Under Test |
| ESD | ElectroStatic Discharge |
| MIL | Military |
| MM | Machine Model |
| TTL | Transistor-Transistor Logic |

13. Revision history

Table 11. Revision history

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|---------------|-----------------|
| 74LVT16240A v.4 | 20181001 | Product data sheet | - | 74LVT16240A v.3 |
| Modifications: | <ul style="list-style-type: none"> The format of this data sheet has been redesigned to comply with the identity guidelines of Nexperia. Legal texts have been adapted to the new company name where appropriate. Type number 74LVT16240ADL (SOT370-1) removed. | | | |
| 74LVT16240A v.3 | 20030221 | Product data sheet | - | 74LVT16240A v.2 |
| Modifications: | <ul style="list-style-type: none"> Table 1 corrected: removed 'North America' column. Fig. 2 modified to correct pin names | | | |
| 74LVT16240A v.2 | 19980219 | Product specification | - | 74LVT16240A v.1 |
| 74LVT16240A v.1 | 19941215 | Product specification | - | - |

14. Legal information

Data sheet status

| Document status [1][2] | Product status [3] | Definition |
|--------------------------------|--------------------|---------------------------------------------------------------------------------------|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

- [1] Please consult the most recently issued document before initiating or completing a design.
- [2] The term 'short data sheet' is explained in section "Definitions".
- [3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the internet at <https://www.nexperia.com>.

Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Nexperia product can reasonably be expected to result in personal

injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Contents

| | |
|--------------------------------------------------|-----------|
| 1. General description | 1 |
| 2. Features and benefits | 1 |
| 3. Ordering information | 1 |
| 4. Functional diagram | 2 |
| 5. Pinning information | 3 |
| 5.1. Pinning..... | 3 |
| 5.2. Pin description..... | 4 |
| 6. Functional description | 4 |
| 7. Limiting values | 4 |
| 8. Recommended operating conditions | 5 |
| 9. Static characteristics | 5 |
| 10. Dynamic characteristics | 6 |
| 10.1. Waveforms and test circuit..... | 7 |
| 11. Package outline | 9 |
| 12. Abbreviations | 10 |
| 13. Revision history | 10 |
| 14. Legal information | 11 |

© Nexperia B.V. 2018. All rights reserved

For more information, please visit: <http://www.nexperia.com>
For sales office addresses, please send an email to: salesaddresses@nexperia.com
Date of release: 1 October 2018

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru