



Product: [1335A](#)

Fieldbus, 2 C #16 Str TC, PO Ins, OS+TC Brd, PVC Jkt, CM

Request Sample

Product Description

Fieldbus, 2 Conductor 16AWG (7x24H) Tinned Copper, PO Insulation, Overall Beldfoil®+Tinned Copper Braid(65%) Shield, Orange PVC Outer Jacket, CM

Technical Specifications

Product Overview

Suitable Applications:

harsh environment digital and serial two-way communication, oil and gas extraction and refining sites, petrochemical, Profibus process automation or Foundation FieldBus process automation, extreme temperature environments, exposure to humidity/moisture, dust, and oil, remote locations long distance applications, etc.

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material           | No. of Pairs |
|-----|-----------|--------------------|--------------|
| 16  | 7x24      | TC - Tinned Copper | 1            |

Conductor Count: 2

Insulation

| Material           |
|--------------------|
| PP - Polypropylene |

Color Chart

| Number | Color         |
|--------|---------------|
| 1      | Blue & Orange |

Outer Shield Material

| Type  | Layer | Material           | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|-------|-------|--------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape  | 1     | Alum / Poly        | Beldfoil®           | 100 %        | TC - Tinned Copper | 20            | 7x28                         |
| Braid | 2     | TC - Tinned Copper |                     | 65 %         |                    |               |                              |

Outer Jacket Material

| Material                 | Nominal Diameter | Ripcord |
|--------------------------|------------------|---------|
| PVC - Polyvinyl Chloride | 0.34 in          | Yes     |

Electrical Characteristics

Conductor DCR

| Max. Outer Shield DCR | Nominal Conductor DCR |
|-----------------------|-----------------------|
| 4.9 Ohm/1000ft        | 4.2 Ohm/1000ft        |

Capacitance

| Max. Capacitance Unbalance | Nom. Capacitance Conductor to Shield | Nom.Mutual Capacitance |
|----------------------------|--------------------------------------|------------------------|
| 1.2 pF/ft                  | 45 pF/ft                             | 24 pF/ft               |

Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
| 100 Ohm                          |

High Frequency (Nominal/Typical)

| Nom. Insertion Loss |
|---------------------|
| 0.066 dB/100ft      |

Delay

| Nominal Velocity of Propagation (VP) [%] |
|------------------------------------------|
| 66 %                                     |

High Freq

| Max. Insertion Loss (Attenuation) | Max./Min. Input Impedance (unFitted) |
|-----------------------------------|--------------------------------------|
| 0.091 dB/100ft                    | 100 Ohm                              |

Current

| Element       | Max. Recommended Current [A] |
|---------------|------------------------------|
| Per Conductor | 8 Amps                       |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS         |

|                                    |                                                                     |
|------------------------------------|---------------------------------------------------------------------|
| Electrical Characteristics Notes:  | Max Propagation Delay Change From 7.812 kHz to 39.06 kHz: 518 pS/ft |
| Other Electrical Characteristic 2: | 31.25 KBits/sec                                                     |

Temperature Range

|                       |                |
|-----------------------|----------------|
| UL Temp Rating:       | 90°C           |
| Operating Temp Range: | -30°C To +90°C |

Mechanical Characteristics

|                                  |        |
|----------------------------------|--------|
| Oil Resistance:                  | Yes    |
| UV Resistance:                   | Yes    |
| Bulk Cable Weight:               | 79 lbs |
| Max Recommended Pulling Tension: | 84 lbs |
| Min Bend Radius/Minor Axis:      | 3.4 in |

Standards

|                          |               |
|--------------------------|---------------|
| NEC/(UL) Specification:  | CM, ITC, PLTC |
| CEC/C(UL) Specification: | CM            |

Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01                    |
| MII Order #39 (China RoHS):           | Yes                           |

Suitability

|                                    |          |
|------------------------------------|----------|
| Suitability - Burial:              | Yes - UL |
| Suitability - Indoor:              | Yes      |
| Suitability - Outdoor:             | Yes      |
| Suitability - Sunlight Resistance: | Yes      |

Flammability, LS0H, Toxicity Testing

|                  |                   |
|------------------|-------------------|
| UL Flammability: | UL1685 UL Loading |
|------------------|-------------------|

|                    |           |
|--------------------|-----------|
| UL voltage rating: | 300 V RMS |
|--------------------|-----------|

Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item #        | Color       | Putup Type | Length   | UPC          |
|---------------|-------------|------------|----------|--------------|
| 1335A 0061000 | Blue, Light | Reel       | 1,000 ft | 612825112198 |
| 1335A 0031000 | Orange      | Reel       | 1,000 ft | 612825112167 |

|           |                        |
|-----------|------------------------|
| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.328 Revision Date: 04-28-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)