

Technical Data Sheet

Rechargeable Lithium-ion Battery Pack RRC2040



Standard Li-ion battery pack RRC2040 3 x 18650 cells (3S1P) with 11.25V / 2950mAh / 33.2Wh

Features:

- Highest available energy density
- SMBus v1.1 compliant
- Fulfills JEITA standards, advanced temperature-dependent charging profile
 - Fastest charging
 - Maximized cycle life
- Impedance tracking and cell balancing
 - No manual recalibration necessary
 - Longest lifetime
- Comprehensive charging/discharging and passive safety systems
- Worldwide approvals
- Registered with recycling systems worldwide

Applications:

Suitable for use with tablet PC's, notebooks, industrial and medical devices, etc.

Specification

General

Basic Cell	18650
Delivery status	30%
battery capacity	
Operating temperature	0°C to 45°C (charge) -20°C to 60°C (discharge)
Storage temperature	-20°C to 60°C max. -20°C to 20°C recommended
Compliance information	CE / UL2054 / FCC / PSE / KC / BSMI / Gost / EAC / CQC / RCM / IEC 62133 / UN 38.3 / ROHS / Reach / BIS

Electrical Parameters

Nominal Voltage	11.25V
Nominal capacity	2950mAh
Initial impedance	<200mΩ @ 1kHz at 20°C
Max. charge current	2065mA
Max. charge voltage	13.05V
Cont. discharge	3000mA
Peak discharge	10000mA
Life expectancy @25°C	>300 cycles with
1.5A Charge/1.5A Discharge	min 75% of initial capacity

Battery Dimensions

Length	84.9mm±0.25
Width	58.8mm±0.25
Thickness	21.9mm+0.5/-0.25
Weight	170g
Contacts	+, C, D, T, -

Safety Parameters PCM

Overcharge detection voltage	4420mV
Overcharge release voltage	4200mV
Overdischarge detection voltage	2600mV
Overdischarge release voltage	3000mV
Overcharge detection current	2300mA
Overdischarge detection current	3500mA

Germany/Headquarters

RRC power solutions GmbH
Technologiepark 1
D-66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.de

USA

RRC power solutions Inc.
18340 Yorba Linda Blvd.,
Suite 107-437
Yorba Linda, CA 92886-4104

Tel.: +1 714 777 3604
Fax: +1 714 777 3658
Email: usa@rrc-ps.com
Web: www.rrc-ps.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial Centre
2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com

China

RRC power solutions Ltd.
Room 520, Yuanlin Building,
Aiguo Road No. 3066,
Luohu District,
Shenzhen 518021


Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com

Technical Data Sheet

Rechargeable Lithium-ion Battery Pack RRC2040



Recommended Accessories

Type		Product	Application
Desktop Battery Charger		RRC-SMB-UBC	65W standard desktop battery charger for optimized charging process with external power supply* for worldwide use.
Desktop Battery Charger		RRC-SMB-MBC	50W standard desktop battery charger for optimized charging process with external power supply* for worldwide use.
Desktop Battery Charger		PMC02A	65W 2-bay desktop battery charger for optimized charging process with external power supply* for worldwide use.
Desktop Battery Charger		PMC10A	320W 10-bay desktop battery charger for optimized charging process with internal power supply*. Wide input voltage range for worldwide use.
Embedded Battery Charger		RRC-PMM240	Power management module for smart battery charging with automatic power source selection. 82W max. output power to battery and 240W max. output power to application. Fits to all 20XX standard smart batteries from RRC.
Power Supply		PS65	External power supply (worldwide use) for embedded battery charger RRC-PMM240 or for mobile devices. Included in RRC-SMB-UBC/MBC and PMC02A.
AC Power Cable		210950 for USA/CAN/JPN 210951 for EU/KOR 211333 for UK/SGP 211334 for AUS/NZL	Country specific power cable for PS65.
Car Adapter		RRC-SMB-CAR	90W car adapter with USB charging port. Power supplying in cars and trucks for RRC-SMB-UBC, RRC-SMB-MBC, PMC02A, RRC-PMM240 or mobile devices.
Battery Diagnostic Tool		SMBus Reader	Simple read out of SMBus batteries data. No external power supply required. 5way blade connector and RS232 interface.
Extension Cable		SMBus Battery Cable	Extension cable for battery applications. Suitable for RRC204X and RRC205X batteries.
Battery Mating Connector		RRC-MC20-90-10 RRC-MC20-180-10	Mating Connector for standard smart batteries from RRC (e.g. RRC2020, RRC2054, ...). Available for 90° or 180° PCB mounting.

* - Additional country specific power cable for power supply available

Germany/Headquarters	USA	Hong Kong	China
RRC power solutions GmbH Technologiepark 1 D-66424 Homburg / Saar	RRC power solutions Inc. 18340 Yorba Linda Blvd., Suite 107-437 Yorba Linda, CA 92886-4104	RRC power solutions Ltd. S-V,6/F, Valiant Industrial Centre 2-12 Au Pui Wan Street Fo Tan, N.T., Hong Kong	RRC power solutions Ltd. Room 520, Yuanlin Building, Aiguo Road No. 3066, Luohu District, Shenzhen 518021
Tel.: +49 6841 98090 Fax: +49 6841 9809280 Email: sales@rrc-ps.de Web: www.rrc-ps.de	Tel.: +1 714 777 3604 Fax: +1 714 777 3658 Email: usa@rrc-ps.com Web: www.rrc-ps.com	Tel.: +852 2376 0106 Fax: +852 2375 0107 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com	Tel.: +86 755 8374 1908 Fax: +86 755 8374 1861 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru