

**SERIES:** ETMA 60W UD | **DESCRIPTION:** MEDICAL AC-DC POWER SUPPLY


**FEATURES**

- up to 60 W power
- universal input (90~264 Vac)
- single regulated output from 12~48 Vdc
- over voltage and short circuit protections
- medical 60601-1 4th edition safety approvals
- designed for 2 x MOPP applications
- level V efficiency
- custom designs available



| MODEL        | output voltage<br>(Vdc) | output current max<br>(A) | output power max<br>(W) | ripple and noise <sup>1</sup> max<br>(mVp-p) | efficiency level |
|--------------|-------------------------|---------------------------|-------------------------|----------------------------------------------|------------------|
| ETMA120500UD | 12                      | 5                         | 60                      | 120                                          | V                |
| ETMA150400UD | 15                      | 4                         | 60                      | 150                                          | V                |
| ETMA180333UD | 18                      | 3.33                      | 60                      | 180                                          | V                |
| ETMA240250UD | 24                      | 2.5                       | 60                      | 240                                          | V                |
| ETMA360166UD | 36                      | 1.66                      | 60                      | 360                                          | V                |
| ETMA480125UD | 48                      | 1.25                      | 60                      | 480                                          | V                |

Notes: 1. At full load, 100 ~ 240 Vac input, 20 MHz bandwidth oscilloscope, each output terminated with 10  $\mu$ F aluminum electrolytic and 0.1  $\mu$ F ceramic capacitors.

**PART NUMBER KEY**


## INPUT

| parameter                 | conditions/description | min | typ | max | units |
|---------------------------|------------------------|-----|-----|-----|-------|
| voltage                   |                        | 90  |     | 264 | Vac   |
| frequency                 |                        | 47  |     | 63  | Hz    |
| inrush current            | at 240 Vac             |     |     | 80  | A     |
| no load power consumption |                        |     |     | 0.3 | W     |

## OUTPUT

| parameter                    | conditions/description | min | typ   | max | units |
|------------------------------|------------------------|-----|-------|-----|-------|
| line regulation <sup>1</sup> |                        |     | ±1    |     | %     |
| load regulation <sup>2</sup> | 12 Vdc output          |     | ±5    |     | %     |
|                              | 15 Vdc output          |     | ±3    |     | %     |
|                              | all other outputs      |     | ±2    |     | %     |
| voltage accuracy             |                        |     | ±2    |     | %     |
| hold-up time                 | at 115 Vac             |     | 8     |     | ms    |
| switching frequency          |                        |     | 100   |     | kHz   |
| temperature coefficient      |                        |     | ±0.05 |     | %/°C  |

Note: 1. measured from 100 ~ 240 Vac, full load  
2. measured from 60% to full load and from 60 ~ 20% load (60% ±40% load)

## PROTECTIONS

| parameter                | conditions/description   | min | typ | max | units |
|--------------------------|--------------------------|-----|-----|-----|-------|
| over voltage protection  | TVS component to clamp   |     |     |     |       |
| short circuit protection | continuous, auto restart |     |     |     |       |

## SAFETY & COMPLIANCE

| parameter         | conditions/description                                  | min     | typ | max   | units |
|-------------------|---------------------------------------------------------|---------|-----|-------|-------|
| isolation voltage | input to output                                         |         |     | 5,656 | Vdc   |
| safety approvals  | medical IEC 60601-1, EN 60601-1, UL 60601-1 4th edition |         |     |       |       |
| EMI/EMC           | EN 55011, EN 60601-1-2, EN 61000-3-(2,3)                |         |     |       |       |
| leakage current   |                                                         |         |     | 0.1   | mA    |
| MTBF              | as per MIL-HDBK-217F, 115 Vac, 25 °C                    | 200,000 |     |       | hours |
| RoHS              | 2011/65/EU                                              |         |     |       |       |

## ENVIRONMENTAL


| parameter             | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature |                        | 0   |     | 40  | °C    |
| storage temperature   |                        | -20 |     | 85  | °C    |
| humidity              | non-condensing         |     |     | 93  | %     |

## MECHANICAL


| parameter  | conditions/description                  | min | typ | max | units |
|------------|-----------------------------------------|-----|-----|-----|-------|
| dimensions | 132 x 58 x 30.5 (5.2 x 2.28 x 1.2 inch) |     |     |     | mm    |
| input plug | IEC320 / C8                             |     |     |     |       |
| weight     |                                         |     | 345 |     | g     |

## MECHANICAL DRAWING


units: mm



## DC OUTPUT PLUG OPTIONS / DC CORD



|        | A   | B   | C   | Unit |
|--------|-----|-----|-----|------|
| P5/P5R | 5.5 | 2.1 | 9.5 | mm   |
| P6/P6R | 5.5 | 2.5 | 9.5 | mm   |




| MODEL NO.    | CABLE GAUGE | CORD LENGTH       |
|--------------|-------------|-------------------|
| ETMA120500UD | 16 AWG      | 720 mm $\pm$ 50   |
| ETMA150400UD | 16 AWG      | 1,220 mm $\pm$ 50 |
| ETMA180333UD | 16 AWG      | 1,500 mm $\pm$ 50 |
| ETMA240250UD | 16 AWG      | 1,800 mm $\pm$ 50 |
| ETMA360166UD | 16 AWG      | 1,800 mm $\pm$ 50 |
| ETMA480125UD | 16 AWG      | 1,800 mm $\pm$ 50 |

### PXXX

Plug Type

Plug Angle:  
"Blank" = Standard  
R = Right Angle

Plug Polarity:  
"Blank" = N/A  
P = Center Positive  
N = Center Negative



## REVISION HISTORY

| rev. | description                            | date       |
|------|----------------------------------------|------------|
| 1.0  | initial release                        | 12/16/2011 |
| 1.01 | updated P7/P7R B dimension             | 03/23/2012 |
| 1.02 | V-Infinity branding removed            | 08/21/2012 |
| 1.03 | updated datasheet                      | 10/31/2012 |
| 1.04 | corrected dc cord table                | 07/02/2013 |
| 1.05 | updated datasheet                      | 07/10/2015 |
| 1.06 | updated to medical 60601-1 4th edition | 06/20/2017 |

The revision history provided is for informational purposes only and is believed to be accurate.



**Headquarters**  
20050 SW 112th Ave.  
Tualatin, OR 97062  
**800.275.4899**

Fax 503.612.2383  
**cui.com**  
techsupport@cui.com

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)