

	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																						
	UNPLATED MATERIAL NUMBER	UNPLATED ENG. NUMBER	UNPLATED MAT. NO. ON TAPE	UNPLATED ENG. NO. ON TAPE	PLATED MATERIAL NUMBER	PLATED ENGINEERING NUMBER	PLATED MAT. NO. ON TAPE	PLATED ENG. NO. ON TAPE	SEE DETAIL	STUD SIZE	AWG WIRE RANGE	"S" ±.010/(0.25)	"L" ±.030/(0.76)	"W" ±.020/(0.50)	"C" ±.040/(1.02)	"B" ±.015/(0.38)	"T" ±.015/(0.38)																																																																																																		
J	1922 I0451	BCL-410	---	---	1922 I0452	BCL-410-PL	---	---	---	10/(4.83)	4	.214/(5.45)	1.500/(38.10)	.531/(13.49)	.429/(10.90)	.286/(7.26)	.080/(2.03)	J																																																																																																	
	1922 I0404	BCL-414	---	---	1922 I0230	BCL-414-PL	---	---	---	1/4/(6.4)	4	.278/(7.06)	1.500/(38.10)	.531/(13.49)	.429/(10.90)	.286/(7.26)	.080/(2.03)																																																																																																		
	1922 I0405	BCL-4516	---	---	1922 I0231	BCL-4516-PL	190820025	BCL-4516-PLT	D	5/16/(7.9)	4	.340/(8.64)	1.500/(38.10)	.531/(13.49)	.429/(10.90)	.286/(7.26)	.080/(2.03)																																																																																																		
	1922 I0461	BCL-4516-WP	---	---	1922 I0460	BCL-4516-WP-PL	---	---	---	5/16/(7.9)	4	.340/(8.64)	1.531/(38.89)	.625/(15.88)	.397/(10.08)	.286/(7.26)	.080/(2.03)																																																																																																		
	1922 I0383	BCL-438	---	---	1922 I0232	BCL-438-PL	190820026	BCL-438-PLT	E	3/8/(9.5)	4	.400/(10.16)	1.500/(38.10)	.531/(13.49)	.429/(10.90)	.286/(7.26)	.080/(2.03)																																																																																																		
	1922 I0458	BCL-438-WP	---	---	1922 I0456	BCL-438-WP-PL	190820027	BCL-438-WP-PLT	E	3/8/(9.5)	4	.400/(10.16)	1.531/(38.89)	.625/(15.88)	.397/(10.08)	.286/(7.26)	.080/(2.03)																																																																																																		
I	1922 I0459	BCL-438-XWP	---	---	1922 I0457	BCL-438-XWP-PL	---	---	---	3/8/(9.5)	4	.400/(10.16)	1.688/(42.88)	.766/(19.46)	.444/(11.28)	.286/(7.26)	.100/(2.54)	I																																																																																																	
	1922 I0453	BCL-412	---	---	1922 I0454	BCL-412-PL	---	---	---	1/2/(12.7)	4	.520/(13.21)	1.688/(42.88)	.766/(19.46)	.444/(11.28)	.286/(7.26)	.100/(2.54)																																																																																																		
	1922 I0419	BCL-214	---	---	1922 I0418	BCL-214-PL	190820001	BCL-214-PLT	C	1/4/(6.4)	2	.278/(7.06)	1.625/(41.28)	.625/(15.88)	.437/(11.10)	.336/(8.53)	.095/(2.41)																																																																																																		
	1922 I0400	BCL-2516	---	---	1922 I0233	BCL-2516-PL	190820002	BCL-2516-PLT	C	5/16/(7.9)	2	.340/(8.63)	1.625/(41.28)	.625/(15.88)	.437/(11.10)	.336/(8.53)	.095/(2.41)																																																																																																		
	1922 I0380	BCL-238	---	---	1922 I0235	BCL-238-PL	---	---	---	3/8/(9.5)	2	.400/(10.16)	1.625/(41.28)	.625/(15.88)	.437/(11.10)	.336/(8.53)	.095/(2.41)																																																																																																		
	1922 I0564	BCL-238-WP	---	---	1922 I0565	BCL-238-WP-PL	---	---	---	3/8/(9.5)	2	.400/(10.16)	1.750/(44.45)	.750/(19.05)	.474/(12.04)	.336/(8.53)	.095/(2.41)																																																																																																		
	1922 I0399	BCL-212-WP	---	---	1922 I0236	BCL-212-WP-PL	---	---	---	1/2/(12.7)	2	.520/(13.21)	1.750/(44.45)	.750/(19.05)	.474/(12.04)	.336/(8.53)	.095/(2.41)																																																																																																		
H	1922 I0594	BCL-110	---	---	1922 I0595	BCL-110-PL	---	---	---	#10/(4.83)	1	.214/(5.45)	1.718/(43.64)	.656/(16.66)	.446/(11.33)	.360/(9.14)	.100/(2.54)	H																																																																																																	
	1922 I0421	BCL-114	---	---	1922 I0420	BCL-114-PL	---	---	---	1/4/(6.4)	1	.278/(7.06)	1.718/(43.64)	.656/(16.66)	.446/(11.33)	.360/(9.14)	.100/(2.54)																																																																																																		
	1922 I0396	BCL-1516	---	---	1922 I0237	BCL-1516-PL	---	---	---	5/16/(7.9)	1	.340/(8.63)	1.718/(43.64)	.656/(16.66)	.446/(11.33)	.360/(9.14)	.100/(2.54)																																																																																																		
	1922 I0378	BCL-138	---	---	1922 I0238	BCL-138-PL	---	---	---	3/8/(9.5)	1	.400/(10.16)	1.718/(43.64)	.656/(16.66)	.446/(11.33)	.360/(9.14)	.100/(2.54)																																																																																																		
	1922 I0580	BCL-138-WP	---	---	1922 I0581	BCL-138-WP-PL	---	---	---	3/8/(9.5)	1	.400/(10.16)	1.844/(46.84)	.750/(19.05)	.474/(12.04)	.360/(9.14)	.100/(2.54)																																																																																																		
	1922 I0395	BCL-112	---	---	1922 I0239	BCL-112-PL	---	---	---	1/2/(12.7)	1	.520/(13.21)	1.844/(46.84)	.750/(19.05)	.474/(12.04)	.360/(9.14)	.100/(2.54)																																																																																																		
G	4 LOGO, AWG & STUD SIZE 4 AWG WIRE SIZE STAMPED ON BARREL 5 IF TONGUE IS TO BE BENT AT ANY ANGLE, IT MUST BE BENT AROUND A RADIUS ONE HALF THE TONGUE THICKNESS. FLARED BARREL FOR EASY WIRE ENTRY "S" DIA. "L" "W" "C" "B" DIA. "T" DETAIL C DETAIL D DETAIL E <table><tr><td rowspan="9">ADDED DETAIL E EC NO: ETC2006-0005 2005/11/23 DRWNL:SHADECK CHKD:JDRROSS APPR:JPW/LCK 2005/11/23</td><td rowspan="9">QUALITY SYMBOLS ▽=0 ▽=0</td><td colspan="2">GENERAL TOLERANCES (UNLESS SPECIFIED)</td><td colspan="2">DIMENSION STYLE</td><td rowspan="5">SCALE ---</td><td rowspan="9">DESIGN UNITS INCH</td><td rowspan="9">THIRD ANGLE PROJECTION</td><td colspan="8" rowspan="5">EYELET STYLE COPPER TERMINALS 4, 2, & 1 AWG LUGS MOLEX INCORPORATED</td></tr><tr><td>mm</td><td>INCH</td><td>DRAWN BY</td><td>DATE</td></tr><tr><td>4 PLACES ±---</td><td>±---</td><td>BE</td><td>06/26/02</td></tr><tr><td>3 PLACES ±---</td><td>±---</td><td>HB</td><td>06/26/02</td></tr><tr><td>2 PLACES ±---</td><td>±---</td><td>RD</td><td>06/26/02</td></tr><tr><td>1 PLACE ±---</td><td>±---</td><td colspan="2">APPROVED BY</td><td colspan="3">DATE</td><td colspan="8" rowspan="4">SD-19221-010</td></tr><tr><td colspan="2">ANGULAR ±---</td><td colspan="2">MATERIAL NO.</td><td colspan="11">DOCUMENT NO.</td></tr><tr><td colspan="2">DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td colspan="2">SEE CHART</td><td colspan="15" rowspan="2">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td></tr><tr><td colspan="15">SHEET NO. 1 OF 1</td></tr></table>																	ADDED DETAIL E EC NO: ETC2006-0005 2005/11/23 DRWNL:SHADECK CHKD:JDRROSS APPR:JPW/LCK 2005/11/23	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	EYELET STYLE COPPER TERMINALS 4, 2, & 1 AWG LUGS MOLEX INCORPORATED								mm	INCH	DRAWN BY	DATE	4 PLACES ±---	±---	BE	06/26/02	3 PLACES ±---	±---	HB	06/26/02	2 PLACES ±---	±---	RD	06/26/02	1 PLACE ±---	±---	APPROVED BY		DATE			SD-19221-010								ANGULAR ±---		MATERIAL NO.		DOCUMENT NO.											DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION															SHEET NO. 1 OF 1															G
ADDED DETAIL E EC NO: ETC2006-0005 2005/11/23 DRWNL:SHADECK CHKD:JDRROSS APPR:JPW/LCK 2005/11/23																				QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE												SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	EYELET STYLE COPPER TERMINALS 4, 2, & 1 AWG LUGS MOLEX INCORPORATED																																																																													
																					mm	INCH	DRAWN BY																							DATE																																																																					
																					4 PLACES ±---	±---	BE																							06/26/02																																																																					
																					3 PLACES ±---	±---	HB																							06/26/02																																																																					
	2 PLACES ±---	±---	RD	06/26/02																																																																																																															
	1 PLACE ±---	±---	APPROVED BY		DATE			SD-19221-010																																																																																																											
	ANGULAR ±---		MATERIAL NO.		DOCUMENT NO.																																																																																																														
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																														
	SHEET NO. 1 OF 1																																																																																																																		
F	F																																																																																																																		
E	E																																																																																																																		
D	D																																																																																																																		
C	C																																																																																																																		
B	NOTES: 1. FOR INSPECTION SIGHT HOLE, PLEASE CONSULT FACTORY. 2. OTHER STUD SIZES MAY BE AVAILABLE, PLEASE CONSULT FACTORY. 3. MATERIAL: COPPER PLATING: TIN 4. MARKINGS CAN BE AT EITHER LOCATION SHOWN. 5. IF TONGUE IS TO BE BENT AT ANY ANGLE, IT MUST BE BENT AROUND A RADIUS ONE HALF THE TONGUE THICKNESS.																	B																																																																																																	
A	C															A																																																																																																			

tb_frame_C_P_ME_T

Rev. D 2004/04/02

12	11	10	9	8	7	6	5	4	3	2	1
----	----	----	---	---	---	---	---	---	---	---	---

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru