Desiccant is a drying agent used to lower the moisture content of air inside a closed space, such as a Moisture Barrier Bag (ANSI/ESD S11.4 Level 1 and Level 2 Static Control Bags). Desiccant is packaged in fractional units in order to facilitate its usage with a variety of bag sizes. One full "unit" of packaged desiccant will absorb the following quantities of water at equilibrium with air at 77°F (25°C): 3.00 grams @ 20% rH and 6.00 grams @ 40% rH, when tested to MIL-D-3464.

In order to provide a complete moisture barrier packaging assembly, desiccant must be inserted into the bag, prior to having the bag vacuum sealed. The recommended amount of desiccant is dependent on the interior surface area of the bag to be used. The table is a reference indicating recommended minimum amounts of desiccant that should be used with <u>Moisture Barrier Bags</u>.



"...it is important to take possible temperature exposure into account when shipping electronic parts. It is particularly important to consider what happens to the interior of a package if the environment has high humidity. If the temperature varies across the dew point of the established interior environment of the package, condensation may occur. The interior of a package should either contain desiccant or the air should be evacuated from the package during the sealing process. The package itself should have a low WVTR." (ESD Handbook ESD TR20.20 section 5.4.3.2.2)



		T UNITS
**MIH <20%	MIH <30%	MIH < 40%
15	1.0	1.0
		1.0
		-
	-	1.5
2.5	2.0	1.5
3.0	2.0	1.5
4.0	2.5	2.0
4.5	3.0	2.5
5.0	3.5	2.5
5.5	4.0	3.0
6.5	4.5	3.5
7.5	5.0	4.0
8.0	5.5	4.0
9.0	6.0	4.5
	$ \begin{array}{r} 1.5 \\ 2.0 \\ 2.5 \\ 3.0 \\ 4.0 \\ 4.5 \\ 5.0 \\ 5.5 \\ 6.5 \\ 7.5 \\ 8.0 \\ \end{array} $	$\begin{array}{cccccccccccccccccccccccccccccccccccc$

Table for recommended desiccant usage. Information taken out of EIA-583, Table 1, Page 8. *To measure interior bag surface area, multiply length x width x 2

**MIH = Maximum Interior Humidity (%)

Desiccant paks are available from Desco in the following unit sizes and standard packages:

Item #	Unit Size	Std. Package	Dimensions
<u>13840</u>	1/2 unit	Box of 700	1.5" x 3"
<u>13843</u>	1 unit	Box of 450	2" x 4"
<u>13844</u>	1 unit	Pail of 300	2" x 4"
<u>13850</u>	1/2 unit	Pail of 550	1.5" x 3"

As packaged Desco 13850 meets MIL-D-3464, Type II and is on the QPL (Qualified Product List). Click <u>here</u> to see Desi-Pak (supplier Cage Code 00334).

Fill Contents:	Activated Clay	
Paper:	Tyvek	555555
Warranty:	3 Years from date of manufacture	
		Made in the

Specifications and procedures subject to change without notice.

ne	Desiccant Pak		
	DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEBSITE: Desco.com PHONE (909) 627-8178	DRAWING NUMBER	DATE: December
	DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370	13850	2013

United States of America

© 2013 DESCO INDUSTRIES INC. Employee Owned

DESCO SAFETY DATA SHEET =

May be used to comply with ANSI Z400.1-2004, and Globally Harmonized System (OSHA Hazcom 29 CFR 1910.1200, (EU) No.453/2010 and Japan JIS 7253:2012). Standards must be consulted for specific requirements.

Revision Date: 2018-02-27

SECTION 1 — IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifiers

Product Name: EC No.: REACH Registration No.: CAS No.:

1.2 Relevant identified uses of the substance or mixture and uses advised against

Desi Pak

None

None

None

Identified use:

Desiccant

1.3 Details of the supplier of the safety data sheet

Supplier:	Desco 3651 Walnut Ave Chino, CA 91710 (909) 627-8178
Email Address:	Service@Desco.com
1.4 Emergency telephone number	
Emergency Number:	(909) 627-8178

SECTION 2 — HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

No reportable hazardous components as defined by the Globally Harmonized System (OSHA Hazcom 29 CFR 1910.1200, (EU) No.453/2010 and Japan JIS 7253:2012).

2.2 Label elements

Not a dangerous substance according to GHS.

2.3 Other hazards

None known.

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

No reportable hazardous components as defined by the Globally Harmonized System (OSHA Hazcom 29 CFR 1910.1200, (EU) No.453/2010 and Japan JIS 7253:2012).

SECTION 4 — FIRST AID MEASURES

4.1 Description of first aid measures

General advice	No known delayed effects. Consult a physician for all exposures except for minor instances.
If inhaled	INHALATION: If exposed to excessive levels of dust or fumes, remove to fresh air and get medical attention. Get medical attention if cough and other symptoms develop. If you feel unwell, seek medical advice (show the label where possible).
In case of skin contact	Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available.
In case of eye contact	Do not rub affected area. Rinse immediately with plenty of lukewarm water, also under the eyelids, for at least 15 minutes. Obtain medical attention.

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com

If swallowed Normally not needed. If whole canisters or sachets are ingested, call a physician or your local Poison Control Center (1-800-222-1222 in the United States). 4.2 Most important symptoms and effects, both acute and delayed Most important symptoms and The possible symptoms known are those derived from the labelling (see section 2). No additional symptoms are known. effects, both acute and delayed 4.3 Indication of any immediate medical attention and special treatment needed Notes to physician Treat symptomatically. SECTION 5 — FIRE FIGHTING MEASURES 5.1 Extinguishing media Suitable Extinguishing Media The product itself does not burn. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray jet Dry powder Foam Carbon dioxide (CO2) Unsuitable Extinguishing Media No restrictions 5.2 Special hazards arising from the substance or mixture The product is not flammable. Does not sustain combustion. No hazardous decomposition products are known. 5.3 Advice for firefighters In the event of fire, wear self-contained breathing apparatus. Special sliding risk through leaking of spilled product in connection with water. SECTION 6 — ACCIDENTAL RELEASE MEASURES 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation. Avoid dust formation. Evacuate personnel to safe areas. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Avoid breathing dust. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Special sliding risk through leaking of spilled product in connection with water. Wearing appropriate personal protective equipment, contain spill and collect into a suitable container. No special precautions required. 6.2 Environmental precautions No special environmental precautions required. 6.3 Methods and materials for containment and cleaning up Pick up and transfer to properly labelled containers. If product is released from trucks in roads, place signposts and remove the spill using vacuum cleaning systems. 6.4 Reference to other sections See SECTION 8 and SECTION 13. SECTION 7 — HANDLING AND STORAGE 7.1 Precautions for safe handling Advice on safe handling Use of proper hygiene practices in the workplace is recommended. Hygiene measures Wash hands before breaks and at the end of workday. DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com

7.2 Conditions for safe storage, incl	7.2 Conditions for safe storage, including any incompatibilities		
Requirements for storage areas and containers	Minimize airborne dust generation and prevent wind dispersal during loading and unloading. Keep containers closed and store packaged products so as to prevent accidental bursting.		
Advice on storage compatibility	No conditions to be specially mentioned.		
Storage stability	Store in a dry place.		
7.3 Specific end uses	Not relevant		
SECTION 8 — EXPOSURE CONTROL	L / PERSONAL PROTECTION		
8.1 Control parameters			
Components with workplace control Contains no substances with occupation			
Engineering measures	Use ventilation adequate to keep exposures below recommended exposure limits. See the safety datasheet.		
8.2 Exposure controls Personal protective equipment			
Respiratory protection	Use local exhaust if dusting occurs. Good general ventaliation is adequate in the absence of dusts.		
Hand protection	Wear protective gloves. Wash thoroughly after handling.		
Eye protection	Safety glasses with side-shields.		
Skin and Body protection	Wear suitable protective equipment.		
Hygiene measures	Wash hands before breaks and at the end of workday.		
9.1 Information on basic physical an Appearance Color: Odor:	nd chemical properties lumpy, granular, powder bright to earthy None		
Odor Threshold:	Not determined		
pH:	6.0 - 11.0 (20°C) Method: aquaous suspension		
Melting point/range:	> 450°C Method: EU A.1		
Boiling point/boiling range: Flash point:	not applicable (solid with a melting point > 450°C) Not applicable		
Evaporation rate: Flammability (solid, gas):	Not applicable Does not ignite Method: EU A.1		
Self-ignition:	Method: 92/69/EEC, A.6. No relative self-ignition temperature below 400°C		
Upper explosion limit: Lower explosive limit:	Not applicable Non explosive (void of any chemical structures commonly associated with explosive properties)		
Vapor pressure: Vapor density relative to air: Density:	not applicable (solid with a melting point > 450°C) Non applicable 2.6 g/cm3		
Bulk density:	500 - 1,100 kg/m3		
Solubility (Water):	< 0.9 g/l (20°Č) Method: Tested according to Directive 92/69/EEC.		
Partition coefficient (n-octanol/water):	No applicable inorganic Not determined		
Auto-ignition temperature: Decomposition temperature:	Not determined No decomposition if used as directed.		
Viscosity (dynamic):	Not applicable		
Viscosity (kinematic):	Not applicable		
DESCO - 3651	Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com		

Oxidizing properties:

No oxidizing properties (Based on the chemical structure, the substance does not contain a surplus of oxygen or any structural groups known to be correlated with a tendency to react exothermally with combustible material).

9.2 Other information

None known.

SECTION 10 — STABILITY AND REACTIVITY

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Forms slippery/greasy layers with water.

10.5 Incompatible materials

Inert, not reactive. Avoid storing together with materials that may be affected by dust.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11 — TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure Eye contact. Ingestion

Acute toxicity

Acute oral toxicity

Acute inhalation toxicity Acute dermal toxicity LD50 (Rat): > 2 g/kg Method: OECD Test Guideline 420

No data available No data available Bentonite is almost insoluble and has a low absorption through the skin.

Skin corrosion/irritation

Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

Serious eye damage/eye irritation

Species: Rabbit Method: OECD Test Guideline 405 Result: No skin irritation

Respiratory or skin sensitisation

No data available

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com

Germ cell mutagenicity	
Genotoxicity in vitro	Test Type: In vitro gene mutation study in bacteria Method: OECD Test Guideline 471 Result: negative
	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
	Test Type: In vitro gene mutation study in mammalian cells Method: OECD Test Guideline 476 Result: negative
Carcinogenicity	
IARC	Not listed
OSHA	Not listed
NTP	Not listed
Reproductive toxicity	
Effects on fertility	Based on available data, the classification criteria are not met.
STOT - Single exposure No organ toxicity observed in acute tes	sts.
Aspiration toxicity No aspiration toxicity classification.	
Experience with human exposure	
General Information	The possible symptoms known are those derived from the labelling (see section 2).
SECTION 12 — ECOLOGICAL INFOR	
12.1 Toxicity	
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 16 g/l Exposure time: 96 h LC50 (Marine water fish): 2.8 - 3.2 g/l Exposure time: 24 h
Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 EC50 (Metacarcinus magister): 81.6 mg/l Exposure time: 96 h EC50 (Pandalus danae): 24.8 mg/l Exposure time: 96 h
Toxicity to algae	EC50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): > 100 mg/l Exposure time: 72 h
Plant toxicity	' (Phaseolus vulgaris): 84.4 mg/kg Remarks: No effect on the growth was observed. (Zea mays): 84.4 mg/kg Remarks: No effect on the growth was observed.
12.2 Persistence and degradability	
Biodegradability	The methods for determining biodegradability are not applicable to inorganic substances.
DESCO - 3651 '	Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: <u>Desco.com</u>

12.3 Bioaccumulative potential		
Bioaccumulation	Not relevant for inorganic substances.	
12.4 Mobility in soil		
Distribution among environmental compartments	Medium: Soil Bentonite is almost insoluble and thus presents a low mobility in most soils.	
12.5 Results of PBT and vPvB asses	sment	
No data available		
12.6 Other adverse effects		
Additional ecological information	According to experience and to the information currently available, the product has no harmful effects on the environment if used correctly as intended.	
SECTION 13 — DISPOSAL CONSIDE	RATIONS	
13.1 Waste treatment methods		
RCRA - Resource Conservation and Recovery Authorization Act	No Not as sold.	
Water Code	NONE	
Waste from residues	This product, if discarded as sold, is not a Federal RCRA hazardous waste. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations.	
Contaminated packaging	No specific requirements.	
SECTION 14 — TRANSPORT INFOR	MATION	
DOT	Not restricted	
ΙΑΤΑ	Not restricted	
IMDG	Not restricted	
14.1 UN Number	N/A	
14.2 UN proper shipping name	N/A	
14.3 Transport hazard class(es)	N/A	
14.4 Packing group	N/A	
14.5 Environmental hazards	N/A	
14.6 Special precautions for user	N/A	
14.7 Transport in bulk according to of MARPOL and the IBC Code	Annex II N/A	
SECTION 15 — REGULATORY INFORMATION15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtureEPCRA - Emergency Planning and Community Right-to-Know ActCERCLA Reportable Quantity This material does not contain any components with a CERCLA RQ.SARA 304 Extremely Hazardous Substances Reportable Quantity This material does not contain any components with a section 304 EHS RQ.SARA 311/312 HazardsNo SARA HazardsSARA 313This product is not subject to SARA Title III Section 313 reporting		
requirements under 40 CFR 372. DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com		

Clean Water Act Contains no known priority pollutants at concentrations greater than 0.1%. The components of this product are reported in the following inventories:		
TSCA	All components of this product are listed or excluded from listing on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) Inventory.	
15.2 Chemical Safety Assessment	Not relevant	
SECTION 16 — OTHER INFORMATION		
HMIS RATING	Health 0, Flammability 0, Reactivity 0, Personal Protection B	
NFPA RATING	Special Hazard: N/A, Health: 0, Flammability: 0, Instability: 0	
SDS Updated	2018-02-27	
Disclaimer		

OTHER INFORMATION: This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for his own particular use.

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com



ООО "ЛайфЭлектроникс"

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru

www.lifeelectronics.ru