# Power SMD LED in PLCC-2 Package

## Description

The TLM.33.. series is an advanced modification of the Vishay TLM.31.. series. It is designed to incorporate larger chips, therefore, capable of withstanding a 50 mA drive current.

The package of the TLM.33.. is the PLCC-2 (equivalent to a size B tantalum capacitor).

It consists of a lead frame which is embedded in a white thermoplast. The reflector inside this package is filled up with clear epoxy.




e3 Pb Pb-free

## Features

- Utilizing (AS) AlInGaP technology
- Available in 8 mm tape
- Luninous intensity, color and forward voltage categorized per packing unit
- Luminous intensity ratio per packing unit $I_{Vmax}/I_{Vmin} \leq 1.6$
- Thermal resistance R = 400 K/W
- ESD class 2
- Suitable for all soldering methods according to CECC
- Lead-free device

## Applications

Traffic Signals and Signs

Interior and exterior lighting

Dashboard illumination

Indicator and backlighting purposes for audio, video, LCD's switches, symbols, illuminated advertising etc.

## Parts Table

| Part | Color, Luminous Intensity | Angle of Half Intensity (±φ) | Technology |
|---|---|---|---|
| TLMK3300 | Red, $I_V$ > 200 mcd | 60 ° | AlInGaP on GaAs |
| TLMK3301 | Red, $I_V$ = (250 to 800) mcd | 60 ° | AlInGaP on GaAs |
| TLMK3302 | Red, $I_V$ = (400 to 800) mcd | 60 ° | AlInGaP on GaAs |
| TLMK3303 | Red, $I_V$ = (400 to 1250) mcd | 60 ° | AlInGaP on GaAs |
| TLMS3300 | Red, $I_V$ > 160 mcd | 60 ° | AlInGaP on GaAs |
| TLMS3301 | Red, $I_V$ = (160 to 400) mcd | 60 ° | AlInGaP on GaAs |
| TLMS3302 | Red, $I_V$ = (250 to 800) mcd | 60 ° | AlInGaP on GaAs |
| TLMO3300 | Soft orange, $I_V$ > 200 mcd | 60 ° | AlInGaP on GaAs |
| TLMO3301 | Soft orange, $I_V$ = (250 to 640) mcd | 60 ° | AlInGaP on GaAs |
| TLMO3302 | Soft orange, $I_V$ = (320 to 800) mcd | 60 ° | AlInGaP on GaAs |

| Part | Color, Luminous Intensity | Angle of Half Intensity (±φ) | Technology |
|---|---|---|---|
| TLMO3303 | Soft orange, $I_V$ = (400 to 1250) mcd | 60 ° | AlInGaP on GaAs |
| TLMY3300 | Yellow, $I_V$ > 200 mcd | 60 ° | AlInGaP on GaAs |
| TLMY3301 | Yellow, $I_V$ = (250 to 640) mcd | 60 ° | AlInGaP on GaAs |
| TLMY3302 | Yellow, $I_V$ = (320 to 800) mcd | 60 ° | AlInGaP on GaAs |
| TLMY3303 | Yellow, $I_V$ = (400 to 1250) mcd | 60 ° | AlInGaP on GaAs |

## Absolute Maximum Ratings

$T_{amb}$ = 25 °C, unless otherwise specified
**TLMY33.., TLMO33.., TLMK33.., TLMS33..**

| Parameter | Test condition | Symbol | Value | Unit |
|---|---|---|---|---|
| Reverse voltage | | $V_R$ | 5 | V |
| DC Forward current | $T_{amb} \leq$ 73 °C (400 K/W) | $I_F$ | 50 | mA |
| Power dissipation | $T_{amb} \leq$ 73 °C (400 K/W) | $P_V$ | 130 | mW |
| Junction temperature | | $T_j$ | 125 | °C |
| Operating temperature range | | $T_{amb}$ | - 40 to + 100 | °C |
| Storage temperature range | | $T_{stg}$ | - 40 to + 100 | °C |
| Soldering temperature | t ≤ 5 s | $T_{sd}$ | 260 | °C |
| Thermal resistance junction/ ambient | mounted on PC board (pad size > 16 $mm^2$) | $R_{thJA}$ | 400 | K/W |

## Optical and Electrical Characteristics

$T_{amb}$ = 25 °C, unless otherwise specified

## Red

**TLMK33..**

| Parameter | Test condition | Part | Symbol | Min | Typ. | Max | Unit |
|---|---|---|---|---|---|---|---|
| Luminous intensity | $I_F$ = 50 mA | TLMK3300 | $I_V$ | 200 | 500 | | mcd |
| | | TLMK3301 | $I_V$ | 250 | | 800 | mcd |
| | | TLMK3302 | $I_V$ | 400 | | 800 | mcd |
| | | TLMK3303 | $I_V$ | 400 | | 1250 | mcd |
| Luminous flux/Luminous intensity | | | $\phi_V/I_V$ | | 3 | | mlm/ mcd |
| Dominant wavelength | $I_F$ = 50 mA | | $\lambda_d$ | 611 | 617 | 622 | nm |
| Peak wavelength | $I_F$ = 50 mA | | $\lambda_p$ | | 624 | | nm |
| Spectral bandwidth at 50 % $I_{rel\ max}$ | $I_F$ = 50 mA | | $\Delta\lambda$ | | 18 | | nm |
| Angle of half intensity | $I_F$ = 50 mA | | φ | | ± 60 | | deg |
| Forward voltage | $I_F$ = 50 mA | | $V_F$ | 1.85 | 2.1 | 2.55 | V |
| Reverse current | $V_R$ = 5 V | | $V_R$ | | 0.01 | 10 | µA |

## Red

**TLMS33..**

| Parameter | Test condition | Part | Symbol | Min | Typ. | Max | Unit |
|---|---|---|---|---|---|---|---|
| Luminous intensity | $I_F$ = 50 mA | TLMS3300 | $I_V$ | 160 | 300 | | mcd |
| | | TLMS3301 | $I_V$ | 160 | | 400 | mcd |
| | | TLMS3302 | $I_V$ | 250 | | 800 | mcd |
| Luminous flux/Luminous intensity | | | $\phi_V/I_V$ | | 3 | | mlm/ mcd |
| Dominant wavelength | $I_F$ = 50 mA | | $\lambda_d$ | 626 | 630 | 638 | nm |
| Peak wavelength | $I_F$ = 50 mA | | $\lambda_p$ | | 641 | | nm |
| Spectral bandwidth at 50 % $I_{rel\ max}$ | $I_F$ = 50 mA | | $\Delta\lambda$ | | 17 | | nm |
| Angle of half intensity | $I_F$ = 50 mA | | $\varphi$ | | ± 60 | | deg |
| Forward voltage | $I_F$ = 50 mA | | $V_F$ | 1.85 | 2.1 | 2.55 | V |
| Reverse current | $V_R$ = 5 V | | $V_R$ | | 0.01 | 10 | µA |

## Soft Orange

**TLMO33..**

| Parameter | Test condition | Part | Symbol | Min | Typ. | Max | Unit |
|---|---|---|---|---|---|---|---|
| Luminous intensity | $I_F$ = 50 mA | TLMO3300 | $I_V$ | 200 | 500 | | mcd |
| | | TLMO3301 | $I_V$ | 250 | | 640 | mcd |
| | | TLMO3302 | $I_V$ | 320 | | 800 | mcd |
| | | TLMO3303 | $I_V$ | 400 | | 1250 | mcd |
| Luminous flux/Luminous intensity | | | $\phi_V/I_V$ | | 3 | | mlm/ mcd |
| Dominant wavelength | $I_F$ = 50 mA | | $\lambda_d$ | 600 | 605 | 611 | nm |
| Peak wavelength | $I_F$ = 50 mA | | $\lambda_p$ | | 611 | | nm |
| Spectral bandwidth at 50 % $I_{rel\ max}$ | $I_F$ = 50 mA | | $\Delta\lambda$ | | 17 | | nm |
| Angle of half intensity | $I_F$ = 50 mA | | $\varphi$ | | ± 60 | | deg |
| Forward voltage | $I_F$ = 50 mA | | $V_F$ | 1.85 | 2.1 | 2.55 | V |
| Reverse current | $V_R$ = 5 V | | $V_R$ | | 0.01 | 10 | µA |

## Yellow

**TLMY33..**

| Parameter | Test condition | Part | Symbol | Min | Typ. | Max | Unit |
|---|---|---|---|---|---|---|---|
| Luminous intensity | $I_F$ = 50 mA | TLMY3300 | $I_V$ | 200 | 450 | | mcd |
| | | TLMY3301 | $I_V$ | 250 | | 640 | mcd |
| | | TLMY3302 | $I_V$ | 320 | | 800 | mcd |
| | | TLMY3303 | $I_V$ | 400 | | 1250 | mcd |
| Luminous flux/Luminous intensity | | | $\phi_V/I_V$ | | 3 | | mlm/ mcd |
| Dominant wavelength | $I_F$ = 50 mA | | $\lambda_d$ | 583 | 588 | 594 | nm |
| Peak wavelength | $I_F$ = 50 mA | | $\lambda_p$ | | 590 | | nm |
| Spectral bandwidth at 50 % $I_{rel\ max}$ | $I_F$ = 50 mA | | $\Delta\lambda$ | | 18 | | nm |
| Angle of half intensity | $I_F$ = 50 mA | | $\varphi$ | | ± 60 | | deg |
| Forward voltage | $I_F$ = 50 mA | | $V_F$ | 1.85 | 2.1 | 2.55 | V |
| Reverse current | $V_R$ = 5 V | | $V_R$ | | 0.01 | 10 | µA |

## Forward Voltage Classification

| Group | Forward Voltage (V) | |
|---|---|---|
| | min | max |
| 1 | 1.85 | 2.25 |
| 2 | 2.15 | 2.55 |

## Color Classification

| Group | Dominant Wavelength (nm) | | | | | |
|---|---|---|---|---|---|---|
| | Red | | Soft Orange | | Yellow | |
| | min | max | min | max | min | max |
| 1 | 611 | 618 | 598 | 601 | 581 | 584 |
| 2 | 614 | 622 | 600 | 603 | 583 | 586 |
| 3 | | | 602 | 605 | 585 | 588 |
| 4 | | | 604 | 607 | 587 | 590 |
| 5 | | | 606 | 609 | 589 | 592 |
| 6 | | | 608 | 611 | 591 | 594 |

## Luminous Intensity Classification

| Group | Luminous Intensity (mcd) | |
|---|---|---|
| | min | max |
| Xa | 160 | 250 |
| Xb | 200 | 320 |
| Ya | 250 | 400 |
| Yb | 320 | 500 |
| Za | 400 | 630 |
| Zb | 500 | 800 |
| 0a | 630 | 1000 |
| 0b | 800 | 1250 |

## Group Name on Label

| Luminous Intensity Group | Halfgroup | Wavelength | Forward Voltage |
|---|---|---|---|
| Z | b | 2 | 1 |

One packing unit/tape contains only one classification group of luminous intensity, color and forward voltage

Only one single classification groups is not available

The given groups are not order codes, customer specific group combinations require marketing agreement

No color subgrouping for Super Red

## Typical Characteristics ($T_{amb}$ = 25 °C unless otherwise specified)




Figure 1. Power Dissipation vs. Ambient Temperature




Figure 3. Rel. Luminous Intensity vs. Angular Displacement




Figure 2. Forward Current vs. Ambient Temperature




Figure 4. Relative Intensity vs. Wavelength




Figure 5. Change of Forward Voltage vs. Ambient Temperature




Figure 6. Relative Luminous Intensity vs. Amb. Temperature




Figure 7. Change of Dominant Wavelength vs. Ambient Temperature




Figure 8. Relative Luminous Intensity vs. Forward Current




Figure 9. Change of Dominant Wavelength vs. Forward Current




Figure 10. Relative Intensity vs. Wavelength




Figure 11. Change of Forward Voltage vs. Ambient Temperature




Figure 14. Relative Luminous Intensity vs. Forward Current




Figure 12. Relative Luminous Intensity vs. Amb. Temperature




Figure 15. Change of Dominant Wavelength vs. Forward Current




Figure 13. Change of Dominant Wavelength vs. Ambient Temperature




Figure 16. Relative Intensity vs. Wavelength




Figure 17. Change of Forward Voltage vs. Ambient Temperature




Figure 18. Relative Luminous Intensity vs. Amb. Temperature




Figure 19. Change of Dominant Wavelength vs. Ambient Temperature




Figure 20. Relative Luminous Intensity vs. Forward Current




Figure 21. Change of Dominant Wavelength vs. Forward Current




Figure 22. Relative Intensity vs. Wavelength




Figure 23. Forward Current vs. Forward Voltage




Figure 24. Forward Current vs. Forward Voltage




Figure 25. Change of Forward Voltage vs. Ambient Temperature




Figure 26. Relative Luminous Intensity vs. Amb. Temperature




Figure 27. Change of Dominant Wavelength vs. Ambient Temperature




Figure 28. Relative Luminous Intensity vs. Forward Current




Figure 29. Change of Dominant Wavelength vs. Forward Current




Figure 30. Forward Current vs. Pulse Length

## Package Dimensions in mm



## Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operatingsystems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

**Vishay Semiconductor GmbH** has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

**Vishay Semiconductor GmbH** can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

**We reserve the right to make changes to improve technical design and may do so without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423

ООО «ЛайфЭлектроникс» “LifeElectronics” LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

*Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.*

*С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров*

*Мы предлагаем:*

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

*В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.*

*Конструкторский отдел помогает осуществить:*

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

*Тел: +7 (812) 336 43 04 (многоканальный)*
*Email: org@lifeelectronics.ru*

***www.lifeelectronics.ru***