

## Vertical Surface Mounting Capacitors




Fig.1 Component outline

### FEATURES

- New Vishay OS-CON series as results of polymerized organic semiconductor as electrolyte
- Features superior heat-proof characteristics compared with previously developed Vishay OS-CON series
- Particularly effective when used as surface mounting devices of the switching power supply
- Rated ripple current values are guaranteed at 105 °C
- No need to consider derating on maximum allowable ripple current



**RoHS**  
COMPLIANT

| QUICK REFERENCE DATA                                                                                        |                                                                                   |                                                        |             |
|-------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------------------------------------------------------|-------------|
| DESCRIPTION                                                                                                 | VALUE                                                                             |                                                        |             |
| Operating Temperature Range                                                                                 | - 55 °C to + 105 °C                                                               |                                                        |             |
| Capacitance Tolerance at 120 Hz                                                                             | M: ± 20 %                                                                         |                                                        |             |
| Tangent of Loss Angle (tan δ) at 120 Hz                                                                     | Values in Standard Ratings Table                                                  |                                                        |             |
| Leakage Current (µA/2 minutes) (or less)*                                                                   | Values in Standard Ratings Table                                                  |                                                        |             |
| Equivalent Series Resistance (Ω), (100 k to 300 kHz)                                                        | Values in Standard Ratings Table                                                  |                                                        |             |
| Characteristics at high temp. and low temp.<br>Impedance Ratio at 100 kHz, + 20 °C                          | - 55 °C                                                                           | Z/Z <sub>20 °C</sub>                                   | 1.0 to 1.25 |
|                                                                                                             | + 105 °C                                                                          | Z/Z <sub>20 °C</sub>                                   | 0.75 to 1.0 |
| Endurance + 105 °C, 2000 hours<br>Rated Voltage Applied (25 WV to 20 V)<br>(1000 hours for A5/B6 sizes)     | ΔC/C                                                                              | Within ± 20 %                                          |             |
|                                                                                                             | tan δ                                                                             | ≤ 1.5 x the value of Tangent of Loss Angle             |             |
|                                                                                                             | ESR                                                                               | ≤ 1.5 x the value of ESR                               |             |
|                                                                                                             | Leakage Current                                                                   | ≤ The Value of Leakage Current                         |             |
| Damp heat (Steady state)<br>(+ 60 °C, 90 to 95 % RH, 1000 hours, no voltage)<br>(500 hours for A5/B6 sizes) | ΔC/C                                                                              | Within ± 20 %                                          |             |
|                                                                                                             | tan δ                                                                             | ≤ 1.5 x the value of Tangent of Loss Angle             |             |
|                                                                                                             | ESR                                                                               | ≤ 1.5 x the value of ESR                               |             |
|                                                                                                             | Leakage Current                                                                   | ≤ The Value of Leakage Current after Voltage Treatment |             |
| Reverse Voltage Guarantee                                                                                   | Temporary: < 20 % of the rated voltage<br>Continuous: < 10 % of the rated voltage |                                                        |             |
| Solder heat resistance (VPS)**<br>(215 °C x 90 s) or (230 °C x 60 s)<br>(Please consult us for A5/B6 sizes) | ΔC/C                                                                              | Within ± 10 %                                          |             |
|                                                                                                             | tan δ                                                                             | ≤ 1.3 x the value of Tangent of Loss Angle             |             |
|                                                                                                             | ESR                                                                               | ≤ 1.3 x the value of ESR                               |             |
|                                                                                                             | Leakage Current                                                                   | ≤ The Value of Leakage Current after Voltage Treatment |             |

\* If any doubt arises, measure the current after applying voltage (voltage treatment). Voltage Treatment: The rated voltage is applied to Vishay OS-CON (2.5 to 20 WV) for 120 minutes at 105 °C. (However, 20 V is applied to a 25 WV Vishay OS-CON).


\*\* Refer to Standard Ratings table for soldering recommendation.

### DIMENSIONS in millimeters



| DIMENSIONS in millimeters |              |           |            |            |            |            |            |
|---------------------------|--------------|-----------|------------|------------|------------|------------|------------|
| SIZE CODE                 | Ø D<br>± 0.5 | L<br>max. | W<br>± 0.2 | H<br>± 0.2 | C<br>± 0.2 | R          | P<br>± 0.2 |
| A5                        | 4.0          | 5.5       | 4.3        | 4.3        | 5.0        | 0.5 to 0.8 | 1.0        |
| B6                        | 5.0          | 6.0       | 5.3        | 5.3        | 6.0        | 0.5 to 0.8 | 1.4        |
| C6                        | 6.3          | 6.0       | 6.6        | 6.6        | 7.3        | 0.5 to 0.8 | 2.1        |
| E7                        | 8.0          | 7.0       | 8.3        | 8.3        | 9.0        | 0.5 to 0.8 | 3.2        |
| F8                        | 10.0         | 8.0       | 10.3       | 10.3       | 11.0       | 0.5 to 0.8 | 4.6        |
| E12                       | 8.0          | 12.0      | 8.3        | 8.3        | 9.0        | 0.8 to 1.1 | 3.2        |
| F12                       | 10.0         | 12.7      | 10.3       | 10.3       | 11.0       | 0.8 to 1.1 | 4.6        |

## RECOMMENDED LAND PATTERN



## DIMENSIONS in millimeters

| SIZE CODE | a   | b    | c   |
|-----------|-----|------|-----|
| A5        | 1.0 | 6.2  | 1.6 |
| B6        | 1.4 | 7.4  | 1.6 |
| C6        | 2.1 | 9.1  | 1.6 |
| E7        | 2.8 | 11.1 | 1.9 |
| F8        | 4.3 | 13.1 | 1.9 |
| E12       | 2.8 | 11.1 | 1.9 |
| F12       | 4.3 | 13.1 | 1.9 |

## CASE CODE LIST

| CAPACITANCE<br>(μF) | WV<br>(SV) | 2.5<br>(3.3) | 4<br>(5.2) | 6.3<br>(8.2) | 10<br>(11.5) | 16<br>(18.4) | 20<br>(23) | 25<br>(25) |
|---------------------|------------|--------------|------------|--------------|--------------|--------------|------------|------------|
| 3.3                 | -          | -            | -          | -            | -            | A5           | -          | -          |
| 4.7                 | -          | -            | -          | -            | A5           | -            | -          | -          |
| 6.8                 | -          | -            | -          | -            | A5           | -            | -          | C6         |
| 10.0                | -          | -            | -          | -            | A5           | -            | B6         | E7         |
| 15.0                | -          | -            | -          | -            | A5           | B6           | -          | -          |
| 27.0                | -          | -            | -          | -            | -            | -            | C6         | -          |
| 22.0                | -          | -            | -          | A5           | -            | B6           | C6         | F8         |
| 33.0                | -          | -            | A5         | -            | B6           | -            | E7         | E12        |
| 39.0                | -          | -            | B6         | -            | -            | C6           | -          | -          |
| 47.0                | -          | -            | -          | B6           | C6           | -            | E7         | -          |
| 56.0                | -          | -            | -          | -            | C6           | E7           | F8         | F12        |
| 68.0                | -          | -            | B6         | -            | -            | -            | F8         | -          |
| 82.0                | -          | -            | -          | C6           | -            | E7           | -          | -          |
| 100.0               | -          | -            | -          | C6           | -            | F8           | E12        | -          |
| 120.0               | -          | -            | -          | -            | E7           | -            | -          | -          |
| 150.0               | -          | -            | C6, E7     | -            | E7, F8       | F8           | F12        | -          |
| 180.0               | -          | -            | -          | -            | -            | E12          | -          | -          |
| 220.0               | -          | -            | -          | E7, F8       | -            | -            | -          | -          |
| 270.0               | -          | -            | -          | -            | E7, F8       | -            | -          | -          |
| 330.0               | -          | -            | E7         | F8           | E12          | F12          | -          | -          |
| 470.0               | -          | -            | -          | F8, E12      | -            | -            | -          | -          |
| 560.0               | -          | -            | E12        | -            | F12          | -            | -          | -          |
| 680.0               | -          | E12          | F8         | -            | -            | -            | -          | -          |
| 820.0               | -          | -            | -          | F12          | -            | -            | -          | -          |
| 1200.0              | -          | -            | F12        | -            | -            | -            | -          | -          |
| 1500.0              | -          | F12          | -          | -            | -            | -            | -          | -          |

\*\*\* WV = Rated Voltage. \*\*\*\* (SV) = Surge Voltage (at room temperature). The description contents are subject to change due to technical improvement without notice. Please ask for latest specifications for order and use.

## STANDARD RATINGS

| CASE CODE | PART NUMBER*    | RATED VOLTAGE (V) | RATED CAPACITANCE (μF) | MAX. ESR (100 k to 300 kHz) (mΩ) | ALLOWABLE RIPPLE CURRENT (mAmps) at 100 kHz, + 105 °C | MAX. TANGENT OF LOSS ANGLE | MAX. LEAKAGE CURRENT (μA) (After 2 Minutes) |
|-----------|-----------------|-------------------|------------------------|----------------------------------|-------------------------------------------------------|----------------------------|---------------------------------------------|
| A5        | 94SVP335X0016A5 | 16                | 3.3                    | 280                              | 590                                                   | 0.07                       | 26.4                                        |
|           | 94SVP475X0010A5 | 10                | 4.7                    | 260                              | 660                                                   | 0.08                       | 23.5                                        |
|           | 94SVP685X0010A5 | 10                | 6.8                    | 260                              | 660                                                   | 0.09                       | 34.0                                        |
|           | 94SVP106X0010A5 | 10                | 10                     | 240                              | 670                                                   | 0.10                       | 50.0                                        |
|           | 94SVP156X0010A5 | 10                | 15                     | 240                              | 670                                                   | 0.10                       | 75.0                                        |
|           | 94SVP226X06R3A5 | 6.3               | 22                     | 220                              | 700                                                   | 0.12                       | 69.3                                        |
|           | 94SVP336X0004A5 | 4                 | 33                     | 200                              | 740                                                   | 0.15                       | 66.0                                        |

\* Part Numbers shown are for ± 20 % capacitance tolerance (X0).

| STANDARD RATINGS |                   |                   |                        |                                  |                                                       |                            |                                             |
|------------------|-------------------|-------------------|------------------------|----------------------------------|-------------------------------------------------------|----------------------------|---------------------------------------------|
| CASE CODE        | PART NUMBER*      | RATED VOLTAGE (V) | RATED CAPACITANCE (μF) | MAX. ESR (100 k to 300 kHz) (mΩ) | ALLOWABLE RIPPLE CURRENT (mAmps) at 100 kHz, + 105 °C | MAX. TANGENT OF LOSS ANGLE | MAX. LEAKAGE CURRENT (μA) (After 2 Minutes) |
| B6               | 94SVP106X0020B6   | 20                | 10                     | 170                              | 850                                                   | 0.10                       | 100                                         |
|                  | 94SVP156X0016B6   | 16                | 15                     | 150                              | 920                                                   | 0.10                       | 120                                         |
|                  | 94SVP226X0016B6   | 16                | 22                     | 150                              | 920                                                   | 0.15                       | 176                                         |
|                  | 94SVP336X0010B6   | 10                | 33                     | 130                              | 990                                                   | 0.15                       | 165                                         |
|                  | 94SVP476X006R3B6  | 6.3               | 47                     | 90                               | 1060                                                  | 0.15                       | 148                                         |
|                  | 94SVP396X0004B6   | 4                 | 39                     | 70                               | 1100                                                  | 0.15                       | 78                                          |
|                  | 94SVP686X0004B6   | 4                 | 68                     | 70                               | 1100                                                  | 0.15                       | 136                                         |
| C6               | 94SVP685X0025C6   | 25                | 6.8                    | 80                               | 1200                                                  | 0.10                       | 85                                          |
|                  | 94SVP226X0020C6   | 20                | 22                     | 65                               | 1390                                                  | 0.10                       | 88                                          |
|                  | 94SVP276X0020C6   | 20                | 27                     | 60                               | 1450                                                  | 0.10                       | 108                                         |
|                  | 94SVP396X0016C6   | 16                | 39                     | 65                               | 1390                                                  | 0.10                       | 125                                         |
|                  | 94SVP476X0010C6   | 10                | 47                     | 60                               | 1450                                                  | 0.12                       | 94                                          |
|                  | 94SVP566X0010C6   | 10                | 56                     | 55                               | 1510                                                  | 0.12                       | 112                                         |
|                  | 94SVP107X006R3C6  | 6.3               | 100                    | 40                               | 1810                                                  | 0.12                       | 126                                         |
|                  | 94SVP826X006R3C6  | 6.3               | 82                     | 50                               | 1570                                                  | 0.12                       | 103                                         |
|                  | 94SVP157X0004C6   | 4                 | 150                    | 50                               | 1620                                                  | 0.12                       | 120                                         |
| E7               | 94SVP106X0025E7   | 25                | 10                     | 60                               | 1500                                                  | 0.10                       | 125                                         |
|                  | 94SVP336X0020E7   | 20                | 33                     | 50                               | 1700                                                  | 0.12                       | 132                                         |
|                  | 94SVP476X0020E7   | 20                | 47                     | 50                               | 1700                                                  | 0.12                       | 188                                         |
|                  | 94SVP566X0016E7   | 16                | 56                     | 50                               | 1800                                                  | 0.12                       | 179                                         |
|                  | 94SVP826X0016E7   | 16                | 82                     | 45                               | 1890                                                  | 0.12                       | 262                                         |
|                  | 94SVP127X0010E7   | 10                | 120                    | 40                               | 2120                                                  | 0.12                       | 240                                         |
|                  | 94SVP157X0010E7   | 10                | 150                    | 35                               | 2560                                                  | 0.12                       | 300                                         |
|                  | 94SVP157X0004E7   | 4                 | 150                    | 35                               | 2350                                                  | 0.12                       | 120                                         |
|                  | 94SVP337X0004E7   | 4                 | 330                    | 35                               | 2560                                                  | 0.12                       | 264                                         |
|                  | 94SVP227X006R3E7  | 6.3               | 220                    | 35                               | 2560                                                  | 0.12                       | 277                                         |
| F8               | 94SVP226X0025F8   | 25                | 22                     | 50                               | 2000                                                  | 0.10                       | 275                                         |
|                  | 94SVP566X0020F8   | 20                | 56                     | 45                               | 2200                                                  | 0.12                       | 224                                         |
|                  | 94SVP686X0020F8   | 20                | 68                     | 45                               | 2200                                                  | 0.12                       | 272                                         |
|                  | 94SVP107X0016F8   | 16                | 100                    | 40                               | 2400                                                  | 0.12                       | 320                                         |
|                  | 94SVP157X0016F8   | 16                | 150                    | 35                               | 2670                                                  | 0.12                       | 480                                         |
|                  | 94SVP157X0010F8   | 10                | 150                    | 35                               | 2670                                                  | 0.12                       | 300                                         |
|                  | 94SVP277X0010F8   | 10                | 270                    | 30                               | 3020                                                  | 0.12                       | 540                                         |
|                  | 94SVP227X006R3F8  | 6.3               | 220                    | 30                               | 3020                                                  | 0.12                       | 277                                         |
|                  | 94SVP477X006R3F8  | 6.3               | 470                    | 25                               | 3700                                                  | 0.12                       | 592                                         |
|                  | 94SVP337X006R3F8  | 6.3               | 330                    | 25                               | 3300                                                  | 0.12                       | 416                                         |
|                  | 94SVP687X0004F8   | 4                 | 680                    | 25                               | 3700                                                  | 0.12                       | 544                                         |
| E12              | 94SVP336X0025E12  | 25                | 33                     | 30                               | 2980                                                  | 0.12                       | 413                                         |
|                  | 94SVP107X0020E12  | 20                | 100                    | 25                               | 3260                                                  | 0.15                       | 400                                         |
|                  | 94SVP187X0016E12  | 16                | 180                    | 22                               | 3480                                                  | 0.15                       | 576                                         |
|                  | 94SVP337X0010E12  | 10                | 330                    | 19                               | 3740                                                  | 0.15                       | 660                                         |
|                  | 94SVP477X006R3E12 | 6.3               | 470                    | 17                               | 3960                                                  | 0.15                       | 592                                         |
|                  | 94SVP567X0004E12  | 4                 | 560                    | 16                               | 4080                                                  | 0.15                       | 448                                         |
|                  | 94SVP687X002R5E12 | 2.5               | 680                    | 16                               | 4080                                                  | 0.15                       | 340                                         |
|                  | 94SVP566X0025F12  | 25                | 56                     | 28                               | 3800                                                  | 0.12                       | 700                                         |
| F12              | 94SVP157X0020F12  | 20                | 150                    | 21                               | 4220                                                  | 0.15                       | 600                                         |
|                  | 94SVP337X0016F12  | 16                | 330                    | 17                               | 4580                                                  | 0.15                       | 792                                         |
|                  | 94SVP567X0010F12  | 10                | 560                    | 15                               | 4870                                                  | 0.15                       | 840                                         |
|                  | 94SVP827X006R3F12 | 6.3               | 820                    | 14                               | 5040                                                  | 0.15                       | 775                                         |
|                  | 94SVP128X0004F12  | 4                 | 1200                   | 13                               | 5230                                                  | 0.18                       | 960                                         |
|                  | 94SVP158X002R5F12 | 2.5               | 1500                   | 13                               | 5230                                                  | 0.18                       | 750                                         |

\* Part Numbers shown are for ± 20 % capacitance tolerance (X0).



### Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)