



Jan. 2017 Ver.2.0.a  
TDK Corporation

## Multilayer High Pass Filter

For 2.4GHz W-LAN & Bluetooth


DEA Series 2.0x1.25mm [EIA 0805] TYPE

P/N: **DEA202400HT-8037A1**

**DEA202400HT-8037A1****■ SHAPES AND DIMENSIONS**

[Top View]

[Bottom View]



Dimensions (mm)

| L       | W       | T       | a       | b       | c       | d       |
|---------|---------|---------|---------|---------|---------|---------|
| 2.00    | 1.25    | 0.90    | 0.275   | 0.25    | 0.60    | 0.95    |
| +/-0.15 | +/-0.10 | +/-0.10 | +/-0.10 | +/-0.10 | +/-0.10 | +/-0.10 |

Terminal functions

|     |             |
|-----|-------------|
| (1) | Input Port  |
| (2) | GND         |
| (3) | Output Port |

**■ TEMPERATURE RANGE**

| Operating temperature | Storage temperature |
|-----------------------|---------------------|
| -40 to +85 °C         | -40 to +85 °C       |

## DEA202400HT-8037A1

### ■ ELECTRICAL CHARACTERISTICS

( Measurement )

| Parameter                      | Frequency (MHz) | TDK Spec     |      |      |
|--------------------------------|-----------------|--------------|------|------|
|                                |                 | Min.         | Typ. | Max. |
| Insertion Loss (dB)            | 2400 to 5850    | -            | 0.35 | 0.50 |
| Attenuation (dB)               | 1610            | 30           | 47   | -    |
| Characteristic Impedance (ohm) |                 | 50 (Nominal) |      |      |


Ta = +25+/-5°C

Jan. 2017 Ver.2.0.a


TDK Corporation

**DEA202400HT-8037A1****FREQUENCY CHARACTERISTICS**


S11 POLA REF 1.0 U SCALE 1.0U FS




S21 Log MAG REF 0.0dB SCALE 1dB/




S21 Log MAG REF 0.0dB SCALE 5.0dB/



S11 Log MAG REF -10.0dB SCALE 5.0dB/



S21 Log MAG REF 0.0dB SCALE 5.0dB/



MARKER 7  
1510 MHz  
46.8 dB

MARKER 8  
1610 MHz  
47.7 dB

MARKER 9  
2400 MHz  
0.30 dB

MARKER 10  
4125 MHz  
0.18 dB

MARKER 11  
5850 MHz  
0.35 dB


All specifications are subject to change without notice.

TDK Technology - Proprietary and Confidential Information of TDK Group Companies

Jan. 2017 Ver.2.0.a  
TDK Corporation

## DEA202400HT-8037A1

### ■ RECOMMENDED LAND PATTERN




### ■ ENVIRONMENT INFORMATION

RoHS Statement  
RoHS Compliance

TDK Corporation

## RECOMMENDED REFLOW PROFILE



| Preheating |       |              | Soldering                |              |              |            |
|------------|-------|--------------|--------------------------|--------------|--------------|------------|
|            |       |              | Critical zone (T3 to T4) |              | Peak         |            |
| Temp.      |       | Time         | Temp.                    | Time         | Temp.        | Time       |
| T1         | T2    | t1           | T3                       | t2           | T4           | t3 *       |
| 150°C      | 200°C | 60 to 120sec | 217°C                    | 60 to 120sec | 240 to 260°C | 30 sec Max |

\* t3 : Time within 5°C of actual peak temperature

The maximum number of reflow is 3.


Note: Lead free solder is recommended.  
Recommended solder is Sn-3.0Ag-0.5Cu. (M705 by Senju Metal Industry)

Jan. 2017 Ver.2.0.a  
TDK Corporation


## DEA202400HT-8037A1

### ■ PACKAGING STYLE

#### Reel Dimensions



#### Carrier Tape



| STANDARD PACKAGE QUANTITY<br>( pieces/reel ) |
|----------------------------------------------|
| 2,000                                        |

## REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

### SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using these products.

#### REMINDERS

The products listed on this specification sheet are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property. Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below or for any other use exceeding the range or conditions set forth in this specification sheet.

1. Aerospace/Aviation equipment
2. Transportation equipment (cars, electric trains, ships, etc.)
3. Medical equipment
4. Power-generation control equipment
5. Atomic energy-related equipment
6. Seabed equipment
7. Transportation control equipment
8. Public information-processing equipment
9. Military equipment
10. Electric heating apparatus, burning equipment
11. Disaster prevention/crime prevention equipment
12. Safety equipment
13. Other applications that are not considered general-purpose applications

When using this product in general-purpose applications, you are kindly requested to take into consideration securing protection circuit/equipment or providing backup circuits, etc., to ensure higher safety.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)