



TECHNICAL DATA SHEET

Document number: TTDS-108

Issue: 5

Date: May 2012

HX-SCE Heat shrinkable sleeves

| | |
|---|---|
| MATERIAL DESCRIPTION: | Thin wall, zero-halogen, low smoke, low toxicity, radiation cross-linked, UV stabilised polyolefin heat-shrinkable tubing, assembled as cut sleeves organized in a ladder format. |
| USE: | Identification of wires and cables by computer-based printing onto sleeves. Ideal for applications where LFH characteristics are critical. The self extinguishing properties with low smoke and low toxic fume emissions make this product ideal for use in enclosed spaces such as mass transit, marine and industrial installations. This product is not recommended where strain relief properties are required. |
| PRINT METHOD/RIBBON: | Refer to TE Identification TT Printer Product Ribbon Matrix Document 411-121005 |
| CONTINUOUS OPERATING TEMPERATURE: | -55°C to +105°C (-40°F to +221°F). |
| MINIMUM RECOVERY TEMPERATURE: | 120°C (248°F). |
| COLOURS: | White or Yellow. Other colors available on request. |
| FLAMMABILITY: | Self-extinguishing (ASTM D2671 Procedure B) Maximum flame spread index, $I_s \leq 35$ (ASTM E 162) |
| OXYGEN INDEX: | 34% minimum (BS EN ISO 4589-2 [1996]). |
| SMOKE EMISSION (A₀) | 0.017 maximum (BS 6853 [1999] Annex D.8.3). |
| SMOKE DENSITY | ASTM E 662 Maximum D _s (1.5) ≤ 100 , D _s (4) ≤ 200 (Flaming and non flaming modes) |
| TOXIC FUME (R) | < 1 (BS 6853 [1999] Annex B – Mass based test method - NF X 70-100) |
| LUL TOXIC FUME (ELEMENTAL ANALYSIS): | No Halogens, P, S, or N sources above trace level (1-085 A3 Fire Safety Performance of Materials). |

Page 1 of 5

Business locations:

☎ N America: + 1 650 361 3860 (West Coast)
☎ France: +33 (0) 476 099696 (Labels)
☎ Germany: + 49 (0) 6074 89080
☎ UK: + 44 (0) 1495 244000 (Labels)
☎ Japan: + 81 (0) 44 900 5102

☎ N America: + 1 401 751 6505 (East Coast)
☎ France: + 33 (0) 134 20 21 22 (Other products)
☎ UK: + 44 (0) 1793 528171 (Other products)
☎ Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. TE Connectivity makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. TE Connectivity only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. TE Connectivity Specifications are subject to change without notice. In addition TE Connectivity reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.



TECHNICAL DATA SHEET

Document number: TTDS-108

Issue: 5

Date: May 2012

HX-SCE Heat shrinkable sleeves

| | |
|---------------------------------|--|
| DIELECTRIC STRENGTH: | 15kV/mm minimum. |
| WATER ABSORPTION: | 1% maximum after 24 hours at 23°C (73°F). |
| COPPER MIRROR CORROSION: | 8% maximum after 16 hours at 150°C (302°F). |
| LONGITUDINAL CHANGE: | +5% to -10%. |
| TENSILE STRENGTH: | 7MPa minimum. |
| ULTIMATE ELONGATION: | 80% minimum. |
| SECANT MODULUS: | 200MPa maximum at 2% elongation. |
| UV RESISTANCE: | Tensile Strength > 90% & Ultimate Elongation > 40% of original value after 1000 hours (ASTM G53: UVA [100% dry cycle]; UVB [8 hours dry/4 hours wet cycle]). |
| PRINT PERMANENCE: | |
| - ADHERENCE | SAE AS5942 ⁱ : 1Kg load 50 rubs: Legible. |
| - FLUID RESISTANCE | MIL-STD-202 Method 215: 3 cycles, 30 brush strokes: Legible. BS EN 50343: 2003: Appendix H: Legible. London Underground specific test fluids to CC3349: Legible. |

ⁱ SAE AS81531 cancelled Oct 2011, superseded by SAE AS5942.

Page 2 of 5

Business locations:

☎ N America: + 1 650 361 3860 (West Coast)
☎ France: +33 (0) 476 099696 (Labels)
☎ Germany: + 49 (0) 6074 89080
☎ UK: + 44 (0) 1495 244000 (Labels)
☎ Japan: + 81 (0) 44 900 5102

☎ N America: + 1 401 751 6505 (East Coast)
☎ France: + 33 (0) 134 20 21 22 (Other products)
☎ UK: + 44 (0) 1793 528171 (Other products)
☎ Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. TE Connectivity makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. TE Connectivity only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. TE Connectivity Specifications are subject to change without notice. In addition TE Connectivity reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.



TECHNICAL DATA SHEET

Document number: TTDS-108

Issue: 5

Date: May 2012

HX-SCE Heat shrinkable sleeves

FLUID RESISTANCE, DETAIL:

| THREAT | TEST | EFFECT |
|--|--|---------------|
| Xylene / butylacetate / cyclohexanone mix (Paint stripper) | 10 Cycles, Crockmeter | Print legible |
| Diesel | 10 Cycles, Crockmeter | Print legible |
| Tunnel dust/white spirit | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| Water | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| Tunnel Dust and Oil (50%/50%) | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| Tunnel Dust and Water (50%/50%) | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| White Spirits | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| Diesel | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| Grease | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| Wash cycle test | 25 cycles at 75°C (167°F), 25 wipes | Print legible |

Page 3 of 5

Business locations:

☎ N America: + 1 650 361 3860 (West Coast)

☎ France: +33 (0) 476 099696 (Labels)

☎ Germany: + 49 (0) 6074 89080

☎ UK: + 44 (0) 1495 244000 (Labels)

☎ Japan: + 81 (0) 44 900 5102

☎ N America: + 1 401 751 6505 (East Coast)

☎ France: + 33 (0) 134 20 21 22 (Other products)

☎ UK: + 44 (0) 1793 528171 (Other products)

☎ Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. TE Connectivity makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. TE Connectivity only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. TE Connectivity Specifications are subject to change without notice. In addition TE Connectivity reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.



TECHNICAL DATA SHEET

Document number: TTDS-108

Issue: 5

Date: May 2012

HX-SCE Heat shrinkable sleeves

FLUID RESISTANCE, DETAIL:

(Continued)

| THREAT | TEST | EFFECT |
|---|---|---------------|
| Glycol rail de-icer (50% glycol/50% water) | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| Cleaning solvent | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| Surface Cleaner (PGP500) | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| Multi-Purpose Graffiti remover gel | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| CGR gel (Chewing gum remover) | LUL C3349 (72hours, 20 strokes dry tissue) | Print legible |
| IRM 902 oil | BS EN 50343 (24 hours at 50°C (122°F) 10 cycles with Crockmeter) | Print legible |
| Hydrochloric acid 5% solution | BS EN 50343 (1 minute at 23°C (73°F) 10 cycles with Crockmeter) | Print legible |
| Sodium Hydroxide 5% solution | BS EN 50343 (1 minute at 23°C (73°F) 10 cycles with Crockmeter) | Print legible |
| Heat Aging | BS EN 50343 (240hrs 120°C (248°F), 10 cycles with Crockmeter) | Print legible |
| Wash cycle test | 25 cycles at 75°C (167°F), 25 wipes with cloth | Print legible |

Page 4 of 5

Business locations:

☎ N America: + 1 650 361 3860 (West Coast)

☎ France: +33 (0) 476 099696 (Labels)

☎ Germany: + 49 (0) 6074 89080

☎ UK: + 44 (0) 1495 244000 (Labels)

☎ Japan: + 81 (0) 44 900 5102

☎ N America: + 1 401 751 6505 (East Coast)

☎ France: + 33 (0) 134 20 21 22 (Other products)

☎ UK: + 44 (0) 1793 528171 (Other products)

☎ Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. TE Connectivity makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. TE Connectivity only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. TE Connectivity Specifications are subject to change without notice. In addition TE Connectivity reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.



TECHNICAL DATA SHEET

Document number: TTDS-108

Issue: 5

Date: May 2012

HX-SCE Heat shrinkable sleeves

FLUID RESISTANCE, DETAIL:

(Continued)

| THREAT | TEST | EFFECT |
|--|---|--|
| Aircraft fuel (ISO 1817 Liquid B) | 24 hours at 40°C (104°F) then 25 strokes dry tissue; IEC 60684-2 – Tensile Strength and Ultimate Elongation | Print legible; 4MPa TS & 90% UE retained |
| Silicone fluid (S1714) | 24 hours at 50°C (122°F) then 25 strokes dry tissue; IEC 60684-2 – Tensile Strength and Ultimate Elongation | Print legible; 4MPa TS & 90% UE retained |
| Propan-2-ol | 24 hours at 23°C (73°F) then 25 strokes dry tissue; IEC 60684-2 – Tensile Strength and Ultimate Elongation | Print legible; 4MPa TS & 90% UE retained |
| De-icing fluid (50% ethylene glycol in water) | 24 hours at 23°C (73°F) then 25 strokes dry tissue; IEC 60684-2 – Tensile Strength and Ultimate Elongation | Print legible; 4MPa TS & 90% UE retained |
| Sullage fluid (formaldehyde/cresol) | 24 hours at 23°C (73°F) then 25 strokes dry tissue; IEC 60684-2 – Tensile Strength and Ultimate Elongation | Print legible; 4MPa TS & 90% UE retained |

Page 5 of 5

Business locations:

☎ N America: + 1 650 361 3860 (West Coast)
☎ France: +33 (0) 476 099696 (Labels)
☎ Germany: + 49 (0) 6074 89080
☎ UK: + 44 (0) 1495 244000 (Labels)
☎ Japan: + 81 (0) 44 900 5102

☎ N America: + 1 401 751 6505 (East Coast)
☎ France: + 33 (0) 134 20 21 22 (Other products)
☎ UK: + 44 (0) 1793 528171 (Other products)
☎ Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. TE Connectivity makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. TE Connectivity only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. TE Connectivity Specifications are subject to change without notice. In addition TE Connectivity reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru