



CATALOG LISTING	
102TL2-70 SERIES	
CHART 1	


THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.



STYLE I LEVER



STYLE 2 LEVER



SCALE FULL

DO NOT SCALE PRINT














UNLESS OTHERWISE NOTED

DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE	(.0)	±.030
TWO PLACE	(.00)	±.015
THREE PLACE	(.000)	±.005
ANGLES		±

WEIGHT 135 LB MAX

MS NUMBER	CATALOG LISTING	AVAILABLE LOCKING COMBINATIONS FOR CONFIGURATION SEE LETTERING DETAILS	STYLE NUMBER	CURRENT CAPACITY (AMPS)								
				RESISTIVE DC VOLTS			LOAD AC VOLTS		LAMP LOAD	INDUCTIVE LOAD		
				28	125	250	125	250	28 VDC	125 VAC	28 VDC	125 VAC
27785-3	102TL2-70	NONE	1	18	.75	.5	11	6	5	2	10	8
27788-3 	102TL2-70 	A,B,D,E,F,G,H,J,K,L,M,N,P	2									
 LOCKED IN THREE POSITIONS	 LOCKED IN CENTER AND EXTREME POSITION (KEYWAY SIDE)	 LOCKED OUT OF CENTER POSITION	 LOCKED IN CENTER POSITION	 LOCKED IN EXTREME POSITION (OPPOSITE KEYWAY)								
 LOCKED IN EXTREME POSITION (KEYWAY SIDE)	 LOCKED OUT OF CENTER AND EXTREME POSITION (KEYWAY SIDE)	 LOCKED OUT OF CENTER AND EXTREME POSITION (OPPOSITE KEYWAY)	 LOCKED IN CENTER AND EXTREME POSITION (OPPOSITE KEYWAY)	 LOCKED OUT OF EXTREME POSITION (KEYWAY SIDE)								
 LOCKED OUT OF AND INTO EXTREME POSITION (OPPOSITE KEYWAY)	 LOCKED OUT OF EXTREME POSITION (OPPOSITE KEYWAY)	 LOCKED OUT OF AND INTO EXTREME POSITION (KEYWAY SIDE)										
CIRCUIT MADE WITH TOGGLE LEVER IN												
KEYWAY SIDE			CENTER			OPPOSITE KEYWAY						
												
MOMENTARY POSITION			MAINTAINED POSITION			MOMENTARY POSITION						
												

NOTES

- 1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
- 2 - CIRCUIT DESIGNATION, MICRO SWITCH CATALOG LISTING, DATE CODE AND MS NUMBER IDENTIFIED ON SIDE OF SWITCH
- 3 - FURNISHED UNASSEMBLED
- 4 - UNUSED TERMINAL HOLES MAY BE SEALED WITH PLUGS M83723/28-20
- 5 - KEYWAY SHOWN ON LEFT SIDE
- 6 - SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE TOGGLE LOCKING
- 7 - THE SEALING GROMMET SHALL SEAL ON A SMOOTH WIRE INSULATION OF .040 TO .083 DIAMETERS (16-20 GAGE)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru