

“Stay Connected” with



Strain Relief Bushings

a PennEngineering® Company



Heyco® Original Strain Relief Bushings

Straight-Thru for Round Cables

.375" (9,5 mm) to .500" (12,7 mm) Mounting Holes

- **Protects the lifeline of your electric/electronic products** by absorbing the forces of pull, push, and twist that maybe exerted on the flexible power cord.
- Securely anchors, insulates, and protects cables at panel entry points.
- Sizes SR 2-Series to SR 6-Series for mounting hole diameters from .375" (9,5 mm) to .500" (12,7 mm).
- See page 4-38 for corresponding **Mounting Hole Plugs** which can be used to fill blank/unused Mounting Holes and thus allow for a single panel design for multiple applications.
- See pages 4-27 & 4-28 for SR assembly tools.
- **See schematic on page 4-20.**
- For Double D Mounting Hole Punches, see page 4-30.



| WILL FIT THESE CABLES | | | | PANEL DIMENSIONS | | | | | | PART NO. | DESCRIPTION | PART DIM. | | Mounting Hole Plug | |
|------------------------------------|--------------------|------------------|---------|-------------------------|-----------|--------------------------|------|-------------------------------|------|-------------|-------------|-----------|------------------|--------------------|---------------|
| UL Type | AWG/ Conductors | Approximate Size | | A Mounting Hole Dia. | | B To Prevent Rotation | | Finished Fit Panel Thickness* | | | | Black | C BODY LENGTH | | PART NO. |
| | | in. | mm. | in. | mm. | in. | mm. | in. | mm. | in. | mm. | | | | |
| AWM | 12/1 | .125-.187 | 3,2-4,8 | .375 | 9,5 | .330 | 8,4 | .062 | 1,6 | 1060 | SR 2M-1 | .406 | 10,3 | 2617 | |
| SV & SVT | 18/2 | .220-.245 | 5,6-6,2 | .500 | 12,7 | .450 | 11,4 | .062 | 1,6 | 1157 | SR 5MN-3 | .438 | 11,1 | 2491 | |
| Same as SR 5MN-3 above except | | | | | | | | | .100 | 2,5 | 1140 | SR 5M-3 | .438 | 11,1 | 2491 |
| For custom interlock cable, not UR | | .250 | 6,4 | .560 | 14,2 | .730 | 18,5 | .125 | 3,2 | 1487 | SR 30-1A** | .672 | 17,1 | consult Heyco | |
| | | .265 | 6,7 | .560 | 14,2 | .730 | 18,5 | .125 | 3,2 | 1490 | SR 30-1B** | | | | |
| SV & SVT | 18/2 | .250 | 6,4 | .500 | 12,7 | .450 | 11,4 | .062 | 1,6 | 1150 | SR 5N-4 | .438 | 11,1 | 2491 | |
| | 18/3 | .255 | 6,5 | .500-.515 | 12,7-13,1 | | | | | | | | | | |
| HPD | 18/2 | .270 | 6,9 | .500 | 12,7 | .450 | 11,4 | .062 | 1,6 | 1150 | SR 5N-4 | .438 | 11,1 | 2491 | |
| | 16/2 | .290 | 7,4 | .500-.515 | 12,7-13,1 | | | | | | | | | | |
| SJT | 18/2 | .300 | 7,6 | .531 | 13,5 | .450 | 11,4 | .062 | 1,6 | 1150 | SR 5N-4 | .438 | 11,1 | 2491 | |
| Same as SR 5N-4 above except | | | | | | | | | | | | | | | .100 |
| | | | | | | | | | .156 | 4,0 | 1154 | SR 5L-1 | .438 | 11,1 | consult Heyco |
| SV & SVT | 18/2 | .255 | 6,5 | .500 | 12,7 | .450 | 11,4 | .100 | 2,5 | 1137 | SR 5P3-4 | .438 | 11,1 | 2491 | |
| | 18/3 | .270 | 6,9 | | | | | | | | | | | | |
| HPD | 18/2 | .290 | 7,4 | .500 | 12,7 | .465 | 11,8 | .090 | 2,3 | 1184 | SR 6W-1 | .438 | 11,1 | 2491 | |
| SJ, SJT & SJO | 18/2 | .300 | 7,6 | | | | | | | | | | | | |
| SPT-3 | 16/2 | | | | | | | | | | | | | | |

Standard color black. Consult Heyco for white and other colors.

*Maximum Panel Thickness. Part has additional clearance. Consult Heyco for your Custom Finished Fit Panel Thickness.

**Use Elongated Mounting Hole.

Quick Specs

| | |
|---------------------|--|
| Material | Nylon 6/6 |
| Certifications | Recognized under the Component Program of Underwriters' Laboratories File E15331 |
| | Certified by the Canadian Standards Association File 8919 |
| Flammability Rating | 94V-2 |
| Temperature Range | -.04°F (-18°C) to 221°F (105°C) |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru