

# Fast-acting UL Class CF CUBEFuse

**Catalog symbol**

- FCF\_RN

**Description**

The Bussmann™ series fast-acting CUBEFuse is a finger-safe, current-limiting UL Class CF branch circuit fuse. It features the smallest installed footprint of any UL Class CC, J, RK or T fuse.

**Ratings**

- Volts 600 Vac/dc
- Amps 1-100 A
- Interrupting rating
  - 300 kA RMS Sym (UL up to 60 A)
  - 200 kA (UL 70-100 A, CSA 1-100 A)
  - 50 kA DC

**Agency information**

- UL Listed Fuse: Guide JDDZ, File E4273
- CSA Certified, Class 1422- 02, File 53787
- RoHS compliant
- CE

**Catalog Numbers (amp)**

|         |         |         |          |
|---------|---------|---------|----------|
| FCF1RN  | FCF20RN | FCF45RN | FCF90RN  |
| FCF3RN  | FCF25RN | FCF50RN | FCF100RN |
| FCF6RN  | FCF30RN | FCF60RN |          |
| FCF10RN | FCF35RN | FCF70RN |          |
| FCF15RN | FCF40RN | FCF80RN |          |

**Electrical characteristics**

- 4 minutes max clearing time at 200% rated current for up to 30 A fuses
- 6 minutes max clearing time at 200% rated current for 35 to 60 A fuses
- 8 minutes max clearing time at 200% rated current for 70 to 100 A fuses

**Watts loss at rated current:**

| Fuse amps | Watts |
|-----------|-------|
| FCF15RN   | 3.48  |
| FCF30RN   | 5.45  |
| FCF60RN   | 7.27  |
| FCF100RN  | 11.50 |

**Operating and storage temperature range:**

-40°C to 80°C

**Materials**

- Case: glass filled PES (Polyethersulfone)
- Terminals: electroless tin plated copper alloy

**Features**

- The world's first finger-safe power fuse system
- Smallest installed footprint of any Class CC, J, and RK fuse
- UL Class CF meets Class J fast-acting electrical performance requirements
- Faster response to damaging faults to help reduce destructive thermal and magnetic forces
- True fast-acting fuse construction
- High interrupting rating to safely interrupt faults up to 300 kA
- No venting of arc or molten metal and gases during opening
- Low let-through currents under fault conditions


**Carton quantity and weight**

| Amps     | Qty. | Weight lbs (kg) |
|----------|------|-----------------|
| up to 30 | 12   | 1.39 (0.63)     |
| 35-60    | 12   | 1.42 (0.65)     |
| 70-100   | 6    | 1.74 (0.79)     |




Powering Business Worldwide

Dimensions – in (mm)




| Amp range | A         | B         | C         | D         | E         |
|-----------|-----------|-----------|-----------|-----------|-----------|
| 1-15      |           |           |           | 0.23 (6)  |           |
| 20        | 1.88 (48) | 0.75 (19) | 1.0 (25)  | 0.27 (7)  |           |
| 25-30     |           |           |           | 0.31 (8)  | 0.67 (17) |
| 35-40     |           |           |           | 0.36 (9)  |           |
| 45-50     | 2.13 (54) |           | 1.13 (29) | 0.44 (11) |           |
| 60        |           | 1.0 (25)  |           |           |           |
| 70        |           |           |           | 0.49 (12) | 0.64 (16) |
| 80-90     | 3.01 (76) |           | 1.26 (32) | 0.57 (14) |           |
| 100       |           |           |           |           |           |

Current limitation curves



Time-current characteristic curves — average melt



CUBEFuse holders, disconnects and panelboards

The CUBEfuse is used in the following Bussmann series products.

| Description                         | Catalog symbol | Data sheet no. |
|-------------------------------------|----------------|----------------|
| 30, 60 and 100 A holders            | TCFH_N         | 9007           |
| 1-, 2- and 3-pole UL 98 switch      | CCP2_CF        | 10801          |
| 1-, 2, and 3-pole panelboard switch | CCP2B          | 1161           |

The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com

Bussmann Division  
114 Old State Road  
Ellisville, MO 63021  
United States  
Eaton.com/bussmannseries

© 2018 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 2147 - BU-SB10811  
August 2018

**EATON**  
Powering Business Worldwide

Eaton and Bussmann are valuable trademarks of Eaton in the US and other countries. You are not permitted to use the Eaton trademarks without prior written consent of Eaton.

CSA is a registered trademark of the Canadian Standards Group  
UL is a registered trademark of the Underwriters Laboratories, Inc.

For Eaton's Bussmann series product information, call 1-855-287-7626 or visit: [Eaton.com/bussmannseries](http://Eaton.com/bussmannseries)

Follow us on social media to get the latest product and support information.



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)