

## Type HOLCO Series

### Key Features

- Ultra Precision - Down To 0.05%
- Matched Sets Available To 2ppm/°C
- High Pulse Withstand
- Low Reactance
- Low TCR - Down To 5ppm/°C
- Long Term Stability
- Up To 1 Watt At 70°C
- Released To CECC 40101 004, 030 And 804



The Holco range of Precision Metal Film Resistors meets the requirement for economically priced components for industrial and military applications. The manufacturing facility utilises closely controlled production processes including the sputter coating of metal alloy films to ceramic substrates, and laser spiralling to achieve close tolerance and high stability resistors. An epoxy coating is applied for environmental and mechanical protection. Commercially the Series is available in two case sizes, from 1 ohm to 4M ohms, tolerances from 0.05% to 1% and TCR's from 5ppm/°C to 100ppm/°C. Offered with release to BS CECC 40101 004, 030 and 804 the H8 is available via distribution.

### Characteristics - Electrical

|                           | H4P  | H4     | H8     |        |
|---------------------------|------|--------|--------|--------|
| <b>BS CECC 40101 004</b>  |      |        |        |        |
| Style:                    |      | K      | H      | J      |
| Power Rating at 70°C:     |      | 0.25W  | 0.063W | 0.125W |
| Temperature Rise (max):   |      | 32°C   | 14°C   | 28°C   |
| Limiting Element Voltage: |      | 250V   | 200V   | 200V   |
| <b>BS CECC 40101 030</b>  |      |        |        |        |
| Style:                    |      | J      | H      |        |
| Power Rating at 125°C:    |      | 0.125W | 0.1W   |        |
| Temperature Rise (max):   |      | 30°C   | 30°C   |        |
| Limiting Element Voltage: |      | 250V   | 200V   |        |
| <b>BS CECC 40101 804</b>  |      |        |        |        |
| Style:                    |      | B      | A      |        |
| Power Rating at 125°C:    |      | 0.25W  | 0.125W |        |
| Limiting Element Voltage: |      | 250V   | 200V   |        |
| <b>Commercial Ratings</b> |      |        |        |        |
| Power Rating at 70°C:     | 1.0W | 0.5W   | 0.25W  |        |
| Temperature Rise:         | 70°C | 55°C   | 40°C   |        |
| Limiting Element Voltage: | 500V | 350V   | 350V   |        |

### General Data

|                            |  |
|----------------------------|--|
| <b>Lead Material:</b>      | Solderability to BS CECC 40101 004 Para 4.15.1   |
| <b>Encapsulation:</b>      | Conformal Epoxy Coating  |
| <b>Resistor Marking:</b>   | Legend printed in accordance with CECC 40000 Para 2.4  |
| <b>Solvent Resistance:</b> | The epoxy coating and print will withstand the action of all commonly used industrial cleansing solvents |

## Type HOLCO Series

### Temperature Coefficient / Tolerance Ranges

| TCR<br>ppm/°C | H4P      |            |           | H4       |            |           | H8       |            |           |
|---------------|----------|------------|-----------|----------|------------|-----------|----------|------------|-----------|
|               | 0.05%    | 0.1%-0.25% | 0.5%-1.0% | 0.05%    | 0.1%-0.25% | 0.5%-1.0% | 0.05%    | 0.1%-0.25% | 0.5%-1.0% |
| 5             | 10R-500K | 10R-500K   | 10R-500K  | 10R-500K | 10R-500K   | 10R-500K  | 10R-500K | 10R-500K   | 10R-500K  |
| 10            | 10R-1M0  | 10R-1M0    | 10R-1M0   | 10R-1M0  | 10R-1M0    | 10R-1M0   | 10R-1M0  | 10R-1M0    | 10R-1M0   |
| 15            | 10R-1M0  | 10R-1M0    | 10R-1M0   | 10R-1M0  | 10R-1M0    | 10R-1M0   | 10R-1M0  | 10R-1M0    | 10R-1M0   |
| 25            | 10R-1M0  | 10R-2M0    | 10R-2M0   | 10R-1M0  | 10R-2M0    | 10R-2M0   | 10R-1M0  | 10R-2M0    | 10R-2M0   |
| 50            | 10R-1M0  | 10R-2M0    | 10R-4M0   | 10R-1M0  | 10R-2M0    | 10R-4M0   | 10R-1M0  | 10R-2M0    | 10R-4M0   |
| 100           | 10R-1M0  | 1R0-2M0    | 1R0-4M0   | 10R-1M0  | 1R0-2M0    | 1R0-4M0   | 10R-1M0  | 1R0-2M0    | 1R0-4M0   |

### Approved Value Ranges 40101-004, 40101-030

| Type | Style<br>004 | Style<br>030 | Z<br>100ppm | C<br>50ppm | D<br>25ppm | Y<br>15ppm |
|------|--------------|--------------|-------------|------------|------------|------------|
| H4   | K            | J            | 10R-1M0     | 49R9-1M0   | 49R9-1M0   | 49R9-1M0   |
| H8   | HJ           | H            | 10R-1M0     | 49R9-1M0   | 49R9-1M0   | 49R9-1M0   |

Tolerances 0.1%, 0.25%, 0.5%, 1%

### 40101-804

| Type | Style | C<br>50ppm | D<br>25ppm | T<br>15ppm |
|------|-------|------------|------------|------------|
| H4   | B     | 49R9-1M0   | 49R9-1M0   | 49R9-1M0   |
| H8   | A     | 49R9-1M0   | 49R9-1M0   | 49R9-1M0   |

Tolerances 0.1%, 0.25%, 0.5%, 1%

### Characteristics - Electrical

|  | Typical Data                       | Reference   |
|--|------------------------------------|---|
| <b>Voltage Coefficient of Resistance (Between 10% and Full Rated Voltage)</b>  | Less Than 5ppm/Volt Applied        | n/a   |
| <b>Insulation Resistance at 500 Volts</b>  | Greater Than 10 <sup>12</sup> Ohms | n/a   |
| <b>Resistance to Soldering Heat (260°C for 10 Secs.)</b>   | Less Than 0.05%                    | BS CECC 40101 004 Para 4.15.2                     |
| <b>Short Term Overload (6.25 Times Rated BS CECC Wattage for 5 Seconds)</b>  | Less Than 0.06%                    | BS CECC 40101 004 Para 4.11                       |
| <b>Ambient Temperature Range</b>   | -55°C to +155°C                    | BS CECC 40101 004, BS CECC 40101 030 & Commercial |
| <b>Rapid Change of Temperature (-55°C to +155°C, 5 cycles)</b>   | Less Than 0.04%                    | BS CECC 40101 004 Para 4.16                       |
| <b>Shelf Life (at Normal Room Temp.)</b>   | Less Than 0.05% Per Annum          | n/a   |
| <b>Vibration (10-500 HZ, Amplitude 0.75mm, or Acceleration 98m/s<sup>2</sup> which is less severe, sweep duration 6 hours)</b> | Less Than 0.04%                    | BS CECC 40101 004 Para 4.19                       |
| <b>Vibration (55-2000 Hz Simple Harmonic Motion, Max. Acceleration 98m/s<sup>2</sup>, Duration 35±5 Minutes)</b>               | Less Than 0.04%                    | MIL STD 202 METHOD 204-C                          |
| <b>Bump (390m/s<sup>2</sup>, 4000 Bumps)</b>   | Less Than 0.03%                    | BS 2011 Part 2.1 Eb 1977 (1984)                   |
| <b>Load Stability</b>  | See Graphs                         | n/a   |
| <b>Damp Heat Steady State</b>  | See Graph                          | BS CECC 40101 004 Para 4.21                       |

## Type HOLCO Series

### Dimensions

To prevent damage to the components conformal coating, the leads should be adequately supported during the forming process



|                                    | H4P     | H4      | H8      |
|------------------------------------|---------|---------|---------|
| <b>Body Length (L) maximum:</b>    | 10.0 mm | 10.0 mm | 7.20 mm |
| <b>Body Diameter (D) maximum:</b>  | 3.70 mm | 3.70 mm | 2.50 mm |
| <b>Lead Diameter (d) maximum:</b>  | 0.60 mm | 0.60 mm | 0.60 mm |
| <b>Lead Length (l) nominal:</b>    | 30.0 mm | 30.0 mm | 30.0 mm |
| <b>Recommended Mounting Pitch:</b> | 12.7 mm | 12.7 mm | 10.2 mm |
| <b>Weight (g/100 resistors)</b>    | 40      | 40      | 24      |

### Characteristics - Long Term Stability



**Long Term Stability**  
BS CECC 40101 004  
Ratings at 70°C  
H4 - 0.25 W  
H8 - 0.125 W



**Long Term Stability**  
BS CECC 40101 030  
Ratings at 125°C  
H4 - 0.125 W  
H8 - 0.1 W



**Long Term Stability**  
Commercial  
Ratings at 125°C  
H4P - 1W  
H4 - 0.5 W  
H8 - 0.25 W



**Damp Heat Steady State**  
93% RH at 40°C

## Type HOLCO Series

### Derating Graph - Approved and Commercial Ratings



### How to Order

| H8                 | 100R  | B  | Y  | B   |
|--------------------|---|--|--|---|
| <b>Common Part</b> | <b>Resistance Value</b>   | <b>Tolerance</b>   | <b>T.C.R. Code</b>   | <b>Release</b>  |
| H4P<br>H4<br>H8    | 1.0 ohm<br>(1000 milli ohms) 1R0<br>10 ohm<br>(10 ohms) 10R<br>100 ohm<br>(100 ohms) 100R<br>1K Ohm<br>(1000 ohms) 1K0<br>10K ohm<br>(10000 ohms) 10K<br>100K ohm<br>(100000 ohms) 100K<br>1M ohm<br>(1000000 ohms) 1M0 | A - 0.05%<br>B - 0.1%<br>C - 0.25%<br>D - 0.5%<br>F - 1.0% | A - 5ppm<br>B - 10ppm<br>Y - 15ppm<br>D - 25ppm<br>C - 50ppm<br>Z - 100ppm | A - Part can only be sold with Commercial or C of C release.<br><br>B - Part can be sold to BS CECC 40101 004, BS CECC 40101 030<br><br>D - Part can be sold to BS CECC 40101 804 |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)