TOSHIBA CMOS DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

TC74ACT240P, TC74ACT240F, TC74ACT240FW, TC74ACT240FT
TC74ACT244P, TC74ACT244F, TC74ACT244FW, TC74ACT244FT

OCTAL BUS BUFFER


TC74ACT240P/F/FW/FT INVERTED, 3 – STATE OUTPUTS
TC74ACT244P/F/FW/FT NON – INVERTED, 3 – STATE OUTPUTS

The TC74ACT240 and 244 are advanced high speed CMOS OCTAL BUS BUFFERs fabricated with silicon gate and double - layer metal wiring C^2MOS technology.
They achieve the high speed operation similar to equivalent Bipolar Schottky TTL while maintaining the CMOS low power dissipation.
The 74ACT240 is an inverting 3-state buffer while the 74ACT244 is non-inverting. Both devices have two active-low output enables.
These devices are designed to be used in such applications as 3-state memory address drivers.
All inputs are equipped with protection circuits against static discharge or transient excess voltage.


FEATURES :

- High Speed ····· t_{pd} = 5.0ns(typ.) at V_{CC} = 5V
- Low Power Dissipation ····· I_{CC} = 8μA(Max.) at Ta = 25°C
- Compatible with TTL outputs ···· V_{IL} = 0.8V(Max.), V_{IH} = 2.0V(Min.)
- Symmetrical Output Impedance ··· $|I_{OH}| = I_{OL}$ = 24mA(Min.) Capability of driving 50Ω transmission lines.
- Balanced Propagation Delays ····· $t_{pLH} \simeq t_{pHL}$
- Pin and Function Compatible with 74F240/244


(Note) The JEDEC SOP (FW) is not available in Japan.




P (DIP20-P-300-2.54A)
Weight : 1.30g (Typ.)



FW (SOL20-P-300-1.27)
Weight : 0.46g (Typ.)





F (SOP20-P-300-1.27)
Weight : 0.22g (Typ.)



FT (TSSOP20-P-0044-0.65)
Weight : 0.08g (Typ.)

PIN ASSIGNMENT






TRUTH TABLE

INPUTS		OUTPUTS	
$\overline{G}$	An	Y_n(244)	$\overline{Y}$n(240)
L	L	L	H
L	H	H	L
H	X	Z	Z

X : Don't Care
Z : High Impedance

IEC LOGIC SYMBOL



ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	VALUE	UNIT
Supply Voltage Range	V_{CC}	−0.5~7.0	V
DC Input Voltage	V_{IN}	−0.5~V_{CC} + 0.5	V
DC Output Voltage	V_{OUT}	−0.5~V_{CC} + 0.5	V
Input Diode Current	I_{IK}	± 20	mA
Output Diode Current	I_{OK}	± 50	mA
DC Output Current	I_{OUT}	± 50	mA
DC V_{CC}/Ground Current	I_{CC}	± 200	mA
Power Dissipation	P_D	500 (DIP)* / 180 (SOP/TSSOP)	mW
Storage Temperature	T_{stg}	−65~150	°C

*500mW in the range of Ta = −40°C~65°C. From Ta = 65°C to 85°C a derating factor of −10mW/°C should be applied up to 300mW.

RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	VALUE	UNIT
Supply Voltage	V_{CC}	4.5~5.5	V
Input Voltage	V_{IN}	0~V_{CC}	V
Output Voltage	V_{OUT}	0~V_{CC}	V
Operating Temperature	T_{opr}	−40~85	°C
Input Rise and Fall Time	dt / dV	0~10	ns / V

DC ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITION		V_{CC} (V)	Ta = 25°C MIN.	Ta = 25°C TYP.	Ta = 25°C MAX.	Ta = −40~85°C MIN.	Ta = −40~85°C MAX.	UNIT
High - Level Input Voltage	V_{IH}			4.5 ~ 5.5	2.0	—	—	2.0	—	V
Low - Level Input Voltage	V_{IL}			4.5 ~ 5.5	—	—	0.8	—	0.8	V
High - Level Output Voltage	V_{OH}	V_{IN} = V_{IH} or V_{IL}	I_{OH} = −50μA	4.5	4.4	4.5	—	4.4	—	V
			I_{OH} = −24mA	4.5	3.94	—	—	3.80	—	
			I_{OH} = −75mA*	5.5	—	—	—	3.85	—	
Low - Level Output Voltage	V_{OL}	V_{IN} = V_{IH} or V_{IL}	I_{OL} = 50μA	4.5	—	0.0	0.1	—	0.1	V
			I_{OL} = 24mA	4.5	—	—	0.36	—	0.44	
			I_{OL} = 75mA*	5.5	—	—	—	—	1.65	
3 - State Output Off - State Current	I_{OZ}	V_{IN} = V_{IH} or V_{IL} V_{OUT} = V_{CC} or GND		5.5	—	—	±0.5	—	±5.0	μA
Input Leakage Current	I_{IN}	V_{IN} = V_{CC} or GND		5.5	—	—	±0.1	—	±1.0	
Quiescent Supply Current	I_{CC}	V_{IN} = V_{CC} or GND		5.5	—	—	8.0	—	80.0	
	I_C	PER INPUT : V_{IN} = 3.4V OTHER INPUT : V_{CC} or GND		5.5	—	—	1.35	—	1.5	mA

* : This spec indicates the capability of driving 50Ω transmission lines.
One output should be tested at a time for a 10ms maximum duration.


AC ELECTRICAL CHARACTERISTICS (C_L = 50pF, R_L = 500Ω, Input $t_r = t_f$ = 3ns)

PARAMETER	SYMBOL	TEST CONDITION	V_{CC} (V)	Ta = 25°C MIN.	Ta = 25°C TYP.	Ta = 25°C MAX.	Ta = −40~85°C MIN.	Ta = −40~85°C MAX.	UNIT
Propagation Delay Time	t_{pLH} t_{pHL}		5.0 ± 0.5	—	5.7	8.0	1.0	9.0	ns
Output Enable Time	t_{pZL} t_{pZH}		5.0 ± 0.5	—	6.0	9.0	1.0	10.5	
Output Disable Time	t_{pLZ} t_{pHZ}		5.0 ± 0.5	—	5.9	8.5	1.0	10.0	
Input Capacitance	C_{IN}			—	5	10	—	10	pF
Output Capacitance	C_{OUT}			—	10	—	—	—	
Power Dissipation Capacitance	C_{PD} (1)	TC74ACT240		—	25	—	—	—	
		TC74ACT244		—	29	—	—	—	

Note (1) C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load.
Average operating current can be obtained by the equation :


$$I_{CC}(opr.) = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC} / 8 \text{ (per bit)}$$

DIP 20PIN PACKAGE DIMENSIONS (DIP20-P-300-2.54A) Unit in mm



Weight : 1.30g (Typ.)


SOP 20PIN (200mil BODY) PACKAGE DIMENSIONS (SOP20-P-300-1.27) Unit in mm



Weight : 0.22g (Typ.)


SOP 20PIN (300mil BODY) PACKAGE DIMENSIONS (SOL20-P-300-1.27) Unit in mm

(Note) This package is not available in Japan.



Weight : 0.46g (Typ.)

TSSOP 20PIN PACKAGE DIMENSIONS (TSSOP20-P-0044-0.65) Unit in mm



Weight : 0.08g (Typ.)

RESTRICTIONS ON PRODUCT USE

000707EBA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
  In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru