



T H E R M O M E T R I C S
A C O M M I T M E N T T O E X C E L L E N C E

NTC Diode

Thermometrics

Thermistors



A range of NTC chip thermistors in DO-35 style glass package (diode outline) with axial solder-coated copper-clad steel wires.

- Designed for accurate temperature measurement, control and compensation
- Tight tolerances on resistance and B value
- Operation up to 482°F (250°C) with excellent stability
- Glass body provides hermetic seal and voltage insulation and excellent stability
- Designed for cost effective solid state sensor
- Lead-wires metallurgically bonded to thermistor element for improved reliability (Type GE only)
- Resistant to corrosive atmospheres and harsh environments
- Available on axial bandolier to IEC-286-1/ EIA-468A and packet taped to EIA RS-481 for MELF.
- Also available loose-packed with axial, radial and SMD wire forms
- Suitable for automotive, telecom (battery packs), HVAC and white goods applications
- Temperature sensing for household appliances such as rice cookers, electronic ranges, ovens, etc.
- Temperature sensing for industrial products such as pharmaceuticals, chemicals, food, etc. components.

Amphenol

Advanced Sensors

Type DK Specifications

Chip thermistor in DO-35 glass package

Options

- Other resistance values within the ranges shown; e.g. code DKA302*2 for 3000 Ω $\pm 2\%$ at 77°F (25°C)
- Reference temperatures in the range 0°F to 302°F (-18°C to 150°C)
- Operation to 572°F (300°C) (no solder coating on wires)
- Wire lengths 0.16 in to 1.26 in (4 mm to 32 mm) ± 0.04 in (± 1 mm) for DK-N; up to 1.02 in (26 mm) for DK-H

Coding

Replace * in the codes shown below as follows:

- Axial, loose-packed: N
- Axial, bandoliered: B
- Radial, loose-packed: H
- Surface mount, loose-packed: M



NTC Type DK wires should not be bent within 0.08 in (2 mm) of glass body

Data

- Operating temperature: -40°F to 482°F (-40°C to 250°C)
- Thermal time constant: 7 seconds (cooling in air)
- Dissipation factor: 3.0 mW/K
- Mass: 0.2 g
- Packing/MOQ: 1000/box (loose), 5000/reel (bandoliered)

| R25 Ω | Material system | B 25/85 K | Code R25 $\pm 2\%$ | Code R25 $\pm 3\%$ | Code R25 $\pm 5\%$ | Code R25 $\pm 10\%$ |
|--------------|-----------------|----------------|--------------------|--------------------|--------------------|---------------------|
| 2000 | 2 | 3540 $\pm 1\%$ | DKA202*2 | DKA202*3 | DKA202*5 | DKA202*10 |
| 5000 | 2 | 3540 $\pm 1\%$ | DKA502*2 | DKA502*3 | DKA502*5 | DKA502*10 |
| 10,000 | 2 | 3540 $\pm 1\%$ | DKA103*2 | DKA103*3 | DKA103*5 | DKA103*10 |
| 10,000 | 5A | 3730 $\pm 2\%$ | | DKC103*3 | DKC103*5 | DKC103*10 |
| 12,000 | 5A | 3730 $\pm 2\%$ | DKC123*2 | DKC123*3 | DKC123*5 | DKC123*10 |
| 10,000 | 3 | 3960 $\pm 1\%$ | DKF103*2 | DKF103*3 | DKF103*5 | DKF103*10 |
| 20,000 | 3 | 3960 $\pm 1\%$ | DKF203*2 | DKF203*3 | DKF203*5 | DKF203*10 |
| 30,000 | 3 | 3960 $\pm 1\%$ | DKF303*2 | DKF303*3 | DKF303*5 | DKF303*10 |
| 50,000 | 3 | 3960 $\pm 1\%$ | DKF503*2 | DKF503*3 | DKF503*5 | DKF503*10 |
| 100,000 | 3 | 3960 $\pm 1\%$ | DKF104*2 | DKF104*3 | DKF104*5 | DKF104*10 |
| 200,000 | G | 4263 $\pm 2\%$ | | | DKG204*5 | DKG204*10 |
| 500,000 | D | 4573 $\pm 2\%$ | | | DKD504*5 | DKD504*10 |
| 1,000,000 | D | 4573 $\pm 2\%$ | | | DKD105*5 | DKD105*10 |

See separate tables for resistance-temperature data.
Consult factory for additional tolerance requirements.

Type DKM Specifications

Glass encapsulated SMD thermistor

Description

A range of thermistors in DO-35 style glass package (diode outline formed for surface lead-wires and applications) with solder-coated copper-clad steel lead-wires.



NTC Type DKM wires should not be bent within 0.08 in (2 mm) of glass body

Options

- Other resistance values within the ranges shown; e.g. code DKA302M2 for 3000 Ω $\pm 2\%$ at 77°F (25°C)
- Reference temperatures in the range 32°F to 302°F (0°C to 150°C)
- For tape and reel, add suffix “AB”
- Operation to 572°F (300°C); no solder coating on lead-wires

Data

- Operating temperature: -40°F to 482°F (-40°C to 250°C)
- Thermal time constant: 7 seconds (cooling in air)
- Dissipation factor: 3.0 mW/K
- Mass: 0.2 g
- Packing/MOQ: 1000/box (loose)

| R25 Ω | Material System | B 25/85 K | Code R25 $\pm 2\%$ | Code R25 $\pm 3\%$ | Code R25 $\pm 5\%$ | Code R25 $\pm 10\%$ |
|--------------|-----------------|----------------|--------------------|--------------------|--------------------|---------------------|
| 2000 | 2 | 3540 $\pm 1\%$ | DKA202M2 | DKA202M3 | DKA202M5 | DKA202M10 |
| 5000 | 2 | 3540 $\pm 1\%$ | DKA502M2 | DKA502M3 | DKA502M5 | DKA502M10 |
| 10,000 | 2 | 3540 $\pm 1\%$ | DKA103M2 | DKA103M3 | DKA103M5 | DKA103M10 |
| 10,000 | 5A | 3730 $\pm 2\%$ | | DKC103M3 | DKC103M5 | DKC103M10 |
| 10,000 | 3 | 3960 $\pm 1\%$ | DKF103M2 | DKF103M3 | DKF103M5 | DKF103M10 |
| 20,000 | 3 | 3960 $\pm 1\%$ | DKF203M2 | DKF203M3 | DKF203M5 | DKF203M10 |
| 30,000 | 3 | 3960 $\pm 1\%$ | DKF303M2 | DKF303M3 | DKF303M5 | DKF303M10 |
| 50,000 | 3 | 3960 $\pm 1\%$ | DKF503M2 | DKF503M3 | DKF503M5 | DKF503M10 |
| 100,000 | 3 | 3960 $\pm 1\%$ | DKF104M2 | DKF104M3 | DKF104M5 | DKF104M10 |
| 200,000 | G | 4263 $\pm 2\%$ | | | DKG204M5 | DKG204M10 |
| 500,000 | D | 4573 $\pm 2\%$ | | | DKD504M5 | DKD504M10 |
| 1,000,000 | D | 4573 $\pm 2\%$ | | | DKD105M5 | DKD105M10 |


See separate tables for resistance-temperature data.
Consult factory for additional tolerance requirements.

Type GE Specifications

Glass encapsulated DO-35 package

Options

- For reel taping
- Nickel leads for welding
- Other resistances in the range 250 Ω to 5 M Ω
- Other tolerances, tolerances at other temperatures
- Alternative leads lengths, lead materials
- Can be expanded to 572°F (300°C) with nickel leads



NTC Type GE dimensions

Data

- Standard resistance tolerance: $\pm 10\%$ @ 77°F (25°C)
- Dissipation constant: 3.0 mW/K
- Time constant: 7 seconds
- Operating range: -58°F to 400°F (-50°C to 204°C)
- Lead Wires metallurgically bonded to thermistor element for improved reliability

| R ₀ @25°C (Ω) | Material System | Beta 25/85 | Type Number |
|-----------------------------------|-----------------|------------|-----------------------|
| 250 | GE5.5* | 2983 | AL03006-165.9-55-G1 |
| 500 | GE5.5* | 2983 | AL03006-331.8-55-G1 |
| 1K | GE7.3 | 3499 | AL03006-624-73-G1 |
| 2K | GE7.3 | 3499 | AL03006-1248-73-G1 |
| 2786 | GE10.1 | 4102 | AL03006-1576-101-G1 |
| 3K | GE7.6 | 3553 | AL03006-1847-76-G1 |
| 4K | GE7.6 | 3553 | AL03006-2463-76-G1 |
| 5K | GE7.6 | 3553 | AL03006-3079-76-G1 |
| 10K | GE9.7A | 3992 | AL03006-5818-97-G1 |
| 20K | GE9.8 | 3974 | AL03006-11.7K-98-G1 |
| 30K | GE9.8 | 3974 | AL03006-17.53K-98-G1 |
| 50K | GE9.7B | 3952 | AL03006-29.1K-97-G1 |
| 100K | GE9.7B | 3952 | AL03006-58.2K-97-G1 |
| 200K | GE12.3 | 4365 | AL03006-111.3K-123-G1 |
| 500K | GE13.8 | 4567 | AL03006-269.8K-138-G1 |
| 1M | GE14.5 | 4661 | AL03006-535K-145-G1 |
| 5M | GE16.4 | 4848 | AL03006-2.6M-164-G1 |

*maximum operating temperature 302°F (150°C)

Type MELF Specifications

Glass encapsulated SMD thermistor

Description

Hermetically sealed, glass encapsulated thermistor in SOD-80 SMD package.

Options

- Pocket Taping
- Other resistances in the range 250 Ω to 5 M Ω available
- Other tolerances, tolerances at other temperatures



NTC Type MELF dimensions

Data

- Standard resistance tolerance: $\pm 10\%$ @ 77°F (25°C)
- Dissipation constant: 3.0 mW/°C
- Time constant: 7 seconds
- Operating range: -58°F to 400°F (-50°C to 204°C)

| R ₀ @25° C (Ω) | Material System | Beta 25/85 | Type Number |
|------------------------------------|-----------------|------------|-----------------------|
| 250 | GE5.5* | 2983 | 03006-165.9-55-G100 |
| 500 | GE5.5* | 2983 | 03006-331.8-55-G100 |
| 1K | GE7.3 | 3499 | 03006-624-73-G100 |
| 2K | GE7.3 | 3499 | 03006-1248-73-G100 |
| 2786 | GE10.1 | 4102 | 03006-1576-101-G100 |
| 3K | GE7.6 | 3553 | 03006-1847-76-G100 |
| 4K | GE7.6 | 3553 | 03006-2463-76-G100 |
| 5K | GE7.6 | 3553 | 03006-3079-76-G100 |
| 10K | GE9.7A | 3992 | 03006-5818-97-G100 |
| 20K | GE9.8 | 3974 | 03006-11.7K-98-G100 |
| 30K | GE9.8 | 3974 | 03006-17.53K-98-G100 |
| 50K | GE9.7B | 3952 | 03006-29.1K-97-G100 |
| 100K | GE9.7B | 3952 | 03006-58.2-97-G100 |
| 200K | GE12.3 | 4365 | 03006-111.3K-123-G100 |
| 500K | GE13.8 | 4567 | 03006-269.8K-138-G100 |
| 1M | GE14.5 | 4661 | 03006-535K-145-G100 |
| 5M | GE16.4 | 4848 | 03006-2.6M-164-G100 |

*maximum operating temperature 302°F (150°C)

Type TH Specifications

Glass encapsulated radial lead thermistor

| Part Number | Resistance (25 Ω) | β Constant (25/50) | Recommended Maximum Operating Current at 77°F (25°C) | Maximum Permissible Current at 77°F (25°C) |
|-------------|-------------------|--------------------|--|--|
| TH220J33G | 2.0 K | 3375 K | 0.22 mA | 30.0 mA |
| TH225J13G | 2.545 K | 3745 K | 0.22 mA | 30.0 mA |
| TH238J34G | 3.896 K | 3434 K | 0.20 mA | 26.5 mA |
| TH253J34G | 5.369 K | 3434 K | 0.16 mA | 24.0 mA |
| TH310J34G | 10.74 K | 3434 K | 0.13 mA | 20.0 mA |
| TH310J36G | 10.0 K | 3684 K | 0.14 mA | 20.0 mA |
| TH310J39G | 10.0 K | 3933 K | 0.14 mA | 20.0 mA |
| TH315J39G | 15.0 K | 3933 K | 0.12 mA | 17.0 mA |
| TH320J39G | 20.0 K | 3952 K | 0.10 mA | 15.0 mA |
| TH349J39G | 49.12 K | 3952 K | 0.06 mA | 10.0 mA |
| TH350J39G | 50.0 K | 3952 K | 0.06 mA | 10.0 mA |
| TH398J40G | 98.63 K | 4014 K | 0.045 mA | 5.0 mA |
| TH410J40G | 100.0 K | 4014 K | 0.045 mA | 5.0 mA |
| TH420J34G | 200.0 K | 3450 K | 0.015 mA | 3.5 mA |
| TH423J41G | 231.4 K | 4176 K | 0.015 mA | 3.5 mA |
| TH510J44G | 1,000 K | 4491 K | 0.007 mA | 1.5 mA |
| TH513J44G | 1,388 K | 4491 K | 0.005 mA | 1.0 mA |

- The tolerance of resistance is ±5% for standard device
- The tolerance of B constant is ±2% for standard device The constant is determined by the equation:
 $B = 3853.9 \ln (R_{25}/R_{50})$
 R25 and R50 represent the thermistor resistance at 77°F and 122°F (25°C and 50°C) respectively
- Others: For non-standard devices, consult Thermometrics

| Dissipation Factor (in still air) | Time Constant (in still air) | Operating Temperature Range | Rated Power at 77°F (25°C) |
|-----------------------------------|------------------------------|---------------------------------|----------------------------|
| 2.0 (mW/°C) | 25 (seconds) | -40°F to 482°F (-40°C to 250°C) | 25 mW |



NTC Type TH dimensions

Explanation of Part Number

| | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|---|-----|
| TH | 410 | S | 40 | F | D | SN | - | T5 |
| (1) | (2) | (3) | (4) | (5) | (6) | (7) | | (8) |

| 1 | 2 | 3 / 5 | 4 | 6 | 7 | 8 |
|--------------------------|--|--|--|---|--|--|
| Type | Resistance R(25°C) | Resistance / B Value Tolerance | B Value Range | Standard Temperature | Lead Wire Type | Packing & Other Description |
| Diode Type Thermistor | 225:25x10 ² = 2.5kΩ 310:10x10 ³ =10kΩ 410:10x10 ⁴ =100kΩ | F : ± 1% G : ± 2% H : ± 3% J : ± 5% K : ± 10% L : ± 15% M : ± 20% : : <u>S : others</u> S : ± 1.5% | 33:3300k ~3399k 40:4000k ~4099k 42:4200k ~4299k | J : -18°C A : 0°C B : 25°C C : 50°C D : 75°C E : 85°C F : 100°C G : 150°C H : 200°C : : S : others | NR : CP wire NI : Ni plated Sn : Sn plated : : : : S : others | T5 : Taping (52mm, Ammo) ----- R3 : Reel (52mm, 3KP) ----- C11 : 11mm (Wire cutting) ----- Other Special Shape or Dim |

Amphenol

Advanced Sensors

www.amphenol-sensors.com

© 2017 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice.
Other company names and product names used in this document are the registered trademarks or
trademarks of their respective owners.

AAS-920-320E - 08/2017

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[DKF104N10](#) [AL03006-535K-145-G1](#) [03006-29.1K-97-G100](#) [03006-1576-101-G100](#) [AL03006-3079-76-G1](#)
[DKF104M10](#) [DKF104H10](#) [DKF203N10](#) [03006-58.2K-97-G100](#) [DKA202B5](#) [DKA202B3](#) [DKA202N3](#) [DKA202N5](#)
[DKA103B10](#) [DKF103B10](#) [AL03006-165.9-55-G1](#) [DKF303B10](#) [DKF203H10](#) [DKF203M10](#) [DKF104H3](#) [DKF104B5](#)
[DKF104B3](#) [DKF104N3](#) [DKF104N5](#) [DKF104H5](#) [AL03006-1847-76-G1](#) [DKF104B10](#) [AL03006-1576-101-G1](#) [03006-](#)
[331.8-55-G100](#) [DKF503B10](#) [03006-165.9-55-G100](#) [03006-535K-145-G100](#) [DKA202M10](#) [AL03006-269.8K-138-G1](#)
[DKF103H10](#) [03006-11.7K-98-G100](#) [AL03006-17.53K-98-G1](#) [DKF303H10](#) [AL03006-624-73-G1](#) [AL03006-58.2K-97-](#)
[G1](#) [DKF203B3](#) [DKF203N5](#) [DKF203B5](#) [DKF203N3](#) [DKF203M5](#) [DKF203M3](#) [DKF203H3](#) [DKF203H5](#) [DKA103B5](#)
[DKA103B3](#) [DKF503H10](#) [DKA103N3](#) [DKA103N5](#) [DKA103H3](#) [DKA103H5](#) [DKA103M3](#) [DKA103M5](#) [DKF503M10](#)
[03006-1847-76-G100](#) [03006-111.3K-123-G100](#) [DKA202N10](#) [DKF103H1](#) [DKF503N10](#) [AL03006-1248-73-G1](#)
[DKA50H25](#) [DKA50N25](#) [AL03006-29.1K-97-G1](#) [DKA50B25](#) [AL03006-2463-76-G1](#) [03006-269.8K-138-G100](#)
[DKF303M10](#) [DKA202B10](#) [DKA502H3](#) [DKF503B3](#) [DKF503N3](#) [DKF503N5](#) [DKF503B5](#) [AL03006-331.8-55-G1](#)
[DKF503H3](#) [DKF503M5](#) [DKF503M3](#) [DKF503H5](#) [DKA202H10](#) [03006-5818-97-G102](#) [03006-1248-73-G100](#)
[DKF303N10](#) [DKA103H10](#) [DKF103M10](#) [AL03006-111.3K-123-G1](#) [DKA103M10](#) [DKF303N3](#) [DKF303N5](#) [DKA202M5](#)
[DKA202M3](#) [DKA202H3](#) [DKA202H5](#) [03006-3079-76-G100](#) [DKA103N10](#) [DKF104M5](#) [DKF104M3](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru