

TYPICAL SWITCH ORDERING EXAMPLE

MB25

11

S2

G

13

—

B

C

Poles & Circuits			
11	SPDT	ON	(ON)
21	DPDT	ON	(ON)
() = Momentary			

Contact Materials & Ratings	
W	Silver Rated 3A @ 125V AC
G	Gold Rated 0.4VA max @ 28V AC/DC max

Caps	
B	.315" (8.0mm) Diameter
C	.394" (10.0mm) Diameter

Bushing	
S2	.300" (7.6mm) Smooth with Keyway

Terminals	
13	.250" (6.35mm) Straight PC with Bracket
30	Right Angle (Single Pole only)
45	Vertical PC

Cap Colors	
A	Black
B	White
C	Red
E	Yellow
F	Green
G	Blue


IMPORTANT:




Switches are supplied without UL, cULus & CSA marking unless specified.
UL, cULus & CSA recognized only when ordered with marking on the switch.
Specific models, ratings, & ordering instructions are noted on the General Specifications page.

DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

MB2511S2G13-BC




POLES & CIRCUITS

Pole	Model	Plunger Position () = Momentary		Connected Terminals		Throw & Switch Schematics
		Normal 	Down 	Normal 	Down 	
SP	MB2511	ON	(ON)	3-1	3-2	SPDT 
DP	MB2521	ON	(ON)	3-1 6-4	3-2 6-5	DPDT 


Note: Terminal numbers are not actually on the switch.

BUSHING

S2 .300" (7.6mm)
Smooth with Keyway



Panel Cutout



CONTACT MATERIALS & RATINGS

W Silver over Silver

Power Level

3A @ 125V AC

G Gold over Brass or Copper



Logic Level

0.4VA maximum @ 28V AC/DC maximum



Note: Complete explanation of operating range in Supplement section.

TERMINALS



13 .250" (6.35mm) Terminal
with .465" (11.8mm) Bracket



30 Right Angle PC
Single Pole only



45 Vertical PC




CAPS & CAP COLORS

B AT443
.315" (8.0mm) Diameter Cap

Material: Polycarbonate


Finish: Glossy



C AT442
.394" (10.0mm) Diameter Cap

Material: Polycarbonate

Finish: Glossy



Cap Colors Available:



Black



White



Red



Yellow



Green







Blue

TYPICAL SWITCH DIMENSIONS

Single Pole

Double Pole




Straight PC • Bracket



MB2511S2G13-BC

Single Pole

Right Angle PC








MB2511S2G30-BC

Single Pole

Double Pole

Vertical PC



MB2511S2G45-BC

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru